

2501-A

Fibre Glast Developments Corporation

385 Carr Drive Brookville, Ohio 45309 Phone: 800.214.8572 Fax: 937.833.6555 www.fibreglast.com

1/16 hp Rocking Piston Vacuum Pump



Specifications	
Thermal Protection	YES
Operating Voltage:	110/115
Regulatory Approval	cURus / CE
Flow @ 50hz	0.66 cfm (1.12 m3h)
Flow @ 60hz	0.8 cfm (1.36 m3h)
Max Pressure	100 psi (6.89 bar)
Max Pressure @ 50hz	100 psi (6.89 bar)
Max Pressure @ 60hz	100 psi (6.89 bar)
Max Vacuum @ 50hz	25 in-hg (846.6 mbar)
Max Vacuum @ 60hz	26 in-hg (880.46 mbar)
Weight	8.6 lbs (3.9 kg)
Duty Cycle	100%
Warranty	1 Year

This lightweight yet durable offers oil-less operation to ensure the discharge air remains free of contamination from lubricants. It can be used as a compressor or vacuum pump for maximum flexibility and its quiet operation makes it ideal for noise sensitive environments while performing vacuum infusion processes, as well as may industrial applications. In addition, this pump's simple field serviceability extends the life of the product and maximizes uptime.

KEY FEATURES

- Critical components are anodized and e-coated for corrosion protection.
- Functions as vacuum pump and compressor.
- Easily serviceable for longer life.
- Oil-less operation.

Information present herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.