

# **GHS SAFETY DATA SHEET (SDS)**

#### **SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT: Part #1099 High Viscosity Epoxy Surface Coat, Side B

FIBRE GLAST DEVELOPMENTS CORP. 385 CARR DRIVE BROOKVILLE, OH 45309

TELEPHONE: (937) 833-5200 FAX: (937) 833-6555 FOR CHEMICAL EMERGENCY CALL (801) 629-0667 24 HRS.

**RECOMMENDED USE:** Industrial Curing Agent supplied exclusively for workplace use.

## **SECTION 2 - HAZARDS IDENTIFICATION**

## **GHS CLASSIFICATION**

Eye Damage : Category 1

**Acute Toxicity** : Category 4

(Oral and Inhalation)

Skin Sensitizer : Category 1

Reproductive Toxicity

(Bisphenol A)

: Category 2

Acute Aquatic Toxicity

(Bisphenol A)

: Category 2

#### **GHS Label Element**

Hazard pictograms







Signal word : Danger Hazard statements : H318 Causes serious eye damage.

: H302+332 Harmful if swallowed, or if inhaled. : H317 May cause an allergic skin reaction.

: H361 Suspected of damaging fertility or the unborn child (Bisphenol A).

: H401 Toxic to aquatic life (Bisphenol A).

Precautionary statements : P202 Do not handle until all safety precautions have beenread/understood

: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.: P270 Do not eat, drink or smoke when using this product.: P281 Use personal protective equipment as required.

: P285 In case of inadequate ventilation wear respiratory protection.

: P273 Avoid release to the environment.

| NO. | CANCER | REPRO-TOX | TARGET ORGANS | ACGIH/TLV | OSHA/PEL              |
|-----|--------|-----------|---------------|-----------|-----------------------|
| P   | NO     | NO        | UNKNOWN       | N.A.mg/M³ | N.A.mg/M <sup>3</sup> |
| 2   | NO     | NO        | LIVER, KIDNEY | 4 mg/M³   | 4 mg/M <sup>3</sup>   |
| 3   | NO     | YES       | EYES, SKIN    | 5 mg/M³   | 5 mg/M <sup>3</sup>   |

#### **SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

UNDER GHS-OSHA §4.11 THE PRECISE COMPOSITION OF THIS PRODUCT IS WITHHELD AS CONFIDENTIAL BUSINESS INFORMATION (CBI). A MORE COMPLETE DISCLOSURE CAN BE PROVIDED TO A HEALTH, OR SAFETY PROFESSIONAL WHEN NECESSARY.

#### Substance/Mixture: Mixture

| NO. | COMPONENT              | CAS. NO. | PERCENT |
|-----|------------------------|----------|---------|
| Р   | MODIFIED AMINE MIXTURE | N.A.     | < 100%  |
| 2   | DIETHYLENETRIAMINE     | 110-40-0 | < 4%    |
| 3   | BISPHENOL A            | 80-05-7  | < 4%    |

## **SECTION 4 - FIRST-AID MEASURES**

#### EMERGENCY AND FIRST AID PROCEDURES:

- EYES: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.
- **SKIN:** WASH AFFECTED AREA IMMEDIATELY WITH LARGE AMOUNTS OF SOAP AND WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. CONTACT A PHYSICIAN IF IRRITATION OCCURS.
- INHALATION: REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.
- INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES OF WATER. CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUSPERSON.

#### **SECTION 5 - FIRE-FIGHTING MEASURES**

FLASH POINT: ≥200°F (FOR PRODUCT OR LOWEST FLASH POINT INGREDIENT)

FLAMMABILITY CLASSIFICATION: COMBUSTIBLE CLASS (IIIB)

EXTINGUISHING MEDIA: WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, OR FOAM.

NOTE: EITHER ATMOSPHERE-SUPPLY OR AIR-PURIFYING RESPIRATORS SHOULD BE AVAILABLE FOR FIRE

FIGHTERS (20 CFR 1910.134).

#### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

- IF MATERIAL IS SPILLED: AVOID CONTACT WITH MATERIAL. PERSONS NOT WEARING PROPER PROTECTIVE EQUIPMENT (SEE BELOW) SHOULD BE EXCLUDED FROM THE AREA UNTIL CLEAN UP IS COMPLETE. DIKE AREA TO PREVENT SPILL SPREADING AND SCOOP UP EXCESS TO RECOVERY CONTAINERS. ABSORB REMNANT ON NONCOMBUSTIBLE MATERIAL SUCH AS CLAY AND SHOVELINTO CONTAINERS FOR DISPOSAL.
- WASTE DISPOSAL METHOD: DISPOSE OF ANY WASTE(S) GENERATED ABOVE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCALREGULATIONS.

#### **SECTION 7 - HANDLING AND STORAGE**

- AVOID SKIN AND EYE CONTACT.
- AVOID BREATHING VAPOR, MIST OR FUMES.
- ENSURE THAT ALL CONTAINERS ARE PROPERLY LABELED TO PREVENT ACCIDENTAL INGESTION OR IMPROPER DISPOSAL.
- RESEAL PARTLY USED CONTAINERS.
- WASH WITH SOAP AND WATER BEFORE EATING, DRINKING OR USING TOILETFACILITIES.
- STORE UNDER COOL, DRY CONDITIONS AND AWAY FROM OPEN FLAMES AND HIGHTEMPERATURES.
- OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICE.

## SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

- **RESPIRATORY PROTECTION:** NOT NORMALLY NECESSARY UNLESS THE MATERIAL IS BEING USED IN SUCH A WAY AS TO PRODUCE DUST, MIST, VAPOR, FUMES, OR SMOKE, IN WHICH CASE NIOSH APPROVED RESPIRATORY PROTECTION SHOULD BEUSED.
- VENTILATION: SHOULD BE SUFFICIENT TO CONTROL ANY DUST, MIST, VAPOR OR FUMES PRODUCED BY PROCESSING OR HANDLING METHOD. BREATHING OF VAPOR MUST BEAVOIDED.
- HAND PROTECTION: IMPERVIOUS GLOVES, NEOPRENE OR NILRILE RUBBERGLOVES.
- EYE PROTECTION: SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDESHIELDS.
- OTHER PROTECTIVE EQUIPMENT: CLEAN, BODY COVERING CLOTHING ANDFOOTWEAR.

#### **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

NOTE: OTHER PROPERTIES ARE EITHER NOT AVAILABLE, OR DO NOTAPPLY.

#### **SECTION 10 - STABILITY AND REACTIVITY**

- STABILITY: STABLE UNDER NORMAL STORAGE CONDITIONS. UNSTABLE AT ELEVATED
  TEMPERATURES. SLOWLY CORRODES COPPER, ALUMINUM, ZINC AND GALVANIZED SURFACES.
- INCOMPATIBILITY: STRONG OXIDIZING AGENTS, ORGANIC, LEWIS, OR MINERAL ACIDS, NITROUS ACID, SODIUM HYPOCHLORITE, AND PEROXIDES.
- HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON AND NITROGEN, NITRIC ACID, NITROSOAMINE, AND OTHER UNKNOWN ORGANIC COMPOUNDS.

#### **SECTION 11 - TOXICOLOGICAL INFORMATION**

#### EFFECTS OF OVEREXPOSURE:

## ACUTE:

- **EYES:** CAUSES SEVERE CONJUNCTIVAL IRRITATION, CORNEAL INJURY ANDIRITIS.
- **SKIN:** MAY CAUSE IRRITATION, BURNS, ULCERATION, OR SKINSENSITIZATION.
- INHALATION: VAPORS ARE IRRITATING AND MAY CAUSE TEARS, BURNING OF NOSE AND THROAT, COUGHING, WHEEZING, NAUSEA, AND VOMITING.
- INGESTION: MODERATELY TOXIC, MAY CAUSE MOUTH AND THROAT BURNS, ABDOMINAL PAIN, NAUSEA, VOMITING, WEAKNESS, THIRST, AND COMA.

## CHRONIC:

 AMINE VAPORS MAY CAUSE LIVER & KIDNEY INJURY. EYE, SKIN OR LUNG DISORDERS MAY DEVELOP OR BE AGGRAVATED BY AMINES.

#### **SECTION 12 - ECOLOGICAL INFORMATION**

#### **ECOTOXICITY EFFECTS:**

- AQUATIC TOXICITY: NO DATA IS AVAILABLE ON THE PRODUCTITSELF.
- TOXICITY TO OTHER ORGANISMS: NO DATA AVAILABLE.

## PERSISTANCE AND DEGRADABILITY:

- MOBILITY: NO DATA IS AVAILABLE ON THE PRODUCTITSELF.
- BIOACCUMULATION: NO DATA IS AVAILABLE ON THE PRODUCTITSELF.

#### **SECTION 13 - DISPOSAL CONSIDERATIONS**

- WASTE DISPOSAL METHOD: DISPOSE OF WASTE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.
- **CONTAINER DISPOSAL:** SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, ALL LABELED HAZARD PRECAUTIONS MUST BE OBSERVED. CONSULT WITH FEDERAL, STATE, AND LOCAL AUTHORITIES FOR DEFINITIONS OF "EMPTY" AND PROPER DISPOSALPRACTICES.

#### **SECTION 14 - TRANSPORT INFORMATION**

#### U.S. Department of Transportation Ground (49 CFR)

| UN NUMBER::            | UN 1/60                  |
|------------------------|--------------------------|
| PROPER SHIPPING NAME : | CORROSIVE LIQUID, N.O.S. |

PROPER SHIPPING NAME.....: CORROSIVE LIQUID, N.O.S.
CONTAINS...... MODIFIED AMINE MIXTURE

HAZARD CLASS....... 8
PACKAGING GROUP...... II

## • International Air Transportation (ICAO/IATA)

| UN NUMBER:: | UN 1760 |  |
|-------------|---------|--|

PROPER SHIPPING NAME...... CORROSIVE LIQUID, N.O.S. MODIFIED AMINE MIXTURE

HAZARD CLASS...... 8
PACKAGING GROUP...... II

## • Water Transportation (IMO/IMDG)

UN NUMBER......: UN 1760
PROPER SHIPPING NAME.....: CORROSIVE LIQUID, N.O.S.

HAZARD CLASS.....: 8
PACKAGING GROUP....: II
MARINE POLLUTANT...: NO

## **SECTION 15 - REGULATORY INFORMATION**

# CAL SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT OF 1986 NO. CHEMICAL NAME CAS. NO. CANCER/REPRO.TOX QUANTITY

3 BISPHENOL A 80-05-7 NO PENDING < 4%

THIS PRODUCT MAY CONTAIN TRACES OF PROP. 65 LISTEDCHEMICALS AS IMPURITIES. HOWEVER, ANY USED AS INGREDIENTS ARE LISTED ABOVE.

## **CERCLA — §40 CFR 302.4**

RELEASES EXCEEDING THE REPORTABLE QUANTITY (**RQ)** MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER. (800)424-8802

RQ = 100 lbs. (UNLISTED HAZARDOUS WASTE - CHARACTERISTIC OF CORROSIVITY)

#### RCRA - §40 CFR 261.33

RQ = 1000 lbs. (UNLISTED CORROSIVE CONTENT > 10%)

| SARA | TITLE III — | §52 CI | FR 1337 | 8, §52 | CFR 21152 |
|------|-------------|--------|---------|--------|-----------|
|      |             |        |         |        |           |

| NO. | RQ(lbs.) | TPQ(lbs.)  | SEC.313    | 313 CAT. | 311/312 |
|-----|----------|------------|------------|----------|---------|
|     | (•1)     | (•2)       | (•3)       | (•4)     | (•5)    |
| Р   | NONE     | NOT LISTED | NOT LISTED | NONE     | H1, H2  |
| 2   | NONE     | NOT LISTED | NOT LISTED | NONE     | H1      |
| 3   | NONE     | NOT LISTED | YES        | NONE     | H1, H2  |

- •1 = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC.302
- •2 = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC. 302
- •3 = TOXIC CHEMICAL, SEC. 313 (INDIVIDUAL CHEMICALLISTED)
- •4 = TOXIC RELEASE INVENTORY FORM CATEGORY SEC. 313 (40 CFR 372.65 C)
- •5 = HAZARD CATEGORY FOR SARA SEC. 311/312REPORTING
- $\mathbf{H1} = \text{IMMED.}$  (ACUTE) HEALTH HAZARD  $\mathbf{H2} = \text{DELAYED}$  (CHRONIC) HEALTH HAZARD
- P3 = FIRE HAZARD P4 = SUDDEN PRESSURE RELEASE HAZARD P5 = REACTIVEHAZ.

**VOC — SCAQMD RULES** 

NO. CHEMICAL QUANTITY VP mm Hg gms/l. @ 20°C

NIL

NOTE: THIS PRODUCT DOES NOT CONTAIN SOLVENTS, BUT MAY CONTAIN INGREDIENTS WITH VP'S LOW ENOUGH TO BE EMITTED IF HEATED ALONE. WHEN 2 PART RESINS AND HARDENERS ARE PROPERLY MIXED TOGETHER THESE INGREDIENTS REACT TOGETHER AND ARE CONSUMED WITHOUT SIGNIFICANT ATMOSPHERIC EMISSIONS.

## **INTERNATIONAL CHEMICAL INVENTORY STATUS:**

EINECS-EU Listed, Exempted, Polymer substance, or as no longerpolymer.

AICS-AUSTRALIA
ENCS-JAPAN
All components are listed or exempted.
ISHL-JAPAN
All components are listed or exempted.
KECI/ECL-KOREA
All components are listed or exempted.
IECSC/SEPA-CHINA All components are listed or exempted.
PICCS-PHILIPPINES All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.
TSCA-USA
All components are listed or exempted.

### WHMIS (CANADA)

WHMIS: D2B Materials Causing Other Toxic Effects – Toxic Material

WHMIS: E – Corrosive Material

#### **SECTION 16 - OTHER INFORMATION**

## **Revision Date**

August 28, 2019

| HMIS III CODES:       |             | RATINGS:    |
|-----------------------|-------------|-------------|
| HEALTH = <b>3</b>     | 0 = MINIMAL | 3 = SERIOUS |
| FLAMMABILITY <b>1</b> | 1 = SLIGHT  | 4 = SEVERE  |
| DEACTIVITY .          | 2 MODEDATE  |             |

REACTIVITY..... 2 = MODERATE

PERSONAL PROTECTION RATING TO BE SUPPLIED BY USER DEPENDING ON CONDITIONS OF USE.

| with <b>Fibre Glast Developments Corporation</b> or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. |
|---|
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |
|   |