



GHS SAFETY DATA SHEET (SDS)

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: Part # 626 - 6 LB. MIX AND POUR FOAM (Side B)

FIBRE GLAST DEVELOPMENTS CORP.
385 CARR DRIVE
BROOKVILLE, OH 45309

TELEPHONE: (937) 833-5200
FAX: (937) 833-6555
**FOR CHEMICAL EMERGENCY
CALL (801) 629-0667 24 HRS.**

CHEMICAL NAME: Polyurethane Resin

RECOMMENDED USE: Component for the manufacture of Polyurethanes

SECTION 2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification:	
• Skin irritation, Category 3	• Eye irritation, Category 2

GHS Labeling:



WARNING

Hazard Statements:	
• May cause skin irritation	• May cause eye irritation
• May cause respiratory irritation	

Precautionary Statements:	
• Do not breathe fume/gas/mist/vapors/spray	• Wear protective gloves/eye protection/face protection
• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	• IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
• IF ON SKIN: Wash with plenty of soap and water.	

Other Hazards:

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components

Type of Product: Mixture

CAS#	Weight %	Name
Proprietary	<1%	Tertiary amine catalysts
102687-65-0	4 - 7%	Trans-1-Chloro-3,3,3-trifluoropropene (CF ₃ HC=CHCl or HFO-1233zd)

SECTION 4 – FIRST AID MEASURES

Inhalation:	Move to fresh air if symptoms develop. If breathing is difficult, give oxygen and call physician.
Eye Contact:	Flush with water for at least 15 minutes. See a physician if irritation develops.
Ingestion:	Do not induce vomiting unless told to do so by a medical professional.
Most important symptoms and effects, acute and delayed:	May cause skin or eye irritation upon contact. Avoid breathing vapors. The dense vapors can displace and reduce breathing air in confined or unventilated spaces causing asphyxiation. Overexposure may cause tremors, confusion, irritation, and may result in cardiac sensitization.
Indication of immediate medical attention and special treatment, if applicable:	N/A
Skin Contact:	Wash with soap and water at first opportunity.

SECTION 5 – FIRE-FIGHTING MEASURES

Suitable extinguishing media:	Water, dry chemicals, CO ₂
Unsuitable extinguishing media:	None
Special hazards arising from the chemical:	Overheated containers may rupture due to pressure produced by CF ₃ HC=CHCl. CF ₃ HC=CHCl burns to form acids and noxious gases.
Precautions for fire-fighters:	A self-contained breathing apparatus should be worn to protect against toxic and irritating vapors.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures:	Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.
Environmental precautions:	Do not discharge into drains, surface waters, or ground water.
Methods and material for containment and cleanup:	Absorb with sawdust, etc., and shovel into container. Waste material should be disposed of under conditions which meet federal, state and local environmental regulations.

SECTION 7 – HANDLING AND STORAGE

Precautions for safe handling:	Store between 65°F and 85°F out of sunlight. Relieve pressure slowly when opening container. Under no circumstances should empty drums be burned or cut open with an electric or gas torch.
Conditions for safe storage, including any incompatibilities:	Keep tightly sealed.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

Components:	Type:	Value:
Tertiary Amine Catalysts ¹		None established
Trans-1-Chloro-3,3,3-trifluoropropene1 (CF ₃ HC=CHCl or HFO-1233zd)	TWA	300ppm recommended

¹ Not listed as a carcinogen (NTA, IARC, OSHA)

Exposure Controls:

Respiratory Protection:	The specific respirator selected must be based on contamination levels of this material found in the workplace and the working limits of the respirator. A supplied air, full-face mask, positive pressure or continuous flow respirator or a supplied air hood is required when airborne concentrations are unknown or exceed threshold limit values. A positive pressure, self-contained breathing apparatus can be used in emergencies or other unusual situations. Full-face air purifying respirators equipped with organic vapor cartridges can be used in certain situations, see OSHA standard 29CFR 1910.134 . All equipment must be NIOSH approved and maintained.
Hand, eye, skin, body protection:	Wear goggles or chemical safety glasses and chemically resistant rubber or plastic gloves. Avoid eye and skin contact. Eye wash system and showers should be available.

SECTION 9 –PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Liquid	Flammability:	N/A
Color:	Brown	Upper/lower flammability or explosive limits	N/A
Odor:	Ethereal odor	Vapor pressure:	N/A
Odor threshold:	N/A	Vapor density:	N/A
pH:	N/A	Relative density:	1.12 g/ml
Melting point/ Freezing point:	<32°F	Solubility(ies):	Slightly soluble in water
Boiling point/ Boiling range:	67°F	Partition coefficient (n-octanol/water)	N/A
Flash point:	>200°F	Auto-ignition temperature:	>500°F
Evaporation rate:	Slower than ether	Decomposition temperature:	>500°F

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability:	Stable
Possibility of hazardous reactions:	N/A
Conditions of avoid:	Temperatures over 85°F
Incompatible materials:	Isocyanates and other chemicals that react with hydroxyl groups.
Hazardous decomposition products:	When burned, CO, CO ₂ , NO _x aliphatic fragments, halogens, halogen acids and possibly carbonyl halides.

SECTION 11 – TOXICOLOGICAL INFORMATION

Acute toxicity:	May cause skin irritation
Chronic toxicity:	Not available
Likely routes of exposure:	Skin
Symptoms related to physical, chemical, and toxicological characteristics:	May cause skin irritation
Delayed and immediate effects and chronic effects from short and long-term exposure:	May cause skin irritation; avoid contact with eyes.
Numerical toxicity measures:	Not available

SECTION 12 – ECOLOGICAL INFORMATION

Eco-toxicity:	Not a marine pollutant
Persistence and degradability:	No known significant effects
Bio-accumulative potential:	Does not bio-accumulate
Mobility in soil:	

SECTION 13 - DISPOSAL CONSIDERATIONS

Water disposal:	R component drums can be sent to drum reconditioners or disposed of as ordinary industrial waste in compliance with pertinent regulations
------------------------	---

SECTION 14 - TRANSPORT INFORMATION

UN Number:	Not regulated
UN Proper shipping name	Not regulated
Transport Hazard class(es):	Not regulated
Packing group, if applicable:	Not regulated
Marine Pollutant (Y or N):	N
Special Precautions:	None

SECTION 15 – REGULATORY INFORMATION

Relevant safety, health, and environmental regulations:

Inventory status:	All components TSCA Listed
US regulations:	No ingredients listed
US Superfund Amendments and Reauthorization Act (SARA) Title III Section 313 Information:	No ingredients listed

SECTION 16 – OTHER INFORMATION

SDS Preparation Date:	03/22/2019
Revision Date:	

The information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of Fibre Glast Developments Corporation. The data on this sheet relates only to the specific material designated herein. Fibre Glast Developments Corporation assumes no legal responsibility for use or reliance upon these data.