

GHS SAFETY DATA SHEET (SDS)

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: Part #4121 Non-Silicone High Temp Paste Wax

FIBRE GLAST DEVELOPMENTS CORP. 385 CARR DRIVE BROOKVILLE, OH 45309

FAX: (937) 833-6555 FOR CHEMICAL EMERGENCY CALL (801) 629-0667 24 HRS.

TELEPHONE: (937) 833-5200

RECOMMENDED USE: Industrial Paste Wax supplied exclusively for workplace use.

SECTION 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION

Eye irritation : Category 2B

Acute Toxicity (Oral and Dermal)

: Category 5

Target Organ

Systemic Toxicity (single exposure)

: Category 3

Target Organ

Systemic Toxicity (repeated exposure)

: Category 2

GHS Label Element

Hazard pictogram



Signal word : Warning

Hazard statements : H320 Causes eye irritation.

H303 May be harmful if swallowed. H313 May be harmful in contact with skin. H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements: P202 Do not handle until all safety precautions have been read/understood.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P270 Do not eat, drink or smoke when using this product. P281 Use personal protective equipment as required.

P285 In case of inadequate ventilation wear respiratory protection.

P273 Avoid release to the environment.

NO.	CANCER	REPRO-TOX	TARGET ORGANS	ACGIH/TLV	OSHA/PEL
Р	NO	NO	UNKNOWN	N.A.mg/M ³	N.A.mg/M ³
2	NO	NO	LUNG, KIDNEY, CNS	100 mg/M ³	100 mg/M^3
3	NO	NO	LUNG, KIDNEY, CNS	400 ppm	400 ppm

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

UNDER GHS-OSHA §4.11 THE PRECISE COMPOSITION OF THIS PRODUCT IS WITHHELD AS CONFIDENTIAL BUSINESS INFORMATION (CBI). A MORE COMPLETE DISCLOSURE CAN BE PROVIDED TO A HEALTH, OR SAFETY PROFESSIONAL WHEN NECESSARY.

Substance/Mixture: Mixture

100%
65%
3%

SECTION 4 - FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

- EYES: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.
- **SKIN:** WASH AFFECTED AREA IMMEDIATELY WITH LARGE AMOUNTS OF SOAP AND WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. CONTACT A PHYSICIAN IF IRRITATION OCCURS.
- INHALATION: REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.
- INGESTION: DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES OF WATER. CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUSPERSON.

SECTION 5 - FIRE-FIGHTING MEASURES

FLASH POINT: ≥ 175°F (FOR PRODUCT OR LOWEST FLASH POINT INGREDIENT) FLAMMABILITY CLASSIFICATION: COMBUSTIBLE CLASS (IIIA)

EXTINGUISHING MEDIA: WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, OR FOAM.

NOTE: EITHER ATMOSPHERE-SUPPLY OR AIR-PURIFYING RESPIRATORS SHOULD BE AVAILABLE FOR FIRE FIGHTERS (20 CFR 1910.134).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- IF MATERIAL IS SPILLED: AVOID CONTACT WITH MATERIAL. PERSONS NOT WEARING PROPER PROTECTIVE EQUIPMENT (SEE BELOW) SHOULD BE EXCLUDED FROM THE AREA UNTIL CLEAN UP IS COMPLETE. DIKE AREA TO PREVENT SPILL SPREADING AND SCOOP UP EXCESS TO RECOVERY CONTAINERS. ABSORB REMNANT ON NONCUMBUSTIBLE MATERIAL SUCH AS CLAY AND SHOVEL INTO CONTAINERS FOR DISPOSAL.
- WASTE DISPOSAL METHOD: DISPOSE OF ANY WASTE(S) GENERATED ABOVE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION 7 - HANDLING AND STORAGE

- AVOID SKIN AND EYE CONTACT.
- AVOID BREATHING VAPOR, MIST OR FUMES.
- ENSURE THAT ALL CONTAINERS ARE PROPERLY LABELED TO PREVENT ACCIDENTAL INGESTION OR IMPROPER DISPOSAL.
- RESEAL PARTLY USED CONTAINERS.
- WASH WITH SOAP AND WATER BEFORE EATING, DRINKING OR USING TOILETFACILITIES.
- STORE UNDER COOL, DRY CONDITIONS AND AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES
- OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKINGPRACTICE.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION: NOT NORMALLY NECESSARY UNLESS THE MATERIAL IS BEING USED IN SUCH A WAY AS TO PRODUCE DUST, MIST, VAPOR, FUMES, OR SMOKE, IN WHICH CASE NIOSH APPROVED RESPIRATORY PROTECTION SHOULD BE USED.

VENTILATION: SHOULD BE SUFFICIENT TO CONTROL ANY DUST, MIST, VAPOR OR FUMES PRODUCED BY PROCESSING OR HANDLING METHOD. BREATHING OF VAPOR MUST BE AVOIDED.

HAND PROTECTION: IMPERVIOUS GLOVES, NEOPRENE OR NILRILE RUBBER GLOVES. EYE PROTECTION: SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS. OTHER PROTECTIVE EQUIPMENT: CLEAN, BODY COVERING CLOTHING AND FOOTWEAR.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

■ VAPOR PRESSURE......: < 32 mm Hg @ 100°F

NOTE: OTHER PROPERTIES ARE EITHER NOT AVAILABLE, OR DO NOT APPLY.

SECTION 10 - STABILITY AND REACTIVITY

STABILITY: STABLE UNDER NORMAL STORAGE CONDITIONS. UNSTABLE AT ELEVATED TEMPERATURES. **INCOMPATIBILITY:** STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS, AND STRONG MINERAL AND ORGANIC BASES.

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON, AND OTHER UNKNOWN ORGANIC COMPOUNDS.

SECTION 11 - TOXICOLOGICAL INFORMATION

EFFECTS OF OVEREXPOSURE:

ACUTE:

- EYES: LIQUID, VAPORS AND MIST ARE IRRITATING AND CAN CAUSE A STINGING SENSATION, TEARING, REDDENING AND SWELLING OF THE EYES.
- SKIN: MODERATELY IRRITATING, & MAY CAUSE SKIN DEFATTING ORSENSITIZATION.
- INHALATION: CAN CAUSE NASAL AND RESPIRATORY IRRITATION, CNS EFFECTS INCLUDING FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS, AND EVEN DEATH.
- INGESTION: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA. ASPIRATION OF THE MATERIAL INTO THE LUNGS CAN CAUSE FATAL CHEMICAL PNEUMONITIS._ CHRONIC:
- EXPOSURE MAY DAMAGE PERIPHERAL NERVE TISSUE & RESULT IN PERIPHERAL NEUROPATHY. MAY CAUSE KIDNEY DAMAGE OR CNS EFFECTS. PREEXISTING DISORDERS MAY ALSO BE AGGRAVATED BY EXPOSURE.

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY EFFECTS:

- AQUATIC TOXICITY: NO DATA IS AVAILABLE ON THE PRODUCTITSELF.
- TOXICITY TO OTHER ORGANISMS: NO DATA AVAILABLE.

PERSISTENCE AND DEGRADABILITY:

- MOBILITY: NO DATA IS AVAILABLE ON THE PRODUCTITSELF.
- BIOACCUMULATION: NO DATA IS AVAILABLE ON THE PRODUCTITSELF.

SECTION 13 - DISPOSAL CONSIDERATIONS

- WASTE DISPOSAL METHOD: DISPOSE OF WASTE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.
- CONTAINER DISPOSAL: SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, ALL LABELED HAZARD PRECAUTIONS MUST BE OBSERVED. CONSULT WITH FEDERAL, STATE, AND LOCAL AUTHORITIES FOR DEFINITIONS OF "EMPTY" AND PROPER DISPOSAL PRACTICES.

SECTION 14 - TRANSPORT INFORMATION

• U.S. Department of Transportation Ground (49 CFR)

UN NUMBER:	N.A.
PROPER SHIPPING NAME:	BUFFING OR POLISHING COMPOUNDS, N.O.I.
CONTAINS:	NOT REGULATED*
HAZARD CLASS:	N.A.
PACKAGING GROUP:	N.A.

• International Air Transportation (ICAO/IATA)

ON NOPIDER	N.A.
PROPER SHIPPING NAME:	BUFFING OR POLISHING COMPOUNDS, N.O.I.
CONTAINS:	NOT REGULATED*
HAZARD CLASS:	N.A.
PACKAGING GROUP .	N.A.

Water Transportation (IMO/IMDG) IIIN NI IMBED

UN NUMBER:	N.A.
PROPER SHIPPING NAME:	BUFFING OR POLISHING COMPOUNDS, N.O.I.
CONTAINS:	NOT REGULATED*
HAZARD CLASS:	N.A.
PACKAGING GROUP:	N.A.
MARINE POLLUTANT:	NO

^{*}Non-Bulk Packages may be shipped as Non-Regulated under §49 CFR 173.150(f).

SECTION 15 - REGULATORY INFORMATION

CAL SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT OF 1986 NO. CHEMICAL NAME CAS. NO. CANCER/REPRO.TOX QUANTITY

THIS PRODUCT MAY CONTAIN TRACES OF PROP. 65 LISTED CHEMICALS AS IMPURITIES. HOWEVER, ANY USED AS INGREDIENTS ARE LISTED ABOVE.

CERCLA — §40 CFR 302.4

RELEASES EXCEEDING THE REPORTABLE QUANTITY (**RQ**) MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER. (800)424-8802

RQ NOT ESTABLISHED OR REQUIRED FOR THIS PRODUCT.

RCRA - §40 CFR 261.33

PRODUCT IS A HAZARDOUS WASTE. DISPOSE BY INCINERATION.

SARA TITLE III — §52 CFR 13378, §52 CFR 21152					
NO.	RQ(lbs.)	TPQ(lbs.)	SEC.313	313 CAT.	311/312
	(•1)	(•2)	(•3)	(•4)	(•5)
Р	NONE	NOT LISTED	NOT LISTED	NONE	H1
2	NONE	NOT LISTED	NOT LISTED	NONE	H1
3	NONE	NOT LISTED	NOT LISTED	NONE	H1

- •1 = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC.302
- •2 = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC. 302
- •3 = TOXIC CHEMICAL, SEC. 313 (INDIVIDUAL CHEMICAL LISTED)
- •4 = TOXIC RELEASE INVENTORY FORM CATEGORY SEC. 313 (40 CFR 372.65C)
- •5 = HAZARD CATEGORY FOR SARA SEC. 311/312 REPORTING
- H1 = IMMED. (ACUTE) HEALTH HAZARD H2 = DELAYED (CHRONIC) HEALTH HAZARD
- P3 = FIRE HAZARD P4 = SUDDEN PRESSURE RELEASE HAZARD P5 = REACTIVE HAZ.

VOC — SCAQMD RULES

NO.	CHEMICAL	QUANTITY	VP mm HG	gms./I. @ 20°C
2	HI DISTILLATE (# 64/42-4/-8)	< 65%	∠ @ TUU~L	< 526
3	2-PROPANOL	< 3%	32 @ 100°F	< 24

NOTE: Products' Typical VOC by % Calculation = 533 gms./l.

INTERNATIONAL CHEMICAL INVENTORY STATUS:

EINECS-EU Listed, Exempted, Polymer substance, or as no longer polymer.

AICS-AUSTRALIA
ENCS-JAPAN
All components are listed or exempted.
ISHL-JAPAN
All components are listed or exempted.
KECI/ECL-KOREA
IECSC/SEPA-CHINA All components are listed or exempted.
PICCS-PHILIPPINES All components are listed or exempted.
CANADA
All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.
TSCA-USA
All components are listed or exempted.

WHMIS (CANADA):

- WHMIS: D2B Materials Causing Other Toxic Effects Toxic Material
- WHMIS: B3 Combustible Liquids Flashpoint of 37.8° 93.3°C (100° -200°F)

SECTION 16 - OTHER INFORMATION

Revision Date

5/4/2023

HMIS III CODES:	RATINGS:		
HEALTH 1	0 = MINIMAL 3 = SERIOUS		
FLAMMABILITY 2	1 = SLIGHT 4 = SEVERE		
REACTIVITY = 0	2 = MODERATE		

PERSONAL PROTECTION RATING TO BE SUPPLIED BY USER DEPENDING ON CONDITIONS OF USE.

The information accumulated herein is believed to be accurate but is not warranted to be, whether originating with **Fibre Glast Developments Corporation** or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.