



HomeGuard™ HOUSEWRAP

Protecting you from the harsh elements of Mother Nature, HomeGuard™ housewrap excels in air and water resistance, moisture vapor permeability and durability. HomeGuard housewrap is an engineered, woven, polyolefin material designed for use as a secondary weather resistive barrier. The strong woven fabric ensures jobsite durability, even in the harshest conditions. HomeGuard's micro-perforations allow damaging moisture as a vapor to escape while shedding bulk water.



HomeGuard is designed to protect commercial and residential buildings from Mother Nature by excelling in four crucial areas:



Air Resistance - Protects the wall assembly from air infiltration to increase the comfort of the building by reducing drafts and increasing energy efficiency.



Moisture Vapor Permeability - Preserves the integrity of the wall assembly by allowing the moisture as vapor to escape to the outside.



Water Resistance - Protects the wall assembly against water intrusion that gets behind the exterior cladding.



Durability - Has the ability to withstand the elements of the weather and tough jobsite conditions.

Test	Method	Units	HomeGuard	Minimum Requirement
Tensile Strength				
Machine Direction	ASTM D 5034	lbs.	119	20
Cross Direction	ASTM D 5034	lbs.	50	20
Air Permeance	ASTM E 2178	L/s/m ² @75 PA cfm/ft ² @1.57 psf	.00018 .0000	0.02 0.004
Water Resistance	ASTM D 779	Minutes	24 Hrs Pass	10 Minutes
Water-vapor Transmission	ASTM E 96	Perms	>8.5	5
Low Temperature Bend	AC38 Section 3.3.4	N/A	Pass	Pass
UV Exposure	AC38 Section 4.1.2	N/A	6 Months	120 Days

Build your business with Custom Imprinting on HomeGuard™ Housewrap



- Imprint your company logo - only one pallet minimum
- Largest exposure area - 40" x 30"
- Many colors are available
- Short lead times - 3 to 4 weeks on initial order, 2 weeks on reorders
- Logo repeats every 48" in center lane
- Available on 9' and 10' wide material

Putting it all together!

Using HomeGuard Housewrap is a great first step in protecting your home or project from Mother Nature's harsh elements. Help protect windows, doors and other critical areas from damaging moisture by using high quality HomeGuard Synthetic Flashing, HomeGuard Flexible Butyl Flashing and HomeGuard Seam Tape. Assure peace of mind when you use the HomeGuard System.

HomeGuard Synthetic Flashing has an extremely aggressive adhesive which can be applied down to -20F° and is compatible with caulking and sealants. HomeGuard Flexible Butyl Flashing is for custom shapes and window sill pan protection.

HomeGuard Seam Tape is a high-density polypropylene facer coated with an acrylic adhesive designed for sealing housewrap seams.

HomeGuard Housewrap Roll Sizes and Quantities

3' x 100' - 234 rolls
3' x 150' - 165 rolls
3' x 195' - 120 rolls

4.5' x 100' - 156 rolls
4.5' x 150' - 110 rolls
5' x 200' - 80 rolls

9' x 100' - 78 rolls
9' x 150' - 55 rolls

10' x 100' - 78 rolls
10' x 150' - 55 rolls



**Homeguard
Building Products
Inc.**

6797 Thoreau Lane
Baltimore, OH 43105
Office: 616.846.0804
Fax: 866.337.4016
www.homeguardhousewrap.com



ESR-2638
CCMC 13424-R



HomeGuard