

General			
Line Enable:	yes		
Streaming Audio Server (SAS)			
SAS Enable:	no	SAS DLG Refresh Intvl:	30
SAS Inbound RTP Sink:			
NAT Settings			
NAT Mapping Enable:	yes	NAT Keep Alive Enable:	yes
NAT Keep Alive Msg:	\$NOTIFY	NAT Keep Alive Dest:	\$PROXY
Network Settings			
SIP ToS/DiffServ Value:	0x68	SIP CoS Value:	3 [0-7]
RTP ToS/DiffServ Value:	0xb8	RTP CoS Value:	6 [0-7]
Network Jitter Level:	high	Jitter Buffer Adjustment:	yes
SIP Settings			
SIP Transport:	UDP	SIP Port:	5060
SIP 100REL Enable:	no	EXT SIP Port:	
Auth Resync-Reboot:	yes	SIP Proxy-Require:	
SIP Remote-Party-ID:	yes	SIP GUID:	no
SIP Debug Option:	none	RTP Log Intvl:	0
Restrict Source IP:	no	Referor Bye Delay:	4
Refer Target Bye Delay:	0	Referee Bye Delay:	0
Refer-To Target Contact:	no	Sticky 183:	no
Auth INVITE:	no	Reply 182 On Call Waiting:	no
Use Anonymous With RPID:	yes	Use Local Addr In FROM:	no
Call Feature Settings			
Blind Attn-Xfer Enable:	no	MOH Server:	
Xfer When Hangup Conf:	yes	Conference Bridge URL:	
Conference Bridge Ports:	3	Enable IP Dialing:	no
Emergency Number:		Mailbox ID:	
Feature Key Sync:	no		
Proxy and Registration			
Proxy:			
Outbound Proxy:	sip1.freshphone.co.za		
Use Outbound Proxy:	yes	Use OB Proxy In Dialog:	yes
Register:	yes	Make Call Without Reg:	no

Register Expires:	3600	Ans Call Without Reg:	no
Use DNS SRV:	yes	DNS SRV Auto Prefix:	yes
Proxy Fallback Intvl:	3600	Proxy Redundancy Method:	Normal
Mailbox Subscribe URL:		Mailbox Subscribe Expires:	2147483647
Auto Register When Failover:	no		

Subscriber Information

Display Name:	2787237****	User ID:	2787237****
Password:	*****	Use Auth ID:	yes
Auth ID:	2787237****	Resident Online Number:	2787237****
SIP URI:	sip1.freshphone.co.za		

Supplementary Service Subscription

Call Waiting Serv:	yes	Block CID Serv:	yes
Block ANC Serv:	yes	Dist Ring Serv:	yes
Cfwd All Serv:	yes	Cfwd Busy Serv:	yes
Cfwd No Ans Serv:	yes	Cfwd Sel Serv:	yes
Cfwd Last Serv:	yes	Block Last Serv:	yes
Accept Last Serv:	yes	DND Serv:	yes
CID Serv:	yes	CWCID Serv:	yes
Call Return Serv:	yes	Call Redial Serv:	yes
Call Back Serv:	yes	Three Way Call Serv:	yes
Three Way Conf Serv:	yes	Attn Transfer Serv:	yes
Unattn Transfer Serv:	yes	MWI Serv:	yes
VMWI Serv:	yes	Speed Dial Serv:	yes
Secure Call Serv:	yes	Referral Serv:	yes
Feature Dial Serv:	yes	Service Announcement Serv:	no
Reuse CID Number As Name:	yes	CONFCID Serv:	yes

Audio Configuration

Preferred Codec:	G729a	Second Preferred Codec:	G711u
Third Preferred Codec:	Unspecified	Use Pref Codec Only:	no
Use Remote Pref Codec:	no	Codec Negotiation:	Default
G729a Enable:	yes	Silence Supp Enable:	no
G726-32 Enable:	yes	Silence Threshold:	medium
FAX V21 Detect Enable:	yes	Echo Canc Enable:	yes
FAX CNG Detect Enable:	yes	FAX Passthru Codec:	G711u

FAX Codec Symmetric:	yes ▼	DTMF Process INFO:	yes ▼
FAX Passthru Method:	NSE ▼	DTMF Process AVT:	yes ▼
FAX Process NSE:	yes ▼	DTMF Tx Method:	Auto ▼
FAX Disable ECAN:	no ▼	DTMF Tx Mode:	Strict ▼
DTMF Tx Strict Hold Off Time:	70	FAX Enable T38:	no ▼
Hook Flash Tx Method:	None ▼	FAX T38 Redundancy:	1 ▼
FAX T38 ECM Enable:	yes ▼	FAX Tone Detect Mode:	caller or callee ▼
Symmetric RTP:	no ▼	FAX T38 Return to Voice:	no ▼
Modem Line:	no ▼	RTP to Proxy in Remote Hold:	no ▼

Dial Plan

Dial Plan:	(*xx [3469]11 0 00 [2-9]xxxxx 1xx[2-9]xxxxxS0 xxxxxxxxxx.)
------------	--

FXS Port Polarity Configuration

Idle Polarity:	Forward ▼	Caller Conn Polarity:	Forward ▼
Callee Conn Polarity:	Forward ▼		