

# PRE-DELIVERY INSPECTION

## HEDGE TRIMMERS



### ASSEMBLY

- Fill the machine up with 2-stroke fuel.
- Start and warm up the engine.
- Lubricate the blades.
- Check the RPM's with a revolution counter and adjust the carburettor if needed following the adjustment procedures.

### SAFETY FUNCTIONS

- Inspect and check the blade guard and nose protection.
- Inspect and check the stop switch.
- Inspect the throttle trigger lockout.
- Inform the customer about start/stop procedure, safety functions, personal protective equipment, basic maintenance and oil, fuels, sprays and grease.

### SERVICE AND MAINTENANCE

- Every 20-30 minutes lubricate the blades to optimize the cutting deck performance.
- Every 15-20hrs greasing of the gear case.
- 1st service: After 8 to 15hrs of use.
- 2nd service: Consumer every 50hrs or once/year  
Professional every 150hrs or once/year.

Model: HC-\_\_\_\_\_

Serial number: \_\_\_\_\_

Dealer: \_\_\_\_\_

Date: \_\_\_\_\_

Dealer Stamp & signature \_\_\_\_\_

Customer's signature \_\_\_\_\_

# PRE-DELIVERY INSPECTION

---

## BEFORE EVERY USE CHECK ALL THE SAFETY FUNCTIONS

- Stop switch
- Anti- vibration springs
- Throttle lock
- Blade guard
- Nose tip

Maintenance before every use see page ..... in the owner's manual.

## FUEL

- Euro 95 + 2% Echo oil (Store own blended fuel for maximum 2 weeks)
- Alkylate 2T (Store Alkylate 2T fuel for maximum 3 years)