

PRE-DELIVERY INSPECTION

TRIMMERS, BRUSHCUTTERS and CLEARING SAWS



ASSEMBLY

- Assemble the machine and cutting equipment (trimmer head).
- Fill the machine up with 2-stroke fuel.
- Start and warm up the engine.
- Extend the trimmer line to the maximum length.
- Check the RPM's with a revolution counter and adjust the carburettor if needed following the adjustment procedures.

SAFETY FUNCTIONS

- Inspect and check the guard and cut-off blade.
- Inspect and check the stop switch.
- Inspect the throttle trigger lockout.
- Inform the customer about start/stop procedure, how to adjust the harness, safety functions, how to change the cutting equipment, personal protective equipment, basic maintenance and oil, fuels and grease.
- Hand over the user manual.

SERVICE AND MAINTENANCE

- Every month greasing of the bevel gear/ gear case.
- 1st service: after 8 to 15hrs of use.
- 2nd service: Consumer every 50hrs or once/year Professional every 150hrs or once/year.

Model: SRM- _____

Serial number: _____

Dealer: _____

Date: _____

Dealer Stamp & signature

Customer's signature

PRE-DELIVERY INSPECTION

BEFORE EVERY USE CHECK ALL THE SAFETY FUNCTIONS

- Stop switch
- Anti- vibration springs
- Throttle lock
- Shield

Maintenance before every use see page in the owner's manual.

CUTTING EQUIPMENT INFO.

- Blade diameter:.....
- Blade fitting diameter:.....
- Trimmer head:.....
- Trimmer line diameter:.....

FUEL

- Euro 95 + 2% Echo oil (Store own blended fuel for maximum 2 weeks)
- Alkylate 2T fuel (Store Alkylate 2T fuel for maximum 3 years)