

Notice: Only CSN is supported for DESFire EV1 in BioStar 1. 2nd generation devices support smart card with DESFire EV1 and EV2 in BioStar 2

SUPREMA Device RF Options

Device Name	Model Name	RF Option	NFC / BLE	Note
BioEntry Plus	BEPL-OC	125kHz EM		
BioEntry Plus	BEPM-OC	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1 (CSN), ISO14443A		
BioEntry Plus	BEPH-OC	125kHz HID Prox		
BioEntry Plus	BEPI-OC	13.56MHz FeliCa, iCLASS SR, ISO15693		
BioEntry Plus	BEPI(FE)-OC	FeliCa		
BioEntry W	BEWM-OC	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1 (CSN), ISO14443A		
BioEntry W	BEWH-OC	125 kHz HID Prox		
BioEntry W	BEWI-OC	13.56MHz FeliCa, iCLASS SE/SR, ISO15693		
BioEntry W2	BEW2-OHP	125kHz HID Prox (supports 125kHz EM, 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1 (CSN), ISO14443A with fw 1.1.0 and above)		
BioEntry W2	BEW2-ODP	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, ISO14443A, ISO15693	NFC	DESFire EV2 supported in BioStar 2
BioEntry W2	BEW2-OAP	125kHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, iCLASS SE/SR, iClass SEOS, ISO14443A, ISO15693		Supports elite key with FW 1.1.3 and above
BioLite Net	BLR-OC	125kHz EM		
BioLite Net	BLN-OC	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1 (CSN), ISO14443A		
BioLite Solo	BLS-OC	N/A		
BioStation	BST-OC	N/A		
BioStation	BSTW-OC	N/A		
BioStation	BSR-OC	125kHz EM		
BioStation	BSRW-OC	125kHz EM		
BioStation	BSH-OC	125kHz HID Prox		
BioStation	BSM-OC	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1 (CSN), ISO14443A		
BioStation 2	BS2-OMPW	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, ISO14443A, ISO15693		DESFire EV2 supported in BioStar 2
BioStation 2	BS2-OIPW	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, iCLASS SE/SR, iClass SEOS, ISO14443A, ISO15693	NFC	Supports elite key with FW 1.5 and above
BioStation 2	BS2-OHPW	125kHz HID Prox		
BioStation 2	BS2-OEPW	125kHz EM		
BioStation L2	BSL2-OE	125kHz EM	NFC	
BioStation L2	BSL2-OM	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, ISO14443A, ISO15693		DESFire EV2 supported in BioStar 2
BioStation A2	BSA2-OEPW	125kHz EM		
BioStation A2	BSA2-OHPW	125kHz HID Prox		
BioStation A2	BSA2-OIPW	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, iCLASS SE/SR, iClass SEOS, ISO14443A, ISO15693,	NFC	Supports elite key with FW 1.4 and above
BioStation A2	BSA2-OMPW	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, ISO14443A, ISO15693		DESFire EV2 supported in BioStar 2
BioStation T2	BST2R-OC	125kHz EM		
BioStation T2	BST2RW	125kHz EM		
BioStation T2	BST2M-OC	13.56MHz MIFARE, MIFARE Plus, DESFire, ISO14443A		
BioStation T2	BST2MW-OC	13.56MHz MIFARE, MIFARE Plus, DESFire, ISO14443A		
FaceStation	FSM	13.56MHz MIFARE, DESFire/EV1 (CSN), ISO14443A		
FaceStation	FSMW	13.56MHz MIFARE, DESFire/EV1 (CSN), ISO14443A		
FaceStation 2	FS2-D	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1/EV2, FeliCa	NFC	
FaceStation 2	FS2-AWB	125kHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1/EV2, FeliCa, iCLASS SE/SR	NFC, BLE	
Xpass	XPE-PoE	125kHz EM		
Xpass	XPM-PoE	13.56MHz MIFARE, DESFire/EV1 (CSN)		
Xpass	XPH-PoE	125kHz HID Prox		
Xpass S2	XPS2M	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1 (CSN), FeliCa, ISO14443A, ISO15693		
X-Station	XSE	125kHz EM		
X-Station	XSM	13.56MHz MIFARE, MIFARE Plus, DESFire/EV1 (CSN), ISO14443A		
BioEntry Plus 2	BEP2-OD	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1/EV2, FeliCa	NFC	
BioEntry Plus 2	BEP2-OA	125kHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1/EV2, FeliCa, iCLASS SE/SR, iCLASS SEOS		
BioEntry R2	BER2-OD	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1/EV2, FeliCa	NFC	
Xpass D2	XPD2 (MDB/GDB/GKDB)	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1/EV2, FeliCa	NFC, BLE	
BioLiteNet 2	BLN2-ODB	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1/EV2, NFC & 2.4GHz BLE	NFC, BLE	
BioLiteNet 2	BLN2-OAB	125kHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1/EV2, FeliCa, iCLASS SE/SR, NFC & 2.4GHz BLE	NFC, BLE	