

CoreBlu A3

Preliminary Specifications



The CoreBlu line is an advanced Bluetooth Low Energy 5.x beacon devices using multi standard beacon technology.

The CoreBlu-A3 is specially conceived for advanced business solutions such as attendance and asset tracking using location based and indoor navigation-based applications. It features an ultra-low power consumption, long battery life. It can be used with lanyards and card clips and can also be easily mounted on various surfaces.

The CoreBlu-A3 comes with a downloadable SDK with an extensive library for easy integration into a wide range of location based and indoor navigation based applications. It also includes a wide range of tools facilitating optimal setup, installation and health-checks.



Bluetooth Radio

Type:

Bluetooth Low energy 5.0

Advertisement:

iBeacon, Eddystone (UID & TLM) & cBeacon (Averos Proprietary)

Advertisement Interval:

100ms to 10.2seconds

Frequency:

2.4GHz

Transmit Power:

+4dBm to -20 dBm

Antenna Type:

PCB antenna, Omni Directional

Sensors and Interfaces

Motion sensing	3 Axis Accelerometer
Button	1 user interact-able button
LED	1 Red LED

Battery

Battery type:

Sealed Lithium Manganese Dioxide, 800mAh, Non-replaceable

Battery Life:

(Advertisement Rate)	(Battery Life ¹)
High - 500 mSec	2 Years 6 Months
Medium - 1000 mSec	4 Years 2 Months
Low - 3000 mSec	7 Years 9 Months

1. Battery Life is calculated at 25 degrees Centigrade and 0 dbm transmit power.

Enclosure

Material:

ABS

Dimensions :

86 mm (L) x 54 mm(H) x 4.6 mm (T)

Weight:

19.5g

Color:

White

Accessories:

Lanyard & Card clip

Protection Class:

IP65

Operating Environment

Operating Temperature	0°C to 60°C
Operating Humidity	90%

Certifications

CE (Pending), FCC (Pending)



CoreBlu Configuration App

With the CoreBlu Beacon Manager App you can scan for nearby configurable CoreBlu beacons, display their battery status, view their settings and make modifications to those settings. Configuration of beacons are password protected with a four (4) digit user settable PIN.

As an added safety feature, the beacons can only be configured within a period of 15 minutes after installing the batteries or can be manually triggered into configuration mode by pressing the reset button on the Tag. However, this time duration can be increased through the settings to up to 3 weeks or forever.



Application Areas

- Indoor localization
- Track & find
- Virtual leash
- Asset & logistics tracking
- Luggage tracking

Caution

- *Dispose of used batteries according to the instructions*

Recycling

This product bears the selective sorting symbol for Waste electrical and electronic equipment (WEEE). This means that this product must be handled pursuant to European directive 2012/19/EU in order to be recycled or dismantled to minimize its impact on the environment

Contact us

 **Email us:**
sales@averos.com

 **Website:**
www.averos.com

All product names, logos, and brands are property of their respective owners. All company, product and service names used in this datasheets are for identification purposes only. Use of these names, logos, and brands does not imply endorsement.