

4 ports IP Power Comparison chart

20140715

	9258S	9258XX	9258HP	9858	9858- Ping	9858DX	9258W2
Hardware Features							
Port	4 IEC / 4 Nema	4 plug- 7 countries	4 IEC / 4 Nema	4 IEC / 4 Nema	4 IEC / 4 Nema	4 IEC / 4 Nema	4 IEC / 4 Nema
Wireless & WPS	X	X	X	Yes, WiFi 802.11n-b/g			
Current Meter	X	Total Meter	X	X	X	X	Per port meter
Voltage Meter	X	X	X	X	X	X	Yes
Temperature	X	X	X	X	X	X	Yes
USB Camera	X	X	X	X	X	X	Yes
Relay	Standard	Dual Cut Relay	High grade	High grade, 10Amp Max. per outlet			
Power Module MTBF	50K hrs	50K hrs	700K hrs min	50K hrs	50K hrs	800K hrs min	700K hrs min
Operation Temperature	0~ 50 (°C) / 32 ~ 122(°F)	0~ 50 (°C) / 32 ~ 122(°F)	" - 20~ 55C (°C) / - 4 ~130(°F)	0~ 50 (°C) / 32 ~ 122(°F)	0~ 50 (°C) / 32 ~ 122(°F)	" - 20~ 55 (°C) / - 4 ~130(°F)	" - 20~ 55 (°C) / - 4 ~130(°F)
Power Surge Protection	Yes	Yes	Higher grade	Yes	Yes	Higher grade	Higher grade
Power Input	Wide range to use both 100V ~230V AC . Standard C14 plug .						
Enclosure	Metal		Metal with ear	Metal & Gray			Metal & Blue
Size MM (LxWxH)	220 x 120 x 44	220 x 120 x 48	260 x 120 x 44	200 x 120 x 44	200 x 120 x 44	200 x 120 x 44	200 x 120 x 44

|