



TECHNICAL SPECIFICATIONS :

Valve Body:

Body Material:..... 304 Stainless Steel
Valve Stem:..... Nickel Plated Brass
Valve Ball:..... 304 Stainless Steel
Valve Seat:..... PTFE disc with backup ring
Valve Packing:..... Double O ring
with PTFE friction ring base

Close Off:..... 100% tight shut off
Working Pressure:..... 150 PSI (10 Bar)
Media Temperature:..... 32°F to 200°F (0°C to 92°C)

Actuator :

Rated Voltage:..... Self selecting from
..... 3V to 24V AC/DC, or 120V AC
Power:..... Max 5 watts
Output Torque:..... 17in/lb (2 NM)
Enclosure:..... NEMA 4 (IP 65)
Connection:..... 32" (1M) PVC Cable
Ambient Temperature:..... 40°F to 120°F
..... (5°C to 50°C)

Travel Time:..... 6 Seconds
Noise Level:..... 55 dB
Approvals:..... CSA Certified 1735440
Standard Features:..... Position Indication
..... Quick Clip Mounting
Optional Features:..... Manual Override

Agency Approvals:..... CE
ESC Certificate..... EN60534-2-3:1998
Quality Assurance System:..... 97/23/EC
Certified to..... NSF/ANSI Standard 61

One year warranty.

ACTUATOR TYPE MS1120/22, 2120

MS1120/2120 2 wire fail safe with position indicator



*Actuator with "Quick Connect" feature for
easy installation in difficult situations.*



DIMENSIONS:

