

# EN62479 TEST REPORT

|                |   |
|----------------|---|
| Prepared For   | Cloudstore Limited<br>Level 3, 32 Market Place, Viaduct, Auckland, New Zealand 1010   |
| Trade Mark     | : Airconsole  |
| Product Name   | : USB/WIFI Router   |
| Model          | : Airconsole, Airconsole Mini, Airconsole XL  |
| Prepared By    | : Shenzhen HUT Testing Technology Co.,Ltd<br>11F Baohe Building At The Intersection Of BaoAn Road And XiXiang Road BaoAn District ShenZhen City |
| Test Date      | : Apr, 15 - Apr. 22, 2015   |
| Date of Report | : Apr. 22, 2015   |
| Report No.     | : HUT11150415001HR  |

Name and address of the testing laboratory : **Shenzhen HUT Testing Technology Co.,Ltd**

11F Baohe Building At The Intersection Of BaoAn  
Road And XiXiang Road BaoAn District ShenZhen  
City

Date of Test:

**Apr. 15 – Apr. 22, 2015**

Prepared by(Engineer):

Kelly Chen

Reviewer(Quality Manager):

Dick Zhang

Approved&Authorized  
Signer(Manager):

Irene 

## 1. General Information

### 1.1 General Description Of EUT

|                        |   |
|------------------------|---|
| Equipment              | USB/WIFI Router   |
| Model Name.            | Airconsole, Airconsole Mini, Airconsole XL  |
| OEM Brand/Model Name   | <b>Airconsole</b>   |
| Model Difference       | N/A   |
| Applicant              | Cloudstore Limited  |
| Applicant Address      | Level 3, 32 Market Place, Viaduct, Auckland, New Zealand 1010   |
| Manufacturer           | Shenzhen Hwnet Times Tech Co., Ltd.   |
| Manufacturer Address   | A411 Mingyou Industrial Products Purchase Center, No.168 Baoyuan Road, Bao'an District Shenzhen   |
| Product Description    | The EUT is Wireless Data Terminal<br>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an USB/WIFI Router Device. More details of EUT technical specification, please refer to the User's Manual. |
| Channel List           | /   |
| Power Source           | DC 5V   |
| Power Rating           | DC 5W   |
| Connecting I/O Port(s) | Please refer to the User's Manual   |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

## 2. EN 62479 REQUIREMENT

### 2.1 GENERAL INFORMATION

The essential requirements of Directive 99/5/ec in the article 3.1(a) and the limits must be taken from Council Recommendation 99/519/EC for General Population or from the ICNIRP Guidelines for Occupational Exposure, EN 62479:2010 assesment of the compliance of low-power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

### 2.2 Limit

A. Typical usage, installation and the physical characteristics of equipment make it inherently compliant with the applicable EMF exposure levels such as those listed in the bibliography. This low-power equipment includes unintentional (or non-intentional) radiators, for example incandescent light bulbs and audio/visual (A/V) equipment, information technology equipment (ITE) and multimedia equipment (MME) that does not contain radio transmitters.

NOTE Equipment is described as A/V equipment, ITE or MME if its main use is playback/recording of music, voice or images, or processing of digital information.

B. The input power level to electrical or electronic components that are capable of radiating electromagnetic energy in the relevant frequency range is so low that the available antenna power and/or the average total radiated power cannot exceed the low-power exclusion level defined in 4.2.

C. The available antenna power and/or the average total radiated power are limited by product standards for transmitters to levels below the low-power exclusion level defined in 4.2.

D. Measurements or calculations show that the available antenna power and/or the average total radiated power are below the low-power exclusion level defined in 4.2.

### 2.3 Result

PASS

The available antenna power of this EUT is **11.32mW(10.54dBm)** the power are below the low-power exclusion level defined in 4.2(Pmax: 20mW).”