



## Igor PoE Device Node - Mid Version I/O Connections

Sensors Terminal Block	
Label	Function and Rating
+24VDC	+24VDC power source for sensors, 500mA total capacity per node
OCC-1	Dry-contact motion sensor input
OCC-2	24VDC active-hi motion sensor input
GND	Ground Terminal
AI-1	Analog Input, 0-10VDC
AI-2	Analog Input, 0-10VDC



Wall Switch Terminal Block	
Label	Function and Rating
SW-1	Dry contact keypad input
SW-2	Dry contact keypad input
SW-3	Dry contact keypad input
SW-4	Dry contact keypad input
SW-5	Dry contact keypad input
GND	Ground Terminal
LT-1	Pilot light output, 24VDC @ 7.5mA
LT-2	Pilot light output, 24VDC @ 7.5mA
LT-3	Pilot light output, 24VDC @ 7.5mA
LT-4	Pilot light output, 24VDC @ 7.5mA
LT-5	Pilot light output, 24VDC @ 7.5mA
GND	Ground Terminal

LED Outputs Terminal Block	
Labels	Function and Rating
W+ & W-	White LED connection, 12V-48V, 100-1750mA, 53W max

 Igor, Inc. 2700 Westown Pkwy Suite 400 WDM, IA 50266 515-661-4412	TITLE PoE Device Node - Mid - I/O Connections		DRAWN BY Andrew Pospisal	PAGE 1 OF 1
	REVISIONS			
	REV	DESCRIPTION	DATE	APPROVED
	B	Updated Specifications	7/1/2016	
	C	Updated LED Driver Specifications	9/1/2016	
	D	Updated LED Outputs Voltage Range	3/27/2017	
E	Updated LED Outputs Current & Power	6/1/2017		