

Tiger Claw TC-2 SOFTWOOD FASTENER:



PRODUCT DESCRIPTIONS

300 Series Stainless Steel with black oxide coating to better hide fastener between boards.

PRODUCT REQUIREMENTS

When using Tiger Claw fasteners please review and comply with these requirements to obtain proper installation. Failure to follow these requirements may result in deck failure and/or void of warranty.

Inspect decking material prior to installation. Omit any planks that contain hooks, twists, splits, cracks, or other defects. Always install decking with the crown upward.

When using:

Recommended for use in 5/4" or thicker lumber. Softwood decking will inherently experience shrinkage. When using decking material prone to high shrinkage, decking should be installed tightly together allowing shrinkage to provide gap over time. Shrinkage of decking board width must be limited to a maximum of 1/4". Ask your lumber provider for information on expected expansion and/or contraction of material for your particular climate.

PRODUCT FEATURES & COMPATIBILITY

TC-2 is ideal for soft and low density woods*, 5/4" to 2" in all environments, including harsh or coastal environments.

TC-2 will work in the following decking lumber varieties:

- Atlantic White Cedar
- Cedar
- Coast Fir
- Douglas Fir
- Eastern Spruce
- Eastern White Cedar
- Port Orford Cedar
- Southern Yellow Pine
- Western Red Cedar
- Western Redwood
- Yellow Cedar

Please consult your lumber professional or ask us for recommendations first if you plan to use any of the following uncommon woods in your decking project:

- Cypress (soft)

Do NOT use TC-2 with:

- Composite Decking
- Hardwoods- Mahogany
- Cellular PVC Decking

Product images and technical data courtesy of Tiger Claw