#### WARNING

- \*\* WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN \*\*
- \* Switch off the main electrical supply from the main fuse box / circuit. Breaker before installation.
- \* Inspect item carefully before attempting to install.
- \* If there is any damages or obvious defects, do not install.
- \* Item may not be returned once it has been installed.

#### **CARE AND MAINTENANCE**

- \* To clean the outside of the fixture, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the surface of the fixture.
- \* To clean the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the interior surface of the fixture.
- \* Do not use any cleaners with chemical, solvents or harsh abrasives. Use only a dry soft cloth to dust or wipe carefully.

## **NOTICE& IMPORTANT SAFETY INSTRUCTIONS**

- \* Please make sure that you have all parts indicated before you begin assembly of this item
- \* This item should be assembled on a soft surface to prevent scratching the finish during assembly
- \* To reduce the risk of fire, electrical shock or injury to persons or property, please follow the guideline below for safe use and installation
- \*The external flexible cable or cord of this lamp cannot be replaced If the cord is damaged, the lamp shall be destroyed


## Part List and Hardware List

PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE	DESCRIPTION	PICTURE	QUANTITY
A	Bulb		1 <b>X</b>	G	Mounting Plate	<del>  -+ </del>	1 <b>X</b>
В	Lamp Body	•	1 <b>X</b>	Н	Mounting Screw	1	2 <b>X</b>
С	Glass Shade		1 <b>X</b>	I	Wire Nut	8	3 <b>X</b>
D	Long Stem		2 <b>X</b>	J	Canopy Nut	0	2 <b>X</b>
Е	Short Stem		2 <b>X</b>	K	Socket		1X
F	Canopy		1 <b>X</b>				



Model#: PND4182A


Product Dimensions: 7"L X 7"W X21.75-51.75"H



and Canopy (F)


- \* Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list.
- \* If any part is missing or damaged, do not attempt to assemble the product.
- \* Estimated Assembly Time: 20 minutes.
- \* If you are having difficulty, our friendly Customer Care team is always here to help. Please email customersupport@safavieh.com

## PLEASE USE TYPE"B" BULB MAX 25-WATT OR CFL BULB MAX 9-WATT OR LED BULB MAX 5-WATT. THERE IS 1PCS LED 4-WATT BULB IN THE BOX



fixture through the stems during assembly. Remove or add stems to adjust the

height. Then screw the Canopy (F) to the stem.







Step 3: Wire connection

Connect fixture neutral wire (ribbed) to the outlet box neutral wire (usually white) using a wire nut. Connect fixture hot wire (smooth with markings) to the outlet box hot wire (usually black) using a wire nut. CAUTION: Do not reverse the hot and neutral connections


# Grounding Instructions:

Wrap ground wire from outlet box around green ground screw on mounting Plate (G), no less than 2" from Step 4: Fix the Mounting Plate(G) to the junction box with wire end. Tighten ground screw(K). If fixture is supplied with a ground wire, connect to outlet ground wire | Mounting Screw (H). with a wire connector.









**Step 6:** Insert the bulbs (A) into the Socket(K). Fix the Glass Shade