## WARNING

- \* Switch off the main electrical supply from the main fuse box / circuit breaker before installation.
- \* Inspect item carefully before attempting to install.
- \* If there is any damages or obvious defects, do not install.
- \* Item may not be returned once it has been installed.

# **CARE AND MAINTENANCE**

- \* To clean the outside of the fixture, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the surface of the fixture.
- \* To clean the inside of the fixture, first disconnect power to the fixture by turning off the circuit breaker or by removing the fuse at the fuse box. Next, use a dry or slightly dampened clean cloth (use clean water, never a solvent) to wipe the interior surface of the fixture.
- \* Do not use any cleaners with chemical, solvents or harsh abrasives. Use only a dry soft cloth to dust or wipe carefully.

# **NOTICE& IMPORTANT SAFETY INSTRUCTIONS**

- \*\* WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN \*\*
- \* Please make sure that you have all parts indicated before you begin assembly of this item
- \* This item should be assembled on a soft surface to prevent scratching the finish during assembly
- \* To reduce the risk of fire, electrical shock or injury to persons or property, please follow the guideline below for safe use and installation


#### **Part List and Hardware List**

PIECE	DESCRIPTION	PICTURE	QUANTITY	PIECE	DESCRIPTION	PICTURE	QUANTITY
Α	mounting bracket		1X	K	rod		1X
В	machine screw	<b>()</b>	2X	L	Round head screws		6X
С	mounting screw		2X	М	Flat tube	0 0	3X
D	ground screw		1X	N	Lamp holder		1X
Е	Wire Nut	0	3X	0	Flat tube ring		1X
F	canopy		1X	Р	bulb		5X
G	screwed ball		2X	R	Top cage frame		1X
Н	6" Stems		2X		screwdriver	•	1X
I	12" Stems		2X				



Model#:PND4193


Product Dimensions: 15"L X 15"W X 24.5-54.5"H




## **PREPARATION**

- \* Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list.
- \* If any part is missing or damaged, do not attempt to assemble the product.
- \* Estimated Assembly Time: 20 minutes.
- \* Tools Required for Assembly (not included): Screwdriver, Junction box
- \* If you are having difficulty, our friendly Customer Care team is always here to help. Please email customersupport@safavieh.com

## NOTE: PLEASE USE TYPE"B" BULB MAX 40-WATT OR LED BULB MAX 9-WATT, THEREARE 5X LED 4-WATT BULB IN THE BOX




**Step 1:** Unpack all parts from cartons carefully. Connect Top cage frame (R) and Flat tube ring (O) with Flat tube (M), using Round head screws (L).




**Step 2:** Connect Lamp body and Lamp holder (N) with Rod (K). Turn clockwise until firmly tightened. Adjust the internal dental tubes(H, I) so that they are locked on the lamp body and the canopy (F).

## **PREPARATION**

- \* Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list.
- \* If any part is missing or damaged, do not attempt to assemble the product.
- \* Estimated Assembly Time: 20 minutes.
- \* Tools Required for Assembly (not included): Screwdriver, Junction box
- \* If you are having difficulty, our friendly Customer Care team is always here to help. Please email customersupport@safavieh.com



Step 3: Secure mounting bracket (A) to outlet box with mounting screws (C) .






Step 4: Wire connection


Connect fixture neutral wire (ribbed) to the outlet box neutral wire (usually white) using a wire nut. Connect fixture hot wire (smooth with markings) to the outlet box hot wire (usually black) using a wire nut. CAUTION: Do not reverse the hot and neutral connections

#### Grounding Instructions:

Wrap ground wire from outlet box around green ground screw(D) on mounting bracket, no less than 2" from wire end. Tighten ground screw. If fixture is supplied with a ground wire, connect to outlet ground wire with a wire connector.



**Step 5:** Attach the canopy (F) to the machine screw (B) and secure with screwed ball (G)



Step 6: Insert the bulb (P).