


ITEM	DESCRIPTION	QTY	COMMENTS
1	STRINGER HEADER PLATE	1	POPULATE ALL HOLES
2	STRINGER	1	
3	FINISH WALL MATERIAL/ DRYWALL	1	CUT OUT WALL BOARD. HEADER PLATE MUST SIT DIRECTLY AGAINST BLOCKING TO AVOID CRUSHING WALL BOARD AND COMPROMISING STRENGTH
4	BLOCKING	2	MINIMUM 2 QTY LVL OR MINIMUM 3 QTY DIMENSIONAL LUMBER (2X10, ETC)
5	FLAT WASHER	14	
6	1/2" BOLT	7	GRADE 8 THROUGH BOLT REQUIRED. LAG SCREWS ARE NOT RECOMMENDED. TORQUE TO 80 ftlbs
7	NYLON INSERT LOCK NUT	7	PLAIN NUT OK IF USING LOCK WASHER INSTEAD OF NYLOC NUT

DRAWN EMK	2/21/2018	FLIGHT FLOATING STAIR SYSTEM	
TESTS		TITLE	
		HEADER PLATE PREFERRED INSTALLATION METHOD	
		SCALE	REV
1722 EISENHOWER DR. N GOSHEN IN 46526		(574) 742-1030 VIEWRAILSYSTEMS.COM	