Electric Actuated Ball Valves– Quick Close

2-way Stainless Steel, Full Port 1/4" to 4" NPT

SERIES 5652 QC

Features

- Quick close actuator– 2, 4 or 8 second cycle times
- Direct mount ISO5211 Full Port 316 stainless steel ball valve
- RTFE (reinforced Teflon) ball seats
- Triple PTFE/Viton live loaded stem seals, adjustable
- Highly visual dome style valve position indicator
- Rugged aluminum Type 4X weatherproof enclosure
- Heavy duty motors with overload protection
- Anti-condensation heater, thermostatically controlled
- Manual override with end of travel mechanical stops
- Two auxiliary limit switches included
- Actuator CSA listed per UL429 and CSA C22.2

Applications

On-off control of water, air, oil and other media compatible with the materials of construction. Steam service up to 25 PSI with optional high temperature mounting kit. Suitable for vacuum service up to 29"Hg. Actuator designed for 70% duty cycle.

Operation

Electric actuated valve uses power-to-open and power-to-close, stays in the last known position with loss of power. On receipt of a continuous voltage signal, the motor runs and via a rugged all metal gear system rotates the ball 90°. The motor is automatically stopped by internal cams striking limit switches. On receipt of a reversing continuous signal, the motor turns in the opposite direction reversing the valve position. Wire directly to terminal strip via supplied cable connector, or use optional 1/2" NPT adapter.

Construction

Valve Body	316 stainless steel ASTM A351 CF8M
Ball/Stem	316 stainless steel
Ball Seats	RTFE (reinforced Teflon)
Stem Seals	PTFE/ Viton
Anti-static Device	Ball to Stem (1/4" - 2") + Stem to Body (1-1/2" - 2")
Gear Drive	Heavy duty alloy steel and aluminium bronze
Actuator Enclosure	Aluminum, polyester powder painted, Type 4X, IP67
Visual Valve Position Indicator	Clear polycarbonate cover, red/yellow open-closed
Fasteners	Stainless Steel
Auxiliary Limit Switches	2 x SPDT 3A@125/250VAC, 30VDC resistive load

Description

Electric actuated 2-piece stainless steel full port ball valves are investment cast with unrestricted flow and minimum pressure loss. Adjustable live loaded stem seal packing helps compensate for wear, pressure and/or temperature fluctuations, extending the cycle life of the valve. Rugged corrosion resistant electric actuator includes a manual override, valve position confirmation switches, thermostatically controlled anti-condensation heater, and over-torque protection.

Approvals

Actuators

- CSA listed:
  - UL429
  - CSA C22.2 No. 139
  - Type 4X weatherproof enclosure
- CE conformance: EN 60204-1:2006
  - ISO5211 mounting
  - IP67 weatherproof enclosure

Valves

- Design: API 608
- Testing: API 598
- Threaded Connection:

ASME B1.20.1 (NPT)/ ISO 228-1/ BS21

- Pressure/Temperature Rating:

ASME B16.34

- Marking: MSS SP-25
- CE conformance: PED 2014/68/UE

Construction Features

Auxiliary Limit Switches(2) for confirming valve position

Heavy duty integral motor design significantly reduces physical size of actuator

Rugged polyester powder coated aluminum corrosion resistant Type 4X weather-proof enclosure.

Triple PTFE/Viton live loaded stem seal design, adjustable

316SS Ball and Stem, RTFE ball seats

Anti-Condensation Heater

Terminal Box, wire directly to terminal strip via included cable connector or optional 1/2" NPT conduit adapters.

Manual Override with protective cover

Self-locking all metal gear drive, no additional brake required

Direct mount ISO5211 flange, no brackets required

Full Port 316 stainless steel ball valve

Visual Valve Position Indicator

Pressure-Temperature*

Pressure Rating: 1000 PSI (69 Bar) (1/4"-2")
800 PSI (55 Bar) (2-1/2"-4") CWP non-shock, 25 PSI saturated steam with high temp kit, Vacuum 29inHg

Ball Valve Temperature Rating: -4 to 392° F (-20 to 200° C)

Actuator Temperature Rating: -13 to +131° F (-25 to 55° C)

*See P/T chart

Specifications: On-Off Valves (English units)

Stock Number	Pipe Size (NPT)	Orifice Size (inch)	Cv Flow Factor	Pressure Max. (PSI)*	Cycle Time /90° (seconds)	Voltage	Current (amps)	Electrical Drawing	Quick Close Accessory
120 VAC ELECTRIC ACTUATED STAINLESS BALL VALVES, QUICK CLOSE version									
565202E	1/4	0.5	6.9	1000	2	110 VAC, 50/60Hz	0.8	B	A561825
565203E	3/8	0.5	6.9	1000	2	110 VAC, 50/60Hz	0.8	B	A561825
565204E	1/2	0.6	9.7	1000	2	110 VAC, 50/60Hz	0.8	B	A561825
565206E	3/4	0.8	18.4	1000	2	110 VAC, 50/60Hz	0.8	B	A561825
565208E	1	1.0	55.4	1000	2	110 VAC, 50/60Hz	0.8	B	A561825
565210E	1-1/4	1.3	89.7	1000	2	110 VAC, 50/60Hz	0.8	B	A561825
565212E	1-1/2	1.5	144.2	1000	4	110 VAC, 50/60Hz	0.8	B	A561850
565216E	2	2.0	226.0	1000	4	110 VAC, 50/60Hz	0.8	B	A561850
565220E	2-1/2	2.6	289.0	800	8	110 VAC, 50/60Hz	1.2	B	A561870
565224E	3	3.1	454.0	800	8	110 VAC, 50/60Hz	1.2	B	A561870
565232E	4	3.9	710.0	800	8	110 VAC, 50/60Hz	1.2	B	A561870
24 VDC ELECTRIC ACTUATED STAINLESS BALL VALVES, QUICK CLOSE version									
565244E	1/4	0.5	6.9	1000	4	DC24	6.0	G	A561851
565245E	3/8	0.5	6.9	1000	4	DC24	6.0	G	A561851
565246E	1/2	0.6	9.7	1000	4	DC24	6.0	G	A561851
565247E	3/4	0.8	18.4	1000	4	DC24	6.0	G	A561851
565249E	1	1.0	55.4	1000	4	DC24	6.0	G	A561851
565250E	1-1/4	1.3	89.7	1000	4	DC24	6.0	G	A561851
565251E	1-1/2	1.5	144.2	1000	4	DC24	6.0	G	A561851
565252E	2	2.0	226.0	1000	4	DC24	6.0	G	A561851
565241E	2-1/2	2.6	289.0	800	8	DC24	6.0	G	A561871
565242E	3	3.1	454.0	800	8	DC24	6.0	G	A561871
565243E	4	3.9	710.0	800	8	DC24	6.0	G	A561871

* Pressure @ 100° F (see P/T chart for maximum pressure at higher temperatures)

Specifications: On-Off Valves (Metric units)

Stock Number	Pipe Size (NPT)	Orifice Size (mm)	Kv Flow Factor	Pressure Max. (Bar)*	Cycle Time /90° (seconds)	Voltage	Current (amps)	Electrical Drawing	Quick Close Accessory
120 VAC ELECTRIC ACTUATED STAINLESS BALL VALVES, QUICK CLOSE version									
565202E	1/4	11.5	5.9	69	2	110 VAC, 50/60Hz	0.8	B	A561825
565203E	3/8	12.5	5.9	69	2	110 VAC, 50/60Hz	0.8	B	A561825
565204E	1/2	15.0	8.4	69	2	110 VAC, 50/60Hz	0.8	B	A561825
565206E	3/4	20.0	15.9	69	2	110 VAC, 50/60Hz	0.8	B	A561825
565208E	1	25.0	47.9	69	2	110 VAC, 50/60Hz	0.8	B	A561825
565210E	1-1/4	32.0	77.6	69	2	110 VAC, 50/60Hz	0.8	B	A561825
565212E	1-1/2	38.0	124.7	69	4	110 VAC, 50/60Hz	0.8	B	A561850
565216E	2	50.0	195.5	69	4	110 VAC, 50/60Hz	0.8	B	A561850
565220E	2-1/2	65.0	250.0	55	8	110 VAC, 50/60Hz	1.2	B	A561870
565224E	3	80.0	392.7	55	8	110 VAC, 50/60Hz	1.2	B	A561870
565232E	4	100.0	614.2	55	8	110 VAC, 50/60Hz	1.2	B	A561870
24 VDC ELECTRIC ACTUATED STAINLESS BALL VALVES, QUICK CLOSE version									
565244E	1/4	11.5	5.9	69	4	DC24	6.0	G	A561851
565245E	3/8	12.5	5.9	69	4	DC24	6.0	G	A561851
565246E	1/2	15.0	8.4	69	4	DC24	6.0	G	A561851
565247E	3/4	20.0	15.9	69	4	DC24	6.0	G	A561851
565249E	1	25.0	47.9	69	4	DC24	6.0	G	A561851
565250E	1-1/4	32.0	77.6	69	4	DC24	6.0	G	A561851
565251E	1-1/2	38.0	124.7	69	4	DC24	6.0	G	A561851
565252E	2	50.0	195.5	69	4	DC24	6.0	G	A561851
565241E	2-1/2	65.0	250.0	55	8	DC24	6.0	G	A561871
565242E	3	80.0	392.7	55	8	DC24	6.0	G	A561871
565243E	4	100.0	614.2	55	8	DC24	6.0	G	A561871

* Pressure @ 70° C (see P/T chart for higher temperatures)

Pressure/Temperature Chart:

Pressure/Temp. Chart - 1000 PSI (69 Bar)

P/T Chart (PSI/°F)				
PSI	1000	1000	100	0
°F	-4	50	330	392



Pressure/Temp. Chart - 800 PSI (55 Bar)

P/T Chart (PSI/°F)				
PSI	800	800	100	0
°F	-4	50	330	392



Pressure/Temp. Chart - 69 Bar (1000 PSI)

P/T Chart (BAR/°C)				
Bar	69	69	7	0
°C	-20	10	166	200



Pressure/Temp. Chart - 55 Bar (800 PSI)

P/T Chart (BAR/°C)				
Bar	55	55	7	0
°C	-20	10	166	200



Electrical Wiring

ON-OFF Valves
AC Voltages



ON-OFF Valves
DC Voltages



Dimensions: 1/4"-2"





Pipe Size (NPT)		A	C	D	E	H	J	K	M	P	Weight (AC/DC)
1/4	inch	7.7	5.0	2.6	1.5	8.6	9.2	1.2	1.0	0.5	10.9 lb
	mm	196.5	126.0	65.3	37.0	218.4	233.7	31.0	25.0	11.5	4.9 kg
3/8	inch	7.7	5.0	2.6	1.5	8.6	9.2	1.2	1.0	0.5	10.9 lb
	mm	196.5	126.0	65.3	37.0	218.4	233.7	31.0	25.0	12.5	4.9 kg
1/2	inch	7.7	5.0	2.6	1.5	8.6	9.2	1.2	1.0	0.6	10.8 lb
	mm	196.5	126.0	65.3	37.0	218.4	233.7	31.0	25.0	15.0	4.9 kg
3/4	inch	7.7	5.0	3.0	1.8	8.9	9.7	1.5	1.0	0.8	11.3 lb
	mm	196.5	126.0	77.3	45.0	226.1	246.4	38.7	25.0	20.0	5.1 kg
1	inch	7.7	5.0	3.5	2.1	9.2	10.2	1.7	1.0	1.0	12.0 lb
	mm	196.5	126.0	88.7	53.5	233.7	259.1	43.8	25.0	25.0	26.4 kg
1-1/4	inch	7.7	5.0	4.0	2.3	9.4	10.7	2.0	1.0	1.3	13.2 lb
	mm	196.5	126.0	102.0	59.0	237.8	271.8	50.7	25.0	32.0	6.0 kg
1-1/2	inch	7.7	5.0	4.3	2.9	10.0	11.5	2.2	1.0	1.5	14.3 lb
	mm	196.5	126.0	109.0	74.8	254.0	292.1	55.0	25.0	38.0	6.5 kg
2	inch	7.7	5.0	4.9	3.3	10.4	12.2	2.4	1.0	2.0	17.0 lb
	mm	196.5	126.0	125.0	83.5	264.2	309.9	61.3	25.0	50.0	7.7 kg

Dimensions: 2-1/2"- 4"



Pipe Size (NPT)		A	C	D	E	H	J	K	M	P	Weight (AC/DC)
2-1/2	inch	10.1	6.4	6.5	4.3	12.8	14.8	6.1	1.0	2.6	35.7 lb
	mm	255.5	161.5	165.0	108.8	325.1	375.9	155.0	25.0	65.0	16.2 kg
3	inch	10.1	6.4	7.5	4.7	13.2	15.8	6.5	1.0	3.1	42.3 lb
	mm	255.5	161.5	189.5	118.3	335.3	401.3	164.5	25.0	80.0	19.2 kg
4	inch	10.1	6.4	9.4	6.1	14.6	17.8	8.5	1.0	3.9	57.5 lb
	mm	255.5	161.5	238.0	153.8	370.8	452.1	217.0	25.0	100.0	26.1 kg