



<p>Brass Ball Valves 5254 vs 5250 Series</p>	<p>NEW</p>  <p>LEAD FREE IAPMO R&T NSF372/NSF61 Drinking Water</p>	
Feature	5254 Series	5250 Series
Type	2-way On-Off	2-way On-Off
Pipe Sizes	1/4" to 3" NPT	1/4" to 4" NPT
Port Size	Full Port	Full Port
Valve Body	Lead Free Brass	Brass
Handle	Stainless Steel w/vinyl grip and latch locking	No Handle Options
Mounting	ISO5211 Direct Mount dual mounting interface up to 2" size	ISO5211 Direct Mount single mounting interface
Ball and Stem	316 Stainless Steel	Chrome Plated Brass
Ball Seats	PTFE with energized seals	PTFE with o-ring backing
Stem Seals	PTFE/FKM (Viton)	PTFE/FKM (Viton)
Pressure Rating	600 PSI CWP	600 PSI WOG
Temperature Rating	0 to 366° F	0 to 366° F
Approvals	Certified to NSF/ANSI 372, NSF 61 Sect. 8 F/G drinking water MSS-SP-110	MSS-SP-110

Brass Ball Valve Selection



Electric
115v - 240v



Electric
12v - 24v



Air Actuated
Spring Return



Air Actuated
Double Acting



Manual or
Direct Mount