


<p><b>3-Way L-port Brass Ball Valves 5368 vs 5365 Series</b></p>	<p style="text-align: center;"><b>NEW</b></p>  <p><b>LEAD FREE</b> IAPMO R&amp;T NSF372/NSF61 Drinking Water</p>	
Feature	5368 Series	5365 Series
Type	3-way L-port	3-way L-port
Pipe Sizes	1/4" to 2" NPT	1/4" to 3" NPT
Port Size	<b>Full Port</b>	Reduced Port
Valve Body	<b>Lead Free Brass</b>	Brass
Handle	<b>Stainless Steel w/vinyl grip and latch locking</b>	Plated Steel w/vinyl grip
Mounting	ISO5211 Direct Mount <b>dual mounting interface</b>	ISO5211 Direct Mount single mounting interface
Ball and Stem	<b>316 Stainless Steel</b>	Chrome Plated Brass
Ball Seats	PTFE with energized seals	PTFE with o-ring backing
Stem Seals	PTFE/Viton	PTFE/Viton
Pressure Rating	400 PSI CWP	400 PSI WOG
Temperature Rating	0 to 344° F	0 to 344° F
Approvals	<b>Certified to NSF/ANSI 372, NSF 61 Sect. 8 F/G Drinking Water MSS-SP-110</b>	MSS-SP-110

3-way L-port Brass Ball Valve Selection



Electric  
110vac - 24vdc



Air Actuated  
Spring Return



Manual or  
Direct Mount