

<p>3-Way T-port Brass Ball Valves 5369 vs 5366 Series</p>	<p style="text-align: right;">NEW</p>  <p>LEAD FREE IAPMO R&T NSF372/NSF61 Drinking Water</p>	
Feature	5369 Series	5366 Series
Type	3-way T-port	3-way T-port
Pipe Sizes	1/4" to 2" NPT	1/4" to 3" NPT
Port Size	Full Port	Reduced Port
Valve Body	Lead Free Brass	Brass
Handle	Stainless Steel w/vinyl grip and latch locking	Plated Steel w/vinyl grip
Mounting	ISO5211 Direct Mount dual mounting interface	ISO5211 Direct Mount single mounting interface
Ball and Stem	316 Stainless Steel	Chrome Plated Brass
Ball Seats	PTFE with energized seals	PTFE with o-ring backing
Stem Seals	PTFE/Viton	PTFE/Viton
Pressure Rating	400 PSI CWP	400 PSI WOG
Temperature Rating	0 to 344° F	0 to 344° F
Approvals	Certified to NSF/ANSI 372, NSF 61 Sect. 8 F/G Drinking Water MSS-SP-110	MSS-SP-110

3-way T-port Brass Ball Valve Selection



Electric
110vac - 24vdc



Air Actuated
Spring Return



Manual or
Direct Mount