

<p>3-Way T-port Brass Ball Valves 5369 vs 5366 Series</p>	<p>NEW</p>  <p>LEAD FREE IAPMO R&T NSF372/NSF61 Drinking Water</p>	
<p>Feature</p>	<p>5369 Series</p>	<p>5366 Series</p>
<p>Type</p>	<p>3-way T-port</p>	<p>3-way T-port</p>
<p>Pipe Sizes</p>	<p>1/4" to 2" NPT</p>	<p>1/4" to 3" NPT</p>
<p>Port Size</p>	<p>Full Port</p>	<p>Reduced Port</p>
<p>Valve Body</p>	<p>Lead Free Brass</p>	<p>Brass</p>
<p>Handle</p>	<p>Stainless Steel w/vinyl grip and latch locking</p>	<p>Plated Steel w/vinyl grip</p>
<p>Mounting</p>	<p>ISO5211 Direct Mount dual mounting interface</p>	<p>ISO5211 Direct Mount single mounting interface</p>
<p>Ball and Stem</p>	<p>316 Stainless Steel</p>	<p>Chrome Plated Brass</p>
<p>Ball Seats</p>	<p>PTFE with energized seals</p>	<p>PTFE with o-ring backing</p>
<p>Stem Seals</p>	<p>PTFE/Viton</p>	<p>PTFE/Viton</p>
<p>Pressure Rating</p>	<p>400 PSI CWP</p>	<p>400 PSI WOG</p>
<p>Temperature Rating</p>	<p>0 to 344° F</p>	<p>0 to 344° F</p>
<p>Approvals</p>	<p>Certified to NSF/ANSI 372, NSF 61 Sect. 8 F/G Drinking Water MSS-SP-110</p>	<p>MSS-SP-110</p>

3-way T-port Brass Ball Valve Selection

