

### Electric Valve Actuators



Feature	Compact 5617 Series	5618 Series
Type	Quarter turn (90°)	Quarter turn (90°)
Enclosure	Rugged aluminum Type 4X/IP67	Rugged aluminum Type 4X/IP67
Approvals	CSA Listed per UL429 & CSA22.2 no. 139 CE mark	CSA Listed per UL429 & CSA22.2 no. 139 CE mark
Voltages	110 VAC, 24 VAC, 24 VDC	110 VAC, 24 VDC
Electrical Connection	Prewired cable with flying leads 3 meter (9.8 feet)	Terminal strip w/cable connector, (optional) 1/2" NPT Conduit
Valve Position Indicator	Flat Style	Dome Style
Manual Override	Hex wrench	Hex wrench (optional hand wheel)
Mechanical Travel Stops	none	Standard
ISO 5211 Mounting Flange	Standard	Standard
Motor	Heavy duty motor, integral to housing	Heavy duty motor, integral to housing
Motor Protection	Standard	Standard
Duty Cycle	60%	70%
Temperature Range	-22 to 140° F (-30 to 60° C)	-22 to 140° F (-20 to 60° C)
Anti-condensation Heater	none	Standard
Auxiliary Limit Switches (2)	Standard (on-off models)	Standard (on-off models)
Positioners	Optional 4-20mA (110v models)	Optional 4-20mA
Dimensions	4.6"H x 3"W x 3"D	6.1"H x 6.3"W x 5.7"D
Weight	2.7 lbs (1.2 kg)	6 lbs (2.7 kg)

#### Electric Actuator Selection



5617 Series



5618 Series