



<h3>Electric Valve Actuators</h3>	<p>New <span style="float: right;">CE</span></p> 	<p><span style="float: right;">CE</span></p> 
<b>Models</b>	<b>561020E, 561055E, 561085E, 561520, 561555, 561585, 561604C</b>	<b>561020C, 561055C, 561085C, 561603A, 561604A</b>
Multi-Voltage Model Range	24v to 240v AC or 24-135 DC (5610, 5616 series)	24v to 240v AC/DC (5610 series)
Single-Voltage Model Range	12v AC/DC (5615 series)	24v or 85-240v AC/DC (5616 series)
Type	Quarter turn (90°)	Quarter turn (90°)
Enclosure	Polyamide IP67	Polyamide IP67
Approvals	CE mark	CE mark
Electrical Connection	DIN Plug Connectors	DIN Plug Connectors
Valve Position Indicator	Dome Style	Dome Style
Manual Override	Hand knob	Hand knob
LED Power On and Diagnostic Light	External Multi-Color Status Indicator	External Multi-Color Status Indicator
ISO Mounting Flange (valve mounting)	Same	Same
Motor	Brushless Motor	Standard Brush Motor
Over-Torque Protection	Electronic	Electronic
Duty Cycle	75%	75%
Temperature Range	-4 to 158° F	-4 to 158° F
Anti-condensation Heater	4 watt	4 watt
Auxiliary Limit Switches (2)	Open and Closed	Open and Closed
Physical Size	Same	Same
Weight	Same	Same
Positioners 4-20mA or 0-10v	Optional 4-20mA or 0-10v with magnetic encoder	Optional 4-20mA or 0-10v with magnetic encoder
Failsafe Model	Optional BSR-Battery Spring Return with improved battery capacity	Optional BSR-Battery Spring Return

Design Changes