200 AMP SINGLE POSITION

Single Position Sockets 200 Amp | 4 Terminal | Ringless | 600 VAC



U7021-RL-TG



U7040-XL-TG



200 Amp - 4 Terminal - Single Position - Ringless

Catalog Number	Service	Hub	Connectors CU/AL		Dimensions			Knockouts			
			Line	Load	D"	W"	H"	1	2	3	4
U7021-RL-TG	OH	H.O.	#6-350	#6-350	4 ½	8	15½	2 ¹ / ₂	1/4,1/2	1⁄4	—
U7040-0-TG	OH/UG	Blank	#6-350	#6-350	4 ½	11	14%	2 ¹ / ₂	1/4,1/2	1⁄4	—
U7040-XL-TG	OH/UG	C.P.	#6-350	#6-350	4 ½	11	14%	2 ¹ / ₂	1/4,1/2	1⁄4	—
U7043-XL-TG	OH/UG	C.P.	#6-350	#6-350	41/8	13	15½	3	2 ¹ / ₂	1/4,1/2	1⁄4
S1619-XL*	OH/UG	C.P.	3⁄8" x 16 Stud	¾" x 16 Stud	4 ½	11	17	2 ¹ / ₂	2	1/4,1/2	1⁄4

Notes

- *S1619-XL: Non-UL listed. For UL listed units, see other items on this page.
- Fifth Terminal: For field mounted fifth terminal, order as extra K5T.
- Hubs: For proper hub selection see the hub suffix chart on the accessory page.
- Connectors: Extruded aluminum connectors are tin plated. Units are supplied with duplex neutral. Stud type units supplied with %"-16 hex head nuts with Belleville washers. For connector kits, order as extra K1539.
- Bypass: Horn bypass is available add suffix -KK to the catalog number.

