

EFFECTIVE JAN 1, 1965

CHECKER MOTORS CORP., KALAMAZOO, MICH.

MODEL	B-11 CHASSIS	DATE	2/11/65	GRAPHIC ILLUSTRATION	
ALSO APPLIES TO	B-12 3/24 2/25	CLUTCH LINKAGE (ADJUSTMENT PROCEDURE)		6086.	
WITH CLUTCH PEDAL SET AT 11 $\frac{3}{4}$ INCHES ADJUSTMENT, PROCECDURE FOR NEW CLUTCH-6CYL					

ADJUST AT 1 □ TO NEUTRAL CLUTCH POSITION
HELLO DOWN BY HAND AGAINST CLUTCH FINICLES
WITH 1/8" THICK GAUGE AT 3 □ ROD 70207C
AT 2 (SEE THIS IS A BENCH ADJUSTMENT)
WITH CLUTCH PEDAL SET AT 11 $\frac{3}{4}$ ADJUST STOP
ADJUST AT 1 □ TO DETAIN 2 $\frac{3}{8}$ " SET DIM
WITH WIRE JUST CONTRACTING CLUTCH FINICLES
INSTILLATION, PROCEDURE FOR NEW CLUTCH-6CYL

550

SHEET NO.

CHANGES

2-20-65 12122 WAS 103375

③ 9 - 10 LBS. FT
② 17 - 23 LBS. FT
④ 30 - 35 LBS. FT

