

SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.

GENERAL INFORMATION

Body Style _____ Multipurpose vehicle
 Assembly Plant _____ Windsor, Ontario, Canada and St. Louis, Missouri
 EPA Vehicle Class _____ Multipurpose vehicle

ENGINE: 3.3-LITER, OHV, 12-VALVE SMPI V-6

Availability _____ Std.—SWB and LWB LX
 Type and Description _____ Six-cylinder, 60° V-type, liquid-cooled
 Displacement _____ 201.5 cu. in. (3301 cu. cm)
 Bore x Stroke _____ 3.66 x 3.19 (93 x 81)
 Valve System _____ OHV, 12 valves, roller followers, hydraulic lifters
 Fuel Injection _____ Sequential, multi-port, electronic
 Construction _____ Cast-iron block, aluminum alloy heads
 Compression Ratio _____ 9.3:1
 Power (SAE net) _____ 180 bhp (134 kW) @ 5000 rpm (54.5 bhp/L)
 Torque (SAE net) _____ 210 lb.-ft. (285 N•m) @ 4000 rpm
 Max. Engine Speed _____ 5600 rpm
 Fuel Recommendation _____ 87 octane (R+M)/2
 Oil Capacity _____ 4 qt. (3.8L) plus filter
 Coolant Capacity _____ 13.36 qt. (12.64L)—std.; 16.28 qt. (15.4L)—with rear heater
 Emission Controls _____ Three-way catalytic converter, heated oxygen sensors,
 electronic EGR and internal engine features(a)
 Max. Gross Trailer Weight _____ 2,000 lbs. (900 kg)—std.;
 3,800 lbs. (1724 kg)—with optional Trailer Tow Preparation Group
 Estimated EPA Fuel Economy mpg (City/Hwy) _____ 19/26—gasoline

(a) Meets Tier 2 Bin 5 (federal) and LEV 2 (CA) emission requirements.

continued

SPECIFICATIONS

ENGINE: 3.8-LITER, OHV, 12-VALVE SMPI V-6

Availability	Std.—Touring and Limited
Type and Description	Six-cylinder, 60° V-type, liquid-cooled
Displacement	230.5 cu. in. (3778 cu. cm)
Bore x Stroke	3.78 x 3.43 (96 x 87)
Valve System	OHV, 12 valves, roller followers, hydraulic lifters
Fuel Injection	Sequential, multi-port, electronic
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	9.6:1
Power (SAE net)	207 bhp (154 kW) @ 5000 rpm (54.5 bhp/L) Torque (SAE net) 238 lb.-ft. (323 N•m) @ 4000 rpm
Max. Engine Speed	5600 rpm
Fuel Recommendation	Unleaded regular, 87 octane (R+M)/2
Oil Capacity	4 qt. (3.8L) plus filter
Coolant Capacity	13.36 qt. (12.64L)—std.; 16.28 qt. (15.4L)—with rear heater
Emission Controls	Three-way catalytic converter, heated oxygen sensors, electronic EGR and internal engine features(a)
Max. Gross Trailer Weight	2,000 lbs. (900 kg)—std.;
	FWD: 3,800 lbs. (1724 kg)—with optional Trailer Tow Preparation Group
Estimated EPA Fuel Economy mpg (City/Hwy)	18/25

ELECTRICAL SYSTEM

Alternator	160-amp, high-speed
Battery	500 CCA—std.; 600 CCA—included with Trailer Tow Preparation Group

TRANSAXLE: AUTOMATIC, FOUR-SPEED OVERDRIVE

Description	Adaptive electronic control, electronically modulated converter clutch
Gear Ratios	
1st	2.84
2nd	1.57
3rd	1
4th	0.69
Final Drive Ratio	3.3L—3.62, 3.8L—3.43
Overall Top Gear Ratio	3.3L—2.49, 3.8L—2.37

(a) Meets Tier 2 Bin 5 (federal) and LEV 2 (CA) emission requirements.

continued

SPECIFICATIONS

DIMENSIONS AND CAPACITIES(a)

Short Wheelbase

Wheelbase	113.3 (2878)
Track, front	63.0 (1600)
Track, rear	64.0 (1626)
Overall length	189.3 (4808)
Overall width	78.6 (1997)
Overall height (without Roof Rails)	68.8 (1749)
Ground clearance	5.4 (137)
Turning diameter (curb-to-curb)	37.6 ft. (1.46 m)
Curb weight (estimated)	3,899 lbs. (1769 kg)—Base
Weight distribution, %F/R	58/42—Base
Frontal area	31.17 sq. ft. (2.90 sq. m)
Drag coefficient	0.35
Fuel tank capacity	20 gal. (75L)

Long Wheelbase LX, Touring and Limited

Wheelbase	119.3 (3030)
Track, front	63.0 (1600)
Track, rear	64.0 (1626)
Overall length	200.5 (5095)
Overall width	78.6 (1997)
Overall height (without Roof Rails)	68.9 (1750)
Ground clearance	5.5 (130) Curb
Turning diameter (curb-to-curb)	39.4 ft. (12 m)
Weight (estimated)	4,239 lbs. (1923 kg)—LX; 4,340 lbs. (1969 kg)—Touring; 4,442 lbs. (2015 kg)—Limited
Weight distribution	57/43—LX, 56/44—Touring, 56/44—Limited
Frontal area	31.17 sq. ft. (2.896 sq. m)
Drag coefficient	0.35
Fuel tank capacity	20 gal. (75L)

(a) All dimensions measured at curb weight with standard tires.

continued

SPECIFICATIONS

ACCOMMODATIONS

Short Wheelbase

Seating Capacity, F/I/R _____ 2/2/3

Front

Head room _____ 39.6 (1005)
 Leg room _____ 40.8 (1032)
 Shoulder room _____ 62.8 (1598)
 Hip room _____ 57.2 (1453)
 Seat travel _____ 8.6 (220)
 Front volume index _____ 55.9 cu. ft. (1.65 cu. m)

Intermediate

Head room _____ 39.7 (1007.5)
 Leg room _____ 36.5 (926.9)
 Knee clearance _____ 2.0 (50.0)
 Shoulder room _____ 64.7 (1644)
 Hip room _____ 67.8 (1717.4)
 Interior volume index _____ 54.3 cu. ft. (1.53 cu. m)

Rear

Head room _____ 37.3 (948)
 Leg room _____ 33.8 (858.9)
 Knee clearance _____ 6.3 (2.0)
 Shoulder room _____ 61.9 (1574)
 Hip room _____ 49 (1246)
 Rear volume index _____ 43.2 cu. ft. (1.19 cu. m)
 Interior volume index _____ 161.3 cu. ft. (4.58 cu. m)

Cargo Volume Indexes

Aft of intermediate seat _____ 45.6 cu. ft. (1.3 cu. m)
 Aft of rear seat _____ 15.3 cu. ft. (0.43 cu. m)
 Seats Removed—max cargo _____ 146.7 cu. ft. (4.15 cu. m)

Long Wheelbase LX, Touring and Limited with Stow 'n Go seating and storage

Seating Capacity, F/I/R _____ 2/2/3

Front

Head room _____ 39.6 (1005)
 Leg room _____ 40.6 (1032)
 Shoulder room _____ 62.9 (1598)
 Hip room _____ 57.2 (1452)
 Seat travel _____ 8.6 (220)
 Front volume index _____ 58.2 cu. ft. (1.65 cu. m)
 Recliner Range _____ 38°

Intermediate

Head room _____ 39.6 (1006)
 Leg room _____ 34.7 (881.1)
 Knee clearance _____ 4.2 (106.7)
 Shoulder room _____ 64.7 (1644)
 Hip room _____ 67.6 (1717)
 Intermediate volume index _____ 51.5 cu. ft. (1.46 cu. m)

continued

SPECIFICATIONS

ACCOMMODATIONS (CONTINUED)

Long Wheelbase LX, Touring and Limited with Stow 'n Go seating and storage

Rear

Head room _____	38.3 (973)
Leg room _____	31.9 (809)
Knee clearance _____	6 (151.3)
Shoulder room _____	62.1 (1577)
Hip room _____	49.0 (1244)
Rear volume index _____	41.0 cu. ft. (1.61 cu. m)
Interior volume index _____	161.7 cu. ft. (4.58 cu. m)

Cargo Volume Indexes

Aft of intermediate seat _____	54.9 cu. ft. (1.53 cu. m)
Aft of rear seat _____	26.4 cu. ft. (0.75 cu. m)
Seats stowed—max cargo (Fold-in-the-floor) _____	160.7 cu. ft. (4.69 cu. m)

continued

SPECIFICATIONS

SUSPENSION

Front _____ ISO struts with integral gas-charged shock absorbers, coil springs, asymmetrical lower control arms, link-type stabilizer bar, urethane jounce bumpers, rubber-isolated cast-aluminum crossmember

Rear _____ Rubber-isolated longitudinal single-leaf springs, tubular beam axle, track bar and gas-charged shock absorbers—std.; revised spring rates and load-leveling shock absorbers—included in Trailer Tow Prep Group

STEERING

Type _____ Rack and pinion, power-assisted

Overall Ratio _____ 17.8:1

Turning Diameter (curb-to-curb) _____ 39.4 ft. (12.0 m)

Steering Turns (lock-to-lock) _____ 3.14

TIRES

Standard—SWB and LX

Size and type _____ 215/70R15 black sidewall all-season

Mfr. and model _____ Goodyear Integrity

Revs per mile (km) _____ 780 (485)

Standard—Touring and Limited

Size and type _____ 215/65R16 low-black letter all-season

Mfr. and model _____ Bridgestone Turanza EL42

Revs per mile (km) _____ 778 (483)

WHEELS

Standard—SWB and LX

Type and material _____ Stamped-steel

Size _____ 15 x 6.5

Standard—Touring

Type and material _____ Cast-aluminum

Size _____ 16 x 6.5

Standard—Limited

Type and material _____ Chrome cast-aluminum

Size _____ 16 x 6.5

continued

SPECIFICATIONS

BRAKES

Standard—Short Wheelbase Town & Country

Front

Size and type _____ 11.1 x 1.10 (281 x 28) vented disc with 2.60 (66) single-piston sliding caliper
Swept area _____ 228.5 sq. in. (1474 sq. cm)

Rear

Size and type _____ 9.8 x 2.2 (250 x 55) dual-action drum
Swept area _____ 134 sq. in. (864 sq. cm)

Power Assist Type _____ 10.62 (270) single-diaphragm vacuum

Optional—Short Wheelbase Town & Country

Front

Size and type _____ 11.1 x 1.10 (281 x 28) vented disc with 2.60 (66) single-piston sliding caliper and ABS
Swept area _____ 228.5 sq. in. (1474 sq. cm)

Rear

Size and type _____ 9.8 x 2.2 (250 x 55) dual-action drum with ABS
Swept area _____ 134 sq. in. (864 sq. cm)

Power Assist Type _____ 10.62 (270) single-diaphragm vacuum

Standard—Long Wheelbase Town & Country LX, Touring and Limited

Front

Size and type _____ 11.1 x 1.10 (281 x 28) vented disc with 2.60 (66) single-piston sliding caliper and ABS
Swept area _____ 228.5 sq. in. (1474 sq. cm)

Rear

Size and type _____ 11.4 x 0.5 (290 x 12.5) solid disc with 1.65 (42) single-piston sliding caliper and ABS
Swept area _____ 190.5 sq. in. (1234 sq. cm)

Power Assist Type _____ 10.62 (270) single-diaphragm vacuum