SPECIFICATIONS

Dimensions are in inches (millimeters) unless otherwise noted.
All dimensions measured on ST model at curb weight with standard tires unless otherwise noted.

GENERAL INFORMATION

Assembly Plant	Dodge City (Warren, Michigan)
Introduction Date	October 2004
EPA Vehicle Class	Club Cab® and Quad Cab™ pickup

ENGINE: NEXT-GENERATION 3.7-LITER, SOHC, 12-VALVE SMPI V-6 MAGNUM®

Availability	Std.
Type and Description	90-degree V-6, liquid cooled with balance shaft
Displacement	226 cu. in. (3701 cu. cm)
Bore x Stroke	3.66 x 3.57 (93.0 x 90.8)
Valve System	Chain-driven SOHC, 12 valves, hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Cast-iron block and bedplate, aluminum alloy heads, balance shaft
Compression Ratio	9.7:1
Power (estimated SAE net)	210 bhp (157 kW) @ 5200 rpm (58.1 bhp/L)
Torque (estimated SAE net)	235 lb.-ft. (319 N•m) @ 4000 rpm
Max. Engine Speed	6000 rpm (electronically limited)
Fuel Requirement	Unleaded regular, 87 octane (R + M)/2
Oil Capacity	5.0 qt. (4.7L) SAE 5W/20
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors, and internal engine features(a)
Estimated EPA Fuel Economy mpg (City/Hwy)	2WD: 16/22—manual trans., 17/22—auto. trans. 4WD: 16/20—manual trans., 15/19—auto. trans.

NEXT-GENERATION 4.7-LITER MAGNUM®, SOHC, 16-VALVE SMPI V-8

Availability	Standard output: Opt.—all; High Output: Opt.—SLT and Laramie
Type and Description	V-type, liquid-cooled
Displacement	287 cu. in. (4701 cu. cm)
Bore x Stroke	3.66 x 3.40 (93.0 x 86.5)
Valve System	Chain-driven SOHC, 16 valves, hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Cast-iron block, aluminum alloy heads
Compression Ratio	9.0:1—Standard Output, 9.7:1—High Output
Power (SAE Net)	230 bhp (170 kW) @ 4600 rpm (48.9 bhp/liter)—Standard Output 250+ bhp (186+ kW) @ 5200 rpm (53.1+ bhp/liter)—High Output (estimated)
Torque (SAE Net)	295 lb.-ft. (400 N•m) @ 3600 rpm—Standard Output 300+ lb.-ft. (400 N•m) @ 3600 rpm—High Output (estimated)
Max. Engine Speed	5750 rpm
Fuel Requirement	Unleaded regular, 87 octane (R + M)/2—Normal Unleaded premium, 93 octane (R+M)/2 recommended—High Output
Oil Capacity	6 qt. (5.7L)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors, and internal engine features(a)
Estimated EPA Fuel Economy mpg (City/Hwy)	Standard Output: 15/20—2WD; 15/19—4WD man. trans. 14/19—4WD auto. trans.; High-Output: 14/18—2WD, 14/18—4WD

(a) Meets federal Bin 10A emission standards and California LEV1 standards.

continued

SPECIFICATIONS

GETRAG 238—MANUAL 6-SPEED OVERDRIVE

Availability — Std.—3.7 and 4.7 standard output
Description — Synchronized in all gears
Gear Ratios
- 1st — 4.23
- 2nd — 2.53
- 3rd — 1.67
- 4th — 1.23
- 5th — 1.00
- 6th — 0.79
- Reverse — 3.84

Overall Top Gear — 2.54 with 3.21 axle ratio, 2.80 with 3.55 axle ratio,

42RLE—Automatic, four-speed overdrive

Availability — Included with 3.7L engine
Description — Clutch-selected planetary gear sets

full electronic control, electronically controlled torque converter clutch

Gear Ratios
- 1st — 2.84
- 2nd — 1.57
- 3rd — 1.00
- 4th — 0.69
- Overall Top Gear — 2.45 with 3.55 axle ratio, 2.74 with 3.92 axle ratio

5-45RFE, Automatic five-speed overdrive

Availability — Included with 4.7L engines
Description — Clutch-selected planetary gear sets,

full electronic control, electronically controlled torque converter clutch

Gear Ratios
- 1st — 3.00
- 2nd — 1.67—upshift; 1.50—kick-down
- 3rd — 1.00
- 4th — 0.75
- 5th — 0.67

Overall Top Gear — 2.34 with 3.55 axle ratio or 2.59 with 3.92 axle ratio

NV233HD

Availability — Standard
Shift Mechanism — Electrical/electronic
Operating Modes — Neutral; 2WD; 4WD High, locked;

4WD Low, locked

Low Range Ratio — 2.72
Center Differential — None

continued

SPECIFICATIONS

NV244HD

Availability	Optional on SLT and Laramie
Shift Mechanism	Electrical/electronic
Operating Modes	Neutral; 4WD High, full-time; 4WD High, locked; 4WD Low, locked
Low Range Ratio	2.72
Center Differential Type	Planetary with lock
Torque Split, F/R	48/52

ELECTRICAL SYSTEM

Alternator	136-amp
Battery	Maintenance-free, top-terminal 600 CCA–std.; 750 CCA–opt.

BODY AND FRAME

Description	2WD	4WD
Layout	Longitudinal front engine, rear drive	Longitudinal front engine with transfer case for rear-wheel drive or four-wheel drive
Construction	Ladder-type frame, steel body mounted on rubber isolators	Ladder-type frame, steel body mounted on rubber isolators

SUSPENSION

Front	Upper and lower “A” arms, coil springs over gas-pressure shock absorbers, link-type stabilizer bar
Rear	Live axle, multi-leaf two-stage longitudinal springs, staggered gas-pressure shock absorbers, link-type stabilizer bar

STEERING

Type	Power rack and pinion
Overall Ratio	17.4:1
Turning Diameter (curb-to-curb)	44.0 ft. (13.4 m)
Steering Turns (lock-to-lock)	3.18

BRAKES

Front	
Availability	Standard
Size and type	12.3 x 1.1 (312 x 28) vented disc with 2.13 (54) dual-piston sliding caliper(a)
Swept area	248 sq. in. (1604 sq. cm)
Rear	
Availability	Standard
Size and type	11.6 x 2.28 (295 x 58) drum with ABS
Swept area	166.6 sq. in. (1076 sq. cm)
Power Assist	
Availability	Standard
Type	9.06 (230) Tandem-diaphragm vacuum

FUEL SYSTEM

Fuel Tank Capacity	22 gal. (83L)

(a) Available with ABS.

continued

SPECIFICATIONS

DIMENSIONS AND CAPACITIES(a)

2WD

	Club Cab	Quad Cab
Wheelbase	131.3 (3335.3)	131.3 (3335.3)
Track, Front	62.8 (1594.5)	62.8 (1594.5)
Track, Rear	62.9 (1598)	62.9 (1598)
Overall Length	218.8 (5558.2)	218.8 (5558.2)
Overall Width(a)	71.7 (1821.7)	71.7 (1821.7)
Overall Height	68.6 (1743.2)	68.7 (1744.7)
Tailgate Load Height	31.9 (809.6)	31.9 (809.6)
Ground Clearance		
Front suspension (lowest point)	7.9 (201.9)	7.9 (201.9)
Rear axle	8.1 (205.1)	8.1 (205.1)
Approach angle, deg.	23	23
Ramp breakover angle, deg.	19.9	19.9
Departure angle, deg.	22.6	22.6
Frontal Area, sq. ft. (sq. m) (estimated)	30.3 (2.81)	30.3 (2.81)
Drag Coefficient (estimated)	0.452	0.457
CdA, sq. ft.	13.7	14.0

4WD

	Club Cab	Quad Cab
Wheelbase	131.3 (3335.3)	131.3 (3335.3)
Track, Front	62.8 (1594.5)	62.8 (1594.5)
Track, Rear	62.9 (1598)	62.9 (1598)
Overall Length	218.8 (5558.2)	218.8 (5558.2)
Overall Width	71.7 (1821.7)	71.7 (1821.7)
Overall Height	68.6 (1741.4)	68.6 (1742.9)
Tailgate Load Height	31.8 (808.9)	31.8 (808.9)
Ground Clearance		
Front suspension (lowest point)	7.9 (201.9)	7.9 (201.9)
Rear axle	8.0 (203.8)	8.0 (203.8)
Approach angle, deg.	22.8	22.8
Ramp breakover angle, deg.	19.6	19.6
Departure angle, deg.	22.5	22.5
Frontal Area, sq. ft. (sq. m) (estimated)	30.3 (2.81)	30.3 (2.81)
Drag Coefficient (estimated)	0.452	0.457
CdA, sq. ft.	13.7	14.0

(a) At seating reference point.

continued

SPECIFICATIONS

CARGO BOX DIMENSIONS

	Club Cab	Quad Cab
Nominal Box Length, ft.	6.4	5.3
Length at Floor, Tailgate Closed	78.8 (2001.5)	64.9 (1648.1)
Length at Floor, Tailgate Open	100.3 (2546.6)	86.3 (2193.1)
Interior Width, Maximum	59.6 (1514.0)	59.6 (1514.0)
Distance Between Wheelhouses	45.2 (1146.9)	45.2 (1148.0)
Tailgate Opening Width	59.6 (1514.0)	59.6 (1514.0)
Depth	17.6 (446.9)	17.6 (446.9)
Volume, cu. ft (cu. m)	46.6 (1.32)	38.2 (1.082)

ACCOMMODATIONS

	Club Cab®	Quad Cab™
Seating Capacity, F/R	2 or 3/0 or 2	2 or 3/3
Front		
Head room	39.6 (1005.3)	39.9 (1013.1)
Leg room	41.9 (1063.1)	41.9 (1063.1)
Shoulder room	57.7 (1466)	57.7 (1466)
Hip room	54.9 (1394.0)	54.9 (1394.0)
Step height	4x2: 20.4 (518.0) 4x4: 20.3 (515.8)	4x2: 20.4 (518.0) 4x4: 20.3 (515.8)
Interior volume, cu. ft. (cu. m)	55.3 (1.57)	55.8 (1.58)
Seat travel	8.7 (220)–driver, 7.5 (190)–passenger	8.7 (220)–driver, 8.7 (220)–passenger
Recliner range, degrees	53	53
Rear		
Head room	36.5 (928.3)	38.4 (974.2)
Leg room–min.	32.1 (815.4)	36.4 (925.1)
Knee clearance	-4.1 (-105.2)	3.0 (75.0)
Shoulder room	57.4 (1458.3)	57.5 (1460.7)
Hip room	56.9 (1446.2)	56.0 (1460.7)
Interior volume, cu. ft. (cu. m)	39.0 (1.10)	46.5 (1.32)
Cab Cargo Volume		
(Rear seat up), cu. ft. (cu. m)	30.0 (0.85)	37.1 (1.05)

continued

SPECIFICATIONS

CURB WEIGHT AND PAYLOAD

Drive	Body Style	Model	Engine	GVWR (lbs)	Base Curb Wt. (lbs.)(a)	Payload (lbs.)(b)
2WD	*Club Cab®*	*ST*	3.7L V-6	6,010	4,294	1,720
			4.7L V-8	6,010	4,377	1,630
		SLT	3.7L V-6	6,010	4,282	1,730
			4.7L V-8	6,010	4,372	1,640
			4.7L V-8 HO	6,010	4,405	1,600
		Laramie	3.7L V-6	6,010	4,346	1,660
			4.7L V-8	6,010	4,436	1,570
			4.7L V-8 HO	6,010	4,468	1,540
	Quad Cab™	*ST*	3.7L V-6	6,010	4,387	1,620
			4.7L V-8	6,010	4,458	1,550
		SLT	3.7L V-6	6,010	4,363	1,650
			4.7L V-8	6,010	4,437	1,570
			4.7L V-8 HO	6,010	4,470	1,540
		Laramie	3.7L V-6	6,010	4,426	1,580
			4.7L V-8	6,010	4,500	1,510
			4.7L V-8 HO	6,010	4,533	1,480
4WD	*Club Cab*	*ST*	3.7L V-6	6,010	4,475	1,530
			4.7L V-8	6,010	4,567	1,440
		SLT	3.7L V-6	6,010	4,515	1,490
			4.7L V-8	6,010	4,591	1,420
			4.7L V-8 HO	6,010	4,627	1,380
		Laramie	3.7L V-6	6,010	4,549	1,460
			4.7L V-8	6,010	4,625	1,390
			4.7L V-8 HO	6,010	4,661	1,350
	Quad Cab	*ST*	3.7L V-6	6,010	4,566	1,440
			4.7L V-8	6,010	4,649	1,360
		SLT	3.7L V-6	6,010	4,594	1,420
			4.7L V-8	6,010	4,634	1,380
			4.7L V-8 HO	6,010	4,702	1,310
		Laramie	3.7L V-6	6,010	4,628	1,380
			4.7L V-8	6,010	4,700	1,310
			4.7L V-8 HO	6,010	4,736	1,270

(a) Curb weight includes standard equipment and full quantities of fuel, lubricant and coolant.

(b) Payload = GVWR minus curb weight minus 50 lbs. and payload is rounded to the nearest 10 lbs.

continued

SPECIFICATIONS

CURB WEIGHT AND PAYLOAD

Club Cab 2WD SLT Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.21	6010	1700	4306	2504	1802	3100	3806	7700	3250
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1700	4306	2504	1802	3100	3806	8500	4050
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1720	4295	2485	1810	3100	3806	9000	4550
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1720	4295	2485	1810	3100	3806	9300	4850
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.21	6010	1640	4374	2559	1815	3100	3806	9500	5000
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1640	4374	2559	1815	3100	3806	10,000	5500
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1600	4413	2590	1824	3100	3806	10,500	5950
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1600	4413	2590	1824	3100	3806	11,500	6950
4.7L V-8 HO (EVC)	A5	545RFE five-speed automatic	3.92	6010	1600	4413	2590	1824	3100	3806	11,500	6950

Club Cab 2WD SLT Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.21	6010	1720	4286	2479	1807	3100	3806	7700	3250
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1720	4286	2479	1807	3100	3806	8500	4050
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1740	4275	2460	1815	3100	3806	9000	4600
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1740	4275	2460	1815	3100	3806	9300	4900
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.21	6010	1660	4345	2542	1804	3100	3806	9500	5000
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1660	4345	2542	1804	3100	3806	10,000	5500
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1630	4385	2572	1812	3100	3806	10,500	5950
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1630	4385	2572	1812	3100	3806	11,500	6950
4.7L V-8 (EVA)(a)	A5	545RFE five-speed automatic	3.92	6010	1640	4367	2566	1802	3100	3806	11,500	7000

(a) Note option with bench seats only (sales code CBE).

NOTE: Payload = GVWR minus Curb Wt.
Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.
Maximum Trailer Weights = GCWR minus Curb. Wt. minus 150 lbs. (allowance for driver)

SPECIFICATIONS

CURB WEIGHT AND PAYLOAD (CONTINUED)

Quad Cab 2WD SLT Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.21	6010	1600	4408	2509	1899	3100	3806	7700	3150
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1600	4408	2509	1899	3100	3806	8500	3950
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1610	4397	2490	1906	3100	3806	9000	4450
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1610	4397	2490	1906	3100	3806	9300	4750
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.21	6010	1520	4485	2567	1919	3100	3806	9500	4850
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1520	4485	2567	1919	3100	3806	10,000	5350
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1480	4525	2598	1927	3100	3806	10,500	5800
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1480	4525	2598	1927	3100	3806	11,500	6800
4.7L V-8 HO (EVC)	A5	545RFE five-speed automatic	3.92	6010	1480	4525	2598	1928	3100	3806	11,500	6800

Quad Cab 2WD ST Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.21	6010	1590	4422	2520	1902	3100	3806	7700	3150
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1590	4422	2520	1902	3100	3806	8500	3950
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1600	4411	2501	1910	3100	3806	9000	4450
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1600	4411	2501	1910	3100	3806	9300	4750
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.21	6010	1510	4505	2577	1927	3100	3806	9500	4850
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1510	4505	2577	1927	3100	3806	10,000	5350
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1470	4545	2609	1936	3100	3806	10,500	5800
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1470	4545	2609	1936	3100	3806	11,500	6800

continued

SPECIFICATIONS

CURB WEIGHT AND PAYLOAD (CONTINUED)

Club Cab Laramie 2WD ST Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.21	6010	1710	4304	2505	1799	3100	3806	7700	3250
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1710	4304	2505	1799	3100	3806	8500	4050
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1720	4293	2486	1807	3100	3806	9000	4550
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1720	4293	2486	1807	3100	3806	9300	4850
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.21	6010	1620	4387	2562	1824	3100	3806	9500	4950
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1620	4387	2562	1824	3100	3806	10,000	5450
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1580	4426	2593	1833	3100	3806	10,500	5900
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1580	4426	2593	1833	3100	3806	11,500	6900
4.7L V-8 HO (EVC)	A5	545RFE five-speed automatic	3.92	6010	1580	4426	2593	1833	3100	3806	11,500	6900

Quad Cab Laramie 2WD Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.21	6010	1620	4389	2513	1876	3100	3806	7700	3150
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1620	4389	2513	1876	3100	3806	8500	3950
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1630	4378	2494	1884	3100	3806	9000	4450
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1630	4378	2494	1884	3100	3806	9300	4750
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.21	6010	1540	4472	2570	1901	3100	3806	9500	4900
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1540	4472	2570	1901	3100	3806	10,000	5400
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1500	4512	2602	1910	3100	3806	10,500	5850
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1500	4512	2602	1910	3100	3806	11,500	6850
4.7L V-8 HO (EVC)	A5	545RFE five-speed automatic	3.92	6010	1500	4512	2602	1910	3100	3806	11,500	6850

continued

SPECIFICATIONS

CURB WEIGHT AND PAYLOAD (CONTINUED)

Club Cab 4WD SLT Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1530	4476	2656	1820	3600	3806	8500	3850
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1550	4464	2636	1828	3600	3806	9000	4400
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1550	4464	2636	1828	3600	3806	9300	4700
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1450	4565	2725	1840	3600	3806	10,000	5300
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1400	4615	2757	1857	3600	3806	10,500	5750
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1400	4615	2757	1857	3600	3806	11,500	6750
4.7L V-8 HO (EVC)	A5	545RFE five-speed automatic	3.92	6010	1400	4615	2758	1857	3600	3806	11,500	6750

Club Cab 4WD ST Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1550	4463	2662	1801	3600	3806	8500	3900
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1560	4451	2642	1808	3600	3806	9000	4400
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1560	4451	2642	1808	3600	3806	9300	4700
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1460	4547	2721	1826	3600	3806	10,000	5300
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1410	4597	2754	1844	3600	3806	10,500	5750
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1410	4597	2754	1844	3600	3806	11,500	6750

continued

SPECIFICATIONS

CURB WEIGHT AND PAYLOAD (CONTINUED)

Quad Cab 4WD SLT Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1430	4579	2662	1917	3600	3806	8500	3750
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1440	4567	2642	1925	3600	3806	9000	4300
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1440	4567	2642	1925	3600	3806	9300	4600
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1360	4646	2717	1929	3600	3806	10,000	5200
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1310	4696	2750	1947	3600	3806	10,500	5650
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1310	4696	2750	1947	3600	3806	11,500	6650
4.7L V-8 HO (EVC)	A5	545RFE five-speed automatic	3.92	6010	1310	4701	2765	1937	3600	3806	11,500	6650

Quad Cab 4WD ST Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1450	4564	2668	1896	3600	3806	8500	3800
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1460	4552	2648	1904	3600	3806	9000	4300
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1460	4552	2648	1904	3600	3806	9300	4600
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1360	4649	2727	1922	3600	3806	10,000	5200
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1310	4699	2760	1939	3600	3806	10,500	5650
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1310	4699	2760	1939	3600	3806	11,500	6650

continued

SPECIFICATIONS

CURB WEIGHT AND PAYLOAD (CONTINUED)

Club Cab Laramie 4WD ST Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1520	4493	2672	1821	3600	3850	8500	3850
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1530	4481	2652	1829	3600	3850	9000	5750
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1530	4481	2652	1829	3600	3850	9300	5750
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1440	4571	2726	1844	3600	3850	10,000	5750
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1390	4621	2759	1862	3600	3850	10,500	5750
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1390	4621	2759	1862	3600	3850	11,500	6750
4.7L V-8 HO (EVC)	A5	545RFE five-speed automatic	3.92	6010	1390	4621	2759	1862	3600	3850	11,500	6750

Quad Cab Laramie 4WD Short Bed

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max. Trail Wt.
3.7L V-6 (EKG)	M6	Getrag six-speed manual	3.55	6010	1390	4623	2694	1929	3600	3850	8500	3750
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.55	6010	1400	4611	2674	1937	3600	3850	9000	4250
3.7L V-6 (EKG)	A4	42RLE four-speed automatic	3.92	6010	1400	4611	2674	1937	3600	3850	9300	4550
4.7L V-8 (EVA)	M6	Getrag six-speed manual	3.55	6010	1300	4707	2753	1955	3600	3850	10,000	5150
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.55	6010	1250	4758	2786	1972	3600	3850	10,500	5600
4.7L V-8 (EVA)	A5	545RFE five-speed automatic	3.92	6010	1250	4758	2786	1972	3600	3850	11,500	6600
4.7L V-8 HO (EVC)	A5	545RFE five-speed automatic	3.92	6010	1240	4772	2792	1980	3600	3850	11,500	6600

DAKOTA POWERTRAIN AVAILABILITY

2WD CLUB CAB AND QUAD CAB

		Engine		Manual Transmission	Automatic Transmission		Axle Ratio(a)			
GVWR, lbs.	3.7L V-6	4.7L V-8	4.7L HO	G-238 Six-Speed	42RLE Four-Speed	5-45RFE Five-Speed	3.21 Open	3.55 Open	3.55 Anti-Spin	3.92 Anti-Spin
ST	S	–	–	S	–	–	S	–	O	–
6010	S	–	–	–	O	–	–	S	O	O
	–	O	–	S	–	–	S	–	O	–
	–	O	–	–	–	O	–	S	O	O
SLT	S	–	–	S	–	–	S	–	O	–
6010	S	–	–	–	O	–	–	S	O	O
	–	O	–	S	–	–	S	–	O	–
	–	O	–	–	–	O	–	S	O	O
	–	–	O	–	–	O	–	–	–	S
Laramie	S	–	–	–	S	–	–	–	O	–
6010	S	–	–	–	–	–	–	S	O	O
	–	O	–	–	–	–	–	–	O	–
	–	O	–	–	–	O	–	S	O	O
	–	–	O	–	–	O	–	–	–	S

4WD CLUB CAB AND QUAD CAB

		Engine		Manual Transmission	Automatic Transmission		Axle Ratio(a)		
GVWR, lbs.	3.7L V-6	4.7L V-8	4.7L HO	G-238 Six-Speed	42RLE Four-Speed	5-45RFE Five-Speed	3.55 Open	3.55 Anti-Spin	3.92 Anti-Spin
ST	S	–	–	S	–	–	S	O	–
6010	S	–	–	–	O	–	S	O	O
	–	O	–	S	–	–	S	O	–
	–	O	–	–	–	O	S	O	O
SLT	S	–	–	S	–	–	S	O	–
6010	S	–	–	–	O	–	S	O	O
	–	O	–	S	–	–	S	O	–
	–	O	–	–	–	O	S	O	O
	–	–	O	–	–	O	–	–	S
Laramie	S	–	–	–	S	–	S	O	–
6010	S	–	–	–	–	–	S	O	O
	–	O	–	–	–	–	S	O	–
	–	O	–	–	–	O	S	O	O
	–	–	O	–	–	O	–	–	S

continued

DAKOTA CLUB CAB® FEATURE AVAILABILITY

	ST	SLT	Laramie
EXTERIOR			
Bedliner, under rail	O	O	O
Bumpers and Fascias			
Front			
Chrome insert on bumper (not available with Sport Appearance Group)	–	S	S
Dark Slate, mold-in-color fascia and bumper; SLT includes chrome insert(a) on bumper	S	S	–
Body color, painted (included in Sport Appearance Group on SLT)	–	P	S
Rear with Step Pads			
Chrome	–	S	S
Dark Slate	S	–	–
Body color, painted (included in Sport Appearance Group on SLT)	–	P	P
Colors			
Atlantic Blue Pearl Coat, Black, Bright Silver Metallic, Bright White, Flame Red, Mineral Gray Metallic, Patriot Blue Pearl Coat(a), Deep Molten Red Pearl Coat(a)	O	O	O
Light Almond Pearl Coat Metallic(a)	–	O	O
Defroster–Rear Window (not available with sliding rear window)	O	O	O
Doors, Rear Access	S	S	S
Fog Lamps	–	S	S
Glass			
Sunscreen, quarter windows	S	S	S
Tinted, windshield and front door windows	S	S	S
Grille			
Bright surround with integrated Dodge signature crosshair grille	S	S	S
Headlamps, Automatic	–	–	S
Mirrors (Black)			
Dual 5" x 7", Manual	S	–	–
Dual 5" x 7", Power	–	S	S
Dual 6" x 9", Folding Power Heated (included in optional Trailer Tow Group)	–	P	P
Molding			
Bodyside, bright	–	–	S
Bodyside, black mold-in-color	–	O	–
Bodyside, body color, painted (included in Sport Appearance Group)	–	P	P
Rear Window, sliding (NA with Rear Defroster)	O	O	O
Windshield Wipers, variable-delay Intermittent	S	S	S
INTERIOR			
Assist Handles, driver and passenger	S	S	S
Climate Control–Air conditioning	S	S	S
Colors			
Khaki	–	O	O
Dark Slate	S	O	O
Courtesy/Map Lamp(s)	S	S	–
Dual Front (included with optional Interior Convenience Group)	–	P	S
Rear Dome/Courtesy	S	S	S
Cruise Control	P	S	S

(a) Not available with Sport Appearance Group.

continued

DAKOTA CLUB CAB® FEATURE AVAILABILITY

	ST	SLT	Laramie
INTERIOR (CONTINUED)			
Floor Covering			
Carpet	S	S	S
Floor Mats—Front, carpeted (color-keyed)	O	S	S
Instrument Cluster			
Digital displays, vacuum-fluorescent: transmission range (with automatic transmission), odometer and trip odometer	S	S	S
Analog Gauges—Speedometer, tachometer, coolant temperature, fuel	S	S	S
Map Pockets, front and rear doors	S	S	S
Mirror, Rearview—Manual day/night	S	S	–
Auto-dimming Day/Night (included with UConnect™ Hands-Free Communications)	–	–	S
Power Outlet, Front	S	S	S
Power Windows/Locks/Keyless Entry	–	S	S
Seats			
Cloth 40/20/40 Seat	S	S	–
Leather 40/20/40 Seat with six-way power driver's seat, manual lumbar	–	O	S
Rear Dual Folding Seats	O	S	S
Cloth Heated Bucket Seats with six-way power driver's seat, manual lumbar	O	O	–
Leather Heated Bucket Seats with six-way power driver's seat, manual lumbar	–	O	O
Driver and Passenger Manual Recliners	S	S	S
Full Length Center Console (bucket seats only) (included in D Package)	P	P	P
Sound Systems			
AM/FM Stereo Radio with Single CD Player and four speakers	S	S	–
Premium AM/FM Stereo Radio, CD Player with MP3 capability, Integral Six-Disc CD Changer	–	O	S
Infinity® Six-Speaker System with 288-watt Amplifier (must have six-disc CD changer)	–	O	S
Satellite Digital Audio Radio (must have Premium audio)	–	O	O
Steering Column, Tilt	P	S	S
Steering Wheel, Leather-wrapped with remote audio controls	–	O	S
Sun Visors, Padded Cloth with passenger-side mirror	S	S	S
UConnect™ Hands-Free Communications System with Bluetooth™ wireless technology (includes auto-dimming Day/Night Mirror)	O	O	O
POWERTRAIN AND CHASSIS			
Brakes, Power			
Front Disc/Rear Drum with rear-wheel anti-lock	S	S	S
Front Disc/Rear Drum with four-wheel anti-lock	O	O	O
Differential, Anti-Slip	O	O	O
Engines			
3.7-liter V-6	S	S	S
4.7-liter V-8	O	O	O
4.7-liter HO V-8	–	O	O
Heater—Engine block	O	O	O
Steering, Power Rack & Pinion	S	S	S
Suspension			
Front: Independent SLA (short- and long-arm) with coil-over-shock spring and shock absorber module	S	S	S
Rear: Multi-leaf springs, two-stage; stabilizer bar	S	S	S

continued

DAKOTA CLUB CAB® FEATURE AVAILABILITY

	ST	SLT	Laramie
POWERTRAIN AND CHASSIS (CONTINUED)			
Tires(a)			
P245/70R16 black sidewall Wrangler SR-A	S	S	–
P255/65R16 outline white letter Eagle LS (two-wheel drive only)	–	O	S
P265/70R16 outline white letter Wrangler RT/S (four-wheel drive only)	–	O	S
P275/60R17 black sidewall Eagle RS-A (two-wheel drive only); (included with chrome-clad aluminum wheels)	–	P	P
P265/65R17 black sidewall Wrangler SR-A (four-wheel drive only); (included with chrome-clad aluminum wheels)	–	P	P
P265/65R17 outline white letter Wrangler SR-A (two-wheel drive and four-wheel drive); must have chrome-clad aluminum wheels	–	O	O
Spare, Conventional	S	S	S
Transfer Cases			
NV233HD Electric-shift part-time (four-wheel drive only)	S	S	S
NV244HD Electric-shift full-time (four-wheel drive only); must have 4.7-liter engine and automatic transmission	–	O	O
Transmissions			
Six-speed Manual	S	S	–
Four-speed Automatic (V-6 only)	O	O	S
Five-speed Automatic (V-8 only)	O	O	O
Wheels			
Styled steel, 16" x 7" painted	S	–	–
Full-face steel, 16" x 7" painted	P	–	–
Cast-aluminum, 16" x 8" painted	–	S	S
Chrome-clad aluminum, 17" x 8"	–	O	O
SAFETY AND SECURITY			
Air Bags			
Multi-stage front (driver and outboard passenger) with Occupant Classification System (OCS) controlling level of passenger air bag deployment; knee-bolsters(b)	S	S	S
Passenger Air Bag Cut-Off Switch–ignition key operated(c)	S	S	S
Supplemental Side-curtain Air Bags	O	O	O
Brake-Shift Interlock (with automatic transmission only)	S	S	S
Security Alarm	–	P	S
Sentry Key Immobilizer	–	P	S
Child Seat Tether Anchors–Top, cab back (three); included on ST with available rear seats	S	S	S
Child Seat Anchor System–LATCH (Lower Anchors and Tethers for CHildren)	S	S	S
EQUIPMENT GROUPS			
Overhead Convenience Group–overhead console includes trip computer with compass and outside temperature display, dual courtesy/map lamps; HomeLink® universal transceiver (included in SLT E package)	–	P	S

(a) All tires have steel-belted radial construction made by Goodyear. Other sizes and brands may also be used.

(b) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.

(c) Important, always remove key. A rearward-facing child seat may be used in the front passenger seat only with the air bag turned off.

continued

DAKOTA CLUB CAB® FEATURE AVAILABILITY

EQUIPMENT GROUPS (CONTINUED)

Skid Plate Group—Engine/transmission/transfer case and fuel tank skid plates (four-wheel drive only) and two front tow hooks	O	O	O
Sport Appearance Package—Body color painted front fascia, rear bumper and bodyside molding	–	O	O
Trailer Tow Group and Heavy-Duty Service Package—Class IV hitch receiver; wiring harness with seven-circuit and four-circuit connectors; Heavy-Duty Service Group consisting of heavy-duty engine cooling, auxiliary transmission cooler with automatic transmission, power steering cooler and 750 CCA battery. Includes Dual 6" x 9" Folding Power Heated Mirrors (NA on ST)	O	O	O

continued

DAKOTA QUAD CAB™ FEATURE AVAILABILITY

	ST	SLT	Laramie
EXTERIOR			
Bedliner, under rail	O	O	O
Bumpers and Fascias			
Front			
Chrome insert on bumper (not available with Sport Appearance Group)	–	S	S
Dark Slate, mold-in-color fascia and bumper; SLT includes chrome insert(a) on bumper	S	S	–
Body color, painted (included in Sport Appearance Group)	–	P	S
Rear with Step Pads			
Chrome	–	S	S
Dark Slate	S	–	–
Body color, painted (included in Sport Appearance Group)	–	P	P
Colors			
Atlantic Blue Pearl Coat, Black, Bright Silver Metallic, Bright White, Flame Red, Mineral Gray Metallic, Patriot Blue Pearl Coat(a), Deep Molten Red Pearl Coat(a)	O	O	O
Light Almond Pearl Coat Metallic(a)	–	O	O
Defroster–Rear Window (not available with sliding rear window)	O	O	O
Fog Lamps	–	S	S
Glass, Tinted	S	S	S
Grille			
Bright surround with integrated Dodge signature crosshair grille	S	S	
Headlamps, Automatic	–	–	S
Mirrors (Black)			
Dual 5" x 7", manual	S	–	–
Dual 5" x 7", power	–	S	S
Dual 6" x 9", folding power heated (included in optional Trailer Tow Group)	–	P	P
Molding			
Bodyside, bright	–	–	S
Bodyside, black mold-in-color	–	O	–
Bodyside, body color, painted (included in Sport Appearance Group)	–	P	P
Rear window, sliding (NA with Rear Defroster)	O	O	O
Windshield wipers, variable-delay intermittent	S	S	S

(a) Not available with Sport Appearance Group.

continued

DAKOTA QUAD CAB™ FEATURE AVAILABILITY

	ST	SLT	Laramie
INTERIOR			
Assist Handles, Driver and Passenger	S	S	S
Climate Control–Air Conditioning	S	S	S
Colors			
Khaki	–	O	O
Dark Slate	S	O	O
Courtesy/Map Lamp(s)	S	S	–
Dual front	S	P	S
Rear dome/courtesy/reading	S	S	S
Glovebox	S	S	S
Cruise Control	P	S	S
Floor Covering			
Carpet	S	S	S
Floor mats–Front and rear, carpeted (color-keyed)	O	S	S
Instrument Cluster			
Digital displays, vacuum-fluorescent: transmission range (with automatic transmission), odometer and trip odometer	S	S	S
Analog gauges: speedometer, tachometer, coolant temperature, fuel	S	S	S
Map Pockets, Front and Rear Doors	S	S	S
Mirror, Rearview–Manual Day/Night	S	S	–
Auto-dimming day/night (included with UConnect™ hands-free communications)	–	–	S
Power Outlet, Front	S	S	S
Power Windows/Locks/Keyless Entry	–	S	S
Seats			
Cloth bucket seats	S	–	–
Cloth bucket seats with full floor console	–	S	–
Leather bucket seats with six-way power driver's seat, manual lumbar and full floor console	–	–	S
Rear 60/40 split-folding bench	S	S	S
Cloth 40/20/40 seat with six-way power driver's seat, manual lumbar	O	O	–
Leather 40/20/40 seat with six-way power driver's seat, manual lumbar	–	O	O
Cloth heated bucket seats with six-way power driver's seat, manual lumbar	O	O	–
Leather heated bucket seats with six-way power driver's seat, manual lumbar	–	O	O
Driver and passenger manual recliners	S	S	S
Full Floor Console	O	S	S
Sound Systems			
AM/FM stereo radio with single CD player and four speakers	S	S	–
Premium AM/FM stereo radio, CD player with MP3 capability, integral six-disc CD changer	–	O	S
Infinity® six-speaker system with 288-watt amplifier (must have six-disc CD changer)	–	O	S
Satellite digital audio radio (must have Premium audio)	–	O	O
Steering Column, Tilt	P	S	S
Steering Wheel, Leather-wrapped with Remote Audio Controls	–	O	S
UConnect hands-free Communications System with Bluetooth™ wireless technology (includes auto-dimming day/night mirror)	O	O	O
Sun Visors, Padded Cloth with Passenger-side Mirror	S	S	S

continued

DAKOTA QUAD CAB™ FEATURE AVAILABILITY

	ST	SLT	Laramie
POWERTRAIN AND CHASSIS			
Brakes, Power			
Front disc/rear drum with rear-wheel anti-lock	S	S	S
Front disc/rear drum brakes with four-wheel anti-lock (part of the Security Group)	O	O	O
Differential, Anti-Slip	O	O	O
Engines			
3.7-liter V-6	S	S	S
4.7-liter V-8	O	O	O
4.7-liter HO V-8	–	O	O
Heater–Engine Block	O	O	O
Steering, Power Rack & Pinion	S	S	S
Suspension			
Front: Independent SLA (short- and long-arm) with “coil-over” spring and shock absorber module	S	S	S
Rear: Multi-leaf springs, two-stage; stabilizer bar	S	S	S
Tires(a)			
P245/70R16 black sidewall Wrangler SR-A	S	S	–
P255/65R16 outline white letter Eagle LS (two-wheel drive only)	–	O	S
P265/70R16 outline white letter Wrangler RT/S (four-wheel drive only)	–	O	S
P275/60R17 black sidewall Eagle RS-A (2WD only); (included with chrome-clad aluminum wheels)	–	P	P
P265/65R17 black sidewall Wrangler SR-A (four-wheel drive only); (included with chrome-clad aluminum wheels)	–	P	P
P265/65R17 outline white letter Wrangler SR-A (two-wheel drive and four-wheel drive); must have chrome-clad aluminum wheels	–	O	O
Spare, conventional	S	S	S
Transfer Cases			
NV233HD electric-shift part-time (four-wheel drive only)	S	S	S
NV244HD electric-shift full-time (four-wheel drive only; must have 4.7-liter engine and automatic transmission)	–	O	O
Transmissions			
Six-speed manual	S	S	–
Four-speed automatic (V-6 only)	O	O	S
Five-speed automatic (V-8 only)	O	O	O
Wheels			
Styled steel, 16" x 7" painted	S	–	–
Full-face steel, 16" x 7" painted	P	–	–
Cast-aluminum, 16" x 8" painted	–	S	S
Chrome-clad aluminum, 17" x 8"	–	O	O

(a) All tires have steel-belted radial construction made by Goodyear. Other sizes and brands may also be used.

continued

DAKOTA QUAD CAB™ FEATURE AVAILABILITY

SAFETY AND SECURITY			
Air Bags			
Advanced front (driver and outboard passenger) with Occupant Classification System (OCS) controlling level of passenger air bag deployment; knee-bolsters(a)	S	S	S
Supplemental side-curtain air bags (part of the Security Group)	O	O	O
Brake-Shift Interlock (with automatic transmission only)	S	S	S
Security Alarm	–	P	S
Sentry Key Immobilizer	–	P	S
Child Seat Tether Anchors–Top, cab back (three)	S	S	S
Child Seat Anchor System–LATCH (Lower Anchors and Tethers for CHildren)	S	S	S
EQUIPMENT GROUPS			
Overhead Convenience Group–Overhead console includes trip computer with compass and outside temperature display, dual courtesy/map lamps; HomeLink® Universal Transceiver (included in SLT E Package)	–	P	S
Skid Plate Group–Engine/transmission/transfer case and fuel tank skid plates (four-wheel drive only) and two front tow hooks	O	O	O
Sport Appearance Package–Body color painted front fascia, rear bumper and bodyside molding	–	O	
Trailer Tow Group and heavy duty Service Package–Class IV hitch receiver; wiring harness with seven-circuit and four-circuit connectors; Heavy-Duty Service Group consisting of heavy-duty engine cooling, auxiliary transmission cooler with automatic transmission, power steering cooler and 750 CCA battery. Includes Dual 6" x 9" Folding Power Heated Mirrors (not available on ST)	O	O	O

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.

continued