All dimensions are in inches (millimeters) unless otherwise noted.

GENERAL INFORMATION	
Body Style	Two-door coupe
Assembly Plant	Mitsubishi Motors North America—Manufacturing Division, Normal, Illinois
EPA Vehicle Class	Compact car
ENGINE: 2.4-LITER SOHC, 16-VALVE	
Availability	Std.—SXT
	l-4, liquid-cooled
	143.4 cu. in. (2351 cu. cm)
Bore x Stroke	
Valve System	SOHC, four valves/cylinder, hydraulic end-pivot roller followers
	Sequential, multi-port, electronic
Construction	Cast-iron block, aluminum head and balance shafts
Compression Ratio	
	147 hp (106 kW) @ 5500 rpm (61.2 hp/L)—manual
, ,	142 hp (104 kW) @ 5500 rpm (59.2 hp/L)—automatic
Torque (SAE net)	158 lbft. (214 N•m) @ 4000 rpm-manual;
,	155 lbft. (210 N•m) @ 4000 rpm—automatic
Fuel Requirement	Unleaded regular, 87 octane (R+M)/2
	4 qt. (3.8L) plus filter
	Enhanced Catalyst, Heated Oxygen Sensor, EGR
	Hwy)22/29-manual; 21/28-automatic
ENGINE: 3.0-LITER SOHC, 24-VALVE	
•	StdR/T
,	V-6, liquid-cooled
	181.4 cu. in. (2972 cu. cm)
Bore x Stroke	
	IC, four valves/cylinder, hydraulic lash adjusters, stamped-steel roller followers
	Sequential, multi-port, electronic
Construction	
Compression Ratio	
	200 hp (149 kW) @ 5500 rpm (66.7 hp/L)-R/T
Torque (SAE net)	
	Unleaded regular, 87 octane (R+M)/2 (Use unleaded premium,
	91 octane (R+M)/2 to obtain maximum performance)
Oil Capacity	4 qt. (3.8L) plus filter
Coolant Capacity	
Emission Controls	Enhanced catalyst, Heated Oxygen Sensor, EGR
Maximum Gross Trailer Weight	
	Hwy)
ELECTRICAL SYSTEM	
Alternator	90-amp
Battery	525 CCA, maintenance-free

TRANSAXLE: MANUAL, FIVE-SPEE	ED OVERDRIVE (WITH 2.4-LITER ENGINE)
Availability	StdSXT
Description	Five-speed, overdrive; fully synchronized; cable-operated
Gear Ratios	
	3.58
2nd	1.94
	1.37
	1.03
5th	0.76
	3.36
Final Drive	3.72
Overall Top Gear	2.82
	SPEED OVERDRIVE (WITH 2.4-LITER ENGINE)
Availability	OptSXT
Description	Electronic control, electronically modulated converter clutch
Gear Ratios	
1st	2.84
2nd	1.52
3rd	1
4th	0.71
Final Drive	4.04
Overall Top Gear	2.86
TRANSAXI.E: MANUAL. FIVE-SPEE	ED OVERDRIVE (WITH 3.0-LITER ENGINE)
Availability	
Description	Five-speed, overdrive; fully synchronized; cable-operated
Gear Ratios	,,,,,,
	3.33
	2.1
	1.4
	1.03
	0.76
	3.41
	3.73
	2.83
·	SPEED OVERDRIVE (WITH 3.0-LITER ENGINE)
Availability	· · · · · · · · · · · · · · · · · · ·
Availability	Electronic control, electronically modulated converter clutch–standard, all;
Description	Electronic control, electronically modulated converter clutch-standard, all, AutoStick®-optional, R/T
Gear Ratios	
	2.84
	0.73
	3.73
Overall Top Gear	2.72

DIMENSIONS AND CAPACITIES	
	103.7 (2635)
	59.4 (1510)
	59.3 (1505)
Overall Length	190.9 (4850)
	70.3 (1785)
Overall Height	53.9 (1370)
Ground Clearance	6.22 (158)—2.4L engine with 16-inch tires
	5.9 (150)—3.0L engine with 16-inch tires
	5.9 (150)—3.0L engine with 17-inch tires
Estimated Curb Weight	3,051 lbs. (1390 kg)—SXT with 2.4L manual
	3,115 lbs. (1421 kg)—SXT with 2.4L automatic
	3,206 lbs. (1454 kg)—R/T 3.0L manual
	3,272 lbs. (1486 kg)-R/T 3.0L automatic
Weight Distribution, F/R	60/40
	0.36
	16.3 gal. (62L)
ACCOMMODATIONS	
	2/3
Front	
	38.5 (977)
	42.3 (1074)
	52.3 (1328)
	51.9 (1318)
Rear	
Head room	36 (916)
	34 (865)
	52.4 (1330)
	49.5 (1258)
Cargo Volume	16.3 cu. ft. (462L)
Passenger Interior Volume	86.4 cu. ft. (2.44 cu. m)
BODY	
	Transverse front engine, front-wheel drive
Construction Steel unibody with	n isolated engine/suspension cradle and isolated rear suspension crossmember
SUSPENSION	
	Independent MacPherson strut with coil springs and 17 mm stabilizer bar
	Multi-link with coil springs and 17 min stabilizer bar
	with think with con springs and stabilizer bar
STEERING	
* *	Rack and pinion; power-assisted
Overall Ratio	
	42.3 ft. (12.9 m) with 16-inch or 17-inch wheels
Steering Turns (lock-to-lock)	3.15 with 16-inch wheels
	2.8 with 17-inch wheels

TIRES	
Stratus SXT	
Size and type	P205/60HR16 black sidewall all-season performance
Mfr. and model	Goodyear
Stratus R/T	
Size and type	P215/50HR17 all-season performance
Mfr. and model	Goodyear
WHEELS	
Stratus SXT	
Type and material	Cast-aluminum
Size	16 x 6 JJ
Stratus R/T-Std.	
Type and material	Cast-aluminum
Size	17 x 6.5 JJ
Stratus R/T-Opt.	
Type and material	Cast-aluminum, chrome
Size	17 x 6.5 JJ
BRAKES	
Stratus SXT	
Front	
Size and type	10.1 x 1 (256 x 23) ventilated disc with single-piston caliper
Swept area	184.7 sq. in. (1192 sq. cm)
Rear	
Size and type	9.0 (22.9) drum with leading and trailing shoes
Swept area	89.1 sq. in. (575 sq. cm)
Power Assist Type	Tandem-diaphragm vacuum
Stratus R/T	
Front	
Size and type	10.9 x 1 (276 x 23) ventilated disc with single-piston calipers
Swept area	205.9 sq. in. (1329 sq. cm)
Rear	
, 	14 (355) solid disc
•	182.4 sq. in. (1177 sq. cm)
Power Assist Type	Tandem-diaphragm vacuum

FEATURE AVAILABILITY

EXTERIOR
Colors-Black, Brilliant Silver Metallic, Deep Blue Pearl Coat, Dark Titanium Metallic, Indy Red,
Deep Red Pearl Coat, Satin White Metallic and Silver Beige Metallic
Door Handles-Body color
Fascias-Body color
Fog Lamps
Glass-Tinted, all windows
Mirrors
Power, dual (gloss black)
Moldings
Belt (black)
Bodyside (body color)
Sill cladding (body color)
Mud Guards—Integral (body color)
Window Opening Moldings (black)
Spoiler, Rear-Trunklid
Sun roof-Power, with express-open, sliding sunshade and 30-second delay when ignition is turned off
(includes dual rearview mirror reading lamps)
Wiper System—Variable intermittent, two-speed wipers with one-pass feature
INTERIOR
Air Conditioning—Manual temperature controls
Battery Saver—Turns off headlamps and interior courtesy lamps
Cargo Net-Trunk
Carpets—Floor and cargo area
Coat Hooks–Rear, dual
Colors—Black and Dark Taupe/Medium Taupe
Console—Full-length, floor with dual cup holders
Defroster—Rear window, electric
Floor Mats—Front and rear, carpeted
Glove Box—Non-locking
Instrument Cluster—Gauges: 140-mph speedometer, tachometer, odometer, trip odometer, fuel level,
and engine coolant temperature
Rear Quarter–Molded with integral cup holders
Mirror, Rearview
Day/night
Day/night with reading lamps (included with power sun roof)
Auto dimming mirror with outside temperature, compass and HomeLink® universal home transceiver
(included in Leather Interior Group)
Lamps—Dual front courtesy/map, dual rear courtesy/reading, overhead courtesy/reading, glove box
and trunk
Two power outlets—Auxiliary 12-volt, located in instrument panel and inside console box
Seat Trim
Cloth
Leather (included in Leather Interior Group)

Legend: S = Standard O = Optional P = Available within package or group noted in parentheses. O/P = Item is a free-standing option and also included in a package or group. — = Not available.

FEATURE AVAILABILITY

	SXT	R
NTERIOR (CONTINUED)		
leats, Front		
Reclining low-back buckets with driver memory recliner, easy-entry passenger seat track and		
adjustable head restraints	S	
Six-way power driver seat (included in Leather Interior Group on R/T)		
Driver manual height adjuster (delete with power seat)		
eats, Rear–60/40 split-folding rear bench	S	
hift Knob–Leather-wrapped		
ound Systems		
AM/FM radio with CD, four-disc CD changer and six speakers	S	
AM/FM radio with CD and four-disc CD changer and seven-speaker Infinity® sound system and		
steering wheel-mounted audio controls		
peed Control-Electronic	S	
teering Column–Tilt		
teering Wheel–Leather-wrapped		
un Visors		
Cloth, left and right with extensions	S	
Cloth with illuminated mirrors, left and right with extensions		
rim Panel		
Front Door—Premium vinyl with map pockets	S	
Trunk Dress-up		
Vindows—Power with driver's one-touch open feature		
OWERTRAIN AND CHASSIS		
.4-liter I-4 engine and five-speed manual transaxle (includes clutch/starter interlock)		
.4-liter I-4 engine and four-speed automatic transaxle (includes brake-park interlock)		
.0-liter V-6 engine and five-speed manual transaxle (includes clutch-starter interlock)		
.0-liter V-6 engine and four-speed automatic transaxle (includes bright exhaust tip and brake-park		
interlock)		
utoStick®—Driver interactive automatic transaxle shifter (requires four-speed automatic transaxle)		
rakes		
Power front disc/rear drum	S	
Power four-wheel disc		
Anti-lock four-wheel disc (includes traction control with automatic transaxle)		
uspension-Touring	S	
uspension—Handling		
ires		
Spare, compact	S	
P205/60HR16 black sidewall all-season performance	S	
P215/50HR17 black sidewall all-season performance		
/heels and Wheel Covers		
	S	
16-inch x 6.5-inch aluminum wheels		

FEATURE AVAILABILITY

	SXT	R/
SAFETY AND SECURITY		
Door Locks-Power, automatic		S
Remote Keyless Entry System—Remote for doors and trunk with panic alarm and two transmitters (includes illuminated entry system)	S	S
Restraint Systems		
Air bags—Next-generation, driver and front-passenger(a)	S	S
Supplemental side air bags	0	0
Seat Belts		
Front–Height adjustable three-point seat belts with traveling inboard buckles	S	S
Rear-Three-point shoulder belts for all passengers	S	S
Security Alarm (included with keyless entry system)		S
Sentry Key® engine immobilizer with two encoded keys and customer programmable key replacement	S	S
Trunk Lid Release—Remote	S	S
User-Ready Child Seat Top Tether Anchors—Three	S	S
BeltAlert Warning System	S	S
EQUIPMENT GROUPS		
Leather Interior Group—Royale leather-trimmed seats, six-way power driver seat and Auto Dimming mirror with compass and temperature display, HomeLink universal three-channel home security system transceiver	_	0

⁽a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.