

LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

## 2007 Dodge Dakota CLUB CAB® FEATURE AVAILABILITY

	ST	SLT	Laramie
<b>EXTERIOR</b>			
Bedliner, Under Rail _____	O	O	O
Bumpers and Fascias			
Front			
Chrome insert on bumper (not available with Sport Appearance Group) _____	—	S	S
Dark Slate, mold-in-color fascia and bumper; SLT includes chrome insert(a) on bumper _____	S	S	—
Body color, painted (P3) _____	—	P	S
Rear with Step Pads			
Chrome _____	—	S	S
Dark Slate _____	S	—	—
Body color, painted (P3) _____	—	P	P
Colors			
Electric Blue, Brilliant Black, Bright Silver Metallic, Bright White, Flame Red, Mineral Gray Metallic, Patriot Blue Pearl Coat(a), Inferno Red Crystal Pearl Coat(a) _____	O	O	O
Light Khaki(a) _____	—	O	O
Defroster—Rear window (not available with sliding rear window) _____	O	O	O
Doors, 180-Degree Rear Access _____	S	S	S
Dual Position Tailgate _____	S	S	S
Fog Lamps _____	—	S	S
Glass			
Sunscreen, quarter windows _____	S	S	S
Tinted, windshield and front door windows _____	S	S	S
Grille			
Bright surround with integrated Dodge signature crosshair grille _____	S	S	S
Headlamps, Automatic _____	—	—	S
Mirrors (Black)			
Dual 5" x 7", Manual _____	S	—	—
Dual 5" x 7", Power _____	—	S	S
Dual 6" x 9", Folding Power Heated (P4) _____	—	P	P
Molding			
Bodyside, bright _____	—	—	S
Bodyside, black mold-in-color _____	—	O	—
Bodyside, body color, painted (P3) _____	—	P	P
Rear Window, sliding (NA with rear defroster) _____	O	O	O
Skid Plates (P2, P6) _____	P	P	P
Slush Mats (P6) _____	—	P	P
Tow Hooks (P2, P5, P6) _____	P	P	P
Windshield Wipers, Variable-delay Intermittent _____	S	S	S

(a) Not available with Sport Appearance Group.

	ST	SLT	Laramie
<b>INTERIOR</b>			
Assist Handles, Driver and Passenger _____	S	S	S
Climate Control—Air conditioning _____	S	S	S
Colors			
Khaki _____	—	O	O
Dark Slate _____	S	O	O
Courtesy/Map Lamp(s) _____	S	S	—
Dual front (P1) _____	—	P	S
Rear dome/courtesy _____	S	S	S
Cruise Control _____	P	S	S
Floor Covering			
Carpet _____	S	S	S
Floor mats—Front, carpeted (color-keyed) _____	O	S	S
Instrument Cluster			
Digital displays, vacuum-fluorescent: transmission range (with automatic transmission), odometer and trip odometer _____	S	S	S
Analog Gauges—Speedometer, tachometer, coolant temperature, fuel _____	S	S	S
Map Pockets, Front and Rear Doors _____	S	S	S
Mirror, Rearview—Manual day/night _____	S	S	—
Auto-dimming day/night (included with UConnect® Hands-free Communication System) _____	—	—	S
Power Accessory Delay _____	S	S	S
Power Outlet, Front _____	S	S	S
Power Windows/Locks/Keyless Entry _____	—	S	S
Seats			
Cloth 40/20/40 seat _____	S	—	—
YES Essentials® Seat Fabric 40/20/40 _____	—	S	—
Leather 40/20/40 seat with six-way power driver's seat, manual lumbar _____	—	O	S
Rear dual folding seats _____	O	S	S
YES Essentials Seat Fabric heated bucket seats with six-way power driver's seat, manual lumbar _____	O	O	—
Leather heated bucket seats with six-way power driver's seat, manual lumbar _____	—	O	O
Driver and passenger manual recliners _____	S	S	S
Sound Systems			
AM/FM stereo radio with single CD player and four speakers (audio auxiliary jack included) _____	S	S	—
Premium AM/FM stereo radio, CD player with MP3 capability, integral six-disc CD changer _____	—	O	S
Alpine® six-speaker system with 276-watt amplifier (must have six-disc CD changer) _____	—	O	S
Satellite digital audio radio (must have Premium audio) _____	—	O	O
SoundBox™ 508-watt audio system _____	—	O	O
Steering Column, Tilt _____	---	S	S
Steering Wheel, Leather-wrapped with remote audio controls _____	—	O	S
Sun Visors, Padded Cloth with passenger-side mirror _____	S	S	S
UConnect Hands-free Communications System with Bluetooth® wireless technology (includes auto-dimming day/night mirror) _____	O	O	O
<b>POWERTRAIN AND CHASSIS</b>			
Brakes, Power			
Front disc/rear drum with rear-wheel anti-lock _____	S	S	S
Front disc/rear drum with four-wheel anti-lock _____	O	O	O
Differential, Anti-Slip _____	O	O	O
Engines			
3.7-liter V-6 _____	S	S	S
4.7-liter V-8 _____	O	O	O
4.7-liter HO V-8 _____	—	O	O

Heater—Engine block _____	O	O	O
Steering, Power Rack and Pinion _____	S	S	S
<b>Suspension</b>			
Front: Independent SLA (short- and long-arm) with coil-over-shock spring and shock absorber module _____	S	S	S
Rear: Multi-leaf springs, two-stage; stabilizer bar _____	S	S	S
Painted shocks (P6) _____	—	P	P
Ride height increase (1-inch—P6) _____	—	P	P
<b>Tires</b>			
P245/70R16 black sidewall Wrangler SR-A _____	S	S	—
P255/65R16 outline white letter Eagle LS (two-wheel drive only) _____	—	O	S
P265/70R16 outline white letter Wrangler RT/S (four-wheel drive only; also included in P5) _____	P	O	S
P265/65R17 black sidewall Wrangler SR-A (included with chrome-clad aluminum wheels) _____	—	P	P
P265/65R17 outline white letter Wrangler SR-A; must have chrome-clad aluminum wheels _____	—	O	O
P265/70R16 BF Goodrich all-terrain (four-wheel drive only; included in P6 w/TRX-specific cast-aluminum wheels) _____	—	P	P
Spare, Conventional _____	S	S	S
<b>Transfer Cases</b>			
NV233HD electric-shift part-time (four-wheel drive only) _____	S	S	S
NV244HD electric-shift full-time (four-wheel drive only); must have 4.7-liter engine and automatic transmission _____	—	O	O
<b>Transmissions</b>			
Six-speed manual _____	S	S	—
Four-speed automatic (V-6 only) _____	O	O	S
Five-speed automatic (V-8 only) _____	O	O	O
<b>Wheels</b>			
Styled steel, 16" x 7" painted _____	S	—	—
Cast-aluminum, 16" x 8" painted _____	O	S	S
Chrome-clad aluminum, 17" x 8" _____	—	O	O
Chrome-clad aluminum, 18" x 8" _____	---	O	O
Black painted aluminum, 18" x 8" (P3) _____	---	O/P	O/P
Unique, TRX-specific cast-aluminum 16" x 8" (P5, P6) _____	P	P	P

## SAFETY & SECURITY

### Air Bags

Advanced multi-stage front (driver and outboard passenger) with Occupant Classification System (OCS) controlling level of passenger air bag deployment(a) _____	S	S	S
Passenger air bag cut-off switch—Ignition key operated(b) _____	S	S	S
Supplemental side-curtain air bags _____	O	O	O
Brake-Shift Interlock (with automatic transmission only) _____	S	S	S
Remote Start _____	---	O	O
Security Alarm _____	—	O	S
Sentry Key Immobilizer _____	—	O	S
Child Seat Tethers Anchors—Top, cab back (three); included on ST with available rear seats _____	S	S	S
Lower Anchors and Tethers for CHildren (LATCH) child seat anchor system _____	S	S	S

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.

(b) Important, always remove key. A rearward-facing child seat may be used in the front-passenger seat only with the air bag turned off.

**PACKAGES**

P1 – Overhead Convenience Group—Overhead console includes trip computer with compass and outside temperature display, dual courtesy/map lamps; HomeLink® universal transceiver (included in SLT E package) _____	—	O	S
P2 – Skid Plate Group—Engine/transmission/transfer case and fuel tank skid plates (four-wheel drive only) and two front tow hooks _____	O	O	O
P3 – Sport Appearance Package—Body color painted front fascia, rear bumper 18-inch painted aluminum wheels and bodyside molding _____	—	O	O
P4 – Trailer Tow Group and Heavy-duty Service Package—Class IV hitch receiver; wiring harness with seven-circuit and four-circuit connectors; Heavy-duty Service Group consisting of heavy-duty engine cooling, auxiliary transmission cooler with automatic transmission, power steering cooler and 750 CCA battery. Includes dual 6" x 9" folding power heated mirrors (NA on ST) _____	O	O	O
P5 – TRX (4x2) Group—Includes unique five-spoke/five-lug 16-inch aluminum wheels and aggressive Goodyear Wrangler off-road tires; tow hooks; limited-slip differential and TRX decal on cargo box _____	O	O	O
P6 – TRX4 (4x4) Off-road Group —Includes painted shocks; unique, five-spoke/five-lug 16-inch aluminum wheels and aggressive BF Goodrich off-road tires; increased ride height of one inch; limited-slip differential; heavy-duty service package; skid plates; tow hooks; specific TRX4 Off-road cargo box decal; and slush mats _____	—	O	O
P7 – Dakota Club Cab R/T—Based on the Dakota Club Cab SLT. Content includes 4.7-liter high-output (HO) engine; 17-inch five-spoke/five-lug chrome-clad aluminum wheels; hood scoop; Sport Appearance Package (in red or black only); body color grille surround; chrome exhaust tip; cargo box decals; R/T headrest; R/T instrument cluster graphic; and Satin Silver center stack/door remotes _____	—	O	—
P8 – Dakota Club Cab Night Runner—Based on the Dakota Club Cab SLT. Content includes Black Chrome grille surround; fascia insert and 17-inch Black Chrome wheels; Sport Appearance Package; cargo box decal; specifically designed Night Runner headrests and instrument cluster graphic; and black center stack/door remotes _____	—	O	—
P9 – Chrome Accent Package—Includes chrome tubular side steps, fuel filler door, hood deflector and exhaust tip _____	---	O	O

Legend: S = Standard O = Optional P = Available within package or group — = Not available

**QUAD CAB® FEATURE AVAILABILITY**

	ST	SLT	Laramie
<b>EXTERIOR</b>			
Bedliner, Under Rail _____	O	O	O
<b>Bumpers and Fascias</b>			
<b>Front</b>			
Chrome insert on bumper (not available with Sport Appearance Group) _____	—	S	S
Dark Slate, mold-in-color fascia and bumper; SLT includes chrome insert(a) on bumper _____	S	S	—
Body color, painted (P3) _____	—	P	S
<b>Rear with step pads</b>			
Chrome _____	—	S	S
Dark Slate _____	S	—	—
Body color, painted (P3) _____	—	P	P
<b>Colors</b>			
Electric Blue, Brilliant Black, Bright Silver Metallic, Bright White, Flame Red, Mineral Gray Metallic, Patriot Blue Pearl Coat(a), Inferno Red Crystal Pearl Coat(a) _____	O	O	O
Light Khaki(a) _____	—	O	O
Defroster—Rear window (not available with sliding rear window) _____	O	O	O

Dual Position Tailgate _____	S	S	S
Fog Lamps _____	—	S	S
Glass, Tinted _____	S	S	S
Grille			
Bright surround with integrated Dodge signature crosshair grille _____	S	S	S
Headlamps, Automatic _____	—	—	S
Mirrors (Black)			
Dual 5" x 7", manual _____	S	—	—
Dual 5" x 7", power _____	—	S	S
Dual 6" x 9", folding power heated (P4) _____	—	P	P
Molding			
Bodyside, bright _____	—	—	S
Bodyside, black mold-in-color _____	—	O	—
Bodyside, body color, painted (P3) _____	—	P	P
Rear Window, Sliding (NA with Rear Defroster) _____	O	O	O
Skid Plates (P2, P6) _____	P	P	P
Slush Mats (P6) _____	—	P	P
Sun Roof _____	—	O	O
Tow Hooks (P2, P5, P6) _____	P	P	P
Windshield Wipers, Variable-delay Intermittent _____	S	S	S

(a) Not available with Sport Appearance Group.

	ST	SLT	Laramie
<b>INTERIOR</b>			
Assist Handles, driver and passenger _____	S	S	S
Climate Control—Air conditioning _____	S	S	S
Colors			
Khaki _____	—	O	O
Dark Slate _____	S	O	O
Courtesy/Map Lamp(s) _____	S	S	—
Dual front (P1) _____	S	P	S
Rear dome/courtesy/reading _____	S	S	S
Glove box _____	S	S	S
Cruise Control _____	P	S	S
Floor Covering			
Carpet _____	S	S	S
Floor mats—Front, carpeted (color-keyed) _____	O	S	S
Instrument Cluster			
Digital displays, vacuum-fluorescent: transmission range (with automatic transmission), odometer and trip odometer _____	S	S	S
Analog gauges—Speedometer, tachometer, coolant temperature, fuel _____	S	S	S
Map Pockets, front and rear doors _____	S	S	S
Mirror, Rearview—Manual day/night _____	S	S	—
Auto-dimming day/night (included with UConnect Hands-free Communication System) _____	—	—	S
Power Accessory Delay _____	S	S	S
Power Outlet, Front _____	S	S	S
Power Windows/Locks/Keyless Entry _____	—	S	S
Seats			
Cloth bucket seats _____	S	—	—
YES Essentials® Seat Fabric cloth bucket seats with full floor console _____	—	S	—
Leather bucket seats with six-way power driver's seat, manual lumbar and full floor console _____	—	—	S
Rear 60/40 split-folding bench _____	S	S	S
Cloth 40/20/40 seat with six-way power driver's seat, manual lumbar _____	O	O	—
Leather 40/20/40 seat with six-way power driver's seat, manual lumbar _____	—	O	O
YES Essentials Fabric heated bucket seats with six-way power driver's seat, manual lumbar _____	O	O	—
Leather heated bucket seats with six-way power driver's seat, manual lumbar _____	—	O	O

Driver and passenger manual recliners _____	S	S	S
Full Floor Console _____	O	S	S
Sound Systems			
AM/FM stereo radio with single CD player and four speakers (audio auxiliary jack included) _____	S	S	—
Sound Systems (continued)			
Premium AM/FM stereo radio, CD player with MP3 capability, integral six-disc CD changer _____	—	O	S
Alpine® six-speaker system with 276-watt amplifier (must have six-disc CD changer) _____	—	O	S
Satellite digital audio radio (must have Premium audio) _____	—	O	O
Steering Column, Tilt _____	---	S	S
Steering Wheel, Leather-wrapped with remote audio controls _____	—	O	S
Sun Visors, Padded Cloth with passenger-side mirror _____	S	S	S
UConnect Hands-free Communication System with Bluetooth wireless technology (includes auto-dimming day/night mirror) _____	O	O	O
<b>POWERTRAIN AND CHASSIS</b>			
Brakes, Power			
Front disc/rear drum with rear-wheel anti-lock _____	S	S	S
Front disc/rear drum with four-wheel anti-lock _____	O	O	O
Differential, Anti-Slip _____	O	O	O
Engines			
3.7-liter V-6 _____	S	S	S
4.7-liter V-8 _____	O	O	O
4.7-liter HO V-8 _____	—	O	O
Heater—Engine block _____	O	O	O
Steering, Power Rack and Pinion _____	S	S	S
Suspension			
Front: Independent SLA (short- and long-arm) with coil-over-shock spring and shock absorber module _____	S	S	S
Rear: Multi-leaf springs, two-stage; stabilizer bar _____	S	S	S
Painted shocks (P6) _____	—	P	P
Ride height increase (1-inch—P6) _____	—	P	P
Tires			
P245/70R16 black sidewall Wrangler SR-A _____	S	S	—
P255/65R16 outline white letter Eagle LS (two-wheel drive only) _____	—	O	S
P265/70R16 outline white letter Wrangler RT/S (four-wheel drive only; also included in P5) _____	P	O	S
P265/65R17 black sidewall Wrangler SR-A (included with chrome-clad aluminum wheels) _____	—	P	P
P265/65R17 outline white letter Wrangler SR-A; must have chrome-clad aluminum wheels _____	—	O	O
Tires (continued)			
P265/70R16 BF Goodrich all-terrain (four-wheel drive only; included in P6 Group w/TRX-specific cast-aluminum wheels) _____	—	P	P
Spare, conventional _____	S	S	S
Transfer Cases			
NV233HD electric-shift part-time (four-wheel drive only) _____	S	S	S
NV244HD electric-shift full-time (four-wheel drive only; must have 4.7-liter engine and automatic transmission) _____	—	O	O
Transmissions			
Six-speed manual _____	S	S	—
Four-speed automatic (V-6 only) _____	O	O	S
Five-speed automatic (V-8 only) _____	O	O	O
Wheels			
Styled steel, 16" x 7" painted _____	S	—	—
Cast-aluminum, 16" x 8" painted _____	O	S	S
Chrome-clad aluminum, 17" x 8" _____	—	O	O

Chrome-clad aluminum, 18" x 8" _____	---	O	O
Black painted aluminum, 18" x 8" (P3) _____	---	O/P	O/P
Unique, TRX-specific cast-aluminum 16" x 8"(P5, P6) _____	P	P	P

**SAFETY & SECURITY**

**Air Bags**

Advanced multi-stage front (driver and outboard passenger) with Occupant Classification System (OCS) controlling level of passenger air bag deployment;			
knee-bolsters(a) _____	S	S	S
Supplemental side-curtain air bags (part of the Security Group) _____	O	O	O
Brake-shift Interlock (with automatic transmission only) _____	S	S	S
Remote Start _____	---	O	O
Security Alarm _____	—	O	S
Sentry Key Immobilizer _____	—	O	S
Child Seat Tethers Anchors—Top, cab back (three) _____	S	S	S
Lower Anchors and Tethers for CHildren (LATCH) child seat anchor system _____	S	S	S

(a) Certified to federal regulations that allow less forceful air bags. Always use seat belts. Remember, a back seat is the safest place for children.

**PACKAGES**

P1 – Overhead Convenience Group—Overhead console includes trip computer with compass and outside temperature display, dual courtesy/map lamps; HomeLink® universal transceiver (included in SLT E package) _____	—	O	S
P2 – Skid Plate Group—Engine/transmission/transfer case and fuel tank skid plates (four-wheel drive only) and two front tow hooks _____	O	O	O
P3 – Sport Appearance Package—Body color painted front fascia, rear bumper 18" painted aluminum wheels and bodyside molding _____	—	O	O
P4 – Trailer Tow Group and Heavy-duty Service Package—Class IV hitch receiver; wiring harness with seven-circuit and four-circuit connectors; Heavy-duty Service Group consisting of heavy-duty engine cooling, auxiliary transmission cooler with automatic transmission, power steering cooler and 750 CCA battery. Includes dual 6" x 9" folding power heated mirrors (NA on ST) _____	O	O	O
P5 – TRX (4x2) Group—Includes unique five-spoke/five-lug 16-inch aluminum wheels and aggressive Goodyear Wrangler off-road tires; tow hooks; limited-slip differential and TRX decal on cargo box _____	O	O	O
P6 – TRX4 (4x4) Off-road Group —Includes painted shocks; unique, five-spoke/five-lug 16-inch aluminum wheels and aggressive BF Goodrich off-road tires; increased ride height of one inch; limited-slip differential; heavy-duty service package; skid plates; tow hooks; specific TRX4 Off-road cargo box decal; and slush mats _____	—	O	O
P7 – Dakota Club Cab R/T—Based on the Dakota Quad Cab SLT. Content includes 4.7-liter High Output (HO) engine; 17-inch five-spoke/five-lug chrome-clad aluminum wheels; hood scoop; sport appearance package (in red or black only); body color grille surround; chrome exhaust tip; cargo box decals; R/T headrest; R/T instrument cluster graphic; and satin silver center stack/door remotes _____	—	O	—
P8 – Dakota Club Cab Night Runner—Based on the Dakota Quad Cab SLT. Content includes Black Chrome grille surround; fascia insert and 17-inch Black Chrome wheels; sport appearance package; cargo box decal; specifically designed Night Runner headrests and instrument cluster graphic; and black center stack/door remotes _____	—	O	—
P9 – Chrome Accent Package—Includes chrome tubular side steps, fuel filler door, hood deflector and exhaust tip _____	---	O	O

Legend: S = Standard O = Optional P = Available within package or group — = Not available

# POWERTRAIN AVAILABILITY

## 2WD CLUB CAB AND QUAD CAB

GVWR, lbs.	3.7L V-6	Engine		Manual Transmission			Automatic Transmission		Axle Ratio	
		4.7L V-8	4.7L HO	G-238 Six-speed	42RLE Four-speed	5-45RFE Five-speed	3.21 Open	3.55 Open	3.55 Anti-spin	3.92 Anti-spin
ST 6010	S	—	—	S	—	—	S	—	O	—
	S	—	—	—	O	—	—	S	O	O
	—	O	—	S	—	—	S	—	O	—
	—	O	—	—	—	O	—	S	O	O
SLT 6010	S	—	—	S	—	—	S	—	O	—
	S	—	—	—	O	—	—	S	O	O
	—	O	—	S	—	—	S	—	O	—
	—	O	—	—	—	O	—	S	O	O
	—	—	O	—	—	O	—	—	—	S
Laramie 6010	S	—	—	—	S	—	—	S	O	O
	—	O	—	—	—	O	—	—	O	—
	—	O	—	—	—	O	—	S	O	O
	—	—	O	—	—	O	—	—	—	S

## 4WD CLUB CAB AND QUAD CAB

GVWR, lbs.	3.7L V-6	Engine		Manual Transmission			Automatic Transmission		Axle Ratio	
		4.7L V-8	4.7L HO	G-238 Six-speed	42RLE Four-speed	5-45RFE Five-speed	3.55 Open	3.55 Anti-spin	3.92 Anti-spin	
ST 6010	S	—	—	S	—	—	S	O	—	
	S	—	—	—	O	—	S	O	O	
	—	O	—	S	—	—	S	O	—	
	—	O	—	—	—	O	S	O	O	
SLT 6010	S	—	—	S	—	—	S	O	—	
	S	—	—	—	O	—	S	O	O	
	—	O	—	S	—	—	S	O	—	
	—	O	—	—	—	O	S	O	O	
	—	—	O	—	—	O	—	—	S	
Laramie 6010	S	—	—	—	S	—	S	O	O	
	—	O	—	—	—	—	S	O	—	
	—	O	—	—	—	O	S	O	O	
	—	—	O	—	—	O	—	—	S	

## SPECIFICATIONS

Dimensions are in inches (millimeters) unless otherwise noted.

All dimensions measured on ST model at curb weight with standard tires unless otherwise noted.

### GENERAL INFORMATION

Assembly Plant \_\_\_\_\_ Dodge City (Warren, Michigan)

Introduction Date \_\_\_\_\_ October 2004

EPA Vehicle Class \_\_\_\_\_ Club Cab® and Quad Cab® pickup

**ENGINE: NEXT-GENERATION 3.7-LITER, SOHC, 12-VALVE SMPI V-6 MAGNUM®**

Availability \_\_\_\_\_ Std.  
 Type and Description \_\_\_\_\_ 90-degree V-6, liquid-cooled with balance shaft  
 Displacement \_\_\_\_\_ 226 cu. in. (3701 cu. cm)  
 Bore x Stroke \_\_\_\_\_ 3.66 x 3.57 (93.0 x 90.8)  
 Valve System \_\_\_\_\_ Chain-driven SOHC, 12 valves, hydraulic end-pivot roller rockers  
 Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic, returnless  
 Construction \_\_\_\_\_ Cast-iron block and bedplate, aluminum alloy heads, balance shaft  
 Compression Ratio \_\_\_\_\_ 9.7:1  
 Power (estimated SAE net) \_\_\_\_\_ 210 bhp (157 kW) @ 5,200 rpm (58.1 bhp/L)  
 Torque (estimated SAE net) \_\_\_\_\_ 235 lb.-ft. (319 N•m) @ 4,000 rpm  
 Max. Engine Speed \_\_\_\_\_ 6,000 rpm (electronically limited)  
 Fuel Requirement \_\_\_\_\_ Unleaded regular, 87 octane (R + M)/2  
 Oil Capacity \_\_\_\_\_ 5.0 qt. (4.7L) SAE 5W/20  
 Emission Controls \_\_\_\_\_ Dual three-way catalytic converters, heated oxygen sensors,  
 and internal engine features(a)  
 Estimated EPA Fuel Economy mpg (City/Hwy) \_\_\_\_ 2WD: 16/22—manual trans., 17/22—auto. trans.  
 4WD: 16/20—manual trans., 15/19—auto. trans.

**NEXT-GENERATION 4.7-LITER MAGNUM®, SOHC, 16-VALVE SMPI V-8**

Availability \_\_\_\_\_ Standard output: Opt.—all  
 Type and Description \_\_\_\_\_ V-type, liquid-cooled  
 Displacement \_\_\_\_\_ 287 cu. in. (4701 cu. cm)  
 Bore x Stroke \_\_\_\_\_ 3.66 x 3.40 (93.0 x 86.5)  
 Valve System \_\_\_\_\_ Chain-driven SOHC, 16 valves, hydraulic end-pivot roller rockers  
 Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic, returnless  
 Construction \_\_\_\_\_ Cast-iron block, aluminum alloy heads  
 Compression Ratio \_\_\_\_\_ 9.0:1—Standard Output  
 Power (SAE Net) \_\_\_\_\_ 230 bhp (170 kW) @ 4,600 rpm  
 (48.9 bhp/L)—Standard Output  
 Torque (SAE Net) \_\_\_\_\_ 290 lb.-ft. (400 N•m) @ 3,600 rpm—Standard Output  
 Max. Engine Speed \_\_\_\_\_ 5,750 rpm  
 Fuel Requirement \_\_\_\_\_ E85 (Ethanol) or Unleaded regular, 87 octane (R+M)/2—Normal

(a) Meets federal Bin 10A emission standards and California LEV1 standards.

**NEXT-GENERATION 4.7-LITER MAGNUM®, SOHC, 16-VALVE SMPI V-8 (CONTINUED)**

Oil Capacity \_\_\_\_\_ 6 qt. (5.7L)  
 Emission Controls \_\_\_\_\_ Dual three-way catalytic converters, heated oxygen sensors,  
 and internal engine features(a)  
 Estimated EPA Fuel Economy mpg (City/Hwy) \_\_\_\_\_ Standard Output:  
 15/20—2WD; 15/19—4WD man. trans.  
 14/19—4WD auto. trans.

**NEXT-GENERATION 4.7-LITER HIGH-OUTPUT MAGNUM®, SOHC, 16-VALVE SMPI V-8**

Availability \_\_\_\_\_ Opt.—SLT, Laramie  
 Type and Description \_\_\_\_\_ V-type, liquid-cooled  
 Displacement \_\_\_\_\_ 287 cu. in. (4701 cu. cm)  
 Bore x Stroke \_\_\_\_\_ 3.66 x 3.40 (93.0 x 86.5)  
 Valve System \_\_\_\_\_ Chain-driven SOHC, 16 valves, hydraulic end-pivot roller rockers  
 Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic, returnless  
 Construction \_\_\_\_\_ Cast-iron block, aluminum alloy heads  
 Compression Ratio \_\_\_\_\_ 9.7:1—High Output  
 Power (SAE Net) \_\_\_\_\_ 260 bhp (186+ kW) @ 5,200 rpm  
 (53.1+ bhp/L)—High Output (estimated)  
 Torque (SAE Net) \_\_\_\_\_ 310+ lb.-ft. (400 N•m) @ 3,600 rpm—High Output (estimated)  
 Max. Engine Speed \_\_\_\_\_ 5,750 rpm  
 Fuel Requirement \_\_\_\_\_ Unleaded premium, 93 octane (R+M)/2 recommended—High Output  
 Oil Capacity \_\_\_\_\_ 6 qt. (5.7L)  
 Emission Controls \_\_\_\_\_ Dual three-way catalytic converters, heated oxygen sensors,

and internal engine features(a)  
Estimated EPA Fuel Economy mpg (City/Hwy) \_\_\_\_\_ High Output: 14/18—2WD, 14/18—4WD

**GETRAG 238—MANUAL SIX-SPEED OVERDRIVE**

Availability \_\_\_\_\_ Std.—3.7 and 4.7 standard output

Description \_\_\_\_\_ Synchronized in all gears

**Gear Ratios**

1st \_\_\_\_\_ 4.23

2nd \_\_\_\_\_ 2.53

3rd \_\_\_\_\_ 1.67

4th \_\_\_\_\_ 1.23

5th \_\_\_\_\_ 1.00

6th \_\_\_\_\_ 0.79

Reverse \_\_\_\_\_ 3.84

Overall Top Gear \_\_\_\_\_ 2.54 with 3.21 axle ratio, 2.80 with 3.55 axle ratio,  
42RLE—Automatic, four-speed overdrive

(a) Meets federal Bin 10A emission standards and California LEV1 standards.

**42RLE—AUTOMATIC, FOUR-SPEED OVERDRIVE**

Availability \_\_\_\_\_ Included with 3.7L engine

Description \_\_\_\_\_ Clutch-selected planetary gear sets  
full electronic control, electronically-controlled torque converter clutch

**Gear Ratios**

1st \_\_\_\_\_ 2.84

2nd \_\_\_\_\_ 1.57

3rd \_\_\_\_\_ 1.00

4th \_\_\_\_\_ 0.69

Overall Top Gear \_\_\_\_\_ 2.45 with 3.55 axle ratio, 2.74 with 3.92 axle ratio  
5-45RFE, automatic five-speed overdrive

**5-45RFE—AUTOMATIC, FIVE-SPEED OVERDRIVE**

Availability \_\_\_\_\_ Included with 4.7L engines

Description \_\_\_\_\_ Clutch-selected planetary gear sets,  
full electronic control, electronically-controlled torque converter clutch

**Gear Ratios**

1st \_\_\_\_\_ 3.00

2nd \_\_\_\_\_ 1.67—upshift; 1.50—kick-down

3rd \_\_\_\_\_ 1.00

4th \_\_\_\_\_ 0.75

5th \_\_\_\_\_ 0.67

Overall Top Gear \_\_\_\_\_ 2.34 with 3.55 axle ratio or 2.59 with 3.92 axle ratio

**NV233HD**

Availability \_\_\_\_\_ Standard

Shift Mechanism \_\_\_\_\_ Electrical/electronic

Operating Modes \_\_\_\_\_ Neutral; 2WD; 4WD High, locked;  
4WD Low, locked

Low Range Ratio \_\_\_\_\_ 2.72

Center Differential \_\_\_\_\_ None

**NV244HD**

Availability \_\_\_\_\_ Optional on SLT and Laramie

Shift Mechanism \_\_\_\_\_ Electrical/electronic

Operating Modes \_\_\_\_\_ Neutral; 4WD High, full-time; 4WD High, locked; 4WD Low, locked

Low Range Ratio \_\_\_\_\_ 2.72

Center Differential Type \_\_\_\_\_ Planetary with lock

Torque Split, F/R \_\_\_\_\_ 48/52

**ELECTRICAL SYSTEM**

Alternator \_\_\_\_\_ 136-amp  
 Battery \_\_\_\_\_ Maintenance-free, top-terminal 600 CCA—std.; 750 CCA—opt.

**BODY AND FRAME**

Description \_\_\_\_\_ 2WD \_\_\_\_\_ 4WD  
 Layout \_\_\_\_\_ Longitudinal front engine, rear drive \_\_\_\_\_ Longitudinal front engine with transfer case  
 for rear-wheel drive or four-wheel drive  
 Construction \_\_\_\_\_ Ladder-type frame, steel body \_\_\_\_\_ Ladder-type frame, steel body  
 mounted on rubber isolators \_\_\_\_\_ mounted on rubber isolators

**SUSPENSION**

Front \_\_\_\_\_ Upper and lower "A" arms, coil springs over gas-pressure shock absorbers,  
 link-type stabilizer bar  
 Rear \_\_\_\_\_ Live axle, multi-leaf two-stage longitudinal springs,  
 staggered gas-pressure shock absorbers, link-type stabilizer bar

**STEERING**

Type \_\_\_\_\_ Power rack and pinion  
 Overall Ratio \_\_\_\_\_ 17.4:1  
 Turning Diameter (curb-to-curb) \_\_\_\_\_ 44.0 ft. (13.4 m)  
 Steering Turns (lock-to-lock) \_\_\_\_\_ 3.18

**BRAKES**

Front  
 Availability \_\_\_\_\_ Standard  
 Size and type \_\_\_\_\_ 12.3 x 1.1 (312 x 28) vented disc  
 with 2.13 (54) dual-piston sliding caliper(a)  
 Swept area \_\_\_\_\_ 248 sq. in. (1604 sq. cm)  
 Rear  
 Availability \_\_\_\_\_ Standard  
 Size and type \_\_\_\_\_ 11.6 x 2.28 (295 x 58) drum with ABS  
 Swept area \_\_\_\_\_ 166.6 sq. in. (1076 sq. cm)  
 Power Assist  
 Availability \_\_\_\_\_ Standard  
 Type \_\_\_\_\_ 9.06 (230) Tandem-diaphragm vacuum

**FUEL SYSTEM**

Fuel Tank Capacity \_\_\_\_\_ 22 gal. (83L)

(a) Available with ABS.

**DIMENSIONS AND CAPACITIES(a)****2WD**

	Club Cab	Quad Cab
Wheelbase _____	131.3 (3335.3) _____	131.3 (3335.3) _____
Track, Front _____	62.8 (1594.5) _____	62.8 (1594.5) _____
Track, Rear _____	62.9 (1598) _____	62.9 (1598) _____
Overall Length _____	218.8 (5558.2) _____	218.8 (5558.2) _____
Overall Width(a) _____	71.7 (1821.7) _____	71.7 (1821.7) _____
Overall Height _____	68.6 (1743.2) _____	68.7 (1744.7) _____
Tailgate Load Height _____	31.9 (809.6) _____	31.9 (809.6) _____
Ground Clearance		
Front suspension (lowest point) _____	7.9 (201.9) _____	7.9 (201.9) _____
Rear axle _____	8.1 (205.1) _____	8.1 (205.1) _____
Approach angle, deg. _____	23 _____	23 _____
Ramp breakover angle, deg. _____	19.9 _____	19.9 _____
Departure angle, deg. _____	22.6 _____	22.6 _____
Frontal Area, sq. ft. (sq. m) (estimated) _____	30.3 (2.81) _____	30.3 (2.81) _____

Drag Coefficient (estimated)	0.452	0.457
CdA, sq. ft.	13.7	14.0

#### 4WD

	Club Cab	Quad Cab
Wheelbase	131.3 (3335.3)	131.3 (3335.3)
Track, Front	62.8 (1594.5)	62.8 (1594.5)
Track, Rear	62.9 (1598)	62.9 (1598)
Overall Length	218.8 (5558.2)	218.8 (5558.2)
Overall Width	71.7 (1821.7)	71.7 (1821.7)
Overall Height	68.6 (1741.4)	68.6 (1742.9)
Tailgate Load Height	31.8 (808.9)	31.8 (808.9)
Ground Clearance		
Front suspension (lowest point)	7.9 (201.9)	7.9 (201.9)
Rear axle	8.0 (203.8)	8.0 (203.8)
Approach angle, deg.	22.8	22.8
Ramp breakover angle, deg.	19.6	19.6
Departure angle, deg.	22.5	22.5
Frontal Area, sq. ft. (sq. m) (estimated)	30.3 (2.81)	30.3 (2.81)
Drag Coefficient (estimated)	0.452	0.457
CdA, sq. ft.	13.7	14.0

(a) At seating reference point.

#### CARGO BOX DIMENSIONS

	Club Cab	Quad Cab
Nominal Box Length, ft.	6.4	5.3
Length at Floor, Tailgate Closed	78.8 (2001.5)	64.9 (1648.1)
Length at Floor, Tailgate Open	100.3 (2546.6)	86.3 (2193.1)
Interior Width, Maximum	59.6 (1514.0)	59.6 (1514.0)
Distance between Wheelhouses	45.2 (1146.9)	45.2 (1148.0)
Tailgate Opening Width	59.6 (1514.0)	59.6 (1514.0)
Depth	17.6 (446.9)	17.6 (446.9)
Volume, cu. ft. (cu. m)	46.6 (1.32)	38.2 (1.082)

#### ACCOMMODATIONS

	Club Cab	Quad Cab
Seating Capacity, F/R	2 or 3/0 or 2	2 or 3/3
Front		
Head room	39.6 (1005.3)	39.9 (1013.1)
Leg room	41.9 (1063.1)	41.9 (1063.1)
Shoulder room	57.7 (1466)	57.7 (1466)
Hip room	54.9 (1394.0)	54.9 (1394.0)
Step height	4x2: 20.4 (518.0)	4x2: 20.4 (518.0)
	4x4: 20.3 (515.8)	4x4: 20.3 (515.8)
Interior volume, cu. ft. (cu. m)	55.3 (1.57)	55.8 (1.58)
Seat travel	8.7 (220)—driver, 7.5 (190)—passenger	8.7 (220)—driver, 8.7 (220)—passenger
Recliner range, degrees	53	53
Rear		
Head room	36.5 (928.3)	38.4 (974.2)
Leg room—min.	32.1 (815.4)	36.4 (925.1)
Knee clearance	-4.1 (-105.2)	3.0 (75.0)
Shoulder room	57.4 (1458.3)	57.5 (1460.7)
Hip room	56.9 (1446.2)	56.0 (1460.7)
Interior volume, cu. ft. (cu. m)	39.0 (1.10)	46.5 (1.32)
Cab Cargo Volume		
(Rear seat up), cu. ft. (cu. m)	30.0 (0.85)	37.1 (1.05)

<b>CURB WEIGHT AND PAYLOAD</b>							
<b>Drive</b>	<b>Body Style</b>	<b>Model</b>	<b>Engine</b>	<b>GVWR (lbs.) (lbs.)(a)</b>	<b>Base Curb Wt. (lbs.)(b)</b>	<b>Payload</b>	
<b>2WD</b>	<i>Club Cab</i>	<i>ST</i>	3.7L V-6	6010	4261	1700	
			4.7L V-8	6010	4347	1610	
			4.7L V-8 HO	6010	4381	1580	
		<i>SLT</i>	3.7L V-6	6010	4285	1680	
			4.7L V-8	6010	4348	1610	
			4.7L V-8 HO	6010	4409	1550	
	<i>Laramie</i>	3.7L V-6	6010	4286	1670		
			6010	4413	1550		
			6010	4409	1550		
		<i>Quad Cab</i>	<i>ST</i>	3.7L V-6	6010	4376	1580
				4.7L V-8	6010	4461	1500
				4.7L V-8 HO	6010	4486	1470
	<i>SLT</i>	3.7L V-6	6010	4379	1580		
			6010	4450	1510		
			6010	4486	1470		
		<i>Laramie</i>	3.7L V-6	6010	4379	1580	
				6010	4507	1450	
				6010	4504	1460	
<b>4WD</b>	<i>Club Cab</i>	<i>ST</i>	3.7L V-6	6010	4456	1500	
			4.7L V-8	6010	4500	1460	
			4.7L V-8 HO	6010	4590	1370	
		<i>SLT</i>	3.7L V-6	6010	4470	1490	
			4.7L V-8	6010	4533	1430	
			4.7L V-8 HO	6010	4590	1370	
	<i>Laramie</i>	3.7L V-6	6010	4518	1440		
			6010	4641	1320		
			6010	4638	1320		
		<i>Quad Cab</i>	<i>ST</i>	3.7L V-6	6010	4573	1390
				4.7L V-8	6010	4624	1340
				4.7L V-8 HO	6010	4690	1270
	<i>SLT</i>	3.7L V-6	6010	4566	1390		
			6010	4632	1330		
			6010	4652	1310		
		<i>Laramie</i>	3.7L V-6	6010	4652	1310	
				6010	4751	1210	
				6010	4748	1210	

(a) Curb weight includes standard equipment and full quantities of fuel, lubricant and coolant.  
(b) Payload = GVWR minus curb weight minus 50 lbs. and payload is rounded to the nearest 10 lbs.

**CURB WEIGHT AND PAYLOAD**

<i>DAKOTA CLUB CAB 2WD SHORT BED ST</i>													
<b>Engine</b>	<b>Trans Type</b>	<b>Transmission</b>	<b>Axle Ratio</b>	<b>Rear Axle</b>	<b>GVWR Wt.</b>	<b>Payload</b>	<b>Base Curb Wt.</b>	<b>Base Curb Wt. Front</b>	<b>Base Curb Wt. Rear</b>	<b>GAWR Front</b>	<b>GAWR Rear</b>	<b>GCWR</b>	<b>Max Trailer</b>
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1750	4261	2461	1800	3100	3600	7700	3300
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	8.25	6010	1750	4261	2461	1800	3100	3600	8500	4100
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	8.25	6010	1750	4256	2448	1808	3100	3600	9000	4600
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	8.25	6010	1750	4256	2448	1808	3100	3600	9300	4900
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.21	9.25	6010	1660	4347	2524	1823	3100	3600	9500	5000
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1660	4347	2524	1823	3100	3600	10,000	5500
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1610	4401	2563	1838	3100	3600	10,500	5950
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1610	4401	2563	1838	3100	3600	11,700	7150

**DAKOTA CLUB CAB 2WD SHORT BED SLT**

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1730	4285	2473	1812	3100	3600	7700	3250
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	8.25	6010	1730	4285	2473	1812	3100	3600	8500	4050
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	8.25	6010	1730	4280	2460	1820	3100	3600	9000	4550
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	8.25	6010	1730	4280	2460	1820	3100	3600	9300	4850
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.21	9.25	6010	1660	4349	2536	1813	3100	3600	9500	5000
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1660	4349	2536	1813	3100	3600	10,000	5500
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1610	4402	2575	1828	3100	3600	10,500	5950
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1610	4402	2575	1828	3100	3600	11,700	7150
4.7L V-8 HO (EVC)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1630	4381	2566	1815	3100	3600	11,700	7150

1. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.  
Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

**DAKOTA QUAD CAB 2WD SHORT BED ST**

Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1630	4376	2470	1906	3100	3600	7700	3150
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	8.25	6010	1630	4376	2470	1906	3100	3600	8500	3950
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	8.25	6010	1640	4371	2457	1914	3100	3600	9000	4500
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	8.25	6010	1640	4371	2457	1914	3100	3600	9300	4800
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.21	9.25	6010	1550	4462	2532	1930	3100	3600	9500	4900
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1550	4462	2532	1930	3100	3600	10,000	5400
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1490	4518	2573	1945	3100	3600	10,500	5850
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1490	4518	2573	1945	3100	3600	11,700	7050

**CURB WEIGHT AND PAYLOAD (CONTINUED)**

<i>DAKOTA QUAD CAB 2WD SHORT BED SLT</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.21	8.25	6010	1630	4379	2480	1899	3100	3600	7700	3150
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	8.25	6010	1630	4379	2480	1899	3100	3600	8500	3950
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	8.25	6010	1640	4374	2467	1907	3100	3600	9000	4500
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	8.25	6010	1640	4374	2467	1907	3100	3600	9300	4800
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.21	9.25	6010	1560	4451	2542	1908	3100	3600	9500	4900
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1560	4451	2542	1908	3100	3600	10,000	5400
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1500	4507	2583	1924	3100	3600	10,500	5850
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1500	4507	2583	1924	3100	3600	11,700	7050
4.7L V-8 HO (EVC)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1520	4486	2575	1911	3100	3600	11,700	7050

1. Payload = GVWR - Curb Wt.  
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.  
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

<i>DAKOTA CLUB CAB LARAMIE 2WD SHORT BED</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	8.25	6010	1720	4287	2478	1809	3100	3600	9000	4550
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	8.25	6010	1720	4287	2478	1809	3100	3600	9300	4850
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1600	4413	2584	1829	3100	3600	10,500	5950
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1600	4413	2584	1829	3100	3600	11,700	7150
4.7L V-8 HO (EVC)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1600	4410	2584	1826	3100	3600	11,700	7150

<i>DAKOTA QUAD CAB LARAMIE 2WD SHORT BED</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	8.25	6010	1630	4379	2484	1895	3100	3600	9000	4450
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	8.25	6010	1630	4379	2484	1895	3100	3600	9300	4750
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1500	4507	2592	1916	3100	3600	10,500	5850
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1500	4507	2592	1916	3100	3600	11,700	7050
4.7L V-8 HO (EVC)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1510	4504	2591	1913	3100	3600	11,700	7050

1. Payload = GVWR - Curb Wt.  
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.  
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

<i>DAKOTA CLUB CAB 4WD SHORT BED ST</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1550	4456	2634	1822	3600	3600	8500	3900
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	9.25	6010	1550	4455	2623	1832	3600	3600	9000	4400
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	9.25	6010	1550	4455	2623	1832	3600	3600	9300	4700
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1510	4500	2683	1817	3600	3600	10,000	5350
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1450	4560	2724	1836	3600	3600	10,500	5800
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1450	4560	2724	1836	3600	3600	11,700	7000

**CURB WEIGHT AND PAYLOAD (CONTINUED)**

<i>DAKOTA CLUB CAB 4WD SHORT BED SLT</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1540	4470	2645	1825	3600	3600	8500	3900
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	9.25	6010	1540	4470	2635	1835	3600	3600	9000	4400
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	9.25	6010	1540	4470	2635	1835	3600	3600	9300	4700
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1480	4533	2693	1839	3600	3600	10,000	5300
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1420	4592	2734	1858	3600	3600	10,500	5750
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1420	4592	2734	1858	3600	3600	11,700	6950
4.7L V-8 HO (EVC)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1420	4589	2734	1855	3600	3600	11,700	6950

1. Payload = GVWR - Curb Wt.  
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.  
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

<i>DAKOTA QUAD CAB 4WD SHORT BED ST</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1440	4573	2646	1927	3600	3600	8500	3800
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	9.25	6010	1440	4573	2636	1937	3600	3600	9000	4300
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	9.25	6010	1440	4573	2636	1937	3600	3600	9300	4600
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1390	4624	2694	1930	3600	3600	10,000	5250
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1330	4684	2736	1949	3600	3600	10,500	5650
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1330	4684	2736	1949	3600	3600	11,700	6850

<i>DAKOTA QUAD CAB 4WD SHORT BED SLT</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1440	4567	2652	1915	3600	3600	8500	3800
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	9.25	6010	1440	4567	2641	1925	3600	3600	9000	4300
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	9.25	6010	1440	4567	2641	1925	3600	3600	9300	4600
4.7L V-8 (EVA)	M6	Getrag 6-spd. MANU (DEJ)	3.55	9.25	6010	1380	4633	2707	1926	3600	3600	10,000	5200
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1320	4693	2748	1945	3600	3600	10,500	5650
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1320	4693	2748	1945	3600	3600	11,700	6850
4.7L V-8 HO (EVC)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1320	4690	2748	1942	3600	3600	11,700	6850

1. Payload = GVWR - Curb Wt.  
 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs.  
 Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)

<i>DAKOTA CLUB CAB LARAMIE 4WD SHORT BED</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	9.25	6010	1490	4518	2658	1860	3600	3600	9000	4350
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	9.25	6010	1490	4518	2658	1860	3600	3600	9300	4650
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1370	4641	2758	1883	3600	3600	10,500	5700
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1370	4641	2758	1883	3600	3600	11,700	6900
4.7L V-8 HO (EVC)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1370	4638	2757	1880	3600	3600	11,700	6900

**CURB WEIGHT AND PAYLOAD (CONTINUED)**

<i>DAKOTA QUAD CAB LARAMIE 4WD SHORT BED</i>													
Engine	Trans Type	Transmission	Axle Ratio	Rear Axle	GVWR Wt.	Payload	Base Curb Wt.	Base Curb Wt. Front	Base Curb Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trailer
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.55	9.25	6010	1390	4621	2680	1941	3600	3600	9000	4250
3.7L V-6 (EKG)	A4	42RLE 4-spd. AUTO (DG6)	3.92	9.25	6010	1390	4621	2680	1941	3600	3600	9300	4550
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.55	9.25	6010	1260	4751	2779	1972	3600	3600	10,500	5600
4.7L V-8 (EVA)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1260	4751	2779	1972	3600	3600	11,700	6800
4.7L V-8 HO (EVC)	A5	545RFE 5-spd. AUTO (DGQ)	3.92	9.25	6010	1260	4748	2779	1970	3600	3600	11,700	6800
1. Payload = GVWR - Curb Wt. 2. Maximum trailer weights are rounded to the nearest 50 lbs. and Payload to nearest 10 lbs. Maximum Trailer Weights = GCWR - Curb. Wt. - 150 lbs. (allowance for driver)													