

LEGEND: S=Standard, O=Optional, P=Package, — = Not available

Complete package information is listed at the end of the Feature Availability section.

NOTE: Information shown is correct at time of publication, and is subject to change without notice.

## 2007 Dodge Magnum FEATURE AVAILABILITY

	SE RWD	SXT AWD	R/T RWD	R/T AWD
<b>EXTERIOR</b>				
Colors:				
Bright Silver Metallic Clear Coat, Brilliant Black Crystal Pearl Coat, Inferno Red Crystal Pearl Coat, Marine Blue Pearl Coat, Silver Steel Metallic Clear Coat, Steel Blue Metallic Clear Coat, Stone White Clear Coat and TorRed_____	O	O	O	O
Badging				
Magnum _____	S	S	S	S
Ram's head _____	S	S	S	S
SXT (P12) _____	P	S	—	—
3.5-liter High Output engine (P12) _____	P	S	—	—
R/T _____	—	—	S	S
HEMI® _____	—	—	S	S
AWD _____	—	S	—	S
Defroster—Electric rear window _____	S	S	S	S
Door Handles—Body color _____	S	S	S	S
Fascias—Body color _____	S	S	S	S
Grille—Body color _____	S	—	—	—
Grille—Body color with bright insert (P12) _____	P	S	S	S
Lamps				
Halogen headlamps with delay feature _____	S	S	S	S
Fog lamps (P12) _____	P	S	S	S
Automatic headlamps (P4, P5) _____	P	P	P	P
Mirrors				
Black, power, fixed _____	S	—	—	—
Body color, power, foldaway, heated (P12) _____	P	S	S	S
Molding				
Bodyside with bright insert _____	O	S	S	S
Roof Rack _____	O	O	O	O
Sun Roof—Power (not available on SE, option on P12) _____	P	O	O	O
Trim				
Black headlamp bezels _____	S	—	—	—
Chrome headlamp bezels (P12) _____	P	S	S	S
Wiper System—Front—variable intermittent and rear _____	S	S	S	S
	SE RWD	SXT AWD	R/T RWD	R/T AWD
<b>INTERIOR</b>				
Air Conditioning				
Manual control _____	S	S	S	S
Dual-Zone Automatic Temperature Control (P4) _____	—	—	P	P
Cargo Compartment Cover (in Roof Rack and Cargo Organizer Group) _____	P	S	S	S
Cargo Net _____	O	O	O	O

Cargo Organizer Group (includes cargo organizer and cargo cover (P9) _____	O	O	O	O
Door Locks—Power _____	S	S	S	S
Glass—Sunscreen privacy _____	S	S	S	S
Interior Colors				
Medium Slate Gray Trumbull Cloth; Dark Slate Gray (surrounding bodyside trim), Medium Slate Gray (lower trim) _____	O	O	—	—
Dark Slate Gray Trumbull Cloth; Dark Slate Gray (surrounding bodyside trim), Light Graystone (lower trim) _____	O	O	—	—
Medium Slate Gray Royale Leather trim; Dark Slate Gray (surrounding bodyside trim); Medium Slate Gray (lower trim) _____	—	O	O	O
Light Graystone Royale Leather trim; Dark Slate Gray (surrounding bodyside trim), Light Graystone (lower trim) _____	—	O	O	O
Center Stack Bezel—Satin Silver (P12) _____	P	S	S	S
Console—Floor (includes two cup holders, covered storage, armrest with tissue holder and pen holder, mini-storage bin next to shifter) _____	S	S	S	S
Cupholder Door with Chrome Accent _____	—	—	S	S
Floor Mats—Front and rear _____	S	S	S	S
Headliner Module with sunglass holder and reading lamps _____	S	S	S	S
Instrument Cluster Appearance—Electroluminescent with white face gauges _____	S	S	S	S
Instrument Cluster with 140-MPH speedometer _____	S	S	—	—
Instrument Cluster with 160-MPH speedometer _____	—	—	S	S
In-cluster Outside Temperature Display _____	S	S	S	S
Instrument Panel Speed Control Indicator Light _____	S	S	S	S
Lamps				
Front and rear reading/courtesy _____	S	S	S	S
Cargo area _____	S	S	S	S
Map Pockets—Front and rear doors _____	S	S	S	S
Mirror				
Day/night rearview _____	S	S	S	S
Dual covered visor vanity mirrors _____	S	—	—	—
Dual illuminated visor vanity mirrors _____	P	S	S	S
Power Adjustable Pedals (P2, P3, P12) _____	P	O/P	S	S
Power Outlets—12-volt, located in instrument panel, center console, rear cargo area _____	S	S	S	S
Seats				
Driver/passenger adjustable lumbar support _____	S	S	S	S
Low-back cloth-trimmed bucket seats _____	S	S	—	—
Power eight-way driver seat (P3, P12) _____	P	S	S	S
Leather-trimmed (P2, P12) _____	P	O/P	S	S
Eight-way power passenger seat (P2, P4, P13, available on SXT) _____	—	P	P	P
Heated front seats (P2, P4, P13, available on SXT) _____	—	P	P	P
Seat—Rear—60/40 split-folding with armrest and cup holders _____	S	S	S	S
Shift Knob				
Urethane _____	S	S	—	—
Leather-wrapped (P2, P12) _____	P	P	S	S
Leather-wrapped with leather-wrapped steering wheel (P2, P12) _____	P	P	S	S
Sound/Entertainment Systems				
AM/FM/CD stereo radio with changer controls and auxillary audio input jack _____	S	S	S	S
AM/FM/cassette/CD stereo radio with six-disc CD changer, MP3 capability _____	O	O	O	O
AM/FM/six-CD radio with 5.8-inch display screen DVD-based GPS navigation system and MP3 capability (P12) _____	O	O	O	O
Four-speaker system _____	S	S	—	—
Six Boston Acoustics speakers with 276-watt digital (DSP) amplifier (available on SXT) _____	—	O	S	S
Rear Seat Video System (VES™) includes DVD player with auxiliary audio/video input jacks, two wireless two-channel headphones and remote (available on SXT) _____	—	O	O	O

SIRIUS Satellite Radio with one-year free subscription _____	O	O	S	S
Speed Control with instrument panel indicator light _____	S	S	S	S
Steering Column—Manual tilt, telescoping _____	S	S	S	S
Steering Wheel				
Urethane _____	S	S	—	—
Leather-wrapped with Satin Silver lower steering wheel spokes (P2) _____	—	P	S	S
UConnect® Hands-free Communication System (includes interior auto-dimming mirror) _____	—	O	O	O
Windows				
Power with driver one-touch down _____	S	S	S	S
Power with driver and passenger one-touch express up/down with auto reverse sensing system (P4, P5, P13) _____	P	P	P	P
	SE	SXT	R/T	R/T
	RWD	AWD	RWD	AWD
<b>POWERTRAIN/CHASSIS</b>				
2.7-liter, DOHC, 24-valve 190 hp V-6 engine and four-speed automatic transmission _____	S	—	—	—
3.5-liter SOHC, High Output 24V 250-hp V-6 Engine and five-speed automatic transmission with Auto Stick (P12) _____	P	S	—	—
5.7-liter HEMI Multi-Displacement V-8 Engine and five-speed automatic transmission with Auto Stick _____	—	—	S	S
Brakes				
Power four-wheel disc _____	S	—	—	—
Power four-wheel disc with Anti-lock Brake System (ABS) with all-speed traction control system (P12) _____	O/P	—	—	—
Power four-wheel performance disc with Anti-lock Brake System (ABS) _____	—	S	S	S
Electronic Stability Program (ESP) with Brake Assist (P12) _____	O/P	S	S	S
Engine Block Heater _____	O	O	O	O
Enhanced Battery Saver _____	S	S	S	S
Dual Exhaust with Bright Tips _____	—	—	S	S
Fuel Tank—18-gallon _____	S	—	—	—
Fuel Tank—19-gallon _____	—	S	S	S
Load-leveling, Height Control (Nivomat™) Shocks and Severe-duty Engine Cooling (P11) _____	O	O	P	P
Power Accessory Delay _____	S	S	S	S
Severe-duty engine cooling (P11) _____	—	—	P	P
Speed Control with Instrument Panel Indicator Light _____	S	S	S	S
Suspension				
Four-wheel independent _____	S	S	—	—
Touring with 18-inch wheels (P12) _____	—	S	S	S
Tire Pressure Monitoring System with Warning Lamp _____	—	—	S	S
Tires				
Compact spare _____	S	S	S	S
P215/65R17 all-season ride _____	S	—	—	—
P215/65R17 all-season ride self-sealing (P8) _____	P	—	—	—
P225/60R18 Touring (available on P12) _____	—	S	S	S
P225/60R18 Touring self-sealing (P8, available on P12) _____	—	P	P	P
P245/45ZR20 (P13) _____	—	—	P	—
Trailer Tow prep package (p11) _____	—	—	O	O
Wheels				
17-inch steel with bolt-on covers _____	S	—	—	—
17-inch machined aluminum (P12) _____	—	—	—	—
18-inch ultra-bright aluminum (option on P12) _____	—	—	S	—
18-inch chrome-clad aluminum (option on P12 and R/T RWD) _____	—	—	O	—
18-inch cast aluminum (AWD models) _____	—	S	—	S
20-inch chrome-clad aluminum (P13) _____	—	—	P	—

	SE RWD	SXT AWD	R/T RWD	R/T AWD
<b>SAFETY AND SECURITY</b>				
Advanced Multi-stage Front Air Bag System (low-risk deployment) (a) _____	S	S	S	S
Brake/Park Interlock _____	S	S	S	S
Side Curtain Air Bags (P8) _____	O/P	P	P	P
Lower Anchors and Tethers for Children (LATCH) child seat anchor system _____	S	S	S	S
Door Locks—Power _____	S	S	S	S
Vehicle speed-sensitive automatic power with illuminated switches _____	S	S	S	S
Central locking _____	S	S	S	S
Child-protection, rear _____	S	S	S	S
Electronic Stability Program (ESP) with Brake Assist, All-speed Traction Control and Four-wheel Anti-lock Brake System (ABS) (included on P12) _____	O	S	S	S
HomeLink Universal Home Security System Transceiver (P6) _____	—	—	P	P
Remote Keyless Illuminated Entry with Panic Button on Key Fob _____	S	S	S	S
Seat Belts _____				
Front: Height-adjustable three-point belts with constant-force retractors, pretensioners and traveling buckles _____	S	S	S	S
Rear: Three-point for all seating positions _____	S	S	S	S
Seat BeltAlert _____	S	S	S	S
Sentry Key® Engine Immobilizer _____	S	S	S	S
Tire Pressure Monitoring System with Warning Lamp _____	—	—	S	S

SE RWD	SXT AWD	R/T RWD	R/T AWD
-----------	------------	------------	------------

**PACKAGES**

<b>P1</b> – All-Wheel-Drive (AWD)—Includes 18-inch machined aluminum wheels and touring tires; performance disc brakes; front differential and transfer case and 19-gallon fuel tank _____	—	S	—	S
<b>P2</b> – Comfort Seating Group—Leather-trimmed bucket seats, steering wheel and shift knob; heated front seats; power eight-way driver/front passenger seat with power recline; power adjustable pedals (SXT RWD and AWD) _____	—	O	—	—
<b>P3</b> – Convenience Group I—Includes eight-way power driver's seat and power adjustable pedals _____	O	O	—	—
<b>P4</b> – Convenience Group II—Includes dual-zone automatic temperature control, heated power eight-way driver/front passenger seat with power recline, auto headlamps, one-touch express up/down windows with auto-reverse sensing system _____	—	—	O	O
<b>P5</b> – Convenience Group III—Includes dual-zone automatic temperature control, automatic headlamps and one-touch express up/down windows with auto-reverse sensing system (Optional on SXT (RWD)) _____	O	O	—	—
<b>P6</b> – Electronics Convenience Group—Instrument cluster with display screen, compass gauge, vehicle information center, traveler/mini-trip computer, security alarm, steering wheel-mounted audio controls and HomeLink universal transceiver garage door opener _____	—	—	O	O

<b>P7</b> – Electronic Stability Program (ESP) with brake assist, four-wheel ABS disc brakes, all-speed traction control. Performance four-wheel disc brakes on R/T RWD and AWD models (Included with P12) _____	O/P	S	S	S
<b>P8</b> – Protection Group—Includes supplemental front and rear side-curtain air bags(a), air filtering system and P215/65R17AS self-sealing tires or P225/60R18 self-sealing tires _____	O	O	O	O
<b>P9</b> – Roof Rack and Cargo Organizer Group—Rear cargo organizer, cargo cover and roof rack _____	O	O	O	O
<b>P10</b> – Smoker’s Group—Front ash tray, cigar lighter _____	S	S	S	S
<b>P11</b> – Trailer Tow Prep Package—Load leveling and height control, severe duty engine cooling _____	—	—	O	O
<b>P12</b> – SXT RWD Package—Includes 3.5-liter SOHC high output 24V 250-hp V-6 engine and five-speed automatic transmission; 17-inch wheels; chrome grille accents;bright headlamp bezels; ABS; ESP w/Brake Assist; all-speed TCS; body color, heated power mirrors; fog lamps; body color grille w/bright insert; cargo net; dual illuminated visor mirrors; leather-wrapped steering wheel and shift knob; eight-way power driver seat and satin-silver center stack bezels. Options include: 18-inch ultra-bright or chrome-clad aluminum wheels; Protection Group; Convenience Group III; Rear-seat Video Entertainment system; AM/FM/six-CD DVD-based navigation radio w/GPS or AM/FM/cassette/ six-CD radio; 276-watt six-speaker Boston Acoustics sound system; sunroof; leather-trimmed seats; Comfort Seating Group; UConnect® Hands-free Communication System with auto-dimming interior mirror and power adjustable pedals _____	O	—	—	—
<b>P13</b> – Road/Track Performance Group—Includes 20-inch chrome-clad aluminum wheels; 245/45ZR20 all-season performance tires; performance exhaust/induction resulting in additional _10-hp; upgraded suspension and steering gear, performance seats with preferred suede inserts, automatic temperature control, express up/down front windows, 8-way driver and passenger heated front seats, automatic headlamps, load leveling and height control shocks, heritage R/T exterior badging and upholstery and five exterior color offerings _____	—	—	O	—

(a) Always use seat belts. Children 12 and under should always be in a back seat correctly using an infant or child restraint system, or the seat belt positioned correctly for the child’s age and size.

## SPECIFICATIONS

Dimensions are in inches (millimeters) unless otherwise noted.

### GENERAL INFORMATION

Body Style \_\_\_\_\_ Sport Tourer  
 Assembly Plant \_\_\_\_\_ Brampton, Ontario, Canada  
 EPA Vehicle Class \_\_\_\_\_ Multi-purpose vehicle  
 Introduction Date \_\_\_\_\_ Spring 2004 as 2005 model

### ENGINE: 2.7-LITER, DOHC 24-VALVE V-6

Availability \_\_\_\_\_ Std.—SE  
 Type and Description \_\_\_ 60-degree bank angle, liquid-cooled, active dual-tuned intake manifold with electronically controlled manifold tuning valve  
 Displacement \_\_\_\_\_ 167 cu. in. (2736 cu. cm)

Bore x Stroke \_\_\_\_\_ 3.38 x 3.09 (86 x 78.5)  
 Valve System \_\_\_\_\_ DOHC, 24 valves, hydraulic end-pivot roller followers  
 Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic  
 Construction \_\_\_\_\_ Semi-permanent mold-aluminum block with cast-in iron liners,  
 cross-bolted main bearing caps, cast-aluminum heads  
 Compression Ratio \_\_\_\_\_ 9.7:1  
 Power (SAE net) \_\_\_\_\_ 190 bhp (142 kW) @ 6,400 rpm (70.4 bhp/L)  
 Torque (SAE net) \_\_\_\_\_ 190 lb.-ft. (258 N•m) @ 4,000 rpm  
 Max. Engine Speed \_\_\_\_\_ 6,600 rpm (electronically limited)  
 Fuel Requirement \_\_\_\_\_ Unleaded regular, 87 octane (R+M)/2  
 Oil Capacity \_\_\_\_\_ 6 qt. (5.7L) with dry filter  
 Coolant Capacity \_\_\_\_\_ 9.5 qt. (9L)  
 Emission Controls \_\_\_\_\_ Dual close-coupled three-way catalytic converters,  
 quad heated oxygen sensors and internal engine features(a)  
 Max. Gross Trailer Weight \_\_\_\_\_ 1,000 lbs. (454 kg)  
 EPA Fuel Economy mpg (City/Hwy) \_\_\_\_\_ 21/28

**ENGINE: 3.5-LITER, HIGH OUTPUT, SOHC 24-VALVE V-6**

Availability \_\_\_\_\_ Std.—SXT RWD Package and SXT AWD model  
 Type and Description \_\_\_\_\_ 60-degree, liquid-cooled, active three-plenum intake manifold with  
 electronically controlled manifold tuning valve and short-runner valves  
 Displacement \_\_\_\_\_ 214.7 cu. in. (3518 cu. cm)  
 Bore x Stroke \_\_\_\_\_ 3.78 x 3.19 (96 x 81)  
 Valve System \_\_\_\_\_ SOHC, 24 valves, hydraulic, center-pivot roller rocker arms  
 Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic  
 Construction \_\_\_\_\_ Precision cast mold-aluminum block with cast-in iron liners,  
 cross-bolted main bearing caps and cast-aluminum heads  
 Compression Ratio \_\_\_\_\_ 10.10:1  
 Power (SAE net) \_\_\_\_\_ 250 bhp (186 kW) @ 6,400 rpm (70.0 bhp/L)  
 Torque (SAE net) \_\_\_\_\_ 250 lb.-ft. (340 N•m) @ 3,800 rpm  
 Max. Engine Speed \_\_\_\_\_ 6,800 rpm (electronically limited)  
 Fuel Requirement \_\_\_\_\_ Unleaded mid-grade, 89 octane (R+M)/2—recommended,  
 unleaded regular, 87 octane (R+M)/2—acceptable  
 Oil Capacity \_\_\_\_\_ 6 qt. (5.7L) with dry filter  
 Coolant Capacity \_\_\_\_\_ 10.3 qt. (9.75L)  
 Emission Controls \_\_\_\_\_ Dual close-coupled three-way catalytic converters,  
 quad heated oxygen sensors and internal engine features(a)  
 Max. Gross Trailer Weight \_\_\_\_\_ 2,000 lbs. (907 kg)  
 EPA Fuel Economy mpg (City/Hwy) \_\_\_\_\_ RWD—19/27, AWD—17/24

*(a) Meets Federal Tier 2, Bin 8 emissions requirements; marketed in California as an ULEV1 (Ultra-low Emission Vehicle) under cleanest vehicle rules.*

**ENGINE: 5.7-LITER, HEMI® MULTI-DISPLACEMENT V-8**

Availability \_\_\_\_\_ Std.—R/T (RWD/AWD)  
 Type and Description \_\_\_\_\_ 90-degree V-type, liquid-cooled  
 Displacement \_\_\_\_\_ 345 cu. in. (5654 cu. cm)  
 Bore x Stroke \_\_\_\_\_ 3.92 x 3.58 (99.5 x 90.9)  
 Valve System \_\_\_\_\_ Pushrod-operated overhead valves, 16 valves, eight deactivating and  
 eight conventional hydraulic lifters, all with roller followers  
 Fuel Injection \_\_\_\_\_ Sequential, multi-port, electronic, returnless  
 Construction \_\_\_\_\_ Deep-skirt cast-iron block with cross-bolted main bearing caps,  
 aluminum alloy heads with hemispherical combustion chambers  
 Compression Ratio \_\_\_\_\_ 9.6:1  
 Power (SAE net) \_\_\_\_\_ 340 bhp (254 kW) @ 5,000 rpm (59.6 bhp/L)  
 \_\_\_\_\_ 350 bhp (261 kW) @ 5,200 rpm – Opt. with Road/Track Performance Group  
 Torque (SAE net) \_\_\_\_\_ 390 lb.-ft. (525 N•m) @ 4,000 rpm

Max. Engine Speed \_\_\_\_\_ 5,800 rpm (electronically limited)  
 Fuel Requirement \_\_\_\_\_ Unleaded mid-grade, 89 octane (R+M)/2—recommended,  
 unleaded regular, 87 octane (R+M)/2—acceptable  
 Oil Capacity \_\_\_\_\_ 7 qt. (6.6L)  
 Coolant Capacity \_\_\_\_\_ 13.75 qt. (13L)  
 Emission Controls \_\_\_\_\_ Dual close-coupled three-way catalytic converters,  
 quad heated oxygen sensors and internal engine features(a)  
 Max. Gross Trailer Weight \_\_\_\_\_ 2,000 lbs. (907 kg)—std. 3,800 lbs. (1724 kg)—opt.  
 EPA Fuel Economy, mpg (City/Hwy) \_\_\_\_\_ RWD—17/25, AWD—17/24

(a) Meets Federal Tier 2, Bin 8 emissions requirements; marketed in California as an ULEV1 (Ultra-low Emission Vehicle) under cleanest vehicle rules.

**TRANSMISSION: AUTOMATIC, FOUR-SPEED OVERDRIVE**

Availability \_\_\_\_\_ Std. with 2.7-liter V-6 engine, SE  
 Description \_\_\_\_\_ Three planetary gear sets, one overrunning clutch, full electronic control,  
 electronically controlled torque converter clutch, Variable Line Pressure (VLP)  
 Gear Ratios  
 1st \_\_\_\_\_ 2.84  
 2nd \_\_\_\_\_ 1.57  
 3rd \_\_\_\_\_ 1.00  
 4th \_\_\_\_\_ 0.69  
 Reverse \_\_\_\_\_ 2.21  
 Final Drive Ratio \_\_\_\_\_ 3.90  
 Overall Top Gear Ratio \_\_\_\_\_ 2.70

**TRANSMISSION: AUTOMATIC, FIVE-SPEED AUTOMATIC WITH AUTO STICK**

Availability \_\_\_\_\_ Std. SXT (RWD/AWD) and R/T (RWD/AWD)  
 Description \_\_\_\_\_ Adaptive electronic control or Auto Stick driver-interactive manual control  
 and electronically modulated torque converter clutch  
 Gear Ratios  
 1st \_\_\_\_\_ 3.59  
 2nd \_\_\_\_\_ 2.19  
 3rd \_\_\_\_\_ 1.41  
 4th \_\_\_\_\_ 1.00  
 5th \_\_\_\_\_ 0.83  
 Reverse \_\_\_\_\_ 3.17  
 Final Drive Ratio \_\_\_\_\_ 3.5L (RWD)—2.87; 5.7L (RWD)—2.82, AWD All—3.07  
 Overall Top Gear \_\_\_\_\_ 3.5L (RWD)—2.38; 5.7L (RWD)—2.34, AWD All—2.55

**TRANSFER CASE**

Availability \_\_\_\_\_ Std. with all-wheel drive  
 Type \_\_\_\_\_ Single-speed constant engagement  
 Center Differential \_\_\_\_\_ Planetary  
 Torque Split, Front/Rear \_\_\_\_\_ 38/62

**ELECTRICAL SYSTEM**

Alternator \_\_\_\_\_ SE 140-amp, SXT and R/T—160-amp  
 Battery \_\_\_\_\_ H7 Case, 600 CCA, maintenance-free

**DIMENSIONS AND CAPACITIES(a)**

Wheelbase \_\_\_\_\_ 120.0 (3048)  
 Track, Front \_\_\_\_\_ 63.0 (1600)  
 Track, Rear \_\_\_\_\_ 63.1 (1603)  
 Overall Length \_\_\_\_\_ 197.7 (5021)  
 Overall Width \_\_\_\_\_ 74.1 (1881)  
 Overall Height \_\_\_\_\_ 58.3 (1481)

Ground Clearance _____	5.6 (143)
Frontal Area, sq. ft. (sq. m) _____	25.4 (2.36)
Drag Coefficient _____	SE—0.337
	SXT RWD—0.346
	R/T RWD—0.355
	SXT and R/T AWD—0.365
Curb Weight, lb. (kg) _____	SE—3847 (1745)
	SXT RWD—3,895 (1766)
	SXT AWD—4,159 (1886)
	R/T RWD—4,179 (1895)
	R/T AWD—4,393 (1992)
Weight Distribution, percent F/R _____	SE—51/49,
	SXT and R/T (RWD)—52/48
	SXT AWD—53/47
	R/T AWD—54/46
Fuel Tank Capacity, gal. (L) _____	SE and SXT Package—18 (68)
	SXT AWD and R/T RWD and AWD—19 (72)

(a) All dimensions measured at curb weight with standard tires.

### ACCOMMODATIONS

Seating Capacity, F/R \_\_\_\_\_ 2/3

#### Front

Head room _____	38.4 (983)
Leg room _____	41.8 (1061)
Shoulder room _____	58.7 (1490)
Hip room _____	56.2 (1427)
Seat travel _____	Driver—10.6 (270), passenger—8.66 (220)
Recliner angle range, deg. _____	Driver—70, passenger—69
SAE front volume index, cu. ft. (cu. m) _____	55.0 (1.56)

#### Rear Seat

Head room _____	38.1 (968)
Leg room _____	40.2 (1020)
Knee clearance _____	4.8 (122)
Shoulder room _____	57.6 (1464)
Hip room _____	55.5 (1409)
SAE rear seat volume index, cu. ft. (cu. m) _____	50.9 (1.44)
SAE interior volume, cu. ft. (cu. m) _____	105.9 (3.00)

#### Cargo Volume Indexes

Rear seats up, cu. ft. (L) _____	27.2 (770)
Rear seats folded, cu. ft. (cu. m) _____	71.6 (2.03)
EPA interior volume index, cu. ft. (cu. m) _____	133.1 (3.77)
Liftover height _____	29.7 (752)

### BODY

Layout \_\_\_\_\_ Longitudinal front engine, rear-wheel drive or all-wheel drive

Construction \_\_\_\_\_ Unitized steel body

### SUSPENSION

Front \_\_\_\_\_ Independent SLA with high upper "A" arm, coil spring over gas-charged shock absorbers and stabilizer bar (with 18-inch wheels)—Std. All; Lateral and diagonal lower links with dual ball joint knuckle—Std. RWD; Lower "A" arm—Std. AWD

Rear \_\_\_\_\_ Five-link independent with coil springs, gas-charged shock absorbers and isolated suspension cradle—Std. All; Nivomat™ self-leveling shock absorbers—Opt. with trailer tow and Road/Track Performance Group; Link-type stabilizer bar, – Opt. with 18-inch and 20-inch wheels and AWD models



**STEERING**

Type \_\_\_\_\_ Rack-and-pinion with hydraulic power assist  
Overall Ratio \_\_\_\_\_ 16.1:1  
Turning Diameter (curb-to-curb) \_\_\_\_\_ Rear-wheel drive—38.9 ft. (11.9 m),  
all-wheel drive—38.8 ft (11.8 m)  
Steering Turns (lock-to-lock) \_\_\_\_\_ Rear-wheel drive—2.75, all-wheel drive—2.90

**TIRES**

*SE and SXT Package—Standard*

Size and type \_\_\_\_\_ P215/65R1798T black sidewall all-season ride  
Mfr. and model \_\_\_\_\_ Goodyear Integrity  
Revs per mile (km) \_\_\_\_\_ 730 (454)

*Optional*

Size and type \_\_\_\_\_ P215/65R1798T black sidewall all-season ride, self-sealing  
Mfr. and model \_\_\_\_\_ Continental CT95 ContiSeal™  
Revs per mile (km) \_\_\_\_\_ 730 (454)

*R/T—Standard; SXT optional*

Size and type \_\_\_\_\_ P225/60R18H99H all-season touring  
Mfr. and model \_\_\_\_\_ Continental CH95  
Revs per mile (km) \_\_\_\_\_ 735 (457)

*Optional*

Size and type \_\_\_\_\_ P225/60R18H99H all-season touring self-sealing  
Mfr. and model \_\_\_\_\_ Continental CH95 ContiSeal  
Revs per mile (km) \_\_\_\_\_ 735 (457)

*Road/Track Performance Group—Standard*

Size and type \_\_\_\_\_ 245/45ZR20 all-season performance  
Mfr. and model \_\_\_\_\_ Goodyear  
Revs per mile (km) \_\_\_\_\_ 725 (451)

**WHEELS**

*SE RWD—Standard*

Type and material \_\_\_\_\_ Stamped-steel  
Size \_\_\_\_\_ 17 x 7.0

*SXT RWD Package—Standard*

Type and material \_\_\_\_\_ Machined-aluminum  
Size \_\_\_\_\_ 17 x 7.0

*R/T RWD—Standard, SXT RWD Package—Optional*

Type and material \_\_\_\_\_ Ultra-bright machined aluminum  
Size \_\_\_\_\_ 18 x 7.5

*R/T & SXT RWD Package—Optional*

Type and material \_\_\_\_\_ Chrome-clad aluminum  
Size \_\_\_\_\_ 18 x 7.5

*SXT AWD; R/T AWD—Standard*

Type and material \_\_\_\_\_ Machined-aluminum  
Size \_\_\_\_\_ 18 x 7.5

Road/Track Performance Group—Standard

Type and material \_\_\_\_\_ Chrome-clad aluminum  
Size \_\_\_\_\_ 20 x 8.0

**BRAKES**

*SE and SXT Package (RWD)*

Front

Rotor size and type \_\_\_\_\_ 12.6 x 1.1 (320 x 28) vented  
Caliper size and type \_\_\_\_\_ 2.36 (60) single-piston sliding with aluminum housing  
Swept area \_\_\_\_\_ 254.8 sq. in. (1644 sq. cm)

Rear

Rotor size and type \_\_\_\_\_ 12.6 x 0.4 (320 x 10) solid  
Caliper size and type \_\_\_\_\_ 1.65 (42) single-piston sliding with aluminum housing  
Swept area \_\_\_\_\_ 260.4 sq. in. (1680 sq. cm)

Four-wheel anti-lock and traction control \_\_\_\_\_ Std.—SXT Package, opt.—SE  
Electronic stability control and brake assist \_\_\_\_\_ Std.—SXT Package, opt.—SE

Power Assist Type \_\_\_\_\_ 8 x 9 (203 x 229) tandem-diaphragm vacuum booster – Std.

*SXT AWD and R/T AWD and RWD*

Front

Rotor size and type \_\_\_\_\_ 13.6 x 1.1 (345 x 28) vented  
Caliper size and type \_\_\_\_\_ 1.65 (42) dual-piston sliding with aluminum housing  
Swept area \_\_\_\_\_ 292 sq. in. (1884 sq. cm)

Rear

Rotor size and type \_\_\_\_\_ 12.6 x 0.87 (320 x 22) vented  
Caliper size and type \_\_\_\_\_ 1.65 (42) single-piston sliding with aluminum housing  
Swept area \_\_\_\_\_ 260.4 sq. in. (1680 sq. cm)

Four-wheel anti-lock and all-speed traction control \_\_\_\_\_ Std.

Electronic Stability Program and Brake Assist \_\_\_\_\_ Std.

Power Assist Type \_\_\_\_\_ 8 x 9 (203 x 229) tandem-diaphragm vacuum booster – Std.