

2010 Dodge Ram Chassis Cab 3500 SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Body Style	Chassis Cab: Regular Cab and Crew Cab
Assembly Plant	Saltillo, Mexico
EPA Vehicle Class	Medium Heavy Duty

ENGINE: 5.7-LITER HEMI® V-8

Availability	Standard
Type and Description	Eight-cylinder, 90° V-type, liquid-cooled, with variable cam timing (VVT)
Displacement	343 cu. in. (5654 cu. cm)
Bore x Stroke	3.92 x 3.58 (99.5 x 90.9)
Valve System	Pushrod-operated overhead valves, 16 valves, hydraulic lifters with roller followers
Fuel Injection	Sequential, multi-port, electronic, returnless
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	9.6:1
Power (SAE net)	383 hp (286 kW) @ 5,600 rpm
Torque (SAE net)	400 lb.-ft. (542 N•m) @ 4,000 rpm
Maximum Engine Speed	5,800 rpm
Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2—recommended Unleaded regular, 87 octane (R+M)/2—acceptable
Oil Capacity	7 qt. (6.6L)
Coolant Capacity	18.7 qt. (17.7L)
Emission Control	Dual three-way catalytic converters, internal engine features with knock sensors

ENGINE: 6.7-LITER HIGH OUTPUT CUMMINS TURBO DIESEL I-6

Availability	Optional
Type and Description	Six-cylinder, inline, liquid-cooled, turbocharged, intercooled
Displacement	408 cu. in. (6690 cu. cm)
Bore x Stroke	4.21 x 4.88 (107 mm x 124 mm)
Valve System	OHV, 24 valves, and solid lifters
Fuel Injection	Electronic high-pressure common rail
Construction	Cast-iron block and head
Compression Ratio	17.3:1
Power (SAE net)	305 hp (227 kW) @ 2,900 rpm—high output
Torque (SAE net)	610 lb.-ft. (827 N•m) @ 1,600 rpm—high output
Maximum High-idle Engine Speed	3,500 rpm
Fuel Requirement	Ultra-low sulfur diesel
Oil Capacity	(Low ash req.) 12 qt. (11.3L) with filter
Coolant Capacity	32.7 qt. (30.9L)
Emission Controls	Selective Catalytic Reduction (SCR)

ELECTRICAL SYSTEM

Alternator

Availability	Standard-Gas
Rating	160 amp
Battery	Maintenance-free, 750 CCA

Availability	Standard-Diesel; Optional—Gas
Rating	180 amp
Battery	Maintenance-free, 750 CCA

Availability	Optional—with diesel engine
Rating	220 amp
Battery	Dual, maintenance-free, 750 CCA

Battery

Availability	Standard
Description	Group 65, maintenance-free, 750 CCA

Availability	Optional—with diesel engine
Description	Dual, Group 65, maintenance-free, 750 CCA

TRANSMISSION: G56-MANUAL SIX-SPEED OVERDRIVE

Availability	Standard—all
Description	Synchronized in all gears
PTO Capable	Six-bolt mounting, left side

Gear Ratios (6.7L Diesel)

1 st	5.94
2 nd	3.28
3 rd	1.98
4 th	1.3
5 th	1
6 th	0.74
Reverse	5.42

TRANSMISSION: 545RFE-AUTOMATIC FIVE-SPEED

Availability	Packaged with 5.7-liter engine
Description	Three planetary gear sets, one overrunning clutch, full electronic control, electronically controlled converter clutch
Gear Ratios	
1 st	3
2 nd	1.67—upshift; 1.50—kickdown
3 rd	1
4 th	0.75
5 th	0.67
Reverse	3
Overall Top Gear	2.50 with 3.73 axle ratio; 2.63 with 4.10 axle ratio

TRANSMISSION: AISIN AS68RC SIX-SPEED

Availability	Optional—with diesel engine
PTO Capable (35 horsepower max)	Six-bolt mounting; right side
Description	Electronically controlled overdrive lockout Electronically controlled converter clutch
Gear Ratios	
1 st	3.74
2 nd	2.00
3 rd	1.34
4 th	1
5 th	0.77
6 th	0.63
Reverse	3.54
Overall Top Gear Ratio	2.42 with 3.73 axle ratio; 2.67 with 4.10 axle ratio

TRANSFER CASE: NV273 (NV271)

Availability	Standard 4x4
Type	Part-time
Operating Modes	2WD; 4WD High; Neutral; 4WD Low
Shift Mechanism	NV273—electric (NV271 manual)
Low-range Ratio	2.73
Center Differential	None

2010 Dodge Ram Chassis Cabs 4500/5500 SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.

All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Body Style	Chassis Cab: Regular Cab and Crew Cab
Assembly Plant	Saltillo, Mexico
EPA Vehicle Class	Medium Heavy Duty

ENGINE: 6.7-LITER HIGH OUTPUT CUMMINS TURBO DIESEL I-6

Availability	Standard
Type and Description	Six-cylinder, inline, liquid-cooled, turbocharged, intercooled
Displacement	408 cu. in. (6690 cu. cm)
Bore x Stroke	4.21 x 4.88 (107 mm x 124 mm)
Valve System	OHV, 24 valves, solid lifters
Fuel Injection	Electronic high-pressure common rail
Construction	Cast-iron block and head
Compression Ratio	17.3:1
Power (SAE net)	305 hp (227 kW) @ 2,900 rpm — high output
Torque (SAE net)	610 lb.-ft. (827 N•m) @ 1,600 rpm — high output
Maximum Engine Speed	3,500 rpm
Fuel Requirement	Ultra-low Sulfur Diesel
Oil Capacity	(Low ash req.) 12 qt. (11.3L) with filter
Coolant Capacity	32.7 qt. (30.9L)
Emission Controls	Selective Catalytic Reduction (SCR)

ELECTRICAL SYSTEM

Alternator

Availability	Standard
Rating	180 amp

Availability	Optional
Rating	220 amp

Battery

Availability	Standard
Description	Dual, Group 65, maintenance-free, 750 CCA

TRANSMISSION: G56-MANUAL SIX-SPEED OVERDRIVE

Availability	Standard — all
Description	Synchronized in all gears
PTO Capable	Six-bolt mounting, left side
Gear Ratios	
1st	5.94
2nd	3.28
3rd	1.98
4th	1.3
5th	1
6th	0.74
Reverse	5.42

TRANSMISSION: AISIN AS68RC SIX-SPEED

Availability	Optional
PTO Capable (35 HP max)	Six-bolt mounting; right side
Description	Electronically controlled overdrive lockout, electronically controlled converter clutch
Gear Ratios	
1st	3.74
2nd	2.00
3rd	1.34
4th	1
5th	0.77
6th	0.63
Reverse	3.54
Overall Top Gear Ratio	2.42 with 3.73 axle ratio; 2.67 with 4.10 axle ratio

**TRANSFER CASE: NV273,
(NV271)**

Availability	Standard (4x4)
Type	Part-time
Operating Modes	2WD; 4WD High; Neutral; 4WD Low
Shift Mechanism	NV273 — electric (NV271 manual)
Low-range Ratio	2.72
Center Differential	None

2010 Dodge Ram Chassis Cab
3500 DIMENSIONS AND CAPACITIES (Preliminary)

REGULAR CAB 143.5"WB 60"CA SRW		
	4x2	4x4
Wheelbase	143.4	143.4
Track Width - Front	68.7	68.7
Track Width - Rear	68.1	68.1
Overall Length	234.1	234.1
Overall Width @ SgRP Front	79.1	79.1
Overall Height	78.3	78.3
Suspension or Axle to Ground - Front	9.9	8.4
Suspension or Axle to Ground - Rear	7.5	7.5
Approach Angle	23.8	23.8
Ramp Breakover Angle	21.3	21.3
Departure Angle	29.5	29.5

REGULAR CAB 143.5"WB 60"CA DRW		
	4X2	4X4
Wheelbase	143.4	143.4
Track Width - Front	69.6	69.6
Track Width - Rear	71.7	71.7
Overall Length	234.1	234.1
Overall Width @ SgRP Front	79.1	79.1
Overall Height	78.4	78.4
Suspension or Axle to Ground - Front	10.0	8.4
Suspension or Axle to Ground - Rear	7.7	7.7
Approach Angle	23.9	23.9
Ramp Breakover Angle	21.4	21.4
Departure Angle	29.6	29.6

REGULAR CAB 167.5"WB 84"CA DRW		
	4X2	4X4
Wheelbase	167.4	167.4
Track Width - Front	69.6	69.6
Track Width - Rear	71.7	71.7
Overall Length	258.1	258.1
Overall Width @ SgRP Front	79.1	79.1
Overall Height	78.0	78.0
Suspension or Axle to Ground - Front	10.0	8.4
Suspension or Axle to Ground - Rear	7.6	7.6
Approach Angle	24.2	24.2
Ramp Breakover Angle	18.4	18.4
Departure Angle	28.7	28.7

CREW CAB 172.4"WB 60"CA SRW		
	4X2	4X4
Wheelbase	172.3	172.3
Track Width - Front	68.7	68.7
Track Width - Rear	68.1	68.1
Overall Length	263.0	263.0
Overall Width @ SgRP Front	79.1	79.1
Overall Height	78.8	78.8
Suspension or Axle to Ground - Front	9.9	8.3
Suspension or Axle to Ground - Rear	7.5	7.5
Approach Angle	23.9	23.9
Ramp Breakover Angle	18.3	18.3
Departure Angle	29.3	29.3

CREW CAB 172.4"WB 60"CA DRW		
	4X2	4X4
Wheelbase	172.3	172.3
Track Width - Front	69.6	69.6
Track Width - Rear	71.7	71.7
Overall Length	263.0	263.0
Overall Width @ SgRP Front	79.1	79.1
Overall Height	78.5	78.5
Suspension or Axle to Ground - Front	9.9	8.4
Suspension or Axle to Ground - Rear	7.5	7.5
Approach Angle	24.3	24.3
Ramp Breakover Angle	18.0	18.0
Departure Angle	28.6	28.6

2010 Dodge Ram Chassis Cab 4500/5500 DIMENSIONS AND CAPACITIES *(Preliminary)*

REGULAR CAB 144.5"WB 60"CA DRW		
	4X2	4X4
Wheelbase	144.3	144.3
Track Width - Front	76.0	76.0
Track Width - Rear	73.6	73.6
Overall Length	234.1	234.1
Overall Width @ SgRP Front	79.1	79.1
Overall Height	80.1	80.1
Suspension or Axle to Ground - Front	10.3	8.7
Suspension or Axle to Ground - Rear	8.4	8.4
Approach Angle	28.0	28.0
Ramp Breakover Angle	23.7	23.7
Departure Angle	31.5	31.5

REGULAR CAB 168.5"WB 84"CA DRW		
	4X2	4X4
Wheelbase	168.3	168.3
Track Width - Front	76.0	76.0
Track Width - Rear	73.6	73.6
Overall Length	258.1	258.1
Overall Width @ SgRP Front	79.1	79.1
Overall Height	80.0	80.0
Suspension or Axle to Ground - Front	10.3	8.7
Suspension or Axle to Ground - Rear	8.4	8.4
Approach Angle	28.1	28.1
Ramp Breakover Angle	20.8	20.8
Departure Angle	31.3	31.3

REGULAR CAB 192.5"WB 108"CA DRW		
	4X2	4X4
Wheelbase	192.3	192.3
Track Width - Front	76.0	76.0
Track Width - Rear	73.6	73.6
Overall Length	282.1	282.1
Overall Width @ SgRP Front	79.1	79.1
Overall Height	79.9	79.9
Suspension or Axle to Ground - Front	10.3	8.7
Suspension or Axle to Ground - Rear	8.4	8.4
Approach Angle	28.2	28.2
Ramp Breakover Angle	18.2	18.2
Departure Angle	31.2	31.2

REGULAR CAB 204.5"WB 120"CA DRW		
	4X2	4X4
Wheelbase	204.3	204.3
Track Width - Front	76.0	76.0
Track Width - Rear	73.6	73.6
Overall Length	294.1	294.1
Overall Width @ SgRP Front	79.1	79.1
Overall Height	79.8	79.8
Suspension or Axle to Ground - Front	10.3	8.7
Suspension or Axle to Ground - Rear	8.4	8.4
Approach Angle	28.3	28.3
Ramp Breakover Angle	17.2	17.2
Departure Angle	31.2	31.2

CREW CAB 173.4"WB 60"CA DRW		
	4X2	4X4
Wheelbase	173.3	173.3
Track Width - Front	76.0	76.0
Track Width - Rear	73.6	73.6
Overall Length	263.0	263.0
Overall Width @ SgRP Front	79.1	79.1
Overall Height	80.6	80.6
Suspension or Axle to Ground - Front	10.3	8.7
Suspension or Axle to Ground - Rear	8.4	8.4
Approach Angle	28.2	28.2
Ramp Breakover Angle	20.4	20.4
Departure Angle	31.4	31.4

CREW CAB 197.4"WB 84"CA DRW		
	4X2	4X4
Wheelbase	197.2	197.2
Track Width - Front	76.0	76.0
Track Width - Rear	73.6	73.6
Overall Length	287.0	287.0
Overall Width @ SgRP Front	79.1	79.1
Overall Height	80.5	80.5
Suspension or Axle to Ground - Front	10.3	8.7
Suspension or Axle to Ground - Rear	8.4	8.4
Approach Angle	28.3	28.3
Ramp Breakover Angle	17.8	17.8
Departure Angle	31.2	31.2

2010 DODGE RAM 3500 CHASSIS CAB TOWING CHART

NOTE: BASE WEIGHTS CAN CHANGE

RAM CREW CHASSIS CAB 2WD - ST

DD 3L93 (SRW)

(with sales code AR9)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	10,200	2,980	7,215	4,333	2,882	5,500	6,200	19,000	11,650
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	10,200	2,980	7,215	4,333	2,882	5,500	6,200	24,000	16,650
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	10,200	2,980	7,215	4,333	2,882	5,500	6,200	24,000	16,650
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	10,200	2,920	7,279	4,389	2,890	5,500	6,200	24,000	16,550

RAM CREW CHASSIS CAB 2WD - ST

DD 3L93 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 VCT GAS (EZC)	A5	545RFE 5-SPD AUTO (DGQ)	NAS	4.10	12,500	6,240	6,257	3,344	2,913	5,200	9,350	17,000	10,600
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	13,000	5,780	7,215	4,333	2,882	5,500	9,350	19,000	11,650
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	13,000	5,780	7,215	4,333	2,882	5,500	9,350	24,000	16,650
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	13,000	5,780	7,215	4,333	2,882	5,500	9,350	26,000	18,650
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	13,000	5,720	7,279	4,389	2,890	5,500	9,350	24,000	16,550

RAM REGULAR CHASSIS CAB 2WD - ST

DD 3L63 (SRW)

(with sales code AR9)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	10,200	3,520	6,680	3,968	2,712	5,500	6,200	19,000	12,150
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	10,200	3,520	6,680	3,968	2,712	5,500	6,200	24,000	17,150
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	10,200	3,520	6,680	3,968	2,712	5,500	6,200	24,000	17,150
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	10,200	3,460	6,744	4,024	2,720	5,500	6,200	24,000	17,100

RAM REGULAR CHASSIS CAB 2WD - ST

DD 3L63 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 VCT GAS (E2C)	A5	545RFE 5-SPD AUTO (DGQ)	NAS	4.10	12,500	6,590	5,913	3,222	2,691	5,200	9,350	17,000	10,950
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	13,000	5,060	7,936	3,968	3,968	5,500	9,350	19,000	10,900
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	13,000	5,060	7,936	3,968	3,968	5,500	9,350	24,000	15,900
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	13,000	5,060	7,936	3,968	3,968	5,500	9,350	26,000	17,900
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	13,000	5,000	8,000	4,024	3,976	5,500	9,350	24,000	15,850

RAM REGULAR CHASSIS CAB 2WD - ST

DD 3L64 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 VCT GAS (E2C)	A5	545RFE 5-SPD AUTO (DGQ)	NAS	4.10	12,500	6,470	6,026	3,278	2,748	5,200	9,350	17,000	10,800
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	13,000	6,170	6,831	4,121	2,710	5,500	9,350	19,000	12,000
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	13,000	6,170	6,831	4,121	2,710	5,500	9,350	24,000	17,000
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	13,000	6,170	6,831	4,121	2,710	5,500	9,350	26,000	19,000
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	13,000	6,100	6,896	4,177	2,719	5,500	9,350	24,000	16,950

NOTES:

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Base Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)
3. Maximum Trailer weight must be reduced by the weight of the applied body and optional equipment.
4. The 6.7L TD DIESEL (ETJ) front GAWR 5200 will be available until 12/09.

RAM CREW CHASSIS CAB 4WD - ST

DD 8L93 (SRW)

(with sales code AR9)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	10,200	2,720	7,475	4,553	2,922	5,500	6,200	19,000	11,350
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	10,200	2,720	7,475	4,553	2,922	5,500	6,200	24,000	16,350
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	10,200	2,720	7,475	4,553	2,922	5,500	6,200	24,000	16,350
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	10,200	2,660	7,539	4,609	2,930	5,500	6,200	24,000	16,300

RAM CREW CHASSIS CAB 4WD - ST

DD 8L93 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 VCT GAS (EZC)	A5	545RFE 5-SPD AUTO (DGQ)	NAS	4.10	12,500	5,790	6,715	3,736	2,979	5,200	9,350	17,000	10,150
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	13,000	5,520	7,475	4,553	2,922	5,500	9,350	19,000	11,350
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	13,000	5,520	7,475	4,553	2,922	5,500	9,350	24,000	16,350
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	13,000	5,520	7,475	4,553	2,922	5,500	9,350	26,000	18,350
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	13,000	5,460	7,539	4,609	2,930	5,500	9,350	24,000	16,300

RAM REGULAR CHASSIS CAB 4WD - ST

DD 8L63 (SRW)

(with sales code AR9)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	10,200	3,260	6,940	4,188	2,752	5,500	6,200	19,000	11,900
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	10,200	3,260	6,940	4,188	2,752	5,500	6,200	24,000	16,900
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	10,200	3,260	6,940	4,188	2,752	5,500	6,200	24,000	16,900
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	10,200	3,200	7,004	4,244	2,760	5,500	6,200	24,000	16,850

RAM REGULAR CHASSIS CAB 4WD - ST

DD 8L63 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 VCT GAS (EZC)	A5	545RFE 5-SPD AUTO (DGQ)	NAS	4.10	12,500	6,330	6,171	3,440	2,731	5,200	9,350	17,000	10,700
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	13,000	6,060	6,940	4,188	2,752	5,500	9,350	19,000	11,900
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	13,000	6,060	6,940	4,188	2,752	5,500	9,350	24,000	16,900
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	13,000	6,060	6,940	4,188	2,752	5,500	9,350	26,000	18,900
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	13,000	6,000	7,004	4,244	2,760	5,500	9,350	24,000	16,850

RAM REGULAR CHASSIS CAB 4WD - ST

DD 8L64 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail
5.7L V8 VCT GAS (E2C)	A5	545RFE 5-SPD AUTO (DGQ)	NAS	4.10	12,500	6,220	6,278	3,496	2,782	5,200	9,350	17,000	10,550
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.42	13,000	5,910	7,091	4,341	2,750	5,500	9,350	19,000	11,750
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	3.73	13,000	5,910	7,091	4,341	2,750	5,500	9,350	24,000	16,750
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAS	4.10	13,000	5,910	7,091	4,341	2,750	5,500	9,350	26,000	18,750
6.7L TD DIESEL (ETJ)	A6	AW68R AISIN 6-SPD AUTO (DG3)	NAS	4.10	13,000	5,840	7,156	4,397	2,759	5,500	9,350	24,000	16,700

NOTES:

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Base Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)
3. Maximum Trailer weight must be reduced by the weight of the applied body and optional equipment.
4. The 6.7L TD DIESEL (ETJ) front GAWR 5200 will be available until 12/09.

2010 DODGE RAM 4500 CHASSIS CAB TOWING CHART

NOTE: BASE WEIGHTS CAN CHANGE

RAM CREW CAB 173.5 WHEELBASE 2WD - ST DP 4L93 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR ⁽⁴⁾	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,000	7,750	8,249	4,870	3,379	7,000	12,000	26,000	17,600
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,000	7,750	8,249	4,870	3,379	7,000	12,000	26,000	17,600
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	6,750	8,249	4,870	3,379	7,000	12,000	26,000	17,600
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	6,750	8,249	4,870	3,379	7,000	12,000	26,000	17,600
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,000	7,700	8,302	4,917	3,385	7,000	12,000	26,000	17,550
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,000	7,700	8,302	4,917	3,385	7,000	12,000	26,000	17,550
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	6,700	8,302	4,917	3,385	7,000	12,000	26,000	17,550
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	6,700	8,302	4,917	3,385	7,000	12,000	26,000	17,550

RAM CREW CAB 197.5 WHEELBASE 2WD - ST DP 4L94 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,500	8,210	8,293	4,975	3,318	7,000	12,000	26,000	17,550
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,500	8,210	8,293	4,975	3,318	7,000	12,000	26,000	17,550
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	6,710	8,293	4,975	3,318	7,000	12,000	26,000	17,550
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	6,710	8,293	4,975	3,318	7,000	12,000	26,000	17,550
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,500	8,150	8,346	5,022	3,324	7,000	12,000	26,000	17,500
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,500	8,150	8,346	5,022	3,324	7,000	12,000	26,000	17,500
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	6,650	8,346	5,022	3,324	7,000	12,000	26,000	17,500
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	6,650	8,346	5,022	3,324	7,000	12,000	26,000	17,500

RAM REGULAR CAB 144.5 WHEELBASE 2WD - ST DP 4L63 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,000	8,440	7,559	4,459	3,101	7,000	12,000	26,000	18,300
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,000	8,440	7,559	4,459	3,101	7,000	12,000	26,000	18,300
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	7,440	7,559	4,459	3,101	7,000	12,000	26,000	18,300
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	7,440	7,559	4,459	3,101	7,000	12,000	26,000	18,300
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,000	8,390	7,613	4,506	3,107	7,000	12,000	26,000	18,250
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,000	8,390	7,613	4,506	3,107	7,000	12,000	26,000	18,250
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	7,390	7,613	4,506	3,107	7,000	12,000	26,000	18,250
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	7,390	7,613	4,506	3,107	7,000	12,000	26,000	18,250

NOTES:

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Base Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)
3. Maximum Trailer weight must be reduced by the weight of the applied body and optional equipment.
4. Optional GVWR (sales code Z4B). To determine your vehicle's GVWR, please check the certification label located on the inside (shut face) of the driver side (left front) door.

RAM REGULAR CAB 168.5 WHEELBASE 2WD - ST DP 4L64 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,500	8,800	7,701	4,631	3,069	7,000	12,000	26,000	18,150
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,500	8,800	7,701	4,631	3,069	7,000	12,000	26,000	18,150
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	7,300	7,701	4,631	3,069	7,000	12,000	26,000	18,150
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	7,300	7,701	4,631	3,069	7,000	12,000	26,000	18,150
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,500	8,750	7,754	4,679	3,076	7,000	12,000	26,000	18,100
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,500	8,750	7,754	4,679	3,076	7,000	12,000	26,000	18,100
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	7,250	7,754	4,679	3,076	7,000	12,000	26,000	18,100
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	7,250	7,754	4,679	3,076	7,000	12,000	26,000	18,100

RAM REGULAR CAB 192.5 WHEELBASE 2WD - ST DP 4L65 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,500	8,690	7,806	4,805	3,001	7,000	12,000	26,000	18,050
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,500	8,690	7,806	4,805	3,001	7,000	12,000	26,000	18,050
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	7,190	7,806	4,805	3,001	7,000	12,000	26,000	18,050
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	7,190	7,806	4,805	3,001	7,000	12,000	26,000	18,050
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,500	8,640	7,859	4,852	3,007	7,000	12,000	26,000	18,000
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,500	8,640	7,859	4,852	3,007	7,000	12,000	26,000	18,000
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	7,140	7,859	4,852	3,007	7,000	12,000	26,000	18,000
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	7,140	7,859	4,852	3,007	7,000	12,000	26,000	18,000

RAM REGULAR CAB 204.5 WHEELBASE 2WD - ST DP 4L66 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,500	8,670	7,832	4,820	3,013	7,000	12,000	26,000	18,000
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,500	8,670	7,832	4,820	3,013	7,000	12,000	26,000	18,000
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	7,170	7,832	4,820	3,013	7,000	12,000	26,000	18,000
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	7,170	7,832	4,820	3,013	7,000	12,000	26,000	18,000
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,500	8,610	7,886	4,867	3,019	7,000	12,000	26,000	17,950
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,500	8,610	7,886	4,867	3,019	7,000	12,000	26,000	17,950
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	7,110	7,886	4,867	3,019	7,000	12,000	26,000	17,950
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	7,110	7,886	4,867	3,019	7,000	12,000	26,000	17,950

NOTES:

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Base Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)
3. Maximum Trailer weight must be reduced by the weight of the applied body and optional equipment.
4. Optional GVWR (sales code Z4B). To determine your vehicle's GVWR, please check the certification label located on the inside (shut face) of the driver side (left front) door.

RAM CREW CAB 173.5 WHEELBASE 4WD - ST

DP 9L93 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,000	7,460	8,537	5,160	3,377	7,000	12,000	26,000	17,300
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,000	7,460	8,537	5,160	3,377	7,000	12,000	26,000	17,300
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	6,460	8,537	5,160	3,377	7,000	12,000	26,000	17,300
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	6,460	8,537	5,160	3,377	7,000	12,000	26,000	17,300
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,000	7,400	8,602	5,217	3,385	7,000	12,000	26,000	17,250
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,000	7,400	8,602	5,217	3,385	7,000	12,000	26,000	17,250
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	6,400	8,602	5,217	3,385	7,000	12,000	26,000	17,250
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	6,400	8,602	5,217	3,385	7,000	12,000	26,000	17,250

RAM CREW CAB 197.5 WHEELBASE 4WD - ST

DP 9L94 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,500	7,880	8,624	5,244	3,380	7,000	12,000	26,000	17,250
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,500	7,880	8,624	5,244	3,380	7,000	12,000	26,000	17,250
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	6,380	8,624	5,244	3,380	7,000	12,000	26,000	17,250
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	6,380	8,624	5,244	3,380	7,000	12,000	26,000	17,250
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,500	7,810	8,690	5,301	3,388	7,000	12,000	26,000	17,150
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,500	7,810	8,690	5,301	3,388	7,000	12,000	26,000	17,150
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	6,310	8,690	5,301	3,388	7,000	12,000	26,000	17,150
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	6,310	8,690	5,301	3,388	7,000	12,000	26,000	17,150

RAM REGULAR CAB 144.5 WHEELBASE 4WD - ST DP 9L63 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,000	8,110	7,887	4,798	3,090	7,000	12,000	26,000	17,950
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,000	8,110	7,887	4,798	3,090	7,000	12,000	26,000	17,950
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	7,110	7,887	4,798	3,090	7,000	12,000	26,000	17,950
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	7,110	7,887	4,798	3,090	7,000	12,000	26,000	17,950
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,000	8,050	7,953	4,855	3,098	7,000	12,000	26,000	17,900
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,000	8,050	7,953	4,855	3,098	7,000	12,000	26,000	17,900
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	7,050	7,953	4,855	3,098	7,000	12,000	26,000	17,900
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	7,050	7,953	4,855	3,098	7,000	12,000	26,000	17,900

NOTES:

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Base Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)
3. Maximum Trailer weight must be reduced by the weight of the applied body and optional equipment.
4. Optional GVWR (sales code Z9B). To determine your vehicle's GVWR, please check the certification label located on the inside (shut face) of the driver side (left front) door.

RAM REGULAR CAB 168.5 WHEELBASE 4WD - ST DP 9L64 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,500	8,440	8,063	4,954	3,110	7,000	12,000	26,000	17,800
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,500	8,440	8,063	4,954	3,110	7,000	12,000	26,000	17,800
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	6,940	8,063	4,954	3,110	7,000	12,000	26,000	17,800
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	6,940	8,063	4,954	3,110	7,000	12,000	26,000	17,800
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,500	8,370	8,128	5,011	3,118	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,500	8,370	8,128	5,011	3,118	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	6,870	8,128	5,011	3,118	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	6,870	8,128	5,011	3,118	7,000	12,000	26,000	17,700

RAM REGULAR CAB 192.5 WHEELBASE 4WD - ST DP 9L65 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,500	8,340	8,159	5,009	3,150	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,500	8,340	8,159	5,009	3,150	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	6,840	8,159	5,009	3,150	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	6,840	8,159	5,009	3,150	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,500	8,280	8,224	5,066	3,158	7,000	12,000	26,000	17,650
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,500	8,280	8,224	5,066	3,158	7,000	12,000	26,000	17,650
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	6,780	8,224	5,066	3,158	7,000	12,000	26,000	17,650
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	6,780	8,224	5,066	3,158	7,000	12,000	26,000	17,650

RAM REGULAR CAB 204.5 WHEELBASE 4WD - ST DP 9L66 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	16,500	8,350	8,154	5,094	3,060	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	16,500	8,350	8,154	5,094	3,060	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.10	15,000	6,850	8,154	5,094	3,060	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	M6	G56 6-SPD MANU (DEG)	NAA NAS	4.44	15,000	6,850	8,154	5,094	3,060	7,000	12,000	26,000	17,700
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	16,500	8,280	8,219	5,151	3,068	7,000	12,000	26,000	17,650
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	16,500	8,280	8,219	5,151	3,068	7,000	12,000	26,000	17,650
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.44	15,000	6,780	8,219	5,151	3,068	7,000	12,000	26,000	17,650
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	15,000	6,780	8,219	5,151	3,068	7,000	12,000	26,000	17,650

NOTES:

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Base Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)
3. Maximum Trailer weight must be reduced by the weight of the applied body and optional equipment.
4. Optional GVWR (sales code Z9B). To determine your vehicle's GVWR, please check the certification label located on the inside (shut face) of the driver side (left front) door.

2010 DODGE RAM 5500 CHASSIS CAB TOWING CHART

NOTE: BASE WEIGHTS CAN CHANGE

RAM CREW CAB 173.5 WHEELBASE 2WD - ST DP 5L93 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	18,750	10,460	8,291	4,886	3,404	7,000	13,500	26,000	17,550
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	18,750	10,410	8,344	4,934	3,410	7,000	13,500	26,000	17,500

RAM CREW CAB 197.5 WHEELBASE 2WD - ST DP 5L94 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	19,500	11,190	8,314	4,974	3,340	7,000	13,500	26,000	17,550
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	19,500	11,130	8,367	5,021	3,346	7,000	13,500	26,000	17,500

RAM REGULAR CAB 144.5 WHEELBASE 2WD - ST DP 5L63 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	18,750	11,160	7,588	4,514	3,074	7,000	13,500	26,000	18,250
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	18,750	11,110	7,641	4,561	3,080	7,000	13,500	26,000	18,200

RAM REGULAR CAB 168.5 WHEELBASE 2WD - ST DP 5L64 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	19,500	11,780	7,717	4,652	3,065	7,000	13,500	26,000	18,150
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	19,500	11,730	7,771	4,700	3,071	7,000	13,500	26,000	18,100

RAM REGULAR CAB 192.5 WHEELBASE 2WD - ST DP 5L65 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	19,500	11,630	7,868	4,791	3,077	7,000	13,500	26,000	18,000
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	19,500	11,580	7,921	4,838	3,083	7,000	13,500	26,000	17,950

RAM REGULAR CAB 204.5 WHEELBASE 2WD - ST DP 5L66 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	19,500	11,610	7,894	4,806	3,089	7,000	13,500	26,000	17,950
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	19,500	11,550	7,948	4,853	3,095	7,000	13,500	26,000	17,900

NOTES:

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Base Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)
3. Maximum Trailer weight must be reduced by the weight of the applied body and optional equipment.

RAM CREW CAB 173.5 WHEELBASE 4WD - ST DP 0L93 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	18,750	10,150	8,601	5,177	3,424	7,000	13,500	26,000	17,250
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	18,750	10,100	8,654	5,224	3,430	7,000	13,500	26,000	17,200

RAM CREW CAB 197.5 WHEELBASE 4WD - ST DP 0L94 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	19,500	10,820	8,679	5,276	3,403	7,000	13,500	26,000	17,150
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	19,500	10,770	8,732	5,323	3,409	7,000	13,500	26,000	17,100

RAM REGULAR CAB 144.5 WHEELBASE 4WD - ST DP 0L63 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	18,750	10,830	7,924	4,809	3,115	7,000	13,500	26,000	17,950
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	18,750	10,770	7,977	4,856	3,122	7,000	13,500	26,000	17,850

RAM REGULAR CAB 168.5 WHEELBASE 4WD - ST DP 0L64 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	19,500	11,420	8,076	4,982	3,093	7,000	13,500	26,000	17,750
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	19,500	11,370	8,129	5,029	3,100	7,000	13,500	26,000	17,700

RAM REGULAR CAB 192.5 WHEELBASE 4WD - ST DP 0L65 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	19,500	11,330	8,171	5,038	3,134	7,000	13,500	26,000	17,700
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	19,500	11,280	8,225	5,085	3,140	7,000	13,500	26,000	17,650

RAM REGULAR CAB 204.5 WHEELBASE 4WD - ST DP 0L66 (DRW)

Engine	Trans Type	Transmission	EMISSIONS	Axle Ratio	GVWR	Payload ⁽¹⁾	Base Wt.	Base Wt. Front	Base Wt. Rear	GAWR Front	GAWR Rear	GCWR	Max Trail ⁽³⁾
6.7L TD DIESEL (ETJ)	M6	DC-G56 6-SPD MANU (DEG)	NAA NAS	4.44	19,500	11,330	8,166	5,138	3,027	7,000	13,500	26,000	17,700
6.7L TD DIESEL (ETJ)	A6	AS68RC AISIN 6-SPD AUTO (DG3)	NAA NAS	4.88	19,500	11,280	8,219	5,186	3,034	7,000	13,500	26,000	17,650

NOTES:

1. Payload is rounded to the nearest 10 lbs. Payload = GVWR - Base Wt.
2. Maximum trailer weights are rounded to the nearest 50 lbs.
Maximum Trailer Weight = GCWR - Curb wt. -150 lbs. (allowance for driver)
3. Maximum Trailer weight must be reduced by the weight of the applied body and optional equipment.