

2013 RAM 3500 CHASSIS CAB TOWING CHART												
NOTE: BASE WEIGHTS CAN CHANGE												
Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
REGULAR CAB - CA 60" - 2WD - SRW												
6.7L DIESEL	M6	DC-G56	3.42	10,200	3,626	6,574	4,196	2,378	5,500	6,200	22,000	15,250
6.7L DIESEL	M6	DC-G56	3.73	10,200	3,626	6,574	4,196	2,378	5,500	6,200	24,000	17,250
6.7L DIESEL	M6	DC-G56	4.1	10,200	3,626	6,574	4,196	2,378	5,500	6,200	26,000	19,250
6.7L DIESEL	A6	AS69RC	3.42	10,200	3,456	6,744	4,324	2,420	5,500	6,200	22,000	15,100
6.7L DIESEL	A6	AS69RC	3.73	10,200	3,456	6,744	4,324	2,420	5,500	6,200	24,000	17,100
6.7L DIESEL	A6	AS69RC	4.1	10,200	3,456	6,744	4,324	2,420	5,500	6,200	26,000	19,100
REGULAR CAB - CA 60" - 2WD - DRW												
6.7L DIESEL	M6	DC-G56	3.42	13,000	6,080	6,920	4,218	2,702	5,500	9,350	22,000	14,900
6.7L DIESEL	M6	DC-G56	3.73	13,000	6,080	6,920	4,218	2,702	5,500	9,350	24,000	16,900
6.7L DIESEL	M6	DC-G56	4.1	13,000	6,080	6,920	4,218	2,702	5,500	9,350	26,000	18,900
6.7L DIESEL	A6	AS69RC	3.42	13,000	5,910	7,090	4,346	2,744	5,500	9,350	24,000	16,750
6.7L DIESEL	A6	AS69RC	3.73	13,000	5,910	7,090	4,346	2,744	5,500	9,350	26,000	18,750
6.7L DIESEL	A6	AS69RC	4.1	13,000	5,910	7,090	4,346	2,744	5,500	9,350	30,000	22,750
5.7L HEMI V8	A6	66RFE	4.1	12,500	6,543	5,957	3,315	2,642	5,200	9,350	18,000	11,850
REGULAR CAB - CA 84" - 2WD - DRW												
6.7L DIESEL	M6	DC-G56	3.42	13,000	5,994	7,006	4,314	2,692	5,500	9,350	22,000	14,800
6.7L DIESEL	M6	DC-G56	3.73	13,000	5,994	7,006	4,314	2,692	5,500	9,350	24,000	16,800
6.7L DIESEL	M6	DC-G56	4.1	13,000	5,994	7,006	4,314	2,692	5,500	9,350	26,000	18,800
6.7L DIESEL	A6	AS69RC	3.42	13,000	5,824	7,176	4,448	2,728	5,500	9,350	24,000	16,650
6.7L DIESEL	A6	AS69RC	3.73	13,000	5,824	7,176	4,448	2,728	5,500	9,350	26,000	18,650
6.7L DIESEL	A6	AS69RC	4.1	13,000	5,824	7,176	4,448	2,728	5,500	9,350	30,000	22,650
5.7L HEMI V8	A6	66RFE	4.1	12,500	6,489	6,011	3,410	2,601	5,200	9,350	18,000	11,800
CREW CAB - CA 60" - 2WD - SRW												
6.7L DIESEL	M6	DC-G56	3.42	10,200	3,186	7,014	4,362	2,652	5,500	6,200	22,000	14,800
6.7L DIESEL	M6	DC-G56	3.73	10,200	3,186	7,014	4,362	2,652	5,500	6,200	24,000	16,800
6.7L DIESEL	M6	DC-G56	4.1	10,200	3,186	7,014	4,362	2,652	5,500	6,200	26,000	18,800
6.7L DIESEL	A6	AS69RC	3.42	10,200	3,016	7,184	4,490	2,694	5,500	6,200	22,000	14,650
6.7L DIESEL	A6	AS69RC	3.73	10,200	3,016	7,184	4,490	2,694	5,500	6,200	24,000	16,650
6.7L DIESEL	A6	AS69RC	4.1	10,200	3,016	7,184	4,490	2,694	5,500	6,200	26,000	18,650
CREW CAB - CA 60" - 2WD - DRW												
6.7L DIESEL	M6	DC-G56	3.42	13,000	5,602	7,398	4,413	2,985	5,500	9,350	22,000	14,450
6.7L DIESEL	M6	DC-G56	3.73	13,000	5,602	7,398	4,413	2,985	5,500	9,350	24,000	16,450
6.7L DIESEL	M6	DC-G56	4.1	13,000	5,602	7,398	4,413	2,985	5,500	9,350	26,000	18,450
6.7L DIESEL	A6	AS69RC	3.42	13,000	5,432	7,568	4,541	3,027	5,500	9,350	24,000	16,250
6.7L DIESEL	A6	AS69RC	3.73	13,000	5,432	7,568	4,541	3,027	5,500	9,350	26,000	18,250
6.7L DIESEL	A6	AS69RC	4.1	13,000	5,432	7,568	4,541	3,027	5,500	9,350	30,000	22,250
5.7L HEMI V8	A6	66RFE	4.1	12,500	6,119	6,381	3,522	2,859	5,200	9,350	18,000	11,450

2013 RAM 4500 CHASSIS CAB TOWING CHART

NOTE: BASE WEIGHTS CAN CHANGE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
REGULAR CAB - CA 60" - 2WD - DRW												
6.7L DIESEL	A6	AS69RC	4.1	15,000	7,326	7,674	4,494	3,180	7,000	12,000	26,000	18,150
6.7L DIESEL	A6	AS69RC	4.44	15,000	7,326	7,674	4,494	3,180	7,000	12,000	32,500	24,650
6.7L DIESEL	M6	DC-G56	4.1	15,000	7,391	7,609	4,438	3,171	7,000	12,000	26,000	18,200
6.7L DIESEL	M6	DC-G56	4.44	15,000	7,391	7,609	4,438	3,171	7,000	12,000	28,000	20,200
6.7L DIESEL	A6	AS69RC	4.44	16,000	8,326	7,674	4,494	3,180	7,000	12,000	32,500	24,650
6.7L DIESEL	A6	AS69RC	4.1	16,000	8,326	7,674	4,494	3,180	7,000	12,000	26,000	18,150
6.7L DIESEL	M6	DC-G56	4.1	16,000	8,391	7,609	4,438	3,171	7,000	12,000	26,000	18,200
6.7L DIESEL	M6	DC-G56	4.44	16,000	8,391	7,609	4,438	3,171	7,000	12,000	28,000	20,200
REGULAR CAB - CA 84" - 2WD - DRW												
6.7L DIESEL	A6	AS69RC	4.44	16,500	8,661	7,839	4,604	3,235	7,000	12,000	32,500	24,500
6.7L DIESEL	A6	AS69RC	4.1	16,500	8,661	7,839	4,604	3,235	7,000	12,000	26,000	18,000
6.7L DIESEL	M6	DC-G56	4.1	16,500	8,726	7,774	4,548	3,226	7,000	12,000	26,000	18,050
6.7L DIESEL	M6	DC-G56	4.44	16,500	8,726	7,774	4,548	3,226	7,000	12,000	28,000	20,050
6.7L DIESEL	A6	AS69RC	4.44	16,000	8,161	7,839	4,604	3,235	7,000	12,000	32,500	24,500
6.7L DIESEL	A6	AS69RC	4.1	16,000	8,161	7,839	4,604	3,235	7,000	12,000	26,000	18,000
6.7L DIESEL	M6	DC-G56	4.1	16,000	8,226	7,774	4,548	3,226	7,000	12,000	26,000	18,050
6.7L DIESEL	M6	DC-G56	4.44	16,000	8,226	7,774	4,548	3,226	7,000	12,000	28,000	20,050
6.7L DIESEL	A6	AS69RC	4.44	15,000	7,161	7,839	4,604	3,235	7,000	12,000	32,500	24,500
6.7L DIESEL	A6	AS69RC	4.1	15,000	7,161	7,839	4,604	3,235	7,000	12,000	26,000	18,000
6.7L DIESEL	M6	DC-G56	4.1	15,000	7,226	7,774	4,548	3,226	7,000	12,000	26,000	18,050
6.7L DIESEL	M6	DC-G56	4.44	15,000	7,226	7,774	4,548	3,226	7,000	12,000	28,000	20,050
REGULAR CAB - CA 108" - 2WD - DRW												
6.7L DIESEL	A6	AS69RC	4.44	16,500	8,571	7,929	4,677	3,252	7,000	12,000	32,500	24,400
6.7L DIESEL	A6	AS69RC	4.1	16,500	8,571	7,929	4,677	3,252	7,000	12,000	26,000	17,900
6.7L DIESEL	M6	DC-G56	4.1	16,500	8,741	7,759	4,539	3,220	7,000	12,000	26,000	18,050
6.7L DIESEL	M6	DC-G56	4.44	16,500	8,741	7,759	4,539	3,220	7,000	12,000	28,000	20,050
6.7L DIESEL	A6	AS69RC	4.44	15,000	7,103	7,897	4,677	3,220	7,000	12,000	32,500	24,450
6.7L DIESEL	A6	AS69RC	4.1	15,000	7,103	7,897	4,677	3,220	7,000	12,000	26,000	17,950
6.7L DIESEL	M6	DC-G56	4.1	15,000	7,241	7,759	4,539	3,220	7,000	12,000	26,000	18,050
6.7L DIESEL	M6	DC-G56	4.44	15,000	7,241	7,759	4,539	3,220	7,000	12,000	28,000	20,050
REGULAR CAB - CA 120" - 2WD - DRW												
6.7L DIESEL	A6	AS69RC	4.44	16,500	8,541	7,959	4,692	3,267	7,000	12,000	32,500	24,350
6.7L DIESEL	A6	AS69RC	4.1	16,500	8,541	7,959	4,692	3,267	7,000	12,000	26,000	17,850
6.7L DIESEL	M6	DC-G56	4.1	16,500	8,711	7,789	4,554	3,235	7,000	12,000	26,000	18,050
6.7L DIESEL	M6	DC-G56	4.44	16,500	8,711	7,789	4,554	3,235	7,000	12,000	28,000	20,050
6.7L DIESEL	A6	AS69RC	4.44	15,000	7,041	7,959	4,692	3,267	7,000	12,000	32,500	24,350
6.7L DIESEL	A6	AS69RC	4.1	15,000	7,041	7,959	4,692	3,267	7,000	12,000	26,000	17,850
6.7L DIESEL	M6	DC-G56	4.1	15,000	7,211	7,789	4,554	3,235	7,000	12,000	26,000	18,050
6.7L DIESEL	M6	DC-G56	4.44	15,000	7,211	7,789	4,554	3,235	7,000	12,000	28,000	20,050

2013 RAM 4500 CHASSIS CAB TOWING CHART

NOTE: BASE WEIGHTS CAN CHANGE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
CREW CAB - CA 60" - 2WD - DRW												
6.7L DIESEL	A6	AS69RC	4.44	15,000	6,748	8,252	4,756	3,496	7,000	12,000	32,500	24,050
6.7L DIESEL	A6	AS69RC	4.1	15,000	6,748	8,252	4,756	3,496	7,000	12,000	26,000	17,550
6.7L DIESEL	M6	DC-G56	4.1	15,000	6,813	8,187	4,700	3,487	7,000	12,000	26,000	17,650
6.7L DIESEL	M6	DC-G56	4.44	15,000	6,813	8,187	4,700	3,487	7,000	12,000	28,000	19,650
6.7L DIESEL	A6	AS69RC	4.44	16,000	7,748	8,252	4,756	3,496	7,000	12,000	32,500	24,050
6.7L DIESEL	A6	AS69RC	4.1	16,000	7,748	8,252	4,756	3,496	7,000	12,000	26,000	17,550
6.7L DIESEL	M6	DC-G56	4.1	16,000	7,813	8,187	4,700	3,487	7,000	12,000	26,000	17,650
6.7L DIESEL	M6	DC-G56	4.44	16,000	7,813	8,187	4,700	3,487	7,000	12,000	28,000	19,650
CREW CAB - CA 84" - 2WD - DRW												
6.7L DIESEL	A6	AS69RC	4.44	16,500	8,108	8,392	4,940	3,452	7,000	12,000	32,500	23,950
6.7L DIESEL	A6	AS69RC	4.1	16,500	8,108	8,392	4,940	3,452	7,000	12,000	26,000	17,450
6.7L DIESEL	M6	DC-G56	4.1	16,500	8,173	8,327	4,884	3,443	7,000	12,000	26,000	17,500
6.7L DIESEL	M6	DC-G56	4.44	16,500	8,173	8,327	4,884	3,443	7,000	12,000	28,000	19,500
6.7L DIESEL	A6	AS69RC	4.44	15,000	6,608	8,392	4,940	3,452	7,000	12,000	32,500	23,950
6.7L DIESEL	A6	AS69RC	4.1	15,000	6,608	8,392	4,940	3,452	7,000	12,000	26,000	17,450
6.7L DIESEL	M6	DC-G56	4.1	15,000	6,673	8,327	4,884	3,443	7,000	12,000	26,000	17,500
6.7L DIESEL	M6	DC-G56	4.44	15,000	6,673	8,327	4,884	3,443	7,000	12,000	28,000	19,500

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded down to the nearest 50 lbs.
3. The recommended tongue weight is 10 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.

2013 RAM 4500 CHASSIS CAB TOWING CHART

NOTE: BASE WEIGHTS CAN CHANGE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
CREW CAB - CA 60" - 4WD - DRW												
6.7L DIESEL	A6	AS69RC	4.44	15,000	6,395	8,605	5,064	3,541	7,000	12,000	32,500	23,700
6.7L DIESEL	A6	AS69RC	4.1	15,000	6,395	8,605	5,064	3,541	7,000	12,000	26,000	17,200
6.7L DIESEL	M6	DC-G56	4.1	15,000	6,460	8,540	5,008	3,532	7,000	12,000	26,000	17,300
6.7L DIESEL	M6	DC-G56	4.44	15,000	6,460	8,540	5,008	3,532	7,000	12,000	28,000	19,300
6.7L DIESEL	A6	AS69RC	4.44	16,000	7,395	8,605	5,064	3,541	7,000	12,000	32,500	23,700
6.7L DIESEL	A6	AS69RC	4.1	16,000	7,395	8,605	5,064	3,541	7,000	12,000	26,000	17,200
6.7L DIESEL	M6	DC-G56	4.1	16,000	7,460	8,540	5,008	3,532	7,000	12,000	26,000	17,300
6.7L DIESEL	M6	DC-G56	4.44	16,000	7,460	8,540	5,008	3,532	7,000	12,000	28,000	19,300
CREW CAB - CA 84" - 4WD - DRW												
6.7L DIESEL	A6	AS69RC	4.44	16,500	7,804	8,696	5,222	3,474	7,000	12,000	32,500	23,650
6.7L DIESEL	A6	AS69RC	4.1	16,500	7,804	8,696	5,222	3,474	7,000	12,000	26,000	17,150
6.7L DIESEL	M6	DC-G56	4.1	16,500	7,869	8,631	5,166	3,465	7,000	12,000	26,000	17,200
6.7L DIESEL	M6	DC-G56	4.44	16,500	7,869	8,631	5,166	3,465	7,000	12,000	28,000	19,200
6.7L DIESEL	A6	AS69RC	4.44	15,000	6,304	8,696	5,222	3,474	7,000	12,000	32,500	23,650
6.7L DIESEL	A6	AS69RC	4.1	15,000	6,304	8,696	5,222	3,474	7,000	12,000	26,000	17,150
6.7L DIESEL	M6	DC-G56	4.1	15,000	6,369	8,631	5,166	3,465	7,000	12,000	26,000	17,200
6.7L DIESEL	M6	DC-G56	4.44	15,000	6,369	8,631	5,166	3,465	7,000	12,000	28,000	19,200

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded down to the nearest 50 lbs.
3. The recommended tongue weight is 10 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.

2013 RAM 5500 CHASSIS CAB TOWING CHART

NOTE: BASE WEIGHTS CAN CHANGE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer	
						Total	Front	Rear	Front	Rear			
REGULAR CAB - CA 60" - 2WD - DRW													
6.7L DIESEL	A6	AS69RC	4.1	18,000	10,272	7,728	4,474	3,254	7,000	13,500	26,000	18,100	
6.7L DIESEL	A6	AS69RC	4.1	18,750	11,022	7,728	4,474	3,254	7,000	13,500	26,000	18,100	
6.7L DIESEL	A6	AS69RC	4.44	18,750	11,022	7,728	4,474	3,254	7,000	13,500	28,000	20,100	
6.7L DIESEL	A6	AS69RC	4.88	18,750	11,022	7,728	4,474	3,254	7,000	13,500	37,500	29,600	
6.7L DIESEL	M6	DC-G56	4.1	18,750	11,087	7,663	4,418	3,245	7,000	13,500	26,000	18,150	
6.7L DIESEL	M6	DC-G56	4.44	18,750	11,087	7,663	4,418	3,245	7,000	13,500	28,000	20,150	
REGULAR CAB - CA 84" - 2WD - DRW													
6.7L DIESEL	A6	AS69RC	4.1	18,000	10,146	7,854	4,614	3,240	7,000	13,500	26,000	17,950	
6.7L DIESEL	A6	AS69RC	4.1	19,500	11,646	7,854	4,614	3,240	7,000	13,500	26,000	17,950	
6.7L DIESEL	A6	AS69RC	4.44	19,500	11,646	7,854	4,614	3,240	7,000	13,500	32,500	24,450	
6.7L DIESEL	A6	AS69RC	4.88	19,500	11,646	7,854	4,614	3,240	7,000	13,500	37,500	29,450	
6.7L DIESEL	M6	DC-G56	4.1	19,500	11,711	7,789	4,558	3,231	7,000	13,500	26,000	18,050	
6.7L DIESEL	M6	DC-G56	4.44	19,500	11,711	7,789	4,558	3,231	7,000	13,500	28,000	20,050	
REGULAR CAB - CA 108" - 2WD - DRW													
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,869	8,131	4,837	3,294	7,000	13,500	26,000	17,700	
6.7L DIESEL	A6	AS69RC	4.1	19,500	11,369	8,131	4,837	3,294	7,000	13,500	26,000	17,700	
6.7L DIESEL	A6	AS69RC	4.44	19,500	11,369	8,131	4,837	3,294	7,000	13,500	32,500	24,200	
6.7L DIESEL	A6	AS69RC	4.88	19,500	11,369	8,131	4,837	3,294	7,000	13,500	37,500	29,200	
6.7L DIESEL	M6	DC-G56	4.1	19,500	11,539	7,961	4,699	3,262	7,000	13,500	26,000	17,850	
6.7L DIESEL	M6	DC-G56	4.44	19,500	11,539	7,961	4,699	3,262	7,000	13,500	28,000	19,850	
REGULAR CAB - CA 120" - 2WD - DRW													
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,817	8,183	4,882	3,301	7,000	13,500	26,000	17,650	
6.7L DIESEL	A6	AS69RC	4.1	19,500	11,317	8,183	4,882	3,301	7,000	13,500	26,000	17,650	
6.7L DIESEL	A6	AS69RC	4.44	19,500	11,317	8,183	4,882	3,301	7,000	13,500	32,500	24,150	
6.7L DIESEL	A6	AS69RC	4.88	19,500	11,317	8,183	4,882	3,301	7,000	13,500	37,500	29,150	
6.7L DIESEL	M6	DC-G56	4.1	19,500	11,487	8,013	4,744	3,269	7,000	13,500	26,000	17,800	
6.7L DIESEL	M6	DC-G56	4.44	19,500	11,487	8,013	4,744	3,269	7,000	13,500	28,000	19,800	
CREW CAB - CA 60" - 2WD - DRW													
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,765	8,235	4,757	3,478	7,000	13,500	26,000	17,600	
6.7L DIESEL	A6	AS69RC	4.1	18,750	10,515	8,235	4,757	3,478	7,000	13,500	26,000	17,600	
6.7L DIESEL	A6	AS69RC	4.44	18,750	10,515	8,235	4,757	3,478	7,000	13,500	32,500	24,100	
6.7L DIESEL	A6	AS69RC	4.88	18,750	10,515	8,235	4,757	3,478	7,000	13,500	37,500	29,100	
6.7L DIESEL	M6	DC-G56	4.1	18,750	10,580	8,170	4,701	3,469	7,000	13,500	26,000	17,650	
6.7L DIESEL	M6	DC-G56	4.44	18,750	10,580	8,170	4,701	3,469	7,000	13,500	28,000	19,650	
CREW CAB - CA 84" - 2WD - DRW													
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,572	8,428	4,935	3,493	7,000	13,500	26,000	17,400	
6.7L DIESEL	A6	AS69RC	4.1	19,500	11,072	8,428	4,935	3,493	7,000	13,500	26,000	17,400	
6.7L DIESEL	A6	AS69RC	4.44	19,500	11,072	8,428	4,935	3,493	7,000	13,500	32,500	23,900	
6.7L DIESEL	A6	AS69RC	4.88	19,500	11,072	8,428	4,935	3,493	7,000	13,500	37,500	28,900	
6.7L DIESEL	M6	DC-G56	4.1	19,500	11,137	8,363	4,879	3,484	7,000	13,500	26,000	17,450	
6.7L DIESEL	M6	DC-G56	4.44	19,500	11,137	8,363	4,879	3,484	7,000	13,500	28,000	19,450	

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.
2. Maximum trailer weights are rounded down to the nearest 50 lbs.
3. The recommended tongue weight is 10 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.
4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.

2013 RAM 5500 CHASSIS CAB TOWING CHART

NOTE: BASE WEIGHTS CAN CHANGE

Engine	Trans Type	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
						Total	Front	Rear	Front	Rear		
REGULAR CAB - CA 60" - 4WD - DRW												
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,928	8,072	4,754	3,318	7,000	13,500	26,000	17,750
6.7L DIESEL	A6	AS69RC	4.1	18,750	10,678	8,072	4,754	3,318	7,000	13,500	26,000	17,750
6.7L DIESEL	A6	AS69RC	4.44	18,750	10,678	8,072	4,754	3,318	7,000	13,500	32,500	24,250
6.7L DIESEL	A6	AS69RC	4.88	18,750	10,678	8,072	4,754	3,318	7,000	13,500	37,500	29,250
6.7L DIESEL	M6	DC-G56	4.1	18,750	10,743	8,007	4,698	3,309	7,000	13,500	26,000	17,800
6.7L DIESEL	M6	DC-G56	4.44	18,750	10,743	8,007	4,698	3,309	7,000	13,500	28,000	19,800
REGULAR CAB - CA 84" - 4WD - DRW												
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,796	8,204	4,920	3,284	7,000	13,500	26,000	17,600
6.7L DIESEL	A6	AS69RC	4.1	19,500	11,296	8,204	4,920	3,284	7,000	13,500	26,000	17,600
6.7L DIESEL	A6	AS69RC	4.44	19,500	11,296	8,204	4,920	3,284	7,000	13,500	32,500	24,100
6.7L DIESEL	A6	AS69RC	4.88	19,500	11,296	8,204	4,920	3,284	7,000	13,500	37,500	29,100
6.7L DIESEL	M6	DC-G56	4.1	19,500	11,361	8,139	4,864	3,275	7,000	13,500	26,000	17,700
6.7L DIESEL	M6	DC-G56	4.44	19,500	11,361	8,139	4,864	3,275	7,000	13,500	28,000	19,700
REGULAR CAB - CA 108" - 4WD - DRW												
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,547	8,453	5,136	3,317	7,000	13,500	26,000	17,350
6.7L DIESEL	A6	AS69RC	4.1	19,500	11,047	8,453	5,136	3,317	7,000	13,500	26,000	17,350
6.7L DIESEL	A6	AS69RC	4.44	19,500	11,047	8,453	5,136	3,317	7,000	13,500	32,500	23,850
6.7L DIESEL	A6	AS69RC	4.88	19,500	11,047	8,453	5,136	3,317	7,000	13,500	37,500	28,850
6.7L DIESEL	M6	DC-G56	4.1	19,500	11,217	8,283	4,998	3,285	7,000	13,500	26,000	17,550
6.7L DIESEL	M6	DC-G56	4.44	19,500	11,217	8,283	4,998	3,285	7,000	13,500	28,000	19,550
REGULAR CAB - CA 120" - 4WD - DRW												
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,469	8,531	5,197	3,334	7,000	13,500	26,000	17,300
6.7L DIESEL	A6	AS69RC	4.1	19,500	10,969	8,531	5,197	3,334	7,000	13,500	26,000	17,300
6.7L DIESEL	A6	AS69RC	4.44	19,500	10,969	8,531	5,197	3,334	7,000	13,500	32,500	23,800
6.7L DIESEL	A6	AS69RC	4.88	19,500	10,969	8,531	5,197	3,334	7,000	13,500	37,500	28,800
6.7L DIESEL	M6	DC-G56	4.1	19,500	11,139	8,361	5,059	3,302	7,000	13,500	26,000	17,450
6.7L DIESEL	M6	DC-G56	4.44	19,500	11,139	8,361	5,059	3,302	7,000	13,500	28,000	19,450
CREW CAB - CA 60" - 4WD - DRW												
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,412	8,588	5,069	3,519	7,000	13,500	26,000	17,250
6.7L DIESEL	A6	AS69RC	4.1	18,750	10,162	8,588	5,069	3,519	7,000	13,500	26,000	17,250
6.7L DIESEL	A6	AS69RC	4.44	18,750	10,162	8,588	5,069	3,519	7,000	13,500	32,500	23,750
6.7L DIESEL	A6	AS69RC	4.88	18,750	10,162	8,588	5,069	3,519	7,000	13,500	37,500	28,750
6.7L DIESEL	M6	DC-G56	4.1	18,750	10,227	8,523	5,013	3,510	7,000	13,500	26,000	17,300
6.7L DIESEL	M6	DC-G56	4.44	18,750	10,227	8,523	5,013	3,510	7,000	13,500	28,000	19,300
CREW CAB - CA 84" - 4WD - DRW												
6.7L DIESEL	A6	AS69RC	4.1	18,000	9,242	8,758	5,235	3,523	7,000	13,500	26,000	17,050
6.7L DIESEL	A6	AS69RC	4.1	19,500	10,742	8,758	5,235	3,523	7,000	13,500	26,000	17,050
6.7L DIESEL	A6	AS69RC	4.44	19,500	10,742	8,758	5,235	3,523	7,000	13,500	32,500	23,550
6.7L DIESEL	A6	AS69RC	4.88	19,500	10,742	8,758	5,235	3,523	7,000	13,500	37,500	28,550
6.7L DIESEL	M6	DC-G56	4.1	19,500	10,807	8,693	5,179	3,514	7,000	13,500	26,000	17,150
6.7L DIESEL	M6	DC-G56	4.44	19,500	10,807	8,693	5,179	3,514	7,000	13,500	28,000	19,150

NOTES:

Note that all the payload and Max Trail weights are ESTIMATED values.

1. Payload is rounded down to the nearest 10 lbs. Payload = GVWR - Curb Wt.

2. Maximum trailer weights are rounded down to the nearest 50 lbs.

3. The recommended tongue weight is 10 percent of the gross trailer weight. However, the maximum tongue weight on Class III (the bumper ball) is limited to 500 pounds, and Class IV (the receiver hitch) to 1,045 pounds. Additionally, the GAWR's and GVWR's should never be exceeded.

4. The maximum trailer weight is 5,000 pounds for a weight-carrying hitch. A weight distributing system is recommended for trailers over 5,000 pounds.