



Dodge Charger SRT

SPECIFICATIONS

2014 Dodge Charger SRT SPECIFICATIONS

All dimensions are in inches (millimeters) unless otherwise noted.

All dimensions are measured at curb weight with standard tires and wheels.

Note: Information shown is correct at time of publication, and is subject to change without notice.

GENERAL INFORMATION

Vehicle Type	E-segment sedan
Assembly Plant	Brampton Assembly Plant, Ontario, Canada
EPA Vehicle Class	Large car
Introduction Date	Summer 2013 as 2014 model

BODY

Layout	Longitudinal front engine, rear-wheel drive (RWD)
Construction	Unitized steel body and aluminum hood

ENGINE: 6.4-LITER HEMI® V-8 WITH FUEL SAVER TECHNOLOGY

Availability	Standard
Type and Description	90-degree V-type, liquid-cooled
Displacement	392 cu. in. (6,417 cu. cm)
Bore x Stroke	4.09 x 3.72 (103.9 x 94.5)
Valve System	Pushrod-operated overhead valves, 16 valves with sodium-filled exhaust valves and hollow stem intake valves, 16 conventional hydraulic lifters, all with roller tips
Fuel Injection	Sequential, multiport, electronic, returnless; automatic features Fuel Saver mode
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.9:1
Power (SAE J2723)	470 hp (351 kW) at 6,000 rpm
Torque (SAE J2723)	470 lb.-ft. (637 N•m) at 4,300 rpm
Max. Engine Speed	6,400 rpm (electronically limited)
Fuel Requirement	Premium 91 octane (R+M)/2 — recommended
Oil Capacity	7 qt. (6.6 liter)
Factory Oil Fill	0W-40 Pennzoil Ultra synthetic
Coolant Capacity	14 qt. (13.25 liter)



Dodge Charger SRT

SPECIFICATIONS

Emission Controls	Dual close-coupled three-way catalytic converters, quad-heated oxygen sensors and internal engine features ^(a)
Exhaust Type	Dual 2.75-in. active exhaust with dual 4-in. round tips (SRT Premium models) Dual 2.75-in. exhaust with dual 4-in. round tips (Super Bee models)
EPA Fuel Economy mpg (city/hwy)	14/23
Assembly Plant	Saltillo Engine Plant, Saltillo, Mexico

(a) Meets Federal Tier 2 Bin 5 emission requirements and ULEV II requirements in California, Massachusetts, New York, Maine, Vermont, Connecticut, Pennsylvania, Rhode Island, New Jersey, Oregon and Washington.

TRANSMISSION: W5A580 FIVE-SPEED AUTOMATIC

Availability	Standard
Description	Adaptive electronic control or driver-interactive manual control with Auto Stick or paddle controls; with "Track" mode (features performance shifting and gear holding feature combined with "Sport" mode suspension damping rates) (SRT Premium models) Adaptive electronic control or driver-interactive manual control with Auto Stick or paddle controls; with "Sport" mode (features performance shifting and gear holding feature. (Super Bee models)
Gear Ratios	
1st	3.59
2nd	2.19
3rd	1.41
4th	1.00
5th	0.83
Reverse	3.16
Final Drive Ratio	3.06 – Getrag limited-slip differential
Overall Top Gear	2.54

ELECTRICAL SYSTEM

Alternator	220-amp
Battery	H7 case, 730 CCA, maintenance free



Dodge Charger SRT

SPECIFICATIONS

SUSPENSION

Type	SRT tuned three-mode adaptive damping system: “Auto” mode — sporty but compliant ride; “Sport” mode — firm, maximum handling; “Track” mode — firm, maximum handling plus performance shifting and gear holding feature (SRT Premium models)
	SRT tuned (Super Bee models)
Front	Independent SLA with high upper “A” arm, coil spring over ADS Bilstein shock absorber, 30 mm stabilizer bar, lateral and diagonal lower links (SRT Premium models)
	Independent SLA with high upper “A” arm, coil spring over Bilstein shock absorber, 30 mm stabilizer bar, lateral and diagonal lower links (Super Bee models)
Rear	Five-link independent with coil spring, Adaptive Damping Suspension (ADS) Bilstein shock absorber and isolated suspension cradle, link type 18 mm stabilizer bar (SRT Premium models)
	Five-link independent with coil spring, Bilstein shock absorber and isolated suspension cradle, link type 18 mm stabilizer bar (Super Bee models)

STEERING

Type	SRT tuned rack and pinion with hydraulic power assist
Overall Ratio	14.4:1
Steering Turns (lock-to-lock)	2.75

DIMENSIONS AND CAPACITIES^(d)

Wheelbase	120.2 (3,053)
Track, Front	63.4 (1,610)
Track, Rear	63.1 (1,603)
Overall Length	200.33 (5,088)
Overall Width	74.24 (1,835)
Overall Height	58.26 (1,480)
Frontal Area	26 ft ²
Ground Clearance (Minimum)	4.37 (111) – front
Drag Coefficient (Cd)	0.338
Curb Weight, lb. (kg)	4,358 (1,977)
Weight Distribution, percent F/R	54/46
Fuel Tank Capacity, gal. (liter)	19.4 (73.4)

(d) All dimensions measured at curb weight with standard tires.



Dodge Charger SRT

SPECIFICATIONS

ACCOMMODATIONS

Seating Capacity, F/R	2/3
Front	
Head room	38.6 (981)
Legroom	41.8 (1,061)
Shoulder room	59.5 (1,510)
Hip room	56.2 (1,428)
Seat travel	Driver — 10.6 (270) Passenger — 8.66 (220)
Recliner angle range, deg.	Power — 70.7 Manual — 70
EPA front row interior volume	55.6 cu. ft. (1.573 cu. m)
Rear Seat	
Head room	37.9 (963) 36.9 (937) with sunroof
Legroom	40.1 (1,019)
Knee clearance	3.9 (99)
Shoulder room	57.7 (1,465)
Hip room	56.1 (142)
EPA second row interior volume	50.7 cu. ft. (1.4 cu. m)
Total Interior Volume	106.3 cu. ft. (3.0 cu. m)
EPA Luggage Compartment Volume	16.3 cu. ft. (0.5 cu. m)
EPA Interior Volume Index	122.6 cu. ft. (3.5 cu. m)
Trunk Liftover Height	30.1 (768.9)

TIRES

Front and Rear	Standard
Size and type	245/45R20 All-season
Mfr. and model	Goodyear Eagle RS-A 2
Revs per mile, (km)	731 (456)
Front and Rear	Optional
Size and type	245/45R20 Three-season
Mfr. and model	Goodyear F1 Supercar
Revs per mile, (km)	726 (450)



Dodge Charger SRT

SPECIFICATIONS

WHEELS

Availability	Standard on Charger SRT (Premium models)
Type and material	Full forged aluminum with painted pockets
Size	20 x 9.0
Availability	Optional on Charger SRT (Premium models)
Type and material	Fully forged aluminum with Black Vapor chrome finish
Size	20 x 9.0
Availability	Standard on Charger SRT (Super Bee models)
Type and material	Cast aluminum with painted pockets
Size	20 x 9.0

BRAKES

Front	
Rotor size and type	14.2 x 1.26 (360 x 32) vented and slotted
Caliper size and type	1.73 (44) Brembo four-piston fixed with aluminum housing
Swept area	351 sq. in. (2,261 sq. cm)
Rear	
Rotor size and type	13.8 x 1.10 (350 x 28) vented and slotted
Caliper size and type	1.26 (32) Brembo four-piston fixed with aluminum housing
Swept area	316 sq. in. (2,036 sq. cm)

