

**RAM**

2017 RAM 3500 10K GVWR CHASSIS CAB

TOWING CHART**2017 Ram 3500 Chassis Cab Trailer Towing Chart**

Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
					Total	Front	Rear	Front	Rear		
REGULAR CAB - CA 60" - 4X2 - SRW											
6.4L V8 HEMI	A6 66RFE	4.10	10,000	4,200	5,800	3,541	2,259	5,500	6,800	21,000	15,050
6.4L V8 HEMI	A6 AS66RC	4.44	10,000	4,070	5,930	3,651	2,279	5,500	6,800	24,000	17,920
6.7L CUMMINS DIESEL	M6 MTXG56	3.73	10,000	3,600	6,404	4,054	2,350	6,000	6,800	24,000	17,450
6.7L CUMMINS DIESEL	A6 AS69RC	3.73	10,000	3,430	6,574	4,196	2,378	6,000	6,800	24,000	17,280
REGULAR CAB - CA 60" - 4X4 - SRW											
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,960	6,043	3,747	2,296	5,500	6,800	21,000	14,810
6.4L V8 HEMI	A6 AS66RC	4.44	10,000	3,830	6,173	3,857	2,316	5,500	6,800	24,000	17,680
6.7L CUMMINS DIESEL	M6 MTXG56	3.73	10,000	3,350	6,647	4,260	2,387	6,000	6,800	24,000	17,200
6.7L CUMMINS DIESEL	A6 AS69RC	3.73	10,000	3,180	6,817	4,402	2,415	6,000	6,800	24,000	17,030
CREW CAB - CA 60" - 4X2 - SRW											
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,760	6,240	3,707	2,533	5,500	6,800	21,000	14,610
6.4L V8 HEMI	A6 AS66RC	4.44	10,000	3,630	6,370	3,817	2,553	5,500	6,800	24,000	17,480
6.7L CUMMINS DIESEL	M6 MTXG56	3.73	10,000	3,160	6,844	4,220	2,624	6,000	6,800	24,000	17,010
6.7L CUMMINS DIESEL	A6 AS69RC	3.73	10,000	2,990	7,014	4,362	2,652	6,000	6,800	24,000	16,840
CREW CAB - CA 60" - 4X4 - SRW											
6.4L V8 HEMI	A6 66RFE	4.10	10,000	3,440	6,559	3,965	2,594	5,500	6,800	21,000	14,290
6.4L V8 HEMI	A6 AS66RC	4.44	10,000	3,310	6,689	4,075	2,614	5,500	6,800	24,000	17,160
6.7L CUMMINS DIESEL	M6 MTXG56	3.73	10,000	2,840	7,163	4,478	2,685	6,000	6,800	24,000	16,690
6.7L CUMMINS DIESEL	A6 AS69RC	3.73	10,000	2,670	7,333	4,620	2,713	6,000	6,800	24,000	16,520

1. Payload and Max Trailer Weights are ESTIMATED values
2. All values are shown in pounds unless otherwise stated
3. Payload and Max Trailer Weight values are rounded to the nearest 10 lbs
4. Payload = GVWR - Base Weight
5. GAWRs, GVWRs, and GCWRs should never be exceeded
6. Recommended tongue weight determined by class hitch receiver and hardware limits of upfit
7. Upfit or Aftermarket weight not included in Base Weight

**RAM**

2017 RAM 3500 10K GVWR CHASSIS CAB TOWING CHART



Canadian Market Only - 2017 Ram 3500 Chassis Cab Trailer Towing Chart

Engine	Transmission	Axle Ratio	GVWR	Payload	Base Weight			GAWR		GCWR	Max Trailer
					Total	Front	Rear	Front	Rear		
REGULAR CAB - CA 60" - 4X2 - SRW											
6.4L V8 HEMI	A6 66RFE	4.10	9,900	4,100	5,800	3,541	2,259	5,500	6,800	21,000	15,050
6.4L V8 HEMI	A6 AS66RC	4.44	9,900	3,970	5,930	3,651	2,279	5,500	6,800	24,000	17,920
6.7L CUMMINS DIESEL	M6 MTXG56	3.73	9,900	3,500	6,404	4,054	2,350	6,000	6,800	24,000	17,450
6.7L CUMMINS DIESEL	A6 AS69RC	3.73	9,900	3,330	6,574	4,196	2,378	6,000	6,800	24,000	17,280
REGULAR CAB - CA 60" - 4X4 - SRW											
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,860	6,043	3,747	2,296	5,500	6,800	21,000	14,810
6.4L V8 HEMI	A6 AS66RC	4.44	9,900	3,730	6,173	3,857	2,316	5,500	6,800	24,000	17,680
6.7L CUMMINS DIESEL	M6 MTXG56	3.73	9,900	3,250	6,647	4,260	2,387	6,000	6,800	24,000	17,200
6.7L CUMMINS DIESEL	A6 AS69RC	3.73	9,900	3,080	6,817	4,402	2,415	6,000	6,800	24,000	17,030
CREW CAB - CA 60" - 4X2 - SRW											
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,660	6,240	3,707	2,533	5,500	6,800	21,000	14,610
6.4L V8 HEMI	A6 AS66RC	4.44	9,900	3,530	6,370	3,817	2,553	5,500	6,800	24,000	17,480
6.7L CUMMINS DIESEL	M6 MTXG56	3.73	9,900	3,060	6,844	4,220	2,624	6,000	6,800	24,000	17,010
6.7L CUMMINS DIESEL	A6 AS69RC	3.73	9,900	2,890	7,014	4,362	2,652	6,000	6,800	24,000	16,840
CREW CAB - CA 60" - 4X4 - SRW											
6.4L V8 HEMI	A6 66RFE	4.10	9,900	3,340	6,559	3,965	2,594	5,500	6,800	21,000	14,290
6.4L V8 HEMI	A6 AS66RC	4.44	9,900	3,210	6,689	4,075	2,614	5,500	6,800	24,000	17,160
6.7L CUMMINS DIESEL	M6 MTXG56	3.73	9,900	2,740	7,163	4,478	2,685	6,000	6,800	24,000	16,690
6.7L CUMMINS DIESEL	A6 AS69RC	3.73	9,900	2,570	7,333	4,620	2,713	6,000	6,800	24,000	16,520

1. Payload and Max Trailer Weights are ESTIMATED values
2. All values are shown in pounds unless otherwise stated
3. Payload and Max Trailer Weight values are rounded to the nearest 10 lbs
4. Payload = GVWR - Base Weight
5. GAWRs, GVWRs, and GCWRs should never be exceeded
6. Recommended tongue weight determined by class hitch receiver and hardware limits of upfit
7. Upfit or Aftermarket weight not included in Base Weight