



2023 Dodge Hornet SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.

All dimensions are in inches (millimeters) unless otherwise noted.

All dimensions measured at curb weight with standard tires and wheels.

LAYOUT

	GT	R/T PHEV
Number of seats	5	5
Drive type	AWD	AWD
Chassis	Unibody	Unibody

INTERNAL COMBUSTION ENGINES

	Hurricane4 2.0-liter, 4-cylinder Turbo	1.3-liter, 4-cylinder Turbo PHEV
Fuel type	Gasoline	Gasoline Plug-in Hybrid
Cylinder capacity	2.0-liter (1,995 cu. cm.)	1.3-liter (1,332 cu. cm.)
Emission standard	EPA and CARB	EPA and CARB
Horsepower	268 (premium fuel)	288 Net Combined
Torque	295 lb.-ft. (400 Nm)	383 lb.-ft. Total Installed Front 199 lb.-ft. (ICE) Rear 184 lb.-ft. (e-Motor)

TRANSMISSIONS

	GT	R/T PHEV
Type	9-speed Auto	6-speed Auto



ELECTRIC MOTORS

	GT	R/T PHEV
E-motor position	NA	P1, P4
E-motor horsepower	NA	P1 BSG — 44 hp, P4 Rear — 121 hp (90 kW)

BATTERY

	GT	R/T PHEV
Capacity	NA	15.5 kWh
Chemistry	NA	Lithium-ion, nickel manganese cobalt graphite
Battery cooling	NA	Refrigerant Gas
Total voltage [V]	NA	306
Cell configuration (Series Parallel)	NA	84S 1P
Battery weight	NA	276 lbs. (125 kg)
Fuel economy	NA	NA
Combined cycle [g/mi]	NA	NA
City/Hwy/Comb	NA	NA

PERFORMANCE

	GT	R/T PHEV
Stop/Start	Yes	Yes
Top Speed [mph]	140	128
0 - 60 mph (sec.)	6.5	6.1



DIMENSIONS—IN. (MM) UNLESS OTHERWISE NOTED

	GT	R/T PHEV
Length (L103)	178 (4,528)	178 (4,528)
Height	63.8 (1,620)	63 (1,601)
Width with mirrors	82 (2,082)	82 (2,082)
Wheelbase	103.8 (2,636)	103.8 (2,636)
Trunk volume	27 cu.-ft. (765 L)	22.9 cu.-ft. (650 L)
Trunk volume rear seats folded	54.7 cu.-ft. (1,550 L)	50.5 cu.-ft. (1,430 L)
Ground clearance	8 (203)	6.1 (156)
Front overhang	37.4 (951)	37.4 (951)
Rear overhang	37 (941)	37 (941)
Fuel tank capacity	13.5 gal (51 L)	11.2 gal (42 L)

WEIGHT—LBS. (KG)

	GT	R/T PHEV
Curb	3,715 (1,600)	4,140 (1,875)
Payload	1,245 (565)	1,195 (542)
Towing capacity	2,000 (907)	2,000 (907)

BRAKES

	GT	R/T PHEV
Front	12.08 (305)	Brembo calipers standard
Rear	10.94 (278)	Brembo calipers standard
Brembo calipers	Front: 13.53 (345) Rear: 12.08 (305)	Front: 13.53 (345) Rear: 12.08 (305)

SUSPENSIONS

	GT	R/T PHEV
Front	MacPherson strut (FSD damping)	MacPherson strut (FSD damping)
Rear	Chapman strut (FSD damping)	Chapman strut (FSD damping)



STEERING		
	GT	R/T PHEV
Power	Electric	Electric
Ratio	13.6: 1	14.5: 1
Turns lock-to-lock	2.28	2.5
Turning circle	37.95 ft. (11.57 m)	37.86 ft. (11.54 m)

#