



2026 Jeep® Grand Wagoneer

SPECIFICATIONS

Specifications are based on the latest product information available at the time of publication.

All dimensions are in inches (millimeters) unless otherwise noted.

All dimensions measured at curb weight with standard tires and wheels.

GENERAL INFORMATION

Vehicle Type	Four-door sport-utility vehicle
Assembly Plant	Warren Truck Assembly Plant, Warren, Michigan
EPA Vehicle Class	Multipurpose vehicle
Introduction Date	Fall 2022 as a 2023 model

BODY AND CHASSIS

Layout	Front engine, rear- or four-wheel drive
Construction	Steel frame

ENGINE: 3.0-LITER HURRICANE TWIN TURBO

Availability	Standard
Type and Description	Inline six-cylinder (I-6), twin turbocharged, direct injection, gasoline
Displacement	183 cu. in. (2.993 cu. cm)
Bore x Stroke	3.31" x 3.54" (84.0 mm x 90.0 mm)
Valve System	DOHC, dual independent valve timing, hydroformed tubular camshafts, 24 valves with sodium-filled exhaust valves, roller finger followers, hydraulic lash adjusters
Fuel Injection	Gasoline direct injection, centrally located injectors, single high-pressure pump providing up to 5,075 psi (350 bar) to a single fuel rail
Construction	Deep-skirt cast-aluminum block with cross-bolted steel main bearing caps, low friction plasma spray-bore coated cylinders, structural die-cast aluminum alloy oil pan, aluminum alloy head with pent-roof combustion chambers, forged and twisted steel crankshaft, forged steel connecting rods, cast aluminum alloy pistons with DLC coated piston pins
Compression Ratio	10.4:1
Power (SAE J2723)	420 hp (313 kW) @ 5,200 rpm
Torque (SAE J2723)	468 lb.-ft. (635 N•m) @ 3,500 rpm
Max. Engine Speed	5,800 rpm (electronically limited)

**ENGINE: 3.0-LITER HURRICANE TWIN TURBO (CONTINUED)**

Fuel Requirement	Unleaded mid-grade, 89 octane (R+M)/2 — recommended Unleaded regular, 87 octane (R+M)/2 — acceptable
Oil Capacity	7.5 quarts (7.1 liters) oil change with filter
Coolant Capacity	High temp. circuit: 16.6 quarts (15.7 liters); Low temp. circuit: 2.85 (2.70)
Factory Oil Fill	Pennzoil Ultra Platinum 0W-20 GF6+ (API SP)
Emission Controls	Dual close-coupled two-stage three-way catalytic converters, quad-heated oxygen sensors, cooled exhaust gas recirculation and internal engine features
EPA Fuel Economy mpg (city/hwy/combined)	(Details forthcoming)

FUEL ECONOMY (MPG)

WHEEL BASE	DRIVE SYSTEM	CITY	HIGHWAY	COMBINED
123"	2WD	17	24	19
	4WD	17	23	19
130"	2WD	17	24	19
	4WD	16	22	18
Assembly Plant	Saltillo Engine Plant, Saltillo, Mexico			

TRANSMISSION: TORQUEFLITE 880RE AUTOMATIC, EIGHT-SPEED OVERDRIVE

Availability	Standard
Description	Five clutches and four planetary gear set architecture. 8.6 overall ratio spread. Start/stop and electronic range select capability. Electronically modulated torque converter clutch with torsional turbine damper
Gear Ratios	
1st	5.5
2nd	3.52
3rd	2.2
4th	1.72
5th	1.301
6th	1.00
7th	0.833
8th	0.640
Reverse	4.543



TRANSFER CASE: 1-SPEED

Availability	Standard — 3.0-liter Hurricane Twin Turbo
Type	Single-speed
Operating Mode	Full-time active 4x4
Torque Split, Front/Rear	Variable — Auto, Tow, Snow, Mud, Sand, Sport
Low Range Ratio	None

TRANSFER CASE: 2-SPEED

Availability	Optional — 3.0-liter Hurricane Twin Turbo
Type	Two-speed electronically shifted
Operating Modes	4x4 Low Active, Neutral, full-time active 4x4
Torque Split, Front/Rear	Variable — Auto, Tow, Snow, Mud, Sand, Rock, Sport
Low Range Ratio	2.64

AXLES

Front	
Differential type	Open
Availability	Standard on 4x4 models
Ring gear diameter	8.5 (215 mm)
Axle ratios	3.55:1 — standard
	3.92:1 — optional
Rear	
Differential type	Limited slip or electronic limited slip (ELSD)
Availability	Limited slip differential — standard
	Electronic limited slip differential (ELSD) — optional
Ring gear diameter	10.2 inches (260mm)
Axle ratios	3.55:1 — standard
	3.92:1 — optional

ELECTRICAL SYSTEM

Alternator	230-amp — standard
Battery	Maintenance-free H7 AGM 700 CCA



SUSPENSION

Front	Short- and long-arm independent with hybrid steel composite upper control arm, aluminum lower control arm, aluminum knuckle, coil springs with monotube shocks or Quadra-lift air suspension with semi-active damping, solid or hollow stabilizer bar
Rear	Five-link independent rear suspension, coil springs with monotube load leveling shocks or Quadra-lift air suspension with semi-active damping, hollow stabilizer bar, forged aluminum links (tension, compression, camber, toe), high-strength steel spring link

STEERING

Type	Electric rack-and-pinion steering
Overall Ratio	Grand Wagoneer: 16.7:1 Grand Wagoneer L: 16.0:1
Turning Diameter (curb-to-curb)	Grand Wagoneer: 40.2 feet (12.3 meters) Grand Wagoneer L: 42.2 feet (12.9 meters)
Steering Turns (lock-to-lock)	Grand Wagoneer: 3.1 Grand Wagoneer L: 2.97

BRAKES

Type	Electronic power brakes (eBooster), anti-lock braking system (ABS)
Availability	Standard
Front	
Rotor size and type, inches (mm)	14.88 x 1.18 (378 x 30) vented disc
Caliper size and type, inches (mm)	2.24 (57) two-piston pin-slider caliper
Swept area, sq. in. (sq. cm)	100.9 (651.5)
Rear	
Rotor size and type, inches (mm)	14.76 x 0.87 (375 x 22) solid disc
Caliper size and type, inches (mm)	2.24 (57) single-piston pin-slider caliper with EPB
Swept area, sq. in. (sq. cm)	79.2 (511.6)
Parking Brake Type	Electric park brake (standard)
Four-wheel Anti-lock Brakes	Standard
Electronic Stability Control	Standard
All-speed Traction Control	Standard
Brake Assist	Standard



DIMENSIONS AND CAPACITIES

Wheelbase	123.0 (3,124) — Grand Wagoneer
	130.0 (3,302) — Grand Wagoneer L
Track, Front	68.5 (1,740)
Track, Rear	68.3 (1,734)
Overall Length	216.1 (5,488) — Grand Wagoneer
	228.1 (5,794) — Grand Wagoneer L
Overall Width (at mirrors)	94.0 (2,388)
Body Width	83.6 (2,124)
Overall Height (at roof rail / at antenna)	79.8 (2,027) / 77.3 (1,964) — Grand Wagoneer
	79.7 (2,024) / 77.3 (1,963) — Grand Wagoneer L
Load Floor Height	34.0 (864) — standard suspension / air suspension (NRH)
	32.5 (825) — air suspension (Park)
Sill Step Height	22.9 (581) — standard suspension / air suspension (NRH)
	21.3 (541) — air suspension (Park)
Ground Clearance (with 275/55R20 tire)	7.4 (189) — standard suspension
	10.1 (257) — air suspension (Off Road 2)
Chassis (fuel tank)	9.7 (247) — standard suspension
	11.0 (279) — air suspension (Off Road 2)
Front Axle	9.6 (245) — standard suspension
	11.6 (296) — air suspension (Off Road 2)
Rear Axle	9.0 (229) — standard suspension
	11.0 (280) — air suspension (Off Road 2)
Approach Angle (degrees)	21.4 — standard suspension
	25.2 — air suspension (Off Road 2)
Ramp Breakover Angle (degrees)	18.6 — standard suspension
	22.0 — air suspension (Off Road 2)
Departure Angle (degrees)	21.2 — standard suspension
	24.0 — air suspension (Off Road 2)
Frontal Area	37.2 sq. ft. (3.46 sq. m)
Drag Coefficient (Cd)	0.364 — Grand Wagoneer
Aero CdA	13.5 sq. ft. (1.26 sq. m) — Grand Wagoneer
Fuel Tank Capacity	26.5 gallons (100.3 liters) — Grand Wagoneer
	30.5 gallons (115.4 liters) — Grand Wagoneer L



ACCOMMODATIONS

Seating Capacity	Standard — 2/2/3 (including captain's chairs) Optional — 2/3/3 (including second-row bench)
SAE Total Interior Passenger Volume, cu. ft. (cu. m)	182.4 (5.2)
Front	
Headroom	41.3 (1,049) Grand Wagoneer / 39.3 (998) Grand Wagoneer with sunroof
Legroom	40.9 (1,040)
Shoulder room	66.1 (1,680)
Hip room	63.5 (1,612)
Seat travel	8.1 (207)
EPA front volume index, cu. ft. (cu. m)	64.7 (1.8)
Cargo volume behind first-row seats, cu. ft. (cu. m)	116.7 (3.3)
Second Row	
Headroom	40.0 (1,016) Grand Wagoneer / 38.4 (975) Grand Wagoneer with sunroof
Legroom	42.7 (1,085)
Knee clearance	6.7 (170)
Shoulder room	65.2 (1,657)
Hip room	63.0 (1,599)
EPA second-row seat volume index cu. ft. (cu. m)	64.5 (1.8)
Cargo volume behind second-row seats cu. ft. (cu. m)	70.8 (2.0)
Third Row	
Headroom	39.0 (991) Grand Wagoneer / 38.5 (977) Grand Wagoneer with sunroof
Legroom	36.6 (930)
Knee clearance	1.9 (47)
Shoulder room	64.4 (1,635)
Hip room	51.6 (1,311)
EPA third-row seat volume index cu. ft. (cu. m)	53.2 (1.5)



ACCOMMODATIONS (CONTINUED)

Cargo volume behind third-row seats cu. ft. (cu. m)	27.9 (0.8) Grand Wagoneer / 42.6 (1.2) Grand Wagoneer L
Total passenger plus cargo volume cu. ft. (cu. m)	210.3 (5.9) Grand Wagoneer / 225.1 (6.4) Grand Wagoneer L

WEIGHTS (ESTIMATES WHEN PROPERLY EQUIPPED)

WHEEL BASE	DRIVE SYSTEM	MODEL	ENGINE	GVWR LBS.	CURB WEIGHT ^(A)	PAYLOAD ^(B) LBS.	WEIGHT DISTRIBUTION, F/R
123"	2WD	Grand Wagoneer	3.0L	7,300	5,730	1,300	50/50
	4WD	Grand Wagoneer	3.0L	7,500	5,940	1,300	52/48
		Limited	3.0L	7,600	6,004	1,300	51/49
		Summit	3.0L	7,800	6,175	1,300	52/48
130"	2WD	Grand Wagoneer	3.0L	7,400	5,980	1,300	51/49
	4WD	Grand Wagoneer	3.0L	7,700	6,185	1,300	52/48
		Limited	3.0L	7,700	6,285	1,300	52/48
		Summit	3.0L	7,950	6,444	1,300	52/48

(a) Curb weight includes standard equipment and full quantities of fuel, lubricant and coolant.

(b) Payload is the maximum allowable weight of driver, passengers, cargo, and options, rounded to the nearest 10 lbs. (5kg).

WHEELS

Availability	Standard on Grand Wagoneer
Type and material	Machined cast aluminum with Black Noise painted pockets, six spokes
Size (in.)	18 x 8
Availability	Optional with Grand Wagoneer
Type and material	Machined cast aluminum with Gloss Black painted pockets, six spokes
Size (in.)	20 x 9
Availability	Standard with Upland Appearance Package
Type and material	Fully painted cast aluminum in Luster Grey Metallic, six spokes
Size (in.)	20 x 9
Availability	Standard on Limited
Type and material	Machined cast aluminum with Gloss Black painted pockets, six spokes
Size (in.)	20 x 9
Availability	Optional on Limited
Type and material	Fully painted cast aluminum in Satin Carbon
Size (in.)	22 x 9



WHEELS (CONTINUED)

Availability	Standard with Altitude Appearance Package
Type and material	Fully painted cast aluminum with Gloss Black painted pockets, six spokes
Size (in.)	20 x 9
Availability	Optional with Limited Reserve Package
Type and material	Fully painted cast aluminum in Gloss Black
Size (in.)	22 x 9
Availability	Standard on Summit
Type and material	Machined cast aluminum with Black Noise painted pockets and brushed nano steel inserts
Size (in.)	22 x 9
Availability	Optional with Summit Reserve Package
Type and material	Cast aluminum with painted Black Noise and Gloss Black inserts
Size (in.)	22 x 9

TIRES

Availability	Standard on Grand Wagoneer
Size and type	275/65R18
Mfr. and model	Bridgestone Dueler H/T all-season
Revs per mile	653
Availability	Standard on Limited SWB, Optional on Grand Wagoneer SWB
Size and type	275/55R20
Mfr. and model	Nexen Roadian HTX RH5 all-season
Revs per mile	656
Availability	Standard on Grand Wagoneer (4x2) and Limited LWB Optional with Trailer Tow Package
Size and type	275/55R20
Mfr. and model	Bridgestone Dueler H/L Alenza all-season T-rated for North America
Revs per mile	655
Availability	Standard on Summit and Limited Reserve
Size and type	285/45R22XL
Mfr. and model	Pirelli Scorpion Verde all-season
Revs per mile	639
Availability	Standard with Upland Appearance Package
Size and type	275/55R20
Mfr. and model	Falken Wildpeak all-terrain
Revs per mile	651



TRAILER TOWING

WHEELBASE	DRIVE SYSTEM	ENGINE	AXLE RATIO	MAXIMUM TRAILER WEIGHT LBS.
123"	2WD	3.0L	3.55	6,210
	4WD	3.0L	3.55	6,030
			3.92	10,000
130"	2WD	3.0L	3.55	5,960
	4WD	3.0L	3.55	5,770
			3.92	9,860

#