



2018 JEEP® COMPASS
**CANADIAN
SPECIFICATIONS**

FCA CANADA

2018 Jeep® Compass
CANADIAN SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.
All dimensions are in millimetres (inches) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.*

GENERAL INFORMATION

Body Style	Sport Utility Vehicle (SUV)
Assembly Plant	Toluca, Mexico
Energide Vehicle Class	Multipurpose vehicle

BODY AND CHASSIS

Layout	Transverse front engine, 4x2 and 4x4
Construction	Steel uniframe

ENGINE: 2.4-PZEV TIGERSHARK WITH MULTIAIR

Availability	Standard — All Models
Type and Description	In-line four-cylinder, 16-valve MultiAir with multiport fuel injection
Displacement	144 cu. in. (2,360 cc)
Bore x Stroke	3.46 X 3.82 (88 X 97)
Valve System	SOHC, four valves per cylinder
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Aluminum block, aluminum cylinder head
Compression Ratio	10:1
Power (SAE net)	180 hp (134 kW) @ 6,400 rpm
Torque (SAE net)	175 lb.-ft. (237 N•m) @ 3,900 rpm
Max. Engine Speed	6,400 rpm
Fuel Requirement	Unleaded regular, 87 octane
Oil Capacity	5.5 quarts (5.2 litres) (total)
Coolant Capacity	6.8 quarts (6.45 litres)
Emission Controls	Single catalytic converter, heated wide band lambda sensor upstream and mid-catalyst heated oxygen sensor



2018 JEEP® COMPASS
**CANADIAN
 SPECIFICATIONS**

EnerGuide Fuel Consumption Ratings L/100km (imp. mpg) (city/hwy/combined)	10.4 (27) / 7.3 (39) (FWD, MTX)
	10.8 (26) / 7.6 (37) (AWD, MTX)
	10.6 (27) / 7.6 (37) (FWD, ATX)
	10.8 (26) / 7.8 (36) (AWD, ATX)

Based on 2018 EnerGuide fuel consumption ratings. Government of Canada test methods used. Your actual fuel consumption will vary based on driving habits and other factors. For EnerGuide information please visit the government of Canada website www.vehicles.nrcan.gc.ca

Towing	2,000 lbs. (907 kg) (not recommended for FWD)
Engine Assembly Plant	Saltillo Engine Plant, Saltillo, Mexico

TRANSMISSION: 9HP48 NINE-SPEED AUTOMATIC

Availability	2.4-litre Tigershark engine with MultiAir (4x4)
Description	Planetary gear train, transverse layout
Ratio Spread	9.81
Gear Ratios	
1st	4.71
2nd	2.84
3rd	1.91
4th	1.38
5th	1.00
6th	0.81
7th	0.70
8th	0.58
9th	0.48
Reverse	3.81
Final-drive Ratio	3.734
	4.334 (Trailhawk)

C635 SIX-SPEED MANUAL TRANSMISSION

Availability	2.4-litre Tigershark engine with MultiAir (Sport)
Description	Planetary gear train, transverse layout
Gear Spread	6.635



2018 JEEP® COMPASS
**CANADIAN
 SPECIFICATIONS**

Gear Ratios	
1st	4.459
2nd	2.508
3rd	1.556
4th	1.142
5th	0.852
6th	0.672

AT6 AISIN SIX-SPEED AUTOMATIC TRANSMISSION

Availability	2.4-litre Tigershark engine with MultiAir (4x2)
Description	Planetary gear train, transverse layout
Gear Spread	6.635

Gear Ratios	
1st	4.459
2nd	2.508
3rd	1.556
4th	1.142
5th	0.852
6th	0.672

4X4 SYSTEMS: JEEP ACTIVE DRIVE, JEEP ACTIVE DRIVE LOW

Availability	Jeep Active Drive is optional on all models Jeep Active Drive Low is standard on Trailhawk
Type	Fully disconnecting 4x2 mode with automatic 4x4 engagement Full-time 4x4 mode with active on demand clutch
Operating Modes	Auto 4x2/4x4, Neutral
Centre Differential Type	None
Terrain Response	Unique tuning in all terrain modes
Crawl Ratio	20:1 (with Jeep Active Drive Low)



2018 JEEP® COMPASS
**CANADIAN
 SPECIFICATIONS**

ELECTRICAL SYSTEM

Alternator	160-amp (2.4-litre Tigershark with MultiAir)
Battery	Dual batteries when equipped with electronic stop-start system: 500-amp (primary) 150-amp (secondary) (2.4-litre Tigershark with MultiAir with ESS)

SUSPENSION

Front	MacPherson strut, coil springs, flat front steel crossmember, high-strength steel double shell lower control stabilizer bar
Rear	Chapman strut, high-strength steel links, isolated steel rear cradle for 4x4 and not-isolated for 4x2, coil springs, stabilizer bar

STEERING

Type	Electric power rack and pinion
Overall Ratio	15.7
Turning Diametre (curb-to-curb)	36.3 (11.07) 4x2 and 4x4 35.3 (10.76) Trailhawk 4x4
Steering Turns (lock-to-lock)	2.68 (4x2 and 4x4) 2.76 (Trailhawk 4x4)

BRAKES

Front	
Size and Type	12 x 1.1 (305 x 28) vented rotor with 2.36 (60) single-piston floating caliper
Swept Area (per caliper)	138.77 sq. in. (895.3 sq. cm), 1 x 60 115.88 sq. in. (747.6 sq. cm), 1 x 57
Rear	
Size and Type	10.95 x 0.47 (278 x 12) solid rotor with 1.5 (38) single-piston floating caliper
Swept Area (per caliper)	101.7 sq. in. (656.4 sq. cm), 1 x 38
Power-assist Type	10 (254) vacuum assist
Four-wheel anti-lock brake system (ABS)	Standard
Electronic stability control (ESC)	Standard
Parking Brake Type	Electric motor



2018 JEEP® COMPASS
**CANADIAN
 SPECIFICATIONS**

DIMENSIONS AND CAPACITIES

Wheelbase	103.8 (2,636)
Track, Front	60.7 (1,542)
Track, Rear	60.3 (1,532)
Overall Length	173 (4,394)
Overall Width (with folded side mirrors)	73.8 (1,874)
Overall Width (with open side mirrors)	80 (2,033)
Overall Height	64.6 (1,641) without rails; 64.8 (1,647) with rails
Load-floor height	29.7 (754) (height measured from curb ground to load floor)
Sill-step height	19.4 (494) (height measured from curb ground to sill trim)
Ground Clearances	4x2 7.8 (198)
	4x4 8.2 (208)
	Trailhawk 4x4 8.5 (216)
Approach Angle, (with air dam) (degrees)	4x2 15.8
	4x4 16.8
	Trailhawk 4x4 30.3
Breakover Angle (degrees)	4x2 21.8
	4x4 22.9
	Trailhawk 4x4 24.4
Departure Angle (degrees)	4x2 30.8
	4x4 31.7
	Trailhawk 4x4 33.6
Curb Weight (kg)	3,184 (1,444) 4x2 and 2.4-litre Tigershark with MultiAir
	3,327 (1,509) 4x4 and 2.4-litre Tigershark with MultiAir
	3,633 (1,648) Trailhawk 4x4 with 2.4-litre Tigershark with MultiAir
Fuel-tank Capacity	13.5 gal. (51 litres)

ACCOMMODATIONS

Seating Capacity — Front/Rear	2/3
Front Row	
Headroom without Sunroof	39.2 (995)
Headroom with Sunroof	38.6 (981)



2018 JEEP® COMPASS
**CANADIAN
 SPECIFICATIONS**

Legroom	41.8 (1,046)
Shoulder Room	56.7 (1,439)
Hip Room	54.1 (1,375)
Seat Travel	8.7 (220) fore/aft travel range
Recliner Range (degrees)	Manual/power recliner travel: 69 degrees Manual fold FWD recliner travel: 107.5 degrees
SAE Volume (standard roof), cu. ft. (cu. m)	52.9 (1.49) front passenger volume
Second Row	
Headroom	38.5 (978)
Legroom	38.3 (973)
Shoulder Room	55.1 (1,400)
Hip Room	49.2 (1,250)
SAE Volume, cu. ft. (cu. m)	46.7 (1.35) Second-row passenger volume
Cargo Access	
Liftover Height	31.1 (792) (Height measured from Curb Ground to Liftgate Scuff Trim)
Maximum Cargo Width at Liftgate Opening	42.1 (1,069)
Minimum Cargo Width at Liftgate Opening	36.9 (938)
Maximum Cargo Height at Liftgate Opening	27.2 (691)
Distance Between Wheelhouse Interior Trim	38.1 (968)
SAE Cargo Volume	
Rear Seats Up, cu. ft. (cu. m)	27.2 (0.8)
Rear Seats Folded, cu. ft. (cu. m)	59.8 (1.7)
EPA Interior Volume Index, cu. ft. (cu. m)	126.7 (3.6)

TIRES

Availability	Standard — Sport 4x2, Sport 4x4
Size and Type	215/65R16 BSW All-season
Mfr. and Model	Continental CrossContact LX Sport (standard) or Kumho Crugen Premium
Revs per Mile (km)	770 (479)



2018 JEEP® COMPASS
**CANADIAN
 SPECIFICATIONS**

Availability	Standard — North 4x2, North 4x4
Size and Type	225/60R17 BSW All-season
Mfr. and Model	Bridgestone (standard) or Kumho
Revs per Mile (km)	749 (466)

Availability	Optional — Limited 4x4
Size and Type	235/45R19 BSW All Season
Mfr. and Model	Continental ContiProContact
Revs per Mile (km)	766 (476)

Availability	Standard — Trailhawk
Size and Type	215/65R17 OWL All-season
Mfr. and Model	Falken WildPeak H/T
Revs per Mile (km)	744 (462.8)

Availability	Standard — Limited Optional — North
Size and Type	225/55 R18 BSW All-season
Mfr. and Model	Continental
Revs per Mile (km)	744 (462)

Availability	Optional — North, Limited
Size and Type	225/55 R18 BSW All-season
Mfr. and Model	Yokohama
Revs per Mile (km)	744 (462)

