



# DAF

## FRONT-MOUNTED BRUSHCUTTER-MULCHERS

SPECIFICATIONS	DAF-250Ex	DAF-225Ex	DAF-225E	DAF-180F	DAF-180D	DAF-150D
Approximate Min. Carrier Power [kW (hp)]	190 (250)	150 (200)	130 (175)	95 (125)	65 (85)	60 (75)
Cutting Width [cm (in)]	251 (99)	216 (85)	222 (88)	189 (74)	189 (74)	150 (59)
Cutting Distance from Ground Level [cm (in)]	1 (0.4)	1 (0.4)	1 (0.4)	1 (0.4)	1 (0.4)	1 (0.4)
Number of Blades on Rotor	35	31	31	27	27	21
Optimal Target Material Diameter [cm (in)]	60 (24)	60 (24)	40 (15)	25 (10)	20 (8)	15 (6)
Exterior Width [cm (in)]	261 (103)	258 (102)	254 (100)	223 (88)	219 (87)	182 (72)
Exterior Height (with Pushbar) [cm (in)]	155 (61)	148 (58)	140 (55)	141 (55)	147 (58)	150 (59)
Exterior Width (with Pushbar) [cm (in)]	127 (50)	130 (51)	139 (55)	115 (45)	131 (51)	122 (48)
Exterior Height (without Pushbar) [cm (in)]	98 (38)	96 (38)	98 (38)	94 (37)	112 (44)	66 (26)
Exterior Width (without Pushbar) [cm (in)]	83 (33)	83 (33)	83 (33)	69 (27)	79 (31)	72 (29)
Rotor Diameter [cm (in)]	51 (20)	51 (20)	51 (20)	51 (20)	46 (18)	46 (18)
Approximate Typical Weight [kg (lbs)]	2450 (5400)	2360 (5200)	2140 (4700)	1500 (3300)	1450 (3200)	1050 (2300)
HYDRAULIC SYSTEM	DAF-250Ex	DAF-225Ex	DAF-225E	DAF-180F	DAF-180D	DAF-150D
Variable Displacement Axial Piston Motor [cc]	2x 115	2x 115	1x 170	1x 115	1x 115	1x 85
Required Continuous Flow [L/min (gal/min)]	276 (73)	276 (73)	205 (54)	170 (45)	115 (30)	87 (23)
Min. Operating Pressure [bar (psi)]	240 (3500)	240 (3500)	240 (3500)	240 (3500)	240 (3500)	240 (3500)
Rotating Speed [rpm]	2500	2500	2500	2500	2500	2500
Pressure Line I.D. [# (in)]	#20 (1.25)	#20 (1.25)	#16 (1.00)	#16 (1.00)	#16 (1.00)	#12 (0.75)
Return Line I.D. [# (in)]	#20 (1.25)	#20 (1.25)	#16 (1.00)	#16 (1.00)	#16 (1.00)	#12 (0.75)
Drain Line I.D. [# (in)]	#16 (1.00)	#16 (1.00)	#12 (0.75)	#10 (0.675)	#10 (0.675)	#8 (0.5)
FEATURES	DAF-250Ex	DAF-225Ex	DAF-225E	DAF-180F	DAF-180D	DAF-150D
Type of Sharpenable Bolt-on Forged Blades	Standard	Standard	Standard	Standard	Standard	Standard
Hydraulic Pushbar	✓	✓	✓	✓	✓	✓
Bolt-On Wear liner	✓	✓	✓	✓	✓	✓

Those are minimum requirements; call your DENIS CIMAF's Sale Representative for guidance in selecting the best match. This information is subject to change without notice.

## CONTACT US

211 rue Notre-Dame  
Roxton Falls QC J0H 1E0  
Canada  
[www.denisCIMAF.com](http://www.denisCIMAF.com)

Toll free : 877-279-2300  
Phone : 450-548-7007  
Fax: 450-548-7008  
[info@deniscimaf.com](mailto:info@deniscimaf.com)

**DENIS**  **CIMAF**

20190423