

300 SERIES LIQUID-COOLED MIDMOUNT™

Torque and power available on demand



ComfortReach™ with "no tools" 2-in. adjustment range

Designed for fuel economy and extended service life for operating efficiency. Equipped with a 3-cylinder Kubota gasoline or EPA Tier 4 Final-compliant diesel engine, so you can tackle even the toughest jobs with the greatest of ease. The engine is mounted with horizontal crankshaft for longer performance life.

Robust, design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

A compact wheelbase provides a great power-to-size ratio for easy transport on trailers and through tighter spaces.

5.5-inch deep DuraMax® decks with anveled design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® with lumbar and coil-spring suspension provides all-day comfort. The adjustable cup holder makes it convenient to tote along your favorite beverage. Electronic fuel gauge/hour meter on the console is standard.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal / 45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

329

52 61 72

962cc, 3-cylinder, MaxTorque™ gasoline engine

3250

52 61 72

898cc, 3-cylinder, MaxTorque™ Clean Diesel engine

● Standard deck ■ DuraMax® deck

Mowing speeds up to 10.5 MPH and 6.88 acres/hr. based on 72" cutting width*
For more details visit: grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck
- » Speed-Trimming™ heavy-duty roller (61" and 72")
- » TrimAide™ Roller (52")
- » Hydraulic height adjustment (61" and 72")
- » Electric height adjustment
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks
- » LED work lights
- » QuikAjust Tilt™ steering levers with "no tools" 9-inch comfort range
- » Extended steering levers
- » Big Boy wide-seat conversion kit
- » Premier suspension seat
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24x12x12 Airless Turf Tires
- » Michelin® X® Tweel® 13x6.5x6 Airless Front Casters
- » Edge-EZE™ edger
- » Shielded sprayer
- » Sunshade Canopy (for ROPS)
- » Yellow beacon light
- » Filter minder
- » Radiator cleaning wand
- » Engine block heater
- » Side discharge control kit
- » Air Dam kit

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements. Models may be shown with optional equipment. *Actual results may vary.

LIQUID-COOLED 300 SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	325D 52"	325D 61"	325D 72"	329 52"	329 61"	329 72"
ENGINE						
Type/Displacement/Cylinders						
Kubota MaxTorque™ / 54.8 cu. in. (898 cc) / 3-cyl.	•	•	•			
Kubota MaxTorque™ / 58.7 cu. in. (962 cc) / 3-cyl.				•	•	•
Crankshaft/Cooling System						
Horizontal / Liquid	•	•	•	•	•	•
Fuel/Capacity						
Diesel - No. 2 / 12 U.S. Gal. (45.4 l)	•	•	•			
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)				•	•	•
Air Cleaner						
Heavy-duty, remote-mounted engine air cleaner with replaceable element	•	•	•	•	•	•
DECKS						
Construction (Robotic-welded steel)						
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	•	•	•	•	•	•
DuraMax® deck	•	•	•	•	•	•
Blades (MARBAIN®, 1/4-in.)						
(3) 18 in. (45.7 cm) – high-lift blades standard	•			•		
(3) 21 in. (53.3 cm) – high-lift blades standard		•			•	
(3) 25 in. (63.5 cm) – high-lift blades standard			•			•
Sentry™ Spindle Assemblies						
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	•	•	•	•	•	•
Spindle Housing – 8-in. (20.3 cm)-diameter with 6-bolt pattern						
Machined aluminum	•	•		•	•	
Cast iron			•			•
QuikAjust™ DropPin™ Height Adjustment						
Foot-controlled height adjustment pedal with pin	•	•	•	•	•	•
Cutting Height Range						
1.0 – 5.0 in. (2.5 – 12.7 cm)	•	•	•	•	•	•
Blade Drive						
Belt drive with single Kevlar® V-belt and idler arm tensioning	•	•	•	•	•	•
STARTER & ELECTRICAL SYSTEM						
Maintenance-Free Battery/Charging Capacity/Starter						
12 volt/40 amp/solenoid shift	•	•	•	•	•	•
Ignition						
Breakerless				•	•	•
Diesel quick heat glow plug	•	•	•			
Interlock System						
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	•	•	•	•	•	•
ULTIMATE OPERATOR STATION™						
Premium Comfort Seat						
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	•	•	•	•	•	•
Premier Suspension Seat	○	○	○	○	○	○
Operator Protection						
ROPS with seat belt	•	•	•	•	•	•
Suspension						
InFrame™ suspension with iso-mounted seat and footrest	•	•	•	•	•	•

MODEL - CUTTING WIDTH	325D 52"	325D 61"	325D 72"	329 52"	329 61"	329 72"
Console-Mounted Instruments						
Low engine oil pressure, combination electronic fuel gauge/hour meter, alternator, temperature and parking brake warning lights, engine temperature and volt gauges, ignition and push/pull PTO switches.	•	•	•	•	•	•
Choke integrated with throttle lever				•	•	•
Glow plug	•	•	•			
Work Lights (Pre-wired)						
LED	○	○	○	○	○	○
TRANSMISSION & STEERING						
Type						
Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 16cc piston-type pumps and high-torque Parker wheel motors.	•	•	•	•	•	•
Filtration/Hydro Fluid						
7 micron absolute, spin-on / Grasshopper CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.	•	•	•	•	•	•
Speed						
0 – 10 mph (0 – 16.1 kph) forward	•			•		
0 – 10.5 mph (0 – 16.9 kph) forward		•	•	•	•	•
0 – 6.0 mph (0 – 9.7 kph) reverse	•	•	•	•	•	•
Turning Radius						
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.	•	•	•	•	•	•
Steering						
One- or two-handed operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	•	•	•	•	•	•
Brakes						
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	•	•	•	•	•	•
Disc brakes	•	•	•	•	•	•
Clutch						
Heavy-duty electric MagStop blade clutch/brake	•	•	•	•	•	•
Temperature Sentry/high temperature clutch cut-out	•	•	•	•	•	•
POWER UNIT TIRE SIZES						
Drive Wheels (4-ply rated): 23x10.50x12 turf	•			•		
Drive Wheels (4-ply rated): 24x12.00x12 turf		•	•	•	•	•
Drive Wheels (4-ply rated): 24x12.00x12 bar tread		○	○		○	○
Front Casters: 13x6.50x6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap.	•	•	•	•	•	•
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS						
Mulch & 4XR Width*/Length: 53.5 in. (135.9 cm) / 82.5 in. (209.6 cm)	•			•		
Mulch & 4XR Width*/Length: 62.5 in. (158.8 cm) / 84.0 in. (213.4 cm)		•	•	•	•	
Mulch & 4XR Width*/Length: 73.5 in. (186.7 cm) / 87.5 in. (222.3 cm)			•	•	•	•
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.						
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)	•	•	•	•	•	•
Height (ROPS): 69.5 in. (176.5 cm)	•	•	•	•	•	•
Height (ROPS): 70.0 in. (177.8 cm)				•		
WEIGHT						
Uncrated** : 1310 lbs. (594.2 kg)	•			•		
Uncrated** : 1360 lbs. (616.9 kg)		•	•	•	•	
Uncrated** : 1450 lbs. (657.7 kg)			•	•	•	•
**Mulching package kit weights with high-low mulching blades. 52-in. – 29 lbs. (13.2 kg); 61-in. – 36 lbs. (16.3 kg); 72-in. – 44 lbs. (20.0 kg)						

• Standard ○ Option

For a complete list of trademarks/registered trademarks, visit grasshoppermower.com/legal.
Litho in U.S.A. 1219-170???



The Grasshopper Company • 105 Old U.S. Highway 81
P.O. Box 637 • Moundridge, KS • 67107 U.S.A.
T: 620-345-8621 • grasshoppermower.com

