

200 SERIES AIR-COOLED MIDMOUNT™

Reliable economy
in a compact
package



ComfortReach™
with "no tools"
2-in. adjustment range

225

48

52

61

747cc, 2-cylinder
Kohler Command
Pro OHV
gasoline engine

● Standard deck ■ DuraMax® deck

Reliable economy delivers a quality cut and powerful, air-cooled performance in a compact package ideal for tight-quarters mowing. Enjoy the maneuverability of a walk-behind without the fatigue, to mow longer and deliver quality results. The horizontal crankshaft configuration adds performance life to the engine.

Design-matched G² hydrostatic transmissions with CoolFan™ hydrostatic pump cooling system and 7 micron absolute filter partnered with wheel motors create a fully hydraulic system for smooth, responsive steering and less maintenance with 1,000-hour fluid change intervals.

Only five Access-Eze™ lubrication points cut maintenance time up to 80%.

5.5-inch deep DuraMax® decks with anvil-edged design for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

Deep-cushioned Premium Comfort Seat featuring CoolTemp Cordura® and coil-spring suspension provides all-day comfort. Electronic fuel gauge/hour meter on the console is standard.

A compact wheelbase provides a great power-to-size ratio for easy transport on trailers and through tighter spaces.

ComfortReach™ provides 2 inches of adjustment at the base of the lever for a custom steering fit. No tools required.

The 12.0 gal/45.4 L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

Optional four-spindle dedicated rear-discharge decks evenly distribute clippings out back for a smooth cut and no windrowing to provide the quality cut you expect.

Mowing speeds up to 9.5 MPH
and 5.27 acres/hr. based on
61" cutting width*
For more details visit:
grasshoppermower.com/acres



OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » Down Discharge™ mulching packages
- » Dedicated 4X Rear Discharge™ deck
- » Speed-Trimming™ heavy-duty roller (61")
- » TrimAide™ Roller (52")
- » Electric height adjustment
- » DuraGuard™ rear bumper (2 bars)
- » DuraFlex™ suspension forks
- » LED work lights
- » Extended steering levers
- » QuikAjust Tilt™ steering levers with "no tools" 9-inch comfort range
- » Big Boy wide-seat conversion kit
- » Premier suspension seat
- » Adjustable cup holder
- » Foldable ROPS with seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24x12x12 Airless Turf Tires (61")
- » Michelin® X® Tweel® 13x6.5x6 Airless Front Casters
- » Edge-EZE™ edger
- » Shielded sprayer
- » Sunshade Canopy (for ROPS)
- » Yellow beacon light
- » Filter minder
- » Side discharge control kit
- » Air Dam kit

Be more productive with the addition of a PowerVac™ Collection System or other implements. Ask for specifications or visit grasshoppermower.com/implements. Models may be shown with optional equipment. *Actual results may vary.

AIR-COOLED 200 SERIES - SPECIFICATIONS

MODEL - CUTTING WIDTH	225 48"	225 52"	225 61"
ENGINE			
Type/Displacement/Cylinders			
Kohler Command Pro / 45.6 cu. in. (747cc) / V-Twin	•	•	•
Crankshaft/Cooling System			
Horizontal / Air	•	•	•
Fuel/Capacity			
Gasoline - unleaded / 12 U.S. Gal. (45.4 l)	•	•	•
Air Cleaner			
Heavy-duty, remote-mounted engine air cleaner with replaceable element	•	•	•
DECKS			
Construction (Robotic-welded steel)			
Double-layered, 10-gauge plus 7-gauge formed-steel laminate spindle plane 0.313 in. (7.95 mm) thick - more than 25% thicker than 0.25 in. (6.35 mm) - with 7-gauge skirts for geometric strength. Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.	•	•	•
DuraMax® deck		•	•
Blades (MARBAIN®, 1/4-in.)			
(2) 18 in. (45.7 cm), (1) 15 in. (38.1 cm) - high-lift blades standard	•		
(3) 18 in. (45.7 cm) - high-lift blades standard		•	
(3) 21 in. (53.3 cm) - high-lift blades standard			•
Sentry™ Spindle Assemblies			
Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Double bearings, greasable from top of deck. Spindle head designed to eliminate fiber wrap. Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.	•	•	•
Spindle Housing - 8-in. (20.3 cm)-diameter with 6-bolt pattern			
Machined aluminum	•	•	•
QuikAjust™ DropPin™ Height Adjustment			
Foot-controlled height adjustment pedal with pin	•	•	•
Cutting Height Range			
1.0 - 5.0 in. (2.5 - 12.7 cm)	•	•	•
Blade Drive			
Belt drive with single Kevlar® V-belt and idler arm tensioning	•	•	•
STARTER & ELECTRICAL SYSTEM			
Maintenance-Free Battery/Charging Capacity/Starter			
12 volt/15 amp/solenoid shift	•	•	•
Ignition			
Breakerless			
Interlock System			
Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.	•	•	•
ULTIMATE OPERATOR STATION™			
Premium Comfort Seat			
Iso-mounted, high-back, deep-cushioned, foam-padded, Cordura®-covered, padded arms/backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back.	•	•	•
Premier Suspension Seat	○	○	○
Operator Protection			
ROPS with seat belt	•	•	•
Suspension			
InFrame™ suspension with iso-mounted seat and footrest	•	•	•
Console-Mounted Instruments			
Low engine oil pressure light, combination electronic fuel gauge/hour meter, parking brake indicator light, ignition switch and push/pull PTO switch. Choke integrated with throttle lever.	•	•	•
Work Lights (Pre-wired)			
LED	○	○	○

MODEL - CUTTING WIDTH	225 48"	225 52"	225 61"
TRANSMISSION & STEERING			
Type			
Design-matched G ² hydrostatic system with auxiliary cooling fans, HydroGear variable displacement 12cc piston-type pumps and high-torque Parker wheel motors.	•	•	•
Filtration/Hydro Fluid			
7 micron absolute, spin-on / Grasshopper CoolTemp Hydra-Max™ fluid withstands high and low temperature extremes for 1,000-hour change intervals.	•	•	•
Speed			
0 - 8.5 mph (0 - 13.7 kph) forward	•		
0 - 9.0 mph (0 - 14.5 kph) forward		•	
0 - 9.5 mph (0 - 15.3 kph) forward			•
0 - 6.0 mph (0 - 9.7 kph) reverse	•	•	•
Turning Radius			
True zero degree, turns within own length with counter-rotating, independently powered drive wheels.	•	•	•
Steering			
One- or two-handed operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.	•	•	•
Brakes			
Dynamic braking through hydrostatic transmission. Disc parking brakes, one for each drive wheel.	•	•	•
Disc brakes	•	•	•
Clutch			
Heavy-duty electric MagStop blade clutch/brake	•	•	•
POWER UNIT TIRE SIZES			
Drive Wheels (4-ply rated): 23x9.50x12 turf	•		
Drive Wheels (4-ply rated): 23x10.50x12 turf		•	
Drive Wheels (4-ply rated): 24x12.00x12 turf			•
Drive Wheels (4-ply rated): 24x12.00x12 bar tread			○
Front Casters: 13x6.50x6; rib tread, pneumatic with greasable, double-sealed bearings to protect from grass wrap	•	•	•
POWER UNIT DIMENSIONS WITH DURAMAX® DECKS			
Mulch and 4XRD Width*/Length: 49.5 in. (125.7 cm) / 76.5 in. (194.3 cm)	•		
Mulch and 4XRD Width*/Length: 53.5 in. (135.9 cm) / 76.5 in. (194.3 cm)		•	
Mulch and 4XRD Width*/Length: 62.5 in. (158.8 cm) / 78.0 in. (198.1 cm)			•
*Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector down.			
Height (seat back/seat cushion): 46.5 in. (118.1 cm) / 31.0 in. (78.7 cm)	•	•	
Height (seat back/seat cushion): 47.0 in. (119.4 cm) / 31.5 in. (80.0 cm)			•
Height (ROPS): 70.0 in. (177.8 cm)	•	•	•
WEIGHT			
Uncrated***: 1050 lbs. (476.3 kg)	•		
Uncrated***: 1070 lbs. (485.4 kg)		•	
Uncrated***: 1120 lbs. (508.0 kg)			•
**Mulching package kit weights with high-low mulching blades: 48-in. - 25 lbs. (11.3 kg); 52-in. - 29 lbs. (13.2 kg); 61-in. - 36 lbs. (16.3 kg).			

• Standard ○ Option

For a complete list of trademarks/registered trademarks, visit grasshoppermower.com/legal.
Litho in U.S.A. 0420-170???



Featured Model 225 with 52-inch DuraMax® deck



The Grasshopper Company • 105 Old U.S. Highway 81
P.O. Box 637 • Moundridge, KS • 67107 U.S.A.
T: 620-345-8621 • grasshoppermower.com

