

MADE FOR **MORE** TO KEEP PACE WITH **YOU**

600HD

**MINI
SKID STEER**

Powered by a 24.8-HP (18.5-kW) diesel engine and producing 11.3 gpm (43 l/min) of auxiliary hydraulic flow from the single remote auxiliary lines, the **Boxer 600HD** provides all the power needed for tough jobs. The 600HD features a 74" (188 cm) hinge pin height and a 531 lb (241 kg) rated operating capacity, with a tip capacity of 1,535 lb (695 kg) and fixed track width of 34.7" (88 cm). The 600HD boasts a variety of new features, including a redesigned platform with added creature comforts, hydrostatic drive, piloted joystick controls, rubber-isolated hydraulic components, tightened boom tolerances and a whole lot more!

FEATURES AND BENEFITS

- 24.8-HP (18.5 kW) Kubota D902 Diesel Engine
- Stand-on platform with generous hip padding and added creature comforts for operator safety and comfort
- Dual hydrostatic operating system
- Piloted joystick controls with rocker-activated auxiliaries
- 2-button pressure relief block
- 2.5" (64 mm) bore-welded tilt cylinder and two 2" (50 mm) bore-welded lift cylinders
- 0.25" (6 mm) thick laser-cut base sides and 0.75" (19 mm) thick boom arms
- 7" (180 mm) low-impact tracks
- Front and rear tie-down points
- Tri-lobe mid-wheels
- Serviceable front idlers
- Well-balanced and stable, with excellent ground speed
- Universal compact utility loader mounting plate and quick-attach system to quickly and easily switch between any standard attachment



SPECIFICATION	US	METRIC
Engine Type		Kubota
Cooling System		Liquid
HP/kW	24.8 HP	18.5 kW
Fuel Type		Diesel
Fuel Capacity	4.5 Gallons	17.1 Litres
Hydraulic Capacity	16 Gallons	60.6 Litres
System Flow (Total)	22 GPM	83 L/min
Hydraulic Flow Aux (Hi)	11.3 GPM	43 L/min
Hydraulic Flow (Drive)	10.7 GPM	41 L/min
System Pressure	3000 PSI	20684 kPa
Engine Warranty	2 years, 2000 Hours	
Product Warranty	1 year, 1000 Hours	
Track Gauge	27"	686 mm
Track Width	7"	180 mm
Weight (No Attachment)	2240 lb	1015 kg
Length (No Attachment)	73.4"	1864 mm
Length (w/Bucket)	96"	2438 mm
Width (Overall)	34.7"	881 mm
Height (Boom Lowered)	52.7"	1339 mm
Height (Boom Raised)	98"	2489 mm
Hinge Pin Height	74"	1880 mm
Dump Height	56"	1422 mm
Dump Angle	37 Degrees	
Reach	34"	864 mm
Tip Capacity	1535 lb	695 kg
Operating Capacity, 35% of tip load	531 lb	241 kg
Ground Clearance	5"	127 mm
Ground Speed	4.3/3.1 MPH	7.0/5.0 km/h
Ground Pressure	5.36 PSI	37 kPa

Updated 11/27/19