

Model		M95GX-IV	M105GX-IV	M115GX-IV	M125GX-IV	M135GX-IV
Motor						
Tip		V3800-CR-TIEF4		V6108-CR-TIEF4		
Cilindree / Nr. cilindri	cm ³	3769/4		6124/4		
Alimentare		Turbo si intercooler				
Viteza de rotatie	rpm	2400		2200		
Putere (97/68/EC)	CP (Kw)	104 (77)	111 (81)	123 (90)	133 (98)	143 (105)
Cuplu maxim	Nm	346	379	503	544	566
RPM cuplu maxim	rpm	1500				
Rezervor combustibil/Adblue [®]	l	190/16				
Transmisie						
Tip		Powershift				
Numar viteze	fata/spate	24/24				
Numar viteze cu creeper	fata/spate	32/32				
Viteza maxima	km/h	40				
Trepte		8 Powershift				
Game		3 sincronizate cu ambreiaj la buton				
Inversor		Inversor electrohidraulic in sarcina				
Ambreiaj		Umed multidisc electrohidraulic				
Frane		Umede, hidraulice, cu angajare 4x4 automata (4WD)				
4WD		Electrohidraulic; ON/OFF/Auto				
Blocare diferential (fata/spate)		Electrohidraulica				
PTO						
Viteza spate	rpm	540/1000; 540/540 Eco (optional)				
Viteza spate	rpm	1000 (optional)				
Sistem hidraulic						
Debit	l/min	76,3		82,5		
Sistem de prindere in 3 puncte		Cuplare rapida, Cat III, stabilizatori telescopici				
Sistem de control		Pozitie, forta				
Capacitate ridicare	kg	5000		6100		
Numar valve auxiliare		2 standard (3, 4 optional)				
Tip valve auxiliare		1 DE FD (cu pozitie flotanta) + 1 DE SCD (flow control) cu debit reglabil				
Dimensiuni cauciucuri standard						
Fata		380/70 R 24		420/70 R 24		
Spate		520/70 R 34		520/70 R 38		
Dimensiuni si greutate						
Lungime totala	mm	4315		4475		
Inaltime totala	mm	2830		2880		
Latime totala (min. ' max.)	mm	2270 ' 2420		2330 ' 2375		
Ampatament	mm	2440/2540 (F-SUS)		2685/2,680 (F-SUS)		
Ecartament	fata	mm		1630; 1675		
	spate	mm		1755; 1805; 1905		
Raza viraj (fara frane)	mm	4,1		4,5		
Greutate	kg	4300/4560 (F-SUS)		4845/5065 (F-SUS)		