



SUPER Z

— AND —

HYPERDRIVE



SUPER Z

AVAILABLE DECK SIZES

54"- 72" 60"- 72" RD



HYPERDRIVE

AVAILABLE DECK SIZES

60"- 72" 60"- 72" RD

SUPER Z

VX4 Deck

Fabricated 7 ga. steel deck engineered to move more grass at high speed while maintaining cut-quality.

Foot Operated Deck Lift

Easily adjust the deck height between 1" - 5.5" with your foot.

Easy to Service

Flip-up seat pan, removable floor pan, vented pulley covers.

SmoothTrak™ Steering

Precision control to help trim and maneuver easily around obstacles. Other brands have sensitive steering arms causing sudden and jerky movements.

Commercial-grade Torque

Hydro-Gear 21cc PY pumps and Parker TG wheel motors.

I3M Suspension Seat

High-back seat with adjustable armrests and 3-inch travel range.

Kawasaki® FX & Vanguard Big Block™ Engines

LIMITED
WARRANTY

5 YEAR | **1200**
HOUR

FIRST 2 YEARS NO HOUR LIMIT



UPGRADES FOUND ON THE HYPERDRIVE

HYPERDRIVE

- ✓ HyperDrive® Hydro System
- ✓ Optional Vanguard® Big Block™ Engine w/ Oil Guard (500 hour oil change)
- ✓ Danfoss DDC-20 Pumps
- ✓ Larger 26" Drive Tire
- ✓ Up to 16 mph (compared to 14 mph)



ACCESSORIES

- ▶ Steering extension kit
- ▶ Electric deck lift
- ▶ Rear hitch kit
- ▶ Anti-scalp deck rear wheels
- ▶ BacVac bagger
- ▶ Semi pneumatic front tire
- ▶ 3-bag powered bagger (12 bushels)
- ▶ Flex Forks®
- ▶ Mulch kit
- ▶ Light kit
- ▶ Sand kit
- ▶ Stripe kit
- ▶ Beacon kit
- ▶ Flasher kit
- ▶ Michelin® X® Tweel® Turf

HYPERDRIVE SYSTEM


Increase the life and performance of your mower with Hustler's exclusive HyperDrive system, the largest, most durable drive system in the industry. With temperature regulation and heavy-duty components, HyperDrive will keep you operating at peak performance.



9" Fan & High-Capacity Oil Cooler with Hot Oil Shuttle



Large Oil Reservoir




Heavy-Duty Parker TG280 Wheel Motors



Industrial-Grade Slipper Piston Pumps

**INDUSTRY'S
BEST WARRANTY**



SUPER Z					HYPERDRIVE				
ENGINE									
Manufacturer	Vanguard Big Block™, Kawasaki FX series					Vanguard Big Block™, Kawasaki FX series			
HP	54", 60", 60" RD, 72" RD deck: 27HP - FX850 60", 66" & 72" deck: 35HP - FX1000 60" & 72" deck: 38.5HP - FX1000 EFI 60", 72" deck: 36HP - Big Block™ (Per SAE J1995)					60", 66", 72" deck: 40HP - Big Block™ EFI 60", 60"RD, 72" & 72" RD deck: 35HP - FX1000 60" & 72" deck: 40HP - Big Block™ EFI w/ Oil Guard 60" & 72" deck: 38.5HP - FX1000 EFI (Per SAE J1995)			
Displacement	FX850: 852cc	FX1000: 999cc	FX1000 EFI: 999cc	Vanguard: 993cc	Vanguard: 993cc Kawasaki: 999cc				
Cooling	Air cooled								
Air Cleaner	Heavy Duty Canister								
Engine Warranty	Kawasaki: 3 year Vanguard: 5 year					Kawasaki: 3 year Vanguard: 5 year			
DRIVE SYSTEM									
Type	Dual hydrostatic								
Pumps	Hydro-Gear 21cc PY					Danfoss DDC-20			
Wheel Motors	Parker TG					Parker TG			
Hydraulic Lines	Stainless Parker Seal-Loc Technology								
Reservoir Capacity	3 gallons								
Speed	Up to 14 mph					Up to 16 mph			
Parking Brakes	Integrated with steering levers								
DECKS									
Cutting Width	Side discharge: 54", 60", 66", 72" Rear-discharge: 60", 72"					Side discharge: 60", 66", 72" Rear-discharge: 60", 72"			
Cutting Heights	1" - 5.5"								
Deck Lift	Foot operated								
Depth	5.5"								
Blades	3								
Blade Length	54" deck: 18.50" 60" deck: 20.50" 66" deck: 22.50" 72" deck: 24.50"					60" deck: 20.50" 66" deck: 22.50" 72" deck: 24.50"			
Blade Tip Speed	54"& 60": 18,600	66": 18,200	72": 18,500			60": 18,600	66": 18,200	72": 18,500	72"RD: 18,500
Spindles	Ductile cast iron with steel shaft and sealed ball bearings								
Drive	Electric PTO clutch								
Construction	Fabricated 7 ga.								
Spindle Mounts	Reinforced 7 ga. stamped disc								
Impact/Trim Areas	Front of deck: 11 ga. formed bump bar Side of deck: 1.5" x .375" steel bar								
CONSTRUCTION									
Frame	1.5" x 3" steel tubing								
Front Axle	Fabricated with tapered roller bearings								
Front Caster Wheels	Tapered wheel bearings and debris cap								
Front Caster Forks	Fabricated 1/2" steel								
GENERAL									
Seat	I3M suspension seat								
Fuel Capacity	11.7 gallons								
Cupholder	Yes								
Front Tire	13 x 6.5 - 6								
Drive Tire	54": 24 x 9.5 - 12	60", 66", 72": 24 x 12 - 12				26 x 12 - 12			
DIMENSIONS									
Weight	54": 1420 lbs 66": 1516 lbs	60": 1451 lbs 72": 1526 lbs	60" RD: 1566 lbs 72"RD: 1626 lbs			60": 1536 lbs 66": 1551 lbs	60"RD: 1606 lbs 72": 1596 lbs	72"RD: 1676 lbs	
Height	46.8" 72.5 w/ ROPs					47.8" 73.5 w/ ROPs			
Length	54", 60": 89"	60"RD, 66": 91.5"	72", 72"RD: 93"			60": 89"	60"RD, 66": 91.5"	72", 72"RD: 93"	
Width w/Chute Up	54": 60"	60": 66"	66"&72": 72"	72": 78"	72"RD: 73.23"	60": 66" 66"&72": 72" 72"RD: 78"			
Tire Width	54": 53"	60", 60"RD: 57"	66", 72"RD, 72": 60"			60", 60"RD: 57"	66", 72"RD, 72": 60"		
Trim Side	54": 2.4"	60": 3.4"	60"RD: 3.1"	66": 4.9"	72": 8.9"	60": 3.4"	60"RD: 3.1"	66": 4.9"	72": 8.9"
PRODUCTIVITY*									
Acres Per Hour	54": 6.11	60": 6.78	66": 7.46	72": 8.14	60": 7.76 66": 8.54 72": 9.31				

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

** Specifications are subject to change without notice.