

# 200V-G4 SERIES | AIR-COOLED MIDMOUNT™

Take performance  
to the next level.



LIMITED WARRANTY

**2 YEAR**

800 HRS

COMMERCIAL

**4 YEAR**

800 HRS

RESIDENTIAL

**225V-G4**

52 61

747 cc, V-twin, OHV  
Kohler Confidant  
gasoline engine

**226V-G4**

52 61

810 cc, V-twin, OHV  
B&S Vanguard  
gasoline engine

**200V-G4:** Increase your productivity  
with speeds up to 9.0 mph and 5.00 acres  
per hour with a 61-inch cutting deck.\*



Enjoy comfort, performance and durability with a compact 200V-G4 Series mower. An ergonomic design and integrated, multi-point suspension, coupled with the industry's most comfortable seat, provides all-day comfort. You'll stay comfortably in control of every mowing maneuver — even at faster mowing speeds.

G4 Hydro-Gear ZT-4400 transmissions feature self-contained, heavy-duty commercial transaxles that provide powerful, smooth response, while integrated cooling fans and 1-3/8-inch axles extend service life. Enjoy best-in-class transmission fluid change intervals after a 100-hour break-in period, reducing costs and maintenance time.

Only two Access-Eze™ lubrication points cut maintenance time up to 95%.

5.5-inch deep decks designed for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple.

The deep-cushioned, deluxe Ultimate Suspension Ride™ (USR™) seat features a coil-spring suspension and padded lumbar support with sliding 2-inch fore and aft adjustment for all-day comfort. Iso-mounting eliminates vibration before it reaches the seat, and both padded seat and foldable armrests are covered in scuff-resistant, breathable CoolTemp Cordura® fabric, which dissipates heat and won't tear or crack with extended use. QuikAjust Tilt™ dual levers with 9-inch adjustment and the adjustable seat work together to provide a custom fit for operators of all sizes.

A compact wheelbase provides a great power-to-size ratio for easy transport on trailers and through tighter spaces.

The 6.5 gal/24.6L single-fill fuel tank lowers the center of gravity, providing more traction and stability for an enhanced ride. The standard bumper protects the rear of the mower while preserving easy access to the service shield.

## OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » 4X Rear Discharge™ decks
- » Down Discharge™ mulching packages
- » Side discharge control kit
- » Foot pedal extension kit for QuikAjust™ DropPin™ height adjustment
- » TrimAide™ roller kit (52-inch decks only)
- » Speed-Trimming™ heavy-duty roller kit (61-inch decks)
- » Air Dam kit
- » LED work lights — plug-in ready
- » Yellow beacon light
- » Sunshade Canopy — vinyl or aluminum
- » Custom Cordura® weather cover
- » GrassMax™ blade options
- » Heavy-duty, grass-grooming striping kit
- » Wide seat conversion kit
- » QuikAjust Tilt™ "Tall Boy" Lever Kit
- » Foldable ROPS with adjustable seat belt
- » DuraFlex™ suspension forks
- » Edge-EZE™ edger



# Air-Cooled 200V-G4 Series MidMount™ Specifications

MODEL - CUTTING WIDTH	225V-G4 52	225V-G4 61	226V-G4 52	226V-G4 61
-----------------------	---------------	---------------	---------------	---------------

## ENGINE

### Type/Displacement/Cylinders

Kohler Confidant gasoline/45.6 cu. in. (747 cc)/V-twin

B&S Vanguard – gasoline/49.4 cu. in. (810cc)/v-twin

### Lubrication System

Pressure Lube, Filter

### Crankshaft

Vertical

### Cooling System

Air

### Fuel / Capacity

Gasoline - unleaded / 6.5 U.S. Gal (24.6 L)

### Air Cleaner

Heavy-duty cyclonic air filter with QuadClean™ multi-stage air filtration

Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management

### Muffler

Ultra-quiet, single, industrial type

## MOWING DECKS

### Construction (Robotic-welded steel)

Double-layered 10-gauge plus 7-gauge formed steel laminate spindle plane 0.313 in. (7.95 mm) thick – more than 25% thicker than 0.25 in. (6.35 mm) – with 7-gauge skirts for geometric strength.

Spindle plane is 0.9 in. (22.86 mm) thick in stress zones. Anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck.

### Blades (ADI MARBAIN®, 1/4-in.)

(3) 18 in. (45.7 cm)

(3) 21 in. (53.3 cm)

### Spindle Assemblies

Sentry™ Spindle System, 2.5 cm (approx. 1 in.) O.D. shaft. Spindle head designed to eliminate fiber wrap. Double bearings, non-greasable.

### Spindle Housing

8-in. (20.3 cm)-diameter machined aluminum housing with 6-bolt pattern.

### Spindle Cones

Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion.

### QuikAjust™ DropPin™ Height Adjustment

Foot-controlled height adjustment pedal with pin

### Cutting Height Range

1.0 – 5.0 in. (2.5 – 12.7 cm) in 1/4-inch increments

### Blade Drive

Belt drive with single Kevlar V-belt & idler arm tensioning

## STARTER & ELECTRICAL SYSTEM

### Maintenance-Free Battery/Charging Capacity/Starter

12 Volt/15 amp/solenoid shift

12 Volt/16 amp/solenoid shift

### Ignition

Breakerless

### Interlock System

Prevents engine start when PTO clutch is engaged or steering levers are in drive position. Allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral.

## ULTIMATE OPERATOR STATION™

### USR™ Seat

Ultimate Suspension Ride™

### Suspension

Roomy, iso-mounted footrest with Shock Impact Reduction System™ (SIRS™).

### Console-Mounted Instruments

Low engine oil pressure, digital hour meter, parking brake indicator light, ignition switch, choke and push/pull PTO switch.

### Work Lights (Pre-wired)

LED (optional)

MODEL - CUTTING WIDTH	225V-G4 52	225V-G4 61	226V-G4 52	226V-G4 61
-----------------------	---------------	---------------	---------------	---------------

## TRANSMISSION & STEERING

### Type

Heavy-duty Hydro-Gear ZT-4400 hydrostatic transmissions with cooling fans. Integrated transaxles with 12cc piston pumps and 16cc piston motors, gear reduction, internal disc brakes, and 1-3/8 inch axles.

### Filtration/Hydro Fluid

Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals after 100-hour break in oil change.

### Speed

0 – 9.0 mph (0 – 14.5 kph) forward

0 – 6.0 mph (0 – 9.7 kph) reverse

### Turning Radius

True zero degree, turns within own length with counter-rotating, independently powered drive wheels.

### Steering

One- or two-hand operation with adjustable Hydra-Smooth™ dual levers that automatically return to neutral from either forward or reverse position.

### Brakes

Dynamic braking through hydrostatic transmission

### Parking Brake

Internal disc brake in transmission.

## TIRE SIZES

### Drive Wheels – Standard (5-bolt pattern)

23x10.50x12 turf type, 4-ply rated

### Front Casters

13x6.5x6 rib tread, pneumatic with double-sealed bearings

## DIMENSIONS (Mower & Deck)

**Mulch Width/Length** (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.)

53.5 in. (135.9 cm)/76.0 in. (193.0 cm)

62.5 in. (158.8 cm)/79.0 in. (200.7 cm)

### Height (Seat back)

46.0 in. (116.8 cm)

### Height (Seat cushion)

30.0 in. (76.2 cm)

### Height (ROPS)

68.0 in. (172.7 cm)

### Drive Tire Track Width (outside edge to outside edge)

50.0 in. (127.0 cm)

## WEIGHT

### Uncrated (Mower & Deck)

960 lbs. (435.4 kg)

980 lbs. (444.5 kg)

1030 lbs. (467.2 kg)

1050 lbs. (476.3 kg)

### Mulching Package (Package includes high-low mulching blades.)

29 lbs. (13.2 kg)

36 lbs. (16.3 kg)

● Standard ○ Option

For a complete list of trademarks/registered trademarks, visit [grasshoppermower.com/legal](http://grasshoppermower.com/legal).

Litho in U.S.A. Form 0618-170866 © 2018 The Grasshopper Company



The Grasshopper Company • 105 Old U.S. Highway 81  
P.O. Box 637 • Moundridge, KS • 67107 U.S.A.  
T: 620-345-8621 • [grasshoppermower.com](http://grasshoppermower.com)

