

MORBARK® BEEVER™ M20R FORESTRY TRACK

FEATURES

- » Infeed system consisting of one 20" (50.8 cm) diameter top compression feed roll, with a 26" (66.04 cm) wide x 9' (2.74 m) long live floor equipped with two strands of WDH-110 chain
- » Straight discharge chute includes hydraulically operated chip deflect with vertical and horizontal adjustment
- » 36" (91.44 cm) diameter x 33.375" (84.77 cm) wide drum with front pocket and six Babbitt-style knives with removable knife holders
- » Discharge clean out door on bottom
- » Steel guard enclosing valve bank and automatic feed system components
- » Spanish and English safety decals
- » 312B Caterpillar undercarriage with 20" (500 mm) grouser pads

Other Specifications

- » Drum diameter: 36" (91.44 cm)
- » Drum width: 33.375" (84.77 cm)
- » Infeed Opening: 65" wide x 43" high (165 cm x 109.22 cm)
- » Throat Opening: 28" wide x 20" high (71.12 cm x 50.8 cm)
- » Frame: 2" x 10" tubular (5.08 cm x 25.4 cm)

OPTIONS


- » Forestry, rotating or top load discharge
- » Forestry Grate System



A 6' (1.83 m) infeed bed with live WDH-110 chain drive

Advantage 3™ Drum creates more uniform chips

Remote Control



SPECIFICATIONS

	US	METRIC
Chipping Capacity	20"	50.8 cm
Length	22'9"	6.93 m
Height	11'5"	3.48 m
Width	8'6"	2.59 m
Gross Weight	26,540 lb	12,040 kg
Engine	CAT	
Horsepower	350 to 415 HP	260 to 309 kW
Fuel Capacity (tank)	74 gallons	280 litres
Hydraulic Oil	56 gallons	212 litres
Tracks	312B Caterpillar undercarriage	



MORBARK®

www.morbark.com

800.831.0042

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

11/20/18