

Java DevOps

on a Budget

Christopher M. Judd



Christopher M. Judd

CTO and Partner at







Central Ohio Java Users Group leader

Columbus



Developer User Group (CIDUG)






NO
PROBLEM



I HOPE HE WILL
NOT ASK ME HOW
TO SET THE LOG
LEVEL



GEEKS



<http://www.youtube.com/watch?v=pVKnF26qFFM>

App Server

Application


App Server

JVM

OS

Hypervisor

Hardware



App Server

Application


App Server

JVM

OS

Hypervisor

Hardware



Web Server

Web Server

OS

Hypervisor

Hardware

App Server

Application

App Server

JVM

OS

Hypervisor

Hardware

Database Server

Database Server


OS

Hypervisor

Hardware


DevOps

an emerging set of principles, methods and practices for communication, collaboration and integration between [software development](#) (application/software engineering) and [IT operations](#) (systems administration/infrastructure) professionals. It has developed in response to the emerging understanding of the interdependence and importance of both the development and operations disciplines in meeting an organization's goal of rapidly producing [software](#) products and services.





Java Web Apps



- Infrastructure
- Monitoring
- Triage

INFRASTRUCTURE

automate



A portrait photograph of Neal Ford, a middle-aged man with dark hair and glasses, wearing a light-colored shirt. He is looking directly at the camera with a slight smile.

"If you keep repeating the same thing over and over you get dumber. If you learn how to automate it you get smarter."

- Neal Ford



<http://www.puppetlabs.com/>




<http://www.opscode.com/>

A photograph of a herd of cattle in a green pasture. A wire fence runs across the foreground. Several cows are visible behind the fence, looking towards the camera. One cow in the center-left has a white patch on its forehead. Another cow to its right has a yellow ear tag with the number "126". In the background, more cattle are grazing in the distance.

treat infrastructure like
cattle not like pets

```
class tomcat {  
  
    $tomcat_port = 735  
    $tomcat_password = 'badwolf'  
  
    notice("Establishing http://$hostname:$tomcat_port/")  
  
    Package { # defaults  
        ensure => installed,  
    }  
  
    package { 'tomcat6':  
    }  
  
    package { 'tomcat6-user':  
        require => Package['tomcat6'],  
    }  
  
    package { 'tomcat6-admin':  
        require => Package['tomcat6'],  
    }  
  
    file { "/etc/tomcat6/tomcat-users.xml":  
        owner => 'root',  
        require => Package['tomcat6'],  
        notify => Service['tomcat6'],  
        content => template('tomcat/tomcat-users.xml.erb')  
    }  
  
    file { '/etc/tomcat6/server.xml':  
        owner => 'root',  
        require => Package['tomcat6'],  
        notify => Service['tomcat6'],  
        content => template('tomcat/server.xml.erb'),  
    }  
  
    service { 'tomcat6':  
        ensure => running,  
        require => Package['tomcat6'],  
    }  
}
```

Infrastructure is code



git



MONITORING

HYPERIC


<http://www.hyperic.com/>

The logo for openNMS features the word "open" in a lowercase, italicized, black font, followed by "NMS" in a bold, black, sans-serif font. A green swoosh graphic starts from the top of the "o" in "open" and curves upwards and to the right, ending under the "S". A registered trademark symbol (®) is positioned at the top right of the "S".

<http://www.opennms.org/>

Nagios®

<http://www.nagios.org/>



Dashboard

The screenshot shows the Hyperic HQ dashboard interface. At the top, there's a header bar with the title "HQ Dashboard" and a URL "hyperic.guest:7080/Dashboard.do?org.apache.catalina.filters.CSRF_NONCE=F78EFE2575620C9503836A56327A06EF". Below the header is the "HYPERIC HQ" logo. The main content area is divided into several sections:

- Search Resources:** A search bar for "Resource Name" and a dropdown for "Platforms".
- Saved Charts:** A section stating "No charts to display".
- Recently Added:** A table showing a single entry: "appserv.guest" added "24 minutes ago".
- Availability Summary:** A table showing availability by resource type. It says "No resources to display, please click the gear icon above to add resources to portlet." Below it is a "Select Portlet" dropdown with a "+" button.
- Auto-Discovery:** A section stating "No resources to display".
- Favorite Resources:** A table listing "appserv.guest" as a Linux resource, updated at 11:45 AM.
- Recent Alerts:** A section stating "No recent alerts to display". It includes buttons for "FIXED" and "ACKNOWLEDGE".
- Control Actions:** A section titled "Recent Control Actions" and "Quick Control Frequency", both stating "No resources to display".
- Add content to this column:** A "Select Portlet" dropdown with a "+" button.

Auto-Discovery

Auto-Discovery			
Resource Name		Status	Changes
<input checked="" type="radio"/> appserv.guest - CentOS 6.3		new	N/A
<input checked="" type="checkbox"/> HQ Agent 4.6.6	/home/hyperic/agent-4.6.6	new	N/A
<input checked="" type="checkbox"/> Apache Tomcat 7.0	/opt/tomcat/apache-tomcat-7.0.33	new	N/A
<input type="radio"/> localhost.localdomain - CentOS 6.3		new	N/A
<input checked="" type="checkbox"/> HQ Agent 4.6.6	/home/hyperic/agent-4.6.6	new	N/A
Add to Inventory	Skip Checked Resources		

Auto-Discovery

Auto-Discovery			
Resource Name		Status	Changes
<input checked="" type="radio"/> appserv.guest - CentOS 6.3		new	N/A
<input checked="" type="checkbox"/> HQ Agent 4.6.6	/home/hyperic/agent-4.6.6	new	N/A
<input checked="" type="checkbox"/> Apache Tomcat 7.0	/opt/tomcat/apache-tomcat-7.0.33	new	N/A
<input type="radio"/> localhost.localdomain - CentOS 6.3		new	N/A
<input checked="" type="checkbox"/> HQ Agent 4.6.6	/home/hyperic/agent-4.6.6	new	N/A
Add to Inventory		Skip Checked Resources	

[Platforms \(1\)](#) | [Servers \(2\)](#) | [Services \(7\)](#) | [Compatible Groups/Clusters \(0\)](#) | [Mixed Groups \(0\)](#) | [Applications \(0\)](#)

[Show Chart View](#)

<input type="checkbox"/>	Platform	Platform Type	Description	Availability
<input checked="" type="checkbox"/> M I A	appserv.guest	Linux	CentOS 6.3	
GROUP	DELETE	ENABLE ALL ALERTS	DISABLE ALL ALERTS	
				Total: 1 Items Per Page: 15

[Platforms \(1\)](#) | [Servers \(2\)](#) | [Services \(7\)](#) | [Compatible Groups/Clusters \(0\)](#) | [Mixed Groups \(0\)](#) | [Applications \(0\)](#)

[Show Chart View](#)

<input type="checkbox"/>	Server	Server Type	Description	Availability
<input checked="" type="checkbox"/> M I A	appserv.guest Apache Tomcat 7.0	Apache Tomcat 7.0		
<input checked="" type="checkbox"/> M I A	appserv.guest HQ Agent 4.6.6	HQ Agent	Hyperic HQ monitor Agent	
GROUP	DELETE	ENABLE ALL ALERTS	DISABLE ALL ALERTS	
				Total: 2 Items Per Page: 15

[Platforms \(1\)](#) | [Servers \(2\)](#) | [Services \(7\)](#) | [Compatible Groups/Clusters \(0\)](#) | [Mixed Groups \(0\)](#) | [Applications \(0\)](#)

[Show Chart View](#)

<input type="checkbox"/>	Service	Service Type	Description	Availability
<input checked="" type="checkbox"/> M I A	appserv.guest Linux CPU 1 (2199Mhz Intel Core(TM) i7-2720QM CPU @ 2.20GHz)	CPU		
<input checked="" type="checkbox"/> M I A	appserv.guest Linux CPU 2 (2199Mhz Intel Core(TM) i7-2720QM CPU @ 2.20GHz)	CPU		
<input checked="" type="checkbox"/> M I A	appserv.guest Linux File System /dev/sda1 mounted on /boot (local/ext4)	FileServer Mount		
<input checked="" type="checkbox"/> M I A	appserv.guest Linux File System /dev/sda3 mounted on / (local/ext4)	FileServer Mount		
<input checked="" type="checkbox"/> M I A	appserv.guest Linux Network Interface eth1 (ethernet)	NetworkServer Interface		
<input checked="" type="checkbox"/> M I A	appserv.guest Linux Network Interface lo (loopback)	NetworkServer Interface		
<input checked="" type="checkbox"/> M I A	appserv.guest Linux sshd Process	Process		
GROUP	DELETE	ENABLE ALL ALERTS	DISABLE ALL ALERTS	
				Total: 7 Items Per Page: 15



Browse > appserv.guest

Description: CentOS 6.3
Architecture : x86_64
OS Version : 2.6.32-279.el6.x86_64
RAM : 2048 MB

Owner: HQ Administrator (hqadmin) - [Change...](#)
CPU Speed : 2 @ 2199 MHz
Vendor Version : 6.3

IP Address : 192.168.248.129
Vendor : CentOS

[Map](#) [Tools Menu](#)

[Monitor](#) [Inventory](#) [Alert](#) [Views](#)

Metric Display Range: [Last](#) **8** Hours [Advanced Settings](#)

RESOURCES

<input type="checkbox"/> Platform Services Health	Avail
<input type="checkbox"/> CPU	
<input type="checkbox"/> FileServer Mount	
<input type="checkbox"/> NetworkServer Interface	
<input type="checkbox"/> appserv.guest Linux sshd Process	
<input type="checkbox"/> Deployed Servers Health	Avail
<input type="checkbox"/> appserv.guest Apache Tomcat 7.0	
<input type="checkbox"/> appserv.guest HQ Agent 4.6.6	

Select Resources above &
click button to view metrics

[View Metrics](#)

All Metrics

Free Memory	
Free Memory (+ buffers/cache)	
Load Average 5 Minutes	
Swap Used	
Availability	

INDICATORS**METRIC DATA**

[Indicator Charts](#) | [Show Last 8 Hours](#)

View: [Update Default](#)

100.0% — Availability

Free Memory


(Linux)

LOW: 71.5 MB AVG: 124.7 MB PEAK: 245.6 MB

**Free Memory (+ buffers/cache)**

(Linux)

LOW: 1.2 GB AVG: 1.2 GB PEAK: 1.3 GB

**Load Average 5 Minutes**

(Linux)


LOW: 0.0 AVG: 0.4 PEAK: 6.8

**Swap Used**


11/25/2012 04:11 AM 11/25/2012 12:03 PM



Browse > appserv.guest



Participating Resources	
Metric Name	Resource
Free Memory	appserv.guest
REDRAW SELECTED ON CHART	




JMX

JMX


Java Management Extensions (JMX) is a [Java](#) technology that supplies tools for managing and monitoring [applications](#), system objects, devices (e. g. [printers](#)) and service oriented networks. Those resources are represented by objects called MBeans (for [Managed Bean](#)). In the API, [classes](#) can be dynamically loaded and instantiated. Managing and monitoring applications can be designed and developed using the [Java Dynamic Management Kit](#).



WIKIPEDIA
The Free Encyclopedia



Manager Level



Agent Level

MBeanServer

MBean
(JVM)

MBean
(app server)


MBean
(library)

MBean
(custom)

Instrumentation Level

Java Virtual Machine

jconsole



Visual VM



jvisualvm

<http://visualvm.java.net/>

visualvm

VisualVM MBeans plug-in

MBeans Browser


Attributes | Operations | Notifications | Metadata

Attribute values

Name	Value
acquireIncrement	5
acquireRetryAttempts	120
acquireRetryDelay	1000
allUsers	[cls]
autoCommitOnClose	false
automaticTestTable	
breakAfterAcquireFailure	false
checkoutTimeout	0
connectionCustomizerClassName	
connectionTesterClassName	com.mchange.v2.c3p0.impl.DefaultConnectionTester
dataSourceName	2w7t8nhhku71dloq5[2698dd08]
debugUnreturnedConnectionStackTraces	false
description	
driverClass	com.mysql.jdbc.Driver
effectivePropertyCycleDefaultUser	0.0
factoryClassLocation	
forceIgnoreUnresolvedTransactions	false
identityToken	2w7t8nhhku71dloq5[2698dd08]
idleConnectionTestPeriod	120
initialPoolSize	3
jdbcUrl	jdbc:mysql://scg-alb-rgtqy-db-master:3306/ds?autoReconnect=true&useUnicode=true&ch...
loginTimeout	0
maxAdministrativeTaskTime	0
maxConnectionAge	0
maxIdleTime	0
maxIdleTimeExcessConnections	0
maxPoolSize	300
maxStatements	0
maxStatementsPerConnection	0
minPoolSize	15
numBusyConnections	85
numBusyConnectionsAllUsers	85
numBusyConnectionsDefaultUser	85
numConnections	300
numConnectionsAllUsers	300
numConnectionsDefaultUser	300
numFailedCheckinsDefaultUser	0
numFailedCheckoutsDefaultUser	0
numFailedIdleTestsDefaultUser	0
numHelperThreads	33
numIdleConnections	215
numIdleConnectionsAllUsers	215
numIdleConnectionsDefaultUser	215
numThreadsAwaitingCheckoutDefaultUser	0
numUnclosedOrphanedConnections	0
numUnclosedOrphanedConnectionsAllUsers	0
numUnclosedOrphanedConnectionsDefaultUser	0
numUserPools	1
overrideDefaultPassword	
overrideDefaultUser	
preferredTestQuery	select curdate()
propertyCycle	0

Refresh

Manager Level



RMI

Connector

HTTP

Connector

HTTP

Adaptor

SNMP

Adaptor

Agent Level

MBeanServer

MBean
(JVM)

MBean
(app server)

MBean
(library)

MBean
(custom)

Instrumentation Level

Java Virtual Machine

appserv.guest:6969 (pid 28434)

MBeans Browser

MBeans

- ▶ Catalina
- ▶ JMImplementation
- ▶ Users
- ▶ com.sun.management
- ▼ java.lang
 - ▶ ClassLoading
 - ▶ Compilation
 - ▶ GarbageCollector
 - ▶ **Memory** ←
 - ▶ MemoryManager
 - ▶ MemoryPool
 - ▶ OperatingSystem
 - ▶ Runtime
 - ▶ Threading
- ▶ java.nio
- ▶ java.util.logging

Attributes

Operations | Notifications | Metadata

Attribute values

Name

Value

< Tabular Navigation >

<< < Composite Navigation >> >

HeapMemoryUsage

Name	Value
committed	87293952
init	30700992
max	438108160
used	48526352

NonHeapMemoryUsage

ObjectName

ObjectPendingFinalizationCount

Verbose

javax.management.openmbean.CompositeDataSup...
java.lang:type=Memory
0
false

Refresh

appserv.guest:6969 (pid 28434)

MBeans Browser


MBeans

- ▶ Catalina
- ▶ JMIImplementation
- ▶ Users
- ▶ com.sun.management
- ▼ java.lang
 - ▶ ClassLoading
 - ▶ Compilation
 - ▶ GarbageCollector
 - Memory** ←
 - ▶ MemoryManager
 - ▶ MemoryPool
 - ▶ OperatingSystem
 - ▶ Runtime
 - ▶ Threading
- ▶ java.nio
- ▶ java.util.logging

Attributes Operations Notifications | Metadata

Operation invocation

void **gc** ()



Manager Level




RMI

Connector

HTTP

Connector



HTTP

Adaptor

SNMP

Adaptor



Agent Level


MBeanServer

MBean
(JVM)

MBean
(app server)

MBean
(library)

MBean
(custom)



Instrumentation Level

Java Virtual Machine

Tomcat (pid 32415) X

Overview | Monitor | Threads | Sampler | Profiler | MBeans | Visual GC

Tomcat (pid 32415)

MBeans Browser

MBeans

Name	Type
Catalina	org.apache.catalina:type=Manager
Cache	org.apache.catalina:type=Manager
Connector	org.apache.catalina:type=Manager
Deployer	org.apache.catalina:type=Manager
Engine	org.apache.catalina:type=Manager
GlobalRequestProcessor	org.apache.catalina:type=Manager
Host	org.apache.catalina:type=Manager
JspMonitor	org.apache.catalina:type=Manager
Loader	org.apache.catalina:type=Manager
MBeanFactory	org.apache.catalina:type=Manager
Manager	org.apache.catalina:type=Manager
/	org.apache.catalina:type=Manager
/webperf	org.apache.catalina:type=Manager
localhost	org.apache.catalina:type=Manager
Mapper	org.apache.catalina:type=Manager
NamingResources	org.apache.catalina:type=Manager
ProtocolHandler	org.apache.catalina:type=Manager
Realm	org.apache.catalina:type=Manager
RequestProcessor	org.apache.catalina:type=Manager
Resource	org.apache.catalina:type=Manager
Server	org.apache.catalina:type=Manager
ServerClassLoader	org.apache.catalina:type=Manager
Service	org.apache.catalina:type=Manager
Servlet	org.apache.catalina:type=Manager
StringCache	org.apache.catalina:type=Manager
ThreadPool	org.apache.catalina:type=Manager
Valve	org.apache.catalina:type=Manager
WebModule	org.apache.catalina:type=Manager
WebappClassLoader	org.apache.catalina:type=Manager
JMImplementation	org.apache.catalina:type=Manager
Users	org.apache.catalina:type=Manager
com.sun.management	org.apache.catalina:type=Manager
java.lang	org.apache.catalina:type=Manager
java.util.logging	org.apache.catalina:type=Manager

Attributes Operations | Notifications | Metadata


Attribute values

Name	Value
activeSessions	1
className	org.apache.catalina.session.StandardManager
distributable	false
duplicates	0
expiredSessions	0
jvmRoute	
maxActive	1
maxActiveSessions	-1
maxInactiveInterval	1800
modelerType	org.apache.catalina.session.StandardManager
name	StandardManager
pathname	SESSIONS.ser
processExpiresFrequency	6
processingTime	0
rejectedSessions	0
secureRandomAlgorithm	SHA1PRNG
secureRandomClass	
secureRandomProvider	
sessionAverageAliveTime	0
sessionCounter	1
sessionCreateRate	20
sessionExpireRate	0
sessionIdLength	16
sessionMaxAliveTime	0
stateName	STARTED


Refresh

A blue arrow points from the 'localhost' entry in the tree view to the 'localhost' entry in the table. Another blue arrow points from the 'activeSessions' row in the table to its value '1'.

Manager Level



Agent Level





```
package com.manifestcorp.webperf;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.stereotype.Controller;
import org.springframework.web.bind.annotation.RequestMapping;

@Controller
public class IndexController {

    private static Logger log = LoggerFactory.getLogger(IndexController.class);

    @RequestMapping(value = "/")
    public String index() {
        System.out.println("HERE!!!");
        log.info("STILL HERE!!!"); ←
        return "WEB-INF/jsp/index.jsp";
    }
}
```

HERE!!!

logback.xml

```
→ <configuration>
    <jmxConfigurator />

    <appender name="STDOUT" class="ch.qos.logback.core.ConsoleAppender">
        <encoder>
            <pattern>%d{HH:mm:ss.SSS} [%thread] %-5level %logger{36} - %msg%n</pattern>
        </encoder>
    </appender>

    <root level="error">
        <appender-ref ref="STDOUT" />
    </root>
</configuration>
```

Tomcat (pid 32512) Overview Monitor Threads Sampler Profiler MBeans Visual GC

Tomcat (pid 32512)

MBeans Browser

MBeans

- Catalina
- JMImplementation
- Users
- ▼ ch.qos.logback.classic
 - ▼ default
 - ch.qos.logback.classic.jmx.JMXConfigurator
- com.sun.management
- java.lang
- java.util.logging

Attributes Operations | Notifications | Metadata

Attribute values

Name	Value
ROOT	
com	
com.manifestcorp	
com.manifestcorp.webperf	
com.manifestcorp.webperf.IndexController	

Statuses

[INFO in ch.qos.logback.classic.LoggerContext[default] - C...]

LoggerList ←

Refresh

The screenshot shows the JConsole interface for a Tomcat process (pid 32512). The left pane displays the MBeans tree, with the 'ch.qos.logback.classic.default' node selected. The right pane shows the 'Attributes' tab of the MBeans browser, specifically the 'Attribute values' section. It lists several loggers: ROOT, com, com.manifestcorp, com.manifestcorp.webperf, and com.manifestcorp.webperf.IndexController. A blue arrow points from the 'LoggerList' label to the 'ch.qos.logback.classic.jmx.JMXConfigurator' entry in the tree. Another blue arrow points from the 'IndexController' entry in the table to the status message at the bottom.

Tomcat (pid 32512) □

Overview Monitor Threads Sampler Profiler MBeans Visual GC

Tomcat (pid 32512)

MBeans Browser

MBeans

- Catalina
- JMImplementation
- Users
- ch.qos.logback.classic
 - default
 - ch.qos.logback.classic.jmx.JMXConfigurator
- com.sun.management
- java.lang
- java.util.logging

Attributes Operations Notifications | Metadata

Operation invocation

java.lang.String getLogLevel (p1 erf.IndexController)

void setLogLevel (p1 erf.IndexController , p2 debug)

void reloadDefaultConfiguration ()

void reloadByFileName (p1 String)

void reloadByUrl (p1 URL)

java.lang.String getLoggerEffectiveLevel (p1 String)





```
package com.manifestcorp.webperf;

import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.stereotype.Controller;
import org.springframework.web.bind.annotation.RequestMapping;

@Controller
public class IndexController {

    private static Logger log = LoggerFactory.getLogger(IndexController.class);

    @RequestMapping(value = "/")
    public String index() {
        System.out.println("HERE!!!");
        log.info("STILL HERE!!!"); ←
        return "WEB-INF/jsp/index.jsp";
    }
}
```

HERE!!!

23:53:03.556 [http-bio-8080-exec-8] INFO c.m.webperf.IndexController - STILL HERE!!!

Manager Level




RMI

Connector

HTTP

Connector



HTTP

Adaptor

SNMP

Adaptor



Agent Level

MBeanServer

MBean
(JVM)

MBean
(app server)

MBean
(library)

MBean
(custom)

Instrumentation Level


Java Virtual Machine

```
public interface IndexCounterMBean {  
    int getCount();  
    void reset();  
}
```




IndexCounterMBean

```
public class IndexCounter implements IndexCounterMBean {  
    static Logger log = LoggerFactory.getLogger(IndexCounter.class);  
    private AtomicInteger count = new AtomicInteger();  
    private static IndexCounter instance;  
  
    static {  
        try {  
            MBeanServer mbs = ManagementFactory.getPlatformMBeanServer();  
            ObjectName name = new ObjectName("com.manifestcorp:type=IndexCounter");  
            instance = new IndexCounter();  
            mbs.registerMBean(instance, name);  
        } catch(Exception ex) {  
            log.error("Unable to register IndexCounter MBean", ex);  
        }  
    }  
  
    private IndexCounter() {}  
  
    public int getCount() { return count.get(); }  
  
    public void increment() { count.incrementAndGet(); }  
  
    public void reset() { count.set(0); }  
  
    public static IndexCounter getInstance() {  
        return instance;  
    }  
}
```



```
package com.manifestcorp.webperf;  
  
public interface IndexCounterMBean {  
    int getCount();  
    void reset();  
}
```



```
package com.manifestcorp.webperf;  
  
public interface IndexCounterMBean {  
    int getCount();  
    void reset();  
}
```

The logo consists of the word "spring" in a lowercase, sans-serif font. A single green leaf icon is positioned above the letter "i".

spring

```
@Component  
@ManagedResource(objectName="com.manifestcorp:type=AlternateCounter")  
public class AlternateCounter {  
  
    static Logger log = LoggerFactory.getLogger(AlternateCounter.class);  
  
    private AtomicInteger count = new AtomicInteger();  
  
    → @ManagedAttribute  
    public int getCount() { return count.get(); }  
  
    public void increment() { count.incrementAndGet(); }  
  
    → @ManagedOperation  
    public void reset() { count.set(0); }  
}
```

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:mvc="http://www.springframework.org/schema/mvc"
    xmlns:context="http://www.springframework.org/schema/context"
    xsi:schemaLocation="
        http://www.springframework.org/schema/mvc http://www.springframework.org/schema/mvc/spring-mvc-3.0.xsd
        http://www.springframework.org/schema/beans http://www.springframework.org/schema/beans/spring-beans-3.0.xsd
        http://www.springframework.org/schema/context http://www.springframework.org/schema/context/spring-context-3.0.xsd

    <context:component-scan base-package="com.manifestcorp" />
    <mvc:annotation-driven />


    → <bean id="exporter" class="org.springframework.jmx.export.MBeanExporter">
        <property name="assembler" ref="assembler"/>
        <property name="namingStrategy" ref="namingStrategy"/>
        <property name="autodetect" value="true"/>
    </bean>

    → <bean id="jmxAttributeSource"
        class="org.springframework.jmx.export.annotation.AnnotationJmxAttributeSource"/>


    → <!-- will create management interface using annotation metadata -->
    → <bean id="assembler"
        class="org.springframework.jmx.export.assembler.MetadataMBeanInfoAssembler">
        <property name="attributeSource" ref="jmxAttributeSource"/>
    </bean>

    → <!-- will pick up the ObjectName from the annotation -->
    → <bean id="namingStrategy"
        class="org.springframework.jmx.export.naming.MetadataNamingStrategy">
        <property name="attributeSource" ref="jmxAttributeSource"/>
    </bean>

</beans>
```




```
@Component  
@ManagedResource(objectName="com.manifestcorp:type=AlternateCounter")  
public class AlternateCounter {  
  
    static Logger log = LoggerFactory.getLogger(AlternateCounter.class);  
  
    private AtomicInteger count = new AtomicInteger();  
  
    @ManagedAttribute  
    public int getCount() { return count.get(); }  
  
    public void increment() { count.incrementAndGet(); }  
  
    @ManagedOperation  
    public void reset() { count.set(0); }  
}
```



```
@Component  
@ManagedResource(objectName="com.manifestcorp:type=AlternateCounter")  
public class AlternateCounter {  
  
    static Logger log = LoggerFactory.getLogger(AlternateCounter.class);  
  
    private AtomicInteger count = new AtomicInteger();  
  
    @ManagedAttribute  
    public int getCount() { return count.get(); }  
  
    public void increment() { count.incrementAndGet(); }  
  
    @ManagedOperation  
    public void reset() { count.set(0); }  
}
```

Manager Level



SNMP

RMI

HTTP

HTTP

SNMP

Connector

Connector

Adaptor

Adaptor

Agent Level

MBeanServer

MBean
(JVM)

MBean
(app server)

MBean
(library)

MBean
(custom)

Instrumentation Level

Java Virtual Machine

```

import javax.management.remote.*

println "Starting..."

def serverList = args.length > 0 ? args : ['appserv.guest', '192.168.248.129']

serverList.each { serverName ->
    try {
        println "\nServer: $serverName"

        def url = "service:jmx:rmi:///jndi/rmi://$serverName:6969/jmxrmi"
        def connection = JMXConnectorFactory.connect(new JMXServiceURL(url))
        def server = connection.MBeanServerConnection
        def mbean = new GroovyMBean(server, 'java.lang:type=Memory')
        println String.format('%15s %7.2f/%7.2f (used/max)', 'heap',
                inBytes(mbean.HeapMemoryUsage.used),
                inBytes(mbean.HeapMemoryUsage.max))
    } catch (e) {
        println e
    }
}

println "Done..."

def inBytes(amount) {
    return amount/1000000
}

```

```

Starting...

Server: appserv.guest
          heap   19.74/ 438.11 (used/max)

Server: 192.168.248.129
          heap   20.09/ 438.11 (used/max)

Done...

```



back to our regularly scheduled
program...



Browse > appserv.guest > appserv.guest Apache Tomcat 7.0

Description:

Owner: HQ Administrator (hqadmin) - Change...

Map Tools Menu

Monitor

Inventory

Alert

Control

Views

Metric Display Range: Last 8 Hours Advanced Settings

RESOURCES

<input type="checkbox"/> Services	Avail
<input type="checkbox"/> Apache Tomcat 7.0 Global Request Processor	
<input type="checkbox"/> Apache Tomcat 7.0 JSP Monitor	
<input type="checkbox"/> Apache Tomcat 7.0 Servlet Monitor	
<input type="checkbox"/> Apache Tomcat 7.0 Thread Pools	
<input type="checkbox"/> Apache Tomcat 7.0 Web Module Stats	
<input type="checkbox"/> Host Platform	Avail
<input type="checkbox"/> appserv.guest	

Select Resources above & click button to view metrics

View Metrics

INDICATORS

METRIC DATA

Indicator Charts | Show Last 8 Hours


View: Update Default



Heap Memory Free

(Apache Tomcat 7.0)

LOW: 8.2 MB AVG: 51.7 MB PEAK: 82.7 MB



Process Cpu Time per Minute

(Apache Tomcat 7.0)


LOW: 481.999ms AVG: 589.969ms PEAK: 957.846ms



UpTime

(Apache Tomcat 7.0)

LOW: 00:55:00.019 AVG: 01:04:00.013 PEAK: 01:13:00.007



11/25/2012 04:52 AM

11/25/2012 12:44 PM



Browse > appserv.guest

Description: CentOS 6.3
Architecture : x86_64
OS Version : 2.6.32-279.el6.x86_64
RAM : 2048 MB

Owner: HQ Administrator (hqadmin) - Change...
CPU Speed : 2 @ 2199 MHz
Vendor Version : 6.3

IP Address : 192.168.248.129
Vendor : CentOS

Map Tools Menu

Monitor Inventory Alert Views

Metric Display Range: Last 8 Hours Advanced Settings

RESOURCES

- Platform Services Health Avail
- CPU
- FileServer Mount
- NetworkServer Interface
- appserv.guest Linux sshd Process
- Deployed Servers Health Avail
- appserv.guest Apache Tomcat 7.0
- appserv.guest HQ Agent 4.6.6

Select Resources above & click button to view metrics

View Metrics

INDICATORS

METRIC DATA

Indicator Charts | Show Last 8 Hours

View Update Default

98.4% — Availability

Free Memory
(Linux)

LOW: 71.5 MB AVG: 133.5 MB PEAK: 245.6 MB



Free Memory (+ buffers/cache)
(Linux)

LOW: 1.2 GB AVG: 1.2 GB PEAK: 1.3 GB



Load Average 5 Minutes
(Linux)

LOW: 0.0 AVG: 0.3 PEAK: 6.8



Swap Used

11/25/2012 05:14 AM

11/25/2012 01:06 PM

Dashboard Resources Analyze Administration



Edit appserv.guest Apache Tomcat 7.0: Tomcat Availability: Alert Condition Set

Condition Set

* If Condition: Metric: Availability

is < (Less than) 10,000.0% (absolute value)
 value changes

Events/Logs Level: Any and match substring (optional, 150 chars max):

Config changed and match file name (optional, 150 chars max):

* Enable Action(s): Each time conditions are met

Once every [] times conditions are met within a time period of [] minutes

Generate one alert and then disable alert definition until fixed

Ok

Reset

Cancel

Recent Alerts				
Date / Time	Alert Name	Resource Name	Fixed	Ack
11/25/2012 01:40 PM	Tomcat Availability	appserv.guest Apache To...	No	
11/25/2012 01:35 PM	Tomcat Availability	appserv.guest Apache To...	No	
11/25/2012 01:30 PM	Tomcat Availability	appserv.guest Apache To...	No	

Updated: 4:43 PM

HYPERIC HQ

Recent Alerts: 01:45 PM - Tomcat Availability
01:40 PM - Tomcat Availability

Welcome, HQ | Sign Out | Screencasts | Help

Dashboard | **Resources** | Analyze | Administration |

appserv.guest Apache Tomcat 7.0: Tomcat Availability: Alert Detail

<< Resource Alert List

Alert Properties

Name: Tomcat Availability	Priority: !!! - High
Resource: appserv.guest Apache Tomcat 7.0	Alert Date: 11/25/2012 01:45 PM
	Alert Status: NOT FIXED

Condition Set

If Condition: Availability < 10,000.0%

Actual Value: 0.0%

Enable Action(s): Each time conditions are met.
Generate one alert and then disable alert definition until fixed

Notification Actions

Notify HQ Users: [hqadmin](#)

Notify Other Recipients: cjudd@juddsolutions.com

Escalation

Escalation Name: Default Escalation

If the alert is acknowledged: Escalation continued without pausing

If the alert state has changed: Previously notified users are notified of the change

Escalation Scheme Actions: None

Escalation Action Logs:

Fx

Previous Fix: (Fixed by hqadmin) Tomcat crashed. Restarted.

Resolution for Fix: Tomcat crashed. Restarted Tomcat.

Click the "Fixed" button to mark alert condition as fixed

<< Resource Alert List

SNMP

1.3.6.1.4.1.42.2.145.3.163.1.1.2.11

rather than

java.lang:type=Memory HeapMemoryUsage

Website Monitoring, Website X

https://www.site24x7.com

rampart manifest aws altair imsafe soccer ecot.html RegExr Reflection.app - AirP DZone Refcardz Other Bookmarks

Site24x7 by Zoho

Home Features Plans & Pricing Tools Support SIGN UP LOGIN

Server Performance Monitoring

Monitor your internal servers.

Track CPU, memory and disk utilization for Windows machines.

Plans, Pricing and Signup

15-day free trial, sign up in 30 seconds.

Disk Utilization

Memory Utilization

CPU Utilization

History Data for: Today Week Month

Type : SERVER Availability 97.31% CPU 4.83 %

Avg CPU Usage 5% Max CPU Usage 100% Min CPU Usage 0%

Time Avg CPU Usage(%)

Time	Avg CPU Usage(%)
16/01/2012 00:00	4
16/01/2012 01:00	4
16/01/2012 02:00	4
16/01/2012 03:00	10
16/01/2012 04:00	3
16/01/2012 05:00	4
16/01/2012 06:00	4
16/01/2012 07:00	3
16/01/2012 08:00	3
16/01/2012 09:00	3

Website Monitoring Maximize your website uptime

End User Experience Track webpage performance

Server Monitoring Server Monitoring as SaaS

Instant Alerts SMS,Email,Push Notification

SLA Management Align IT & Business goals

The screenshot shows a web browser window for Site24x7. The main content area features a large orange call-to-action button for 'Plans, Pricing and Signup'. To its right are three monitoring panels: 'Disk Utilization' (pie chart and bar chart), 'Memory Utilization' (stacked bar chart), and 'CPU Utilization' (horizontal bar chart). Below these are five service cards: 'Website Monitoring', 'End User Experience', 'Server Monitoring', 'Instant Alerts', and 'SLA Management'. The top navigation bar includes links for Home, Features, Plans & Pricing, Tools, Support, SIGN UP, and LOGIN. The address bar shows the URL https://www.site24x7.com. The overall theme is green and white.

<https://www.site24x7.com/>

TRIAGE



OpenJDK



What are the things that effect Java performance?

- Memory
- CPU
- Threads

Command-line

List Java Processes

pid or process id

ps aux | grep java



```
501 17737 130 0 8:33.83 ?? 38:01.79 /Users/cjudd/devl/java/
sts-2.5.2.SR1/STS.app/Contents/MacOS/STS -psn_0_2876094
501 26644 17737 0 4:18.68 ?? 10:03.41 /System/Library/Frameworks/
JavaVM.framework/Versions/1.6.0/Home/bin/java -
agentlib:jdwp=transport=dt_socket,suspend=y,address=localhost:60315 -Dcatalina.base=/
Users/cjudd/devl/java/apache-tomcat-6.0.29 -Dcatalina.home=/Users/cjudd/devl/java/
apache-tomcat-6.0.29 -Dwtp.deploy=/Users/cjudd/devl/java/apache-tomcat-6.0.29/
wtpwebapps -Djava.endorsed.dirs=/Users/cjudd/devl/java/apache-tomcat-6.0.29/endorsed -
Xms512m -Xmx1024m -XX:MaxPermSize=128m -Xshare:off -Dfile.encoding=UTF-8 -classpath /
Users/cjudd/devl/java/apache-tomcat-6.0.29/bin/bootstrap.jar
org.apache.catalina.startup.Bootstrap start
501 33146 25845 0 0:00.01 ttys002 0:00.01 grep java
```

jps

```
26644 Bootstrap  
17737  
20294  
33167 Jps
```

jps -l

full package names

```
33171 sun.tools.jps.Jps  
26644 org.apache.catalina.startup.Bootstrap  
17737  
20294
```

jps -l -v

JVM Arguments

```
33186 sun.tools.jps.Jps -Dapplication.home=/System/Library/Java/JavaVirtualMachines/1.6.0.jdk/  
Contents/Home -Xms8m  
26644 org.apache.catalina.startup.Bootstrap -  
agentlib:jdwp=transport=dt_socket,suspend=y,address=localhost:60315 -Dcatalina.base=/Users/cjudd/  
devl/java/apache-tomcat-6.0.29 -Dcatalina.home=/Users/cjudd/devl/java/apache-tomcat-6.0.29 -  
Dwtp.deploy=/Users/cjudd/devl/java/apache-tomcat-6.0.29/wtpwebapps -Djava.endorsed.dirs=/Users/  
cjudd/devl/java/apache-tomcat-6.0.29/endorsed -Xms512m -Xmx1024m -XX:MaxPermSize=128m -Xshare:off  
-Dfile.encoding=UTF-8  
17737 -Dosgi.requiredJavaVersion=1.5 -Xms40m -Xmx768m -XX:MaxPermSize=256m -XstartOnFirstThread -  
Dorg.eclipse.swt.internal.carbon.smallFonts  
20294 -Xbootclasspath/a:/System/Library/PrivateFrameworks/JavaApplicationLauncher.framework/  
Resources/LauncherSupport.jar -Dsun.security.ssl.allowUnsafeRenegotiation=true -Xms128m -Xmx1200m  
-Dsoapui.ext.actions=/Applications/eviware/soapUI-3.6.1.app/Contents/Resources/app/bin/actions -  
Dsoapui.properties=soapui.properties -Dsoapui.home=/Applications/eviware/soapUI-3.6.1.app/  
Contents/Resources/app/bin -Dxe4j.moduleName=/Applications/eviware/soapUI-3.6.1.app -Dwsdl.dir=/  
Applications/eviware/soapUI-3.6.1.app/Contents/Resources/app/wsi-test-tools -Djava.library.path=/  
Applications/eviware/soapUI-3.6.1.app/Contents/Resources/app/bin:/System/Library/  
PrivateFrameworks/JavaApplicationLauncher.framework/Resources -Dsoapui.jxbrowser.disable=true -  
Dsoapui.ext.listeners=/Applications/eviware/soapUI-3.6.1.app/Contents/Resources/app/bin/listeners  
-Dsoapui.ext.libraries=/Applications/eviware/soapUI-3.6.1.app/Contents/Resources/app/bin/ext
```

jinfo

Attaching to process ID 7485, please wait...
Debugger attached successfully.
Server compiler detected.
JVM version is 17.1-b03
Java System Properties:

```
java.runtime.name = Java(TM) SE Runtime Environment
sun.boot.library.path = /usr/java/jdk1.6.0_22/jre/lib/amd64
java.vm.version = 17.1-b03
java.vm.vendor = Sun Microsystems Inc.
java.vm.name = Java HotSpot(TM) 64-Bit Server VM
com.sun.management.jmxremote.port = 8999
java.vm.specification.name = Java Virtual Machine Specification
user.dir = /usr/tomcat/apache-tomcat-6.0.29
java.runtime.version = 1.6.0_22-b04
java.vm.specification.vendor = Sun Microsystems Inc.
java.library.path = /usr/java/jdk1.6.0_22/jre/lib/amd64/server:/usr/java/jdk1.6.0_22/jre/lib/amd64:/usr/ja
jdk1.6.0_22/jre/..../lib/amd64:/usr/java/packages/lib/amd64:/usr/lib64:/lib64:/lib:/usr/lib
java.specification.name = Java Platform API Specification
sun.management.compiler = HotSpot 64-Bit Server Compiler
os.version = 2.6.18-8.el5
com.sun.management.config.file = /usr/java/current/jre/lib/management/management.properties
java.specification.version = 1.6
catalina.home = /usr/tomcat/current
java.class.path = /usr/tomcat/current/bin/bootstrap.jar
user.name = tomcat
java.home = /usr/java/jdk1.6.0_22/jre
user.language = en
java.specification.vendor = Sun Microsystems Inc.
java.version = 1.6.0_22
```

properties

VM Flags:

vm flags

```
-Djava.util.logging.config.file=/usr/tomcat/current/conf/logging.properties -Xms2g -Xmx2g -Xss256k -XX:Per
-XX:MaxPermSize=512m -XX:+UseConcMarkSweepGC -XX:-HeapDumpOnOutOfMemoryError -XX:HeapDumpPath=/usr/tomcat/
logs/heap_dump.hprof -Dcom.sun.management.jmxremote.port=8999 -Dcom.sun.management.config.file=/usr/java/c
jre/lib/management/management.properties -Duser.home=/usr/tomcat/current -Ddak.home=/usr/tomcat/current -
Djava.util.logging.manager=org.apache.juli.ClassLoaderLogManager -Djava.endorsed.dirs=/usr/tomcat/current/
Dcatalina.base=/usr/tomcat/current -Dcatalina.home=/usr/tomcat/current -Djava.io.tmpdir=/usr/tomcat/curren
```

Stack Trace

jstack

```
Full thread dump Java HotSpot(TM) 64-Bit Server VM (20.1-b02-384 mixed mode):

"Attach Listener" daemon prio=9 tid=102958000 nid=0x11a307000 waiting on condition [00000000]
  java.lang.Thread.State: RUNNABLE

"http-8080-6" daemon prio=5 tid=102d26000 nid=0x11a50d000 in Object.wait() [11a50c000]
  java.lang.Thread.State: WAITING (on object monitor)
    at java.lang.Object.wait(Native Method)
    at java.lang.Object.wait(Object.java:485)
    at org.apache.tomcat.util.net.JIoEndpoint$Worker.await(JIoEndpoint.java:458)
    - locked <7c8961bf8> (a org.apache.tomcat.util.net.JIoEndpoint$Worker)
    at org.apache.tomcat.util.net.JIoEndpoint$Worker.run(JIoEndpoint.java:484)
    at java.lang.Thread.run(Thread.java:680)

"pool-1-thread-1" prio=5 tid=102f23000 nid=0x11a40a000 waiting on condition [11a409000]
  java.lang.Thread.State: TIMED_WAITING (parking)
    at sun.misc.Unsafe.park(Native Method)
    - parking to wait for  <7c5fdadb8> (a java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject)
    at java.util.concurrent.locks.LockSupport.parkNanos(LockSupport.java:198)
    at java.util.concurrent.locks.AbstractQueuedSynchronizer$ConditionObject.awaitNanos(AbstractQueuedSynchronizer.java:2025)
    at java.util.concurrent.DelayQueue.take(DelayQueue.java:164)
    at java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:393)
    at java.util.concurrent.ScheduledThreadPoolExecutor$DelayedWorkQueue.take(ScheduledThreadPoolExecutor.java:357)
    at java.util.concurrent.ThreadPoolExecutor.getTask(ThreadPoolExecutor.java:947)
    at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:907)
    at java.lang.Thread.run(Thread.java:680)
```

kill -3 <pid>

kill -QUIT <pid>

thread name

thread id

"TP-Processor195" daemon prio=10 tid=0x00002aab614b6800 nid=0x4009 runnable [0x0000000046905000]
java.lang.Thread.State: **RUNNABLE** ← thread state
at com.mysql.jdbc.MysqlIO.unpackField(MysqlIO.java:765)
at com.mysql.jdbc.MysqlIO.getResultSet(MysqlIO.java:416)
at com.mysql.jdbc.ConnectionImpl.execSQL(ConnectionImpl.java:2568)
- locked <0x00002aab04914c60> (a java.lang.Object)
at com.mysql.jdbc.PreparedStatement.executeInternal(PreparedStatement.java:2113)
at com.mysql.jdbc.PreparedStatement.executeQuery(PreparedStatement.java:2275)
- locked <0x00002aab04914c60> (a java.lang.Object)
at com.mchange.v2.c3p0.impl.NewProxyPreparedStatement.executeQuery(NewProxyPreparedStatement.java:76)
at org.hibernate.hql.ast.QueryTranslatorImpl.list(QueryTranslatorImpl.java:363)
at org.hibernate.engine.query.HQLQueryPlan.performList(HQLQueryPlan.java:196)
at org.hibernate.impl.SessionImpl.list(SessionImpl.java:1258)
at org.hibernate.impl.QueryImpl.list(QueryImpl.java:102)
at com.mydoman.dao.impl.HibernateClassroomDAO\$4.doInHibernate(HibernateClassroomDAO.java:252)
at com.mydoman.common.framework.orm.hibernate.SimpleHibernateDAO.execute(SimpleHibernateDAO.java:31)
at com.mydoman.dao.impl.HibernateClassroomDAO.getClassroomUsersByRoleAndStatus(HibernateClassroomDAO.java:245)
at com.mydoman.manager.impl.DefaultClassroomManager.getClassroomUsersByRole(DefaultClassroomManager.java:676)
at com.mydoman.web.gradebook.ClazzScheduleController.getTeachers(ClazzScheduleController.java:181)
at com.mydoman.web.gradebook.ClazzScheduleController.showForm(ClazzScheduleController.java:272)
at com.mydoman.web.classroom.ClassroomClazzScheduleController.showForm(ClassroomClazzScheduleController.java:20)
at java.lang.Thread.run(Thread.java:662)

"TP-Processor194" daemon prio=10 tid=0x00002aab614b5000 nid=0x4008 in Object.wait() [0x0000000044b0f000]
java.lang.Thread.State: **BLOCKED** (on object monitor)
at java.lang.Object.wait(Native Method)
at com.mchange.v2.resourcepool.BasicResourcePool.awaitAvailable(BasicResourcePool.java:1315)
- locked <0x00002aaab4eb5218> (a com.mchange.v2.resourcepool.BasicResourcePool)
at com.mchange.v2.resourcepool.BasicResourcePool.checkoutResource(BasicResourcePool.java:477)
at org.hibernate.engine.query.HQLQueryPlan.performList(HQLQueryPlan.java:196)
at org.hibernate.impl.SessionImpl.list(SessionImpl.java:1258)
at org.hibernate.impl.QueryImpl.list(QueryImpl.java:102)
at com.mydoman.manager.impl.DefaultOrganizationManager.getRoot(DefaultOrganizationManager.java:524)
at com.mydoman.manager.impl.DefaultOrganizationManager.isRoot(DefaultOrganizationManager.java:529)
at sun.reflect.GeneratedMethodAccessor763.invoke(Unknown Source)
at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:25)
at java.lang.reflect.Method.invoke(Method.java:597)
at com.mydoman.web.homeroom.announcements.AnouncementsController.showForm(AnnouncementsController.java:150)
at java.lang.Thread.run(Thread.java:662)

"TP-Processor193" daemon prio=10 tid=0x00002aab605eb800 nid=0x4007 waiting on condition [0x0000000044371000]
java.lang.Thread.State: **WAITING** (parking)
at sun.misc.Unsafe.park(Native Method)
- parking to wait for <0x00002aaacc6775b8> (a java.util.concurrent.locks.AbstractQueuedSynchronizer\$ConditionObject)
at java.util.concurrent.locks.LockSupport.park(LockSupport.java:158)
at org.apache.activemq.ActiveMQSession.send(ActiveMQSession.java:1760)
- locked <0x00002aaace30bed8> (a java.lang.Object)
at org.apache.activemq.ActiveMQMessageProducer.send(ActiveMQMessageProducer.java:231)
at org.apache.activemq.ActiveMQMessageProducerSupport.send(ActiveMQMessageProducerSupport.java:241)
at com.mydoman.dao.BusApplicationEventDAO.create(BusApplicationEventDAO.java:329)
at com.mydoman.manager.impl.DefaultApplicationEventManager.create(DefaultApplicationEventManager.java:172)

Heap Dump

```
jmap -dump:format=b,file=<heap_dump.out>
```

```
jmap -F -dump:format=b,file=<heap_dump.out>
```



heap dump will equal jvm memory size

jhat -J-Xmx2048MB heapdump.hprof

Heap Histogram

All Classes (excluding platform)

Class	Instance Count	Total Size
class [C	5187759	305558528
class java.lang.String	5192640	103852800
class []	20795	50646904
class [Ljava.lang.String;	23584	48058624
class [B	19633	22810538

Object Query Language (OQL) query

All Classes (excluding platform) [OQL Help](#)

```
select cl
from instanceof java.lang.ClassLoader cl
where !cl.isof(cl).name.startsWith("sun.reflect") && !cl.isof(cl).name.startsWith("org.apache.jasper")
```

Execute

sun.misc.Launcher\$AppClassLoader@0x2aab174ebf0
sun.misc.Launcher\$ExtClassLoader@0x2aab174bca0
org.apache.catalina.loader.WebappClassLoader@0x2aab199eba0
org.apache.catalina.loader.StandardClassLoader@0x2aab17ce5d8
com.sun.jmx.remote.util.OrderClassLoaders@0x2aad8401f60
com.sun.jmx.remote.util.OrderClassLoaders@0x2aad8401fd0
com.sun.jmx.remote.util.OrderClassLoaders@0x2aad8402120
com.sun.jmx.remote.util.OrderClassLoaders@0x2aad8402190
com.sun.jmx.remote.util.OrderClassLoaders@0x2aad8402040

Remote Access

- Dcom.sun.management.jmxremote
- Dcom.sun.management.jmxremote.port=6969
- Dcom.sun.management.jmxremote.ssl=false
- Dcom.sun.management.jmxremote.authenticate=false

- Dcom.sun.management.jmxremote
- Dcom.sun.management.jmxremote.port=6969
- Dcom.sun.management.jmxremote.ssl=false
- Dcom.sun.management.jmxremote.authenticate=true
- Dcom.sun.management.jmxremote.password.file=../conf/jmxremote.password \
- Dcom.sun.management.jmxremote.access.file=../conf/jmxremote.access \

jmxremote.password *(this file must be read-only for the user running app)*

monitorRole QED
controlRole R&D


jmxremote.access

monitorRole readonly
controlRole readwrite



example files can be found at <java_home>/jre/lib/management

Remote Access


monitoring tools



jvisualvm
jconsole



jps
jinfo
jmap
jstack
jvisualvm
jconsole



Remote Access


jstatd daemon

```
jstatd -J-Djava.security.policy=allowall.pol
```

```
jps 10.1.55.7
```

GUI


Visual VM



jvisualvm

<http://visualvm.java.net/>

visualvm




● Memory


● CPU

● Threads


Healthy CPU



Healthy Heap





Healthy Threads




Role Playing

Example |







Example 2



Example 3



Example 4



○ [heapdump] Yesterday, 11:08:11 PM

Heap Dump



Classes

[Compare with another heap dump](#)

Class Name	Instances [%]	Instances	Size
org.apache.solr.common.params.CoreAdminParams\$CoreAdminAction		13 (0%)	364 (0%)
org.apache.solr.servlet.cache.Method		4 (0%)	112 (0%)
org.apache.solr.servlet.cache.Method[]		2 (0%)	96 (0%)
org.apache.solr.common.params.CoreAdminParams\$CoreAdminAction[]		1 (0%)	120 (0%)
org.apache.solr.servlet.RawRequestParser		1 (0%)	16 (0%)
org.apache.solr.servlet.SimpleRequestParser		1 (0%)	16 (0%)
org.apache.solr.response.RawResponseWriter		1 (0%)	24 (0%)
org.apache.solr.response.PHPSerializedResponseWriter		1 (0%)	16 (0%)
org.apache.solr.logging.jul.JulWatcher		1 (0%)	48 (0%)
org.apache.solr.logging.CircularList		1 (0%)	36 (0%)
org.apache.solr.response.XMLResponseWriter		1 (0%)	16 (0%)
org.apache.solr.response.JSONResponseWriter		1 (0%)	24 (0%)
org.apache.solr.handler.admin.CoreAdminHandler		1 (0%)	97 (0%)
org.apache.solr.response.PythonResponseWriter		1 (0%)	16 (0%)
org.apache.solr.servlet.StandardRequestParser		1 (0%)	32 (0%)
org.apache.solr.handler.admin.CollectionsHandler		1 (0%)	97 (0%)
org.apache.solr.servlet.MultipartRequestParser		1 (0%)	24 (0%)
org.apache.solr.logging.jul.RecordHandler		1 (0%)	73 (0%)
org.apache.solr.response.PHPResponseWriter		1 (0%)	16 (0%)
org.apache.solr.core.CoreContainer		1 (0%)	243 (0%)
org.apache.solr.core.SolrResourceLoader		1 (0%)	73 (0%)
org.apache.solr.core.Config		1 (0%)	48 (0%)
org.apache.solr.servlet.SolrDispatchFilter		1 (0%)	64 (0%)
org.apache.solr.servlet.LoadAdminUiServlet		1 (0%)	24 (0%)
org.apache.solr.common.util.XMLErrorLogger		1 (0%)	24 (0%)
org.apache.solr.servlet.SolrRequestParsers		1 (0%)	42 (0%)
org.apache.solr.core.SolrXMLLoader		1 (0%)	16 (0%)
org.apache.solr.response.CSVResponseWriter		1 (0%)	16 (0%)
org.apache.solr.response.RubyResponseWriter		1 (0%)	16 (0%)
org.apache.solr.response.BinaryResponseWriter		1 (0%)	16 (0%)
org.apache.solr.response.transform.ValueSourceAugmenter		0 (0%)	0 (0%)
org.apache.solr.response.transform.ScoreAugmenter		0 (0%)	0 (0%)
org.apache.solr.search.QParserPlugin		0 (0%)	0 (0%)
org.apache.solr.core.NRTCachingDirectoryFactory		0 (0%)	0 (0%)
org.apache.solr.client.solrj.SolrRequest		0 (0%)	0 (0%)
org.apache.solr.schema.SortableDoubleField		0 (0%)	0 (0%)
org.apache.solr.core.SolrCore\$8		0 (0%)	0 (0%)
org.apache.solr.schema.IntField		0 (0%)	0 (0%)
org.apache.solr.common.cloud.ZkNodeProps		0 (0%)	0 (0%)
org.apache.solr.request.SolrRequestHandler		0 (0%)	0 (0%)
org.apache.solr.schema.TrieDateField		0 (0%)	0 (0%)
org.apache.solr.common.SolrDocumentList		0 (0%)	0 (0%)
org.apache.solr.schema.BCDStrField		0 (0%)	0 (0%)
org.apache.solr.handler.component.HttpShardHandlerFactory		0 (0%)	0 (0%)
org.apache.solr.response.ResultContext		0 (0%)	0 (0%)

○ [heapdump] Yesterday, 11:08:11 PM

Heap Dump



Query Results

[sun.misc.Launcher\\$AppClassLoader#1](#)
[javax.management.remote.rmi.RMIClientImpl\\$CombinedClassLoader\\$ClassLoaderWrapper#1](#)
[javax.management.remote.rmi.RMIClientImpl\\$CombinedClassLoader\\$ClassLoaderWrapper#2](#)
[java.net.FactoryURLClassLoader#1](#)
[java.util.ResourceBundle\\$RBClassLoader#1](#)
[org.apache.catalina.loader.WebappClassLoader#1](#)
[org.apache.catalina.loader.WebappClassLoader#2](#)
[org.apache.catalina.loader.WebappClassLoader#3](#)
[org.apache.catalina.loader.WebappClassLoader#4](#)
[org.apache.catalina.loader.WebappClassLoader#5](#)
[org.apache.catalina.loader.WebappClassLoader#6](#)
[org.apache.catalina.loader.StandardClassLoader#1](#)
[com.sun.jmx.remote.util.ClassLoaderWithRepository#1](#)
[com.sun.jmx.remote.util.ClassLoaderWithRepository#2](#)
[javax.management.remote.rmi.RMIClientImpl\\$CombinedClassLoader#1](#)
[javax.management.remote.rmi.RMIClientImpl\\$CombinedClassLoader#2](#)
[sun.misc.Launcher\\$ExtClassLoader#1](#)
[javax.management.remote.rmi.NoCallStackClassLoader#1](#)
[javax.management.remote.rmi.NoCallStackClassLoader#2](#)

Query Editor

```
select cl
from instanceof java.lang.ClassLoader cl
where !classef(cl).name.startsWith("sun.reflect") && !classef(cl).name.startsWith("org.apache.jasper")
```

Saved Queries

- ▼ [Custom](#)
 <No Custom Queries Defined>
- ▼ [Samples](#)
 - [List java.io.File instances](#)
 - [Overallocted Strings](#)
 - [Overallocted Strings \(JS\)](#)
 - [Too many Booleans](#)
- ▶ [PermGen Analysis](#)

Save

Execute

Properties

Delete

Open

OQL

```
-- # of loaded classes
select count(heap.classes())

-- # of classes loaded in JVM bootstrap
select count(heap.classes(), 'it.loader == null')

-- parent child relationship of classloaders
select map(heap.objects('java.lang.ClassLoader'),
  function(it) {
    var res='';
    while (it != null) {
      res += toHtml(it) + "->";
      it = it.parent;
    }
    res += "null";
    return res + "<br>";
  )


-- list of sub classes that start with a particular package
select classof(cl).name
from instanceof java.lang.ClassLoader cl
where classof(cl).name.startsWith("sun.reflect")


-- list sub classes that don't start with a particular package
select cl
from instanceof java.lang.ClassLoader cl
where !classof(cl).name.startsWith("sun.reflect") && !
classof(cl).name.startsWith("org.apache.jasper")

-- number of objects in memory of a particular class
select count(heap.objects("sun.reflect.DelegatingClassLoader"))

-- show path value of all File objects
select file.path.toString() from java.io.File file
```

Type	Name	Value
ref	checksumCalc	java.util.zip.CRC32 @ 0x17923b10
ref	SAVED_STATE	0
ref	UPDATING_ST	1
ref	UNKNOWN_ST	2
ref	REBUILDING_S	3
ref	indexLocation	org.eclipse.jdt.internal.core.search.indexing.IndexManager @ 0x17923b10
ref	indexes	org.eclipse.jdt.internal.core.search.indexing.IndexManager @ 0x17923b10
boolean	needToSave	true
ref	javaPluginLoc	org.eclipse.core.runtime.IPath @ 0x17923b10
ref	indexStates	org.eclipse.jdt.internal.core.search.indexing.IndexManager @ 0x17923b10
ref	savedIndexName	java.io.File @ 0x17923b10
ref	awaitingJobs	org.eclipse.jdt.internal.core.search.indexing.IndexManager @ 0x17923b10
int	jobStart	0
int	jobEnd	-1
boolean	executing	false
ref	processingThread	Java indexing
ref	progressJob	null
int	enableCount	1
boolean	activated	true
int	awaitingClient	0





<http://plumbr.eu/>

TDA - Thread Dumps of /Users/cjudd/devl/workspaces/rampart/logs/20130730-perf-test/data-load-2/td-2013-07-30_10_11_02.txt ...

File View Tools Help

▶ /Users/cjudd/devl/workspaces/rampart/logs/20130730-perf-test
 ▼ /Users/cjudd/devl/workspaces/rampart/logs/20130327-prod-iq-
 Logfile
 ▼ Dump No. 1 at line 2 around 2013-03-27 14:40:31
 Threads (327 Threads overall)
 Threads waiting for Monitors (32 Threads waiting)
 Threads sleeping on Monitors (38 Threads sleeping)
 Threads locking Monitors (239 Threads locking)
 Monitors (193 Monitors)

Name	Type	Thread-ID	Native-ID	State	Address R...
TP-Processor535	Da...	469155632...	24295	in Object.w...	[0x000000...
TP-Processor533	Da...	469155731...	24255	in Object.w...	[0x000000...
TP-Processor531	Da...	469155558...	24253	Runnable	[0x000000...
TP-Processor529	Da...	469155632...	24251	in Object.w...	[0x000000...
TP-Processor526	Da...	469155602...	24248	in Object.w...	[0x000000...
TP-Processor525	Da...	469155426...	24247	Waiting on...	[0x000000...
TP-Processor522	Da...	469155426...	24244	Waiting on...	[0x000000...
TP-Processor521	Da...	469155421...	24243	in Object.w...	[0x000000...
TP-Processor520	Da...	469155602...	24242	Runnable	[0x000000...
TP-Processor519	Da...	469155675...	24241	Runnable	[0x000000...
TP-Processor517	Da...	469155505...	24239	Runnable	[0x000000...
TP-Processor514	Da...	469155610...	24220	Runnable	[0x000000...
TP-Processor513	Da...	469155672...	24219	in Object.w...	[0x000000...
TP-Processor511	Da...	469155460...	24217	in Object.w...	[0x000000...
TP-Processor506	Da...	469155434...	24204	in Object.w...	[0x000000...
TP-Processor503	Da...	469155483...	24192	in Object.w...	[0x000000...

```
"TP-Processor517" daemon prio=10 tid=0x00002aab60b91800 nid=0x5eaf runnable [0x000000004acd000]
java.lang.Thread.State: RUNNABLE
  at java.net.SocketInputStream.socketRead0(Native Method)
  at java.net.SocketInputStream.read(SocketInputStream.java:129)
  at com.mysql.jdbc.util.ReadAheadInputStream.fill(ReadAheadInputStream.java:114)
  at com.mysql.jdbc.util.ReadAheadInputStream.readFromUnderlyingStreamIfNecessary(ReadAheadInputStream.java:161)
  at com.mysql.jdbc.util.ReadAheadInputStream.read(ReadAheadInputStream.java:189)
  - locked <0x00002aab67d8eb8> (a com.mysql.jdbc.util.ReadAheadInputStream)
  at com.mysql.jdbc.MysqlIO.readFully(MysqlIO.java:2499)
  at com.mysql.jdbc.MysqlIO.reuseAndReadPacket(MysqlIO.java:2952)
  at com.mysql.jdbc.MysqlIO.reuseAndReadPacket(MysqlIO.java:2941)
  at com.mysql.jdbc.MysqlIO.checkErrorPacket(MysqlIO.java:3489)
  at com.mysql.jdbc.MysqlIO.sendCommand(MysqlIO.java:1959)
  at com.mysql.jdbc.MysqlIO.sqlQueryDirect(MysqlIO.java:2113)
  at com.mysql.jdbc.ConnectionImpl.execSQL(ConnectionImpl.java:2568)
  - locked <0x00002aab697e940> (a java.lang.Object)
  at com.mysql.jdbc.PreparedStatement.executeInternal(PreparedStatement.java:2113)
  at com.mysql.jdbc.PreparedStatement.executeQuery(PreparedStatement.java:2275)
  - locked <0x00002aab697e940> (a java.lang.Object)
  at com.mchange.v2.c3p0.impl.NewProxyPreparedStatement.executeQuery(NewProxyPreparedStatement.java:76)
  at org.springframework.jdbc.core.JdbcTemplate$1.doInPreparedStatement(JdbcTemplate.java:643)
  at org.springframework.jdbc.core.JdbcTemplate.execute(JdbcTemplate.java:586)
  at org.springframework.jdbc.core.JdbcTemplate.query(JdbcTemplate.java:636)
  at org.springframework.jdbc.core.JdbcTemplate.query(JdbcTemplate.java:665)
  at org.springframework.jdbc.core.JdbcTemplate.query(JdbcTemplate.java:669)
  at org.springframework.jdbc.core.JdbcTemplate.query(JdbcTemplate.java:709)
  at org.springframework.jdbc.core.JdbcTemplate.queryForList(JdbcTemplate.java:792)
  at com.altair.cls.common.event.eis.sql.SQLContentItemAccessEventDAO.hasUserVisitedContentItem(SQLContentItemAccessEventDAO.java:60)
  at com.altair.cls.manager.impl.DefaultApplicationEventManager.hasUserVisitedContentItem(DefaultApplicationEventManager.java:433)
  at sun.reflect.GeneratedMethodAccessor384.invoke(Unknown Source)
  at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:25)
  at java.lang.reflect.Method.invoke(Method.java:597)
  at org.springframework.aop.support.AopUtils.invokeJoinpointUsingReflection(AopUtils.java:309)
  at org.springframework.aop.framework.ReflectiveMethodInvocation.invokeJoinpoint(ReflectiveMethodInvocation.java:183)
  at org.springframework.aop.framework.ReflectiveMethodInvocation.proceed(ReflectiveMethodInvocation.java:150)
  ...

```

TDA - Thread Dump Analyzer 2.2 22.9MB/81.1MB



Generating Load



<http://jmeter.apache.org/>

G Gatling Project - Stress Tool

gatling-tool.org

rampart manifest aws altair lmsafe soccer ecot.html RegExr Reflection.app - Air DZone Refcardz Other Bookmarks

 **Gatling**
STRESS TOOL

[+1](#) 77 [Tweet](#) 329 [Fork me on GitHub](#)

Efficient Load Testing


Links

Sponsors









About

Gatling is an [Open Source](#) Stress Tool with:

- High performances
- Simple concepts
- A DSL to describe scenarios
- HTTP support
- A scenario recorder
- Meaningful reports

Download

11/22/2012: Gatling 1.3.5 is out! ([Changelog](#))

You can download it here:

- [gatling-charts-highcharts-1.3.5-bundle.tar.gz](#)
- [gatling-charts-highcharts-1.3.5-bundle.zip](#)
- [gatling-charts-highcharts-1.3.5.deb](#)

Documentation

Gatling comes with helpful [User Documentation](#)...

- [Getting Started](#)
- [First Steps With Gatling](#)
- [Advanced Usage](#)

Examples

Check these examples out!

- [Gatling's DSL vs JMeter's](#)
- [HTML Reports](#)

Gatling In Action



Gatling

<http://gatling-tool.org/>

Gatling Tool **GatlingTool**

GatlingTool Gatling 1.3.5 is out. Fixed cookies, redirects JsonPath and many more. Enjoy! [gatling-tool.org](#) [github.com/excilys/gatlin...](#) yesterday · reply · retweet · favorite

soccertrash #Gatling appear to be a great stress/load test tool, thanks for introduction #devoxx 11 days ago · reply · retweet · favorite

AuroreBossus Gatling pres @devoxx was so cool, too bad it had to be that short... Nice job guys ;-) 11 days ago · reply · retweet · favorite

ebottard @islandelle talking about @GatlingTool at #devoxx Antwerp. The audience seem to appreciate the slides! [pic.twitter.com/44ucUAEj](#) 11 days ago · reply · retweet · favorite

nvahlas #devoxx #gatling: stress tool based on async architecture and scala: scenarios written in scala w/ rich dsl ... interesting approach. 11 days ago · reply · retweet · favorite

[Join the conversation](#)

Other Profilers



<http://www.ej-technologies.com/products/jprofiler/overview.html>



<http://www.yourkit.com/>



<http://newrelic.com/>



<http://www.appdynamics.com/>



<http://www.appfirst.com>

**MAKE YOUR OWN
TOOLS**

Starting...

Date: Mon Apr 23 09:46:23 EDT 2012

Server: 10.0.50.161

cpu usage 65.12%
 heap 1665.33/2138.77 (used/max)
 threads 207/198/218 (live/daemon/peak)
queue size 0
[mls_mail] 0/ 10/ 60 (busy/total/max) 2rw7tt8m1miverrzbuxaz|7f5c693a
[sessionlog] 0/ 20/100 (busy/total/max) 2rw7tt8m1miverrzbuxaz|3612af8d
[mls] 5/ 35/300 (busy/total/max) 2rw7tt8m1miverrzbuxaz|6a48ffbc
active sessions 906

Server: 10.0.50.162

cpu usage 1.40%
 heap 850.19/2138.77 (used/max)
 threads 210/201/213 (live/daemon/peak)
queue size 0
[mls] 0/ 25/300 (busy/total/max) 2rw7tu8m1m49xy13vtggq|60f00e0f
[mls_mail] 0/ 10/ 60 (busy/total/max) 2rw7tu8m1m49xy13vtggq|5999ef99
[sessionlog] 0/ 15/100 (busy/total/max) 2rw7tu8m1m49xy13vtggq|15a1ad24
active sessions 321

Server: 10.0.50.164

cpu usage 95.79%
 heap 1194.39/2138.77 (used/max)
 threads 431/421/1308 (live/daemon/peak)
queue size 38
[sessionlog] 5/ 85/100 (busy/total/max) 2rw7tw8m1mj7yhpaojbdy|1bdf2b92
[cls] 60/300/300 (busy/total/max) 2rw7tw8m1mj7yhpaojbdy|334021a9
[cls_mail] 13/ 60/ 60 (busy/total/max) 2rw7tw8m1mj7yhpaojbdy|4da84fae
active sessions 664

Done...

Thread Analysis for app06

file:///localhost/Users/cjudd/devl/workspaces/rampart/logs/201211107-app06-highcpu/2012-11-07_17_14_46-2012-11-07_17_14_58.html

Java Thread State: **RUNNABLE**

```

at java.io.BufferedInputStream.read1(BufferedInputStream.java:258)
at java.io.BufferedInputStream.read(BufferedInputStream.java:317)
- locked <0x0002aaafef19e0> is java.io.BufferedInputStream
at org.apache.jk.common.ChannelSocket.read(ChannelSocket.java:626)
at org.apache.jk.common.ChannelSocket.receive(ChannelSocket.java:564)
at org.apache.jk.common.ChannelSocket.processConnection(ChannelSocket.java:691)
at org.apache.jk.common.ChannelSocket$SocketConnection.runit(ChannelSocket.java:896)
at org.apache.tomcat.util.threads.ThreadPool$ControlRunnable.run(ThreadPool.java:690)
at java.lang.Thread.run(Thread.java:662)

```

"TP-Processor3337" daemon prio=10 tid=0x0002aab413b2800 nid=0x62a0 runnable [0x00000004c377000]
java.lang.Thread.State: **RUNNABLE**

```

at org.apache.log4j.Category.getEffectiveLevel(Category.java:462)
at org.apache.log4j.Logger.isTraceEnabled(Logger.java:209)
at org.altair.cis.logging.impl.SLF4JLocationAwareLog.java:60
at org.jsecurity.rsi.util.ThreadContext.get(ThreadContext.java:93)
at org.jsecurity.rsi.context.ThreadLocalSecurityContextAccessor.getAuthorizationContext(ThreadLocalSecurityContextAccessor.java:34)
at org.jsecurity.context.SecurityContext.getAuthorizationContext(SecurityContext.java:201)
at com.altair.cis.common.util.SecurityUtil.getCurrentUserId(SecurityUtil.java:24)
at com.altair.aspects.TraceAspect.<clinit>(com.altair.aspects.TraceAspect$2@f001(TraceAspect.aj:35))
at com.altair.common.gradebook.AbstractGradeItem.equals(AbstractGradeItem.java:113)
at java.util.HashMap.put(HashMap.java:378)
at java.util.HashSet.add(HashSet.java:203)
at java.util.AbstractCollection.addAll(AbstractCollection.java:303)
at org.hibernate.collection.PersistentSet.endRead(PersistentSet.java:352)
at org.hibernate.engine.loading.CollectionLoadContext.endLoadingCollections(CollectionLoadContext.java:260)
at org.hibernate.engine.loading.CollectionLoadContext.endLoadingCollections(CollectionLoadContext.java:243)
at org.hibernate.engine.loading.CollectionLoadContext.endLoadingCollections(CollectionLoadContext.java:218)
at org.hibernate.loader.Loader.loadCollectionAndCollections(Loader.java:309)
at org.hibernate.loader.Loader.loadAll(Loader.java:733)
at org.hibernate.loader.Loader.loadQueryAndInitializeNonLazyCollections(Loader.java:270)
at org.hibernate.loader.Loader.loadCollection(Loader.java:2082)
at org.hibernate.loader.CollectionLoader.initialize(CollectionLoader.java:62)
at org.hibernate.persistor.collection.AbstractCollectionPersister.initialize(AbstractCollectionPersister.java:628)
at org.hibernate.event.def.DefaultInitializeCollectionEventListener.onInitializeCollection(DefaultInitializeCollectionEventListener.java:63)
at org.hibernate.impl.SessionImpl.initializeCollection(SessionImpl.java:1853)
at org.hibernate.collection.AbstractPersistentCollection.initialize(AbstractPersistentCollection.java:369)
at org.hibernate.collection.AbstractPersistentCollection.read(AbstractPersistentCollection.java:111)
at org.hibernate.collection.PersistentSet.iterator(PersistentSet.java:186)
at com.altair.cis.entity.GradeBookItem.getUniqueGradeItemsForEnrollment(GradeBookItem.java:394)
at com.altair.cis.manager.impl.DefaultGradeBookManager.getGradeSheetLine(DefaultGradeBookManager.java:659)
at com.reflect.GeneratedMethodAccessor1040.invoke(Unknown Source)
at sun.reflect.GeneratedMethodAccessor1040.invoke(Unknown Source)
at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:25)
at java.lang.reflect.Method.invoke(Method.java:597)
at org.springframework.aop.support.AopUtils.invokeJoinpointUsingReflection(AopUtils.java:309)
at org.springframework.aop.framework.ReflectiveMethodInvocation.invokeJoinpoint(ReflectiveMethodInvocation.java:183)
at org.springframework.aop.framework.ReflectiveMethodInvocation.proceed(ReflectiveMethodInvocation.java:130)
at org.springframework.transaction.interceptor.TransactionInterceptor.invoke(TransactionInterceptor.java:110)
at org.springframework.aop.framework.ReflectiveMethodInvocation.proceed(ReflectiveMethodInvocation.java:172)
at org.springframework.aop.framework.JdkDynamicAopProxy.invoke(JdkDynamicAopProxy.java:202)
at $Proxy50.getGradeSheetLine(Unknown Source)
at com.altair.cis.web.gradebook.roster.StudentGradebookController.getStudentGradebook(StudentGradebookController.java:465)
at com.altair.cis.web.gradebook.roster.StudentGradebookController.handleHttpRequestInternal(StudentGradebookController.java:241)
at org.springframework.web.servlet.mvc.AbstractController.handleRequest(AbstractController.java:153)
at org.springframework.web.servlet.mvc.SimpleControllerHandlerAdapter.handle(SimpleControllerHandlerAdapter.java:48)
at org.springframework.web.servlet.DispatcherServlet.doDispatch(DispatcherServlet.java:788)
at org.springframework.web.servlet.DispatcherServlet.doService(DispatcherServlet.java:717)
at org.springframework.web.servlet.FrameworkServlet.processRequest(FrameworkServlet.java:644)
at org.springframework.web.servlet.FrameworkServlet.doPost(FrameworkServlet.java:569)
at javax.servlet.http.HttpServlet.service(HttpServlet.java:637)
at javax.servlet.http.HttpServlet.service(HttpServlet.java:717)
at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:290)
at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:206)
at com.altair.cis.common.filter.compress.CompressFilter.java:24
at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:235)
at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:206)
at org.springframework.web.filter.CharacterEncodingFilter.doFilterInternal(CharacterEncodingFilter.java:88)
at org.springframework.web.filter.CharacterEncodingFilter.doFilterOncePerRequest(CharacterEncodingFilter.java:76)
at org.apache.catalina.core.ApplicationFilterChain.internalDoFilter(ApplicationFilterChain.java:235)
at org.apache.catalina.core.ApplicationFilterChain.doFilter(ApplicationFilterChain.java:206)
at org.apache.catalina.core.StandardWrapperValve.invoke(StandardWrapperValve.java:233)
at org.apache.catalina.core.StandardContextValve.invoke(StandardContextValve.java:191)
at org.apache.catalina.core.StandardHostValve.invoke(StandardHostValve.java:127)
at org.apache.catalina.valves.ErrorReportValve.invoke(ErrorReportValve.java:102)
at org.apache.catalina.core.StandardEngineValve.invoke(StandardEngineValve.java:109)
at org.apache.catalina.connector.CoyoteAdapter.service(CoyoteAdapter.java:298)
at org.apache.jk.server.JkCoyoteHandler.invoke(JkCoyoteHandler.java:190)
at org.apache.jk.common.HandlerRequest.invoke(HandlerRequest.java:291)
at org.apache.jk.common.ChannelSocket.invoke(ChannelSocket.java:774)
at org.apache.jk.common.ChannelSocket.processConnection(ChannelSocket.java:703)
at org.apache.jk.common.ChannelSocket$SocketConnection.runit(ChannelSocket.java:896)
at org.apache.tomcat.util.threads.ThreadPool$ControlRunnable.run(ThreadPool.java:690)
at java.lang.Thread.run(Thread.java:662)
```

"TP-Processor3337" daemon prio=10 tid=0x0002aab413b2800 nid=0x62a0 runnable [0x00000004c377000]
java.lang.Thread.State: **RUNNABLE**

```

at java.io.BufferedInputStream.read1(BufferedInputStream.java:258)
at java.io.BufferedInputStream.read(BufferedInputStream.java:317)
- locked <0x0002aaafef19e0> is java.io.BufferedInputStream
at org.apache.jk.common.ChannelSocket.read(ChannelSocket.java:626)
at org.apache.jk.common.ChannelSocket.receive(ChannelSocket.java:564)
at org.apache.jk.common.ChannelSocket.processConnection(ChannelSocket.java:691)
at org.apache.jk.common.ChannelSocket$SocketConnection.runit(ChannelSocket.java:896)
at org.apache.tomcat.util.threads.ThreadPool$ControlRunnable.run(ThreadPool.java:690)
at java.lang.Thread.run(Thread.java:662)

```

"TP-Processor3517" daemon prio=10 tid=0x0002aab40245800 nid=0x6fd0 in Object.wait() [0x00000004d78d000]
java.lang.Thread.State: **WAITING** (on object monitor)

```

at java.lang.Object.wait(Native Method)
at java.lang.Object.wait(Object.java:485)
at org.apache.tomcat.util.threads.ThreadPool$ControlRunnable.run(ThreadPool.java:662)
- locked <0x0002aaafef68500> is org.apache.tomcat.util.threads.ThreadPool$ControlRunnable
at java.lang.Thread.run(Thread.java:662)

```

"TP-Processor3517" daemon prio=10 tid=0x0002aab40245800 nid=0x6fd0 in Object.wait() [0x00000004d78d000]
java.lang.Thread.State: **WAITING** (on object monitor)

```

at java.lang.Object.wait(Native Method)
at java.lang.Object.wait(Object.java:485)
at org.apache.tomcat.util.threads.ThreadPool$ControlRunnable.run(ThreadPool.java:662)
- locked <0x0002aaafef68500> is org.apache.tomcat.util.threads.ThreadPool$ControlRunnable
at java.lang.Thread.run(Thread.java:662)

```

capture

- notes
- screen shots
- heap dumps
- thread dumps
- snapshots
- app server logs
- web server access and error logs
- os process lists
- database process list
- key jmx values
- slow query logs
- core dumps

more info

The two principal products in the Java SE platform are: Java Development Kit (JDK) and Java SE Runtime Environment (JRE).

The JDK is a superset of the JRE, and contains everything that is in the JRE, plus tools such as the compilers and debuggers necessary for developing applets and applications. The Java Runtime Environment (JRE) provides the libraries, the Java Virtual Machine, and other components to run applets and applications written in the Java programming language.

The following conceptual diagram illustrates all the component technologies in Java SE platform and how they fit together.

The diagram shows the Java SE platform architecture. It is divided into two main sections: the Java Development Kit (JDK) and the Java SE Runtime Environment (JRE). The JDK section includes 'Java Language' (with sub-components like java, javac, javadoc, apt, jar, javap, JPDA, JConsole, Java VisualVM, and Java DB), 'Tools & Tool APIs' (Security, Int'l, RMI, IDL, Deploy, Monitoring, Troubleshoot, Scripting, and JVM TI), 'RIAs' (Java Web Start and Applet / Java Plug-in), 'User Interface Toolkits' (AWT, Swing, and Java 2D), 'Integration Libraries' (IDL, JDBC, JNDI, RMI, RMI-IIOP, and Scripting), 'Other Base Libraries' (Beans, Intl Support, Input/Output, JMX, JNI, Math, Networking, Override Mechanism, Security, Serialization, Extension Mechanism, XML JAXP), 'lang and util Base Libraries' (lang and util, Collections, Concurrency Utilities, JAR, Logging, Management, Preferences API, Ref Objects, Reflection, Regular Expressions, Versioning, Zip, Instrumentation), and the 'Java Virtual Machine'. The JRE section is shown as a subset of the JDK components.

[Java SE 6 API Documentation](http://docs.oracle.com/javase/6/docs/)



CONTENTS INCLUDE:

- Configuration
- JMX
- Available Plugins
- Java Memory Types
- JVM Settings
- and More!

Java Profiling with VisualVM

X-Ray Vision for Dramatic Performance Gains

By Mick Knutson

ABOUT VISUALVM

VisualVM is a visual tool integrating several command-line JDK tools and lightweight profiling capabilities. Designed for both production and development time use, it further enhances the capability of monitoring and performance analysis for the Java SE platform. <http://visualvm.java.net/>

CONFIGURATION

Repositories

Windows 7: C:\Users\[userId]\AppData\Roaming\.visualvm\[version]\repository\

OS X: /Users/[userId]/Library/Application Support/visualvm/[version]/repository/

User Directory

Windows 7: C:\Users\[userId]\AppData\Roaming\.visualvm\[version]\var\log\message.log

OS X: /Users/[userId]/Library/Application Support/visualvm/[version]/var/log/message.log

JMX

JMX connections

Default connection:

```
<hostname>:<port>
```

Detailed connection:

```
service:jmx:<protocol>:<sap>
```

Detailed connection example:

```
service:jmx:rmi://<hostname>:<port>/jndi/rmi://<hostname>:<port>/jmxrmi
```

Container specific configuration

Configuration for exposing JMX.

Glassfish administration:

JVM options can be set via Glassfish web administration page:
<http://localhost:4848/common/javaConfig/serverJvmOptions.jsf?configName=server-config>

Glassfish configuration file:

%GLASSFISH_HOME%\glassfish\domains\[domain]\config\domain.xml
 configuration file:

```
<configs> <config name="server-config">
  ->java-config -> ...
  ->jvm-options><JMX configuration parameters></jvm-options>
  ...
</configs>
```

Tomcat:

```
export CATALINA_OPTS=<JMX configuration parameters>
```

Jetty standalone:

```
java <JMX configuration parameters> -jar start.jar etc/jetty-jmx.xml
```

Maven:

```
export MAVEN_OPTS=<JMX configuration parameters>
```

Container specific configuration parameters

Name	Parameter
Access file	-Dcom.sun.management.jmxremote.access.file=<access file>
Authenticate	-Dcom.sun.management.jmxremote.authenticate=<true / false>
Debug	-Djavax.net.debug=<level>
JMX port	-Dcom.sun.management.jmxremote.port=<PortNumber>
JMX remote enabled	-Dcom.sun.management.jmxremote
* Keystore file	-Djavax.net.ssl.keyStore=<keystore file>
* Keystore password	-Djavax.net.ssl.keyStorePassword=<password>
Management level	-Djavax.management.level=<level>
Password file	-Dcom.sun.management.jmxremote.password file=<password file>
RMI server hostname	-Djava.rmi.server.hostname=<public.ip.address>
SSL enabled	-Dcom.sun.management.jmxremote.ssl=<true / false>

AnswerHub Social Q&A for the Enterprise

1/2 of the Top 10 StackExchange 1.0 Sites Now Run on AnswerHub

Discover Why Now!



Christopher M. Judd



CTO and Partner

email: cjudd@juddsolutions.com

web: www.juddsolutions.com

blog: juddsolutions.blogspot.com

twitter: [javajudd](https://twitter.com/javajudd)

