

*Quick view displays current version compatibility and 2 versions back, this doesn't mean that support for v2.30 has been dropped. For details on the prior version compatibility please see the Advanced Details section and the Software Downloads page (link provided below)

C-CURE® 9000	v3.00
Partner	DSC
Partner Product	PowerSeries Neo and Pro
Partner Product version	• Hardware version: UA628 REV03, Keypad Model: HS2LCD, and Firmware version: v01.10.01.51, v01.11.01.13, v1.20.01.29, v1.30.01.04, v1.33.01.02, and v1.35.01.03 • Hardware version: UA601 REV03, Communicator Model: TL280/TL280R/TL2803G, and Firmware version: v04.11.04.31 • Hardware version: UA685 REV01, Communicator Model: TL280E/TL280RE, and Firmware version: v5.00.04.27, v05.02.04.03, v5.03.04.04, v5.40.04.07 and v5.41.04.01 • Hardware version: UA621 REV03, DSC Neo Panel Model: HS2016, HS2032, HS2064, HS2128, HS2128 E, and Firmware version: v01.12.01.13, v01.14.01.10, v1.20.01.31, v1.21.01.01, v01.30.01.08, v1.31.01.01, v1.33.01.05, v1.35.01.07 and v1.37.01.12 • Expansion Module: Output expander/Zone expander (HSM2108/HSM2208) • Wireless Module: HSM2HOST/PG4984/PG4945 • Hardware version (Pro Panel): UA718 Rev03, Hardware Model: HS3128PCB / HS3248PCB, and Firmware version: v1.30 • Hardware version (Pro Panel): UA628 Rev03, Hardware Model: HS2LCD, and Firmware version: v2.30
Integration driver version	6.0.18.18
C-CURE® 9000 License option	CC9000-NEO
Enterprise Certified	Yes
Redundancy Certified	No
Supported Server OS	All OS supported by C•CURE 9000 server
Supported Client OS	All OS supported by C•CURE 9000 Client
Supported SQL	All SQL supported by C•CURE 9000 server

Driver Software	Driver is available for download by Authorized Software House integrators, and no connection license is required
	Click here for driver
	SDK Integration
Tech Support	Software House: Contact your Authorized Software House integrator (Dealer of Record) for C•CURE 9000 and integration support

C-CURE® 9000	v2.90
Partner	DSC
Partner Product	PowerSeries Neo and Pro
Partner Product version	Hardware version: UA628 REV03, Keypad Model: HS2LCD, and Firmware version: v01.10.01.51, v01.11.01.13, v1.20.01.29, v1.30.01.04, v1.33.01.02, and v1.35.01.03 • Hardware version: UA601 REV03, Communicator Model: TL280/TL280R/TL2803G, and Firmware version: v04.11.04.31 5 • Hardware version: UA685 REV01, Communicator Model: TL280E/TL280RE, and Firmware version: v5.00.04.27, v05.02.04.03, v5.03.04.04, v5.40.04.07 and v5.41.04.01 • Hardware version: UA621 REV03, DSC Neo Panel Model: HS2016, HS2032, HS2064, HS2128, HS2128 E, and Firmware version: v01.12.01.13, v01.14.01.10, v1.20.01.31, v1.21.01.01, v01.30.01.08, v1.31.01.01, v1.33.01.05, and v1.35.01.07 • Expansion Module: Output expander/Zone expander (HSM2108/HSM2208) • Wireless Module: HSM2HOST/PG4984/PG4945 • Hardware version (Pro Panel): UA718 Rev03, Hardware Model: HS3128PCB / HS3248PCB, and Firmware version: v1.30 • Hardware version (Pro Panel): UA628 Rev03, Hardware Model: HS2LCD, and Firmware version: v2.30
Integration driver version	5.6.82.0
C-CURE® 9000 License option	CC9000-NEO
Enterprise Certified	Yes
Redundancy Certified	No
Supported Server OS	All OS supported by CCURE Server
Supported Client OS	All OS supported by CCURE Client
Supported SQL	All OS supported by C•CURE 9000 server

Driver Software	Driver is available for download by Authorized Software House integrators, and no connection license is required
	Click here for driver
	SDK Integration
Tech Support	Software House: Contact your Authorized Software House integrator (Dealer of Record) for C•CURE 9000 and integration support
Additional Information:	Data Sheet v2.90

C-CURE® 9000	v2.80
Partner	DSC
Partner Product	PowerSeries Neo
Partner Product version	Hardware version: UA628 REV03, Keypad Model: HS2LCD, and Firmware version: v01.10.01.51, v01.11.01.13, v1.20.01.29, v1.30.01.04, v1.33.01.02, and v1.35.01.03 • Hardware version: UA601 REV03, Communicator Model: TL280/TL280R/TL2803G, and Firmware version: v04.11.04.31 • Hardware version: UA685 REV01, Communicator Model: TL280E/TL280RE, and Firmware version: v5.00.04.27, v05.02.04.03, v5.03.04.04, v5.40.04.07 and v5.41.04.01 • Hardware version: UA621 REV03, DSC Neo Panel Model: HS2016, HS2032, HS2064, HS2128, HS2128 E, and Firmware version: v01.12.01.13, v01.14.01.10, v1.20.01.31, v1.21.01.01, v01.30.01.08, v1.31.01.01, v1.33.01.05, and v1.35.01.07 • Expansion Module: Output expander/Zone expander (HSM2108/HSM2208) • Wireless Module: HSM2HOST/PG4984/PG4945 • Hardware version (Pro Panel): UA718 Rev03, Hardware Model: HS3128PCB / HS3248PCB, and Firmware version: v1.30 • Hardware version (Pro Panel): UA628 Rev03, Hardware Model: HS2LCD, and Firmware version: v2.30
Integration driver version	5.4.221.0
C-CURE® 9000 License option	CC9000-NEO
Enterprise Certified	Yes
Redundancy Certified	No
Supported Server OS	All OS supported by CCURE Server
Supported Client OS	All OS supported by CCURE Client
Supported SQL	All OS supported by C•CURE 9000 server

Driver Software	Driver is available for download by Authorized Software House integrators, and no connection license is required
	Click here for driver
	SDK Integration
Tech Support	Software House: Contact your Authorized Software House integrator (Dealer of Record) for C•CURE 9000 and integration support
Additional Information:	Data Sheet v2.80