

# Release Notes for victor v5.4.1 EntraPass Integration v5.4.19.0

Document Revision A0 July 2019

This document provides important information about the victor EntraPass Integration software. Read this document before you install the product.

**Product**: victor Integration Software for EntraPass

• Integration Software Version: 5.4.19.0

**NOTE**: This version is compatible with victor versions 5.4 and 5.4.1 and EntraPass software version 8.00.32.

#### Contents

- 1. Overview
- 2. Features
- 3. Qualified Hardware and Firmware Requirements
- 4. Software Requirements
- 5. Contents of the Installation Package
- 6 Pre-Installation
- 7. <u>Installation</u>
- 8. Post-Installation
- 9. Upgrading the EntraPass Integration
- 10. Scalability
- 11. Language Support
- 12. Compatibility Matrix
- 13. Known Issues and Limitations
- 14. <u>Defects Fixed</u>
- 15. End of Release Notes

## 1. Overview

The victor platform provides seamless integration with the EntraPass including the ability to view EntraPass objects in victor through synchronization.

# 2. Features

The victor integration software for EntraPass offers the following features:

- Create, edit, or delete a server object.
- Supports KT NCC Gateway.
- View and Delete feature for Gateway, Site, Controller, Door, Input, and Relay.

**Note**: When server has large number of objects (5000+), it is recommended to delete sites instead of deleting EntraPass server.

- Supports configuration of a Server object by using either the Machine Name or IP Address.
- Manual and Auto Synchronization for Server.

**Note**: In EntraPass Integration driver, it is recommended to perform sync operation on one server at a time.

8200-1147-1199 A0

- Supports the following manual actions for Door objects: Lock, Unlock, Unlock Temporarily, Enable Reader, Disable Reader, Arm, Disarm Door, and One Time Access.
- Supports the following manual actions for Input objects: Continuous, No Supervision, No Supervision-Delay, and Normal.
- Supports the following manual actions for Relay objects: Activate, Deactivate, and Activate Temporarily.
- Integration with victor **Roles**, victor **Object Association**, victor **Journal**, and victor Event Management.
- EntraPass Object integration with the victor features: Maps, Find in Journal, Find on Map, and the victor Health Dashboard.
- Supports the smart service binding in the form of https.
- Supports Swipe and Show feature, Synchronization of Personnel and Synchronization of Personnel Images.
- Supports predefined events for Servers, Sites, Controllers and Doors.
- Supports EntraPass Actions feature for Servers, Doors and Relays.

# 3. Qualified Hardware and Firmware Requirements

The EntraPass Integration has the same hardware and disk space requirements as victor. If the target computer meets victor installation requirements, then it meets EntraPass Integration requirements. The EntraPass Integration supports the following:

- EntraPass Corporate Edition: 8.00.32
- EntraPass Global Edition: 8.00.32
- KT-NCC, Firmware version: 8.00.32
- KT-1, Firmware version: 2.03.03
- KT-400 Rev01, Firmware version: 2.02.03
- KT-400v1, Firmware version: 1.25.01
- KT-300, Firmware version: 2.03.01
- A valid SSL certificate in IIS is required

## 4. Software Requirements

The victor Integration software for EntraPass server requires the following software:

- victor Application Server: v5.4.1
- victor Client: v5.4.1
- Smart Service installed on EntraPass Server

## 5. Contents of the Installation Package

Table 1: Installation Package lists the contents of the EntraPass Integration installation package.

**Table 1: Installation Package** 

File	Description			
EntraPass Integration.exe	EntraPass Integration software setup file			
victor-EntraPas-v5-4-1-UM-8200-1147-1203-A0-en.pdf	EntraPass victor Integration User Manual			
victor-EntraPas-v5-4-1-RN-8200-1147-1199-A0-en.pdf	EntraPass victor Integration Release Notes			

8200-1147-1199 A0

## 6. Pre-Installation

Prerequisites to install EntraPass Integration on the victor Application Server:

- You must have appropriate Windows permissions.
- You must be a member of the local Administrators group or have equivalent privileges.
- Ensure that you are on a reliable network.
- You must install victor Application Server.

Prerequisites to install EntraPass Integration on the clients:

- You must have appropriate Windows permissions.
- You must be a member of the local Administrators group or have equivalent privileges.
- You must install victor Unified Client.

### Prerequisites on EntraPass Server System:

- a. Smart Service installed on EntraPass Server.
- b. The login operator for EntraPass should have Security Level set as Installer and the Workspace set as Installer instead of the Administrator security level because the Administrator security level does not have access to certain sections of EntraPass.
- c. Due to an update in the license for EntraPass v6.05, the EntraPass server requires a minimum of two EntraPass Web licenses to maintain constant communication between victor and the EntraPass server
  - On the **Web Parameters** tab, ensure that Concurrent logins option is disabled. With this configuration, any loss in communication between victor and the EntraPass server disconnects the previous login and attempts to reconnect. The new connection temporarily uses the second instance of the license before releasing first instance of license.
  - If the EntraPass server has only one 'EntraPass web' license, any loss in communication between victor and the EntraPass server is restored only after the Connection Timeout on Idle duration of SmartLink is completed.
- d. Concurrent request per connection in EntraPass server should be set to 16.
- e. Connection timeout on idle should be set to 59 minutes.
- f. A valid SSL certificate in IIS is required for smart service binding in the form of https.

### 7. Installation

### Note:

- You must install the EntraPass Integration in the same folder as victor.
- Close all applications to avoid problems during installation.

Follow the steps to install the EntraPass Integration on the server and remote clients:

- 1. Double-click the **EntraPass Integration.exe** file.
- 2. Click **Next** and follow the Install Wizard prompts.
- On the License Agreement, select I accept the terms in the license agreement check box and then Next.
- 4. Click **Finish** to complete the installation.

## 8. Post-Installation

Perform the following steps after installation:

- 1. Obtain License with the EntraPass option enabled.
- 2. Launch the **Server Configuration Application**:

8200-1147-1199 A0

- a. On the taskbar, click the **Start** button and then click **All Programs**.
- b. Click **Tyco**, right-click the **Server Configuration** and then click **Run as Administrator**. The **Server Configuration Application** page opens.

#### 3. Start the **EntraPass Services**:

- a. On the **Server Configuration Application** page, click the **Services** tab.
- b. Ensure that both Crossfire Framework Service and Crossfire Server Component Framework Service is Running.
- c. In the **Extension Services** area, locate the **EntraPass Driver Service**. Select the **Enabled** check box and then click the **Start** button. The status of the EntraPass Driver Service changes to **Running**.

### 4. Launch the victor client:

- a. On the taskbar, click the **Start** button and then click **All Programs**.
- b. Click **victor**.

# 9. Upgrading the EntraPass Integration

#### **Caution:**

If you have made any changes in the configuration file - EntraPassDriverService.exe.config, ensure that you back up the file before upgrading. The configuration file is located at Tyco\CrossFire\ServerComponents.

Follow the step to upgrade the EntraPass Integration:

• Upgrade victor v5.2 or v5.3 to victor v5.4.1 and then install the integration and resynchronize.

# 10. Scalability

Scalability testing is performed on a system with the following system and object configurations, refer Table 2: System Configuration and Table 3: Object Configuration.

**Table 2: System Configuration** 

System Configuration			
CPU	8 Core		
Memory	16GB		
Config file entries	Key ="ComponentStatusBatchSize" value=50		
	Key ="StatusQueueCount" value=4		
	Key =" SyncBatchSize" value=5		
	Status poll Time: 45 seconds		

**Table 3: Object Configuration** 

Object Type	Server2(Global	Server3(Corporate	Server5(Global	Total object
	Edition)	Edition)	edition)	count/object type
Relay	496	849	1321	2666
Input	766	3003	3361	7130
Door	7676	922	1646	10244
Controller	1925	465	610	3000
Connection/Site	84	134	29	247
KT NCC Gateway	1	0	1	2
Software gateway	13	1	2	16
Total Object	10961	5374	6970	23305
Count				

# 11. Language Support

This driver supports the following languages:

- English (US)
- French
- Hungary
- Czech

# 12. Compatibility Matrix

Table 4: Compatibility Matrix, lists the Compatibility Matrix of the EntraPass Integration:

**Table 4: Compatibility Matrix** 

victor version 5.4.1				
VICUOT VETSIOII 5.4.1				
Partner	Kantech			
Partner Product	Kantech EntraPass			
Partner Product version	EntraPass 8.00.32 KT-NCC, Firmware version: 8.00.32. KT-1, Firmware version: 2.03.03 KT-400 Rev01, Firmware version: 2.02.03 KT-400v1, Firmware version: 1.25.01 KT-300, Firmware version: 2.03.01			
Integration driver version	5.4.19.0			
victor License option	ADVC-EntraPass			
Non-supported Hardware and Firmware/OS version	KT-100, Firmware version – 1.09			
Unified Compatibility	No			
Enterprise certified	Yes			
Redundancy certified	Yes (EMC only)			
Supported Server OS	All OS supported by victor Server			
Supported Client OS	All OS supported by victor Client			
Supported SQL	All SQL Server supported by victor Server			

### 13. Known Issues and Limitations

This section describes the EntraPass Integration known limitations.

- The EntraPass Integration does not support, Hardware KT-100, Firmware version: 1.09.
- If you delete the EntraPass server in victor, personnel and images that are associated with that server are not deleted; you must delete them manually. If you add a server that was deleted previously, former users are not recognized by the server and you must resynchronize the personnel and personnel images.
- EntraPass site information may not update correctly in the following scenarios:
  - When the connection type is **IP**: the serial port, protocol, and baud rate may not update correctly.
  - When connection type is **Serial**: the IP port number, protocol, and IP address may update correctly.

8200-1147-1199 A0 5

- Actions such as Momentarily Unlock Door, Grace Personnel, Area Lockout Grace, and Antipassback Reset Card from the Swipe and Show feature are not supported.
- Migration of a standalone machine with an EntraPass Driver to SAS is not supported.
- If you install the EntraPass Integration on remote clients, the **Integration Setup** dialogue box appears and you may be prompted to select an **Installation Option** for Redundancy server. Ignore this message and click **Next** to continue with installation. If you select the **Redundancy server installation using supported third party redundancy** check box, provide the virtual server location, and then click **Next**; this selection is ignored and there is no functional impact.
- If you delete objects, personnel, or personnel images from Kantech, the same objects, personnel, or personnel images are not deleted from victor even after synchronization; this may impact the status of other objects, personnel, or personnel images.
  - o **Workaround**: Delete the objects, personnel, or personnel images from victor that are already deleted from EntraPass server and then synchronize.
- There is no specific **EntraPass door** option under **Device** or **Edit** list, instead all **EntraPass doors** are listed under **Doors** option.
- For EntraPass Server, Site communication status is displayed as offline in victor client even though it
  is online
- For KT 300 controller, Tamper status and schedule values are displayed as unknown in victor client.
- When gateways are renamed in EntraPass server, the new name may not reflect correctly in victor client.
- For EntraPass objects after synchronization, component address is not displayed in victor client.
- In EntraPass Integration driver, KT NCC gateway Onboard Relays are not synchronized.
- During the resynchronization of the EntraPass Driver, window displays to choose the file path. This is an intermittent issue.
  - o **Workaround**: Choose the EntraPass installer and resync process will proceed.
- Only the First and Last name of personnel is displayed in the Personnel view.
- In the Personal Edit window, Customer Personnel details are not supported.
- While synchronizing, sometimes a standard fault SMARTLINK\_RPC\_EXCEPTION occurs and EntraPass Smartlink crashes. This may affect synchronization of server and synchronization status of server may continue to remain in synchronizing state or sync may fail.
  - Workaround: Reduce the value for SyncBatchSize to 5 or lower in config file and restart the driver.
- In case of large number of objects, it is recommended to set the status poll time entry to a higher value.
- In EntraPass server, name field for any object should not have more than 100 characters. If the length is more than 100 characters, those objects will not be synchronized.
- When Kantech smart service or EntraPass Smartlink is stopped, communication status of controller or site may go offline momentarily and then comes back online. This does not affect functionality, as server is set to offline.
- In Map for Input objects, input state may not reflect correctly.

# 14. Defects Fixed

No defects in this release.

# 15. End of Release Notes

The trademarks, logos, and service marks displayed on this document are registered in the United States [or other countries]. Any misuse of the trademarks is strictly prohibited and Johnson Controls will aggressively enforce its intellectual property rights to the fullest extent of the law, including pursuit of criminal prosecution wherever necessary. All trademarks not owned by Johnson Controls are the property of their respective owners, and are used with permission or allowed under applicable laws.

Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.

©2019 Johnson Controls. All rights reserved.

8200-1147-1199 A0 7